



Cree Performance XHP35 LED Module

Power of Cree XHP Series in Standard and Custom LED modules

Data Sheet

Illumination Accelerated

Design Faster – use standard, UL-listed modules

Superior Performance & Cost – top flux bin LEDs at competitive prices

Thermal Interface Included – pre-installed to simplify assembly

Add Standard Optics – configured for off-the-shelf optics

Primary Applications



| | |
|---------------|----------|
| High Mast | Canopy |
| Streetlight | Garage |
| Stadium | Portable |
| Architectural | High bay |



Superior Performance in Standard & Custom Modules

- Market leading L90 & L70 lifetimes, even in high stress conditions
- 70, 80, and 90 CRI LEDs available
- Metal core PCB for optimal thermal management
- Configurable with off the shelf optics, and heat sinks
- Private label or custom designs available

Simplify Your Next Design

The Cree performance modules, built with Cree SC5 technology, are an off-the-shelf platform to rapidly move from prototype to finished LED lighting fixture. These versatile building blocks are UL-listed and include Cree XHP35, XHP50 & XHP70 LEDs in square, linear or rectangle formats. The thermal interface is already installed with easy to use connectors to help simplify the lighting design and get to market faster. These competitively priced modules come in a range of lumen outputs and can achieve both DLC Premium or DLC Standard lumens per watt specifications.

Integrate Further

Opulent Americas also offers standard heat sinks and fully assembled IP-rated modules.



About Opulent Americas

Opulent Americas, part of Singapore based Opulent Group, is a fully integrated, global manufacturer for the lighting, automotive and medical industries. Through 30 years of manufacturing experience and state-of-the-art facilities, the company offers leading solid state lighting components and modules. The NC-based office provides quick engineering & sales support with an R&D lab to provide prototype development and custom solutions. See Opulent-Americas.com for more information.



XHP35 Series Specifications

Product Selection Table

| Configuration | LED Layout | Part Number | CCT | CRI | Binning | Luminous Flux (lm) | | Efficacy Nominal (lm/W) | Watts (W) | |
|----------------------------|------------|------------------------|-------|-----|---------|--------------------|-------|-------------------------|-----------|------------------------|
| | | | | | | Nominal | Max | | Nominal | Max |
| Rectangular ⁽¹⁾ | 2x2 | XHP35A-0R-04-0D0HC427E | 2700K | 80 | 5-Step | 1900 | 4537 | 120 | 16 | 51 |
| Rectangular ⁽¹⁾ | 2x2 | XHP35A-0R-04-0D0BD430E | 3000K | 70 | 5-Step | 2200 | 5253 | 139 | 16 | 51 |
| Rectangular ⁽¹⁾ | 2x2 | XHP35A-0R-04-0D0BE240E | 4000K | 70 | 5-Step | 2360 | 5635 | 149 | 16 | 51 |
| Rectangular ⁽¹⁾ | 2x2 | XHP35A-0R-04-0D0BE450E | 5000K | 70 | 5-Step | 2540 | 6065 | 161 | 16 | 51 |
| Rectangular ⁽¹⁾ | 2x2 | XHP35A-0R-04-0D0BE457E | 5700K | 70 | 5-Step | 2540 | 6065 | 161 | 16 | 51 |
| Rectangular ⁽²⁾ | 2x4 | XHP35A-0R-08-0D0HC427E | 2700K | 80 | 5-Step | 3800 | 9074 | 120 | 32 | 100 ⁽⁴⁾ |
| Rectangular ⁽²⁾ | 2x4 | XHP35A-0R-08-0D0BD430E | 3000K | 70 | 5-Step | 4400 | 10506 | 139 | 32 | 100 ⁽⁴⁾ |
| Rectangular ⁽²⁾ | 2x4 | XHP35A-0R-08-0D0BE240E | 4000K | 70 | 5-Step | 4720 | 11270 | 149 | 32 | 100 ⁽⁴⁾ |
| Rectangular ⁽²⁾ | 2x4 | XHP35A-0R-08-0D0BE450E | 5000K | 70 | 5-Step | 5080 | 12131 | 161 | 32 | 100 ⁽⁴⁾ |
| Rectangular ⁽²⁾ | 2x4 | XHP35A-0R-08-0D0BE457E | 5700K | 70 | 5-Step | 5080 | 12131 | 161 | 32 | 100 ⁽⁴⁾ |
| Rectangular ⁽³⁾ | 2x6 | XHP35A-0R-12-0D0HC427E | 2700K | 80 | 5-Step | 5700 | 13610 | 120 | 48 | 100/150 ⁽⁴⁾ |
| Rectangular ⁽³⁾ | 2x6 | XHP35A-0R-12-0D0BD430E | 3000K | 70 | 5-Step | 6600 | 15759 | 139 | 48 | 100/150 ⁽⁴⁾ |
| Rectangular ⁽³⁾ | 2x6 | XHP35A-0R-12-0D0BE240E | 4000K | 70 | 5-Step | 7080 | 16906 | 149 | 48 | 100/150 ⁽⁴⁾ |
| Rectangular ⁽³⁾ | 2x6 | XHP35A-0R-12-0D0BE450E | 5000K | 70 | 5-Step | 7620 | 18197 | 161 | 48 | 100/150 ⁽⁴⁾ |
| Rectangular ⁽³⁾ | 2x6 | XHP35A-0R-12-0D0BE457E | 5700K | 70 | 5-Step | 7620 | 18197 | 161 | 48 | 100/150 ⁽⁴⁾ |

⁽¹⁾ Product performance at 350mA T_j = 85°C.

⁽²⁾ Product performance at 700mA T_j = 85°C.

⁽³⁾ Product performance at 1050mA T_j = 85°C.

⁽⁴⁾ Input power not to exceed 100W for UL Class 2. Suitability for usage in other than Class 2 circuits shall be determined in the end-product investigation.

⁽⁵⁾ Cree XLamp XHP35 LED order codes specify only a minimum flux bin and not a maximum. Opulent North America may ship modules in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.

XHP35 Series Specifications

Order Code Formatting



XHP35 Series Specifications

Electrical Characteristics

| Part Number | Forward Voltage (v) | | Typical Thermal Resistance - Junction to Heat Sink (K/W) RTh J-HS |
|----------------|---------------------|---------|--|
| | Typical | Maximum | |
| XHP35A-0R-04-x | 45.2 | 47.6 | 1.8 |
| XHP35A-0R-08-x | 45.2 | 47.6 | 1.8 |
| XHP35A-0R-12-x | 45.2 | 47.6 | 1.8 |

Intended for connection to a class 2 power source with a maximum operating voltage of 50 Vdc

Maximum Ratings

| Part Number | DC Current (A) | Tsp Temp (°C) | Power (W) |
|----------------|----------------|---------------|------------------------|
| XHP35A-0R-04-x | 1.05 | 105 | 51 |
| XHP35A-0R-08-x | 2.10 | 105 | 100 ⁽¹⁾ |
| XHP35A-0R-12-x | 3.15 | 105 | 100/150 ⁽¹⁾ |

⁽¹⁾ Input power not to exceed 100W for UL Class 2. Suitability for usage in other than Class 2 circuits shall be determined in the end-product investigation.

Relative Flux Vs Board Current (T_J = 85°C)



(XHP35A-0R-04-x)



(XHP35A-0R-08-x)



(XHP35A-0R-12-x)

XHP35 Series Specifications

Spatial Distribution



Performance Groups – Chromaticity

| 5-Step Binning | | | | | |
|----------------|--------------|--------|------------|------------|--------------------|
| CCT | Center Point | | Major Axis | Minor Axis | Rotation Angle (°) |
| | X | Y | a | b | |
| 5700K | 0.3287 | 0.3417 | 0.01230 | 0.00600 | 72.0 |
| 5000K | 0.3447 | 0.3553 | 0.01400 | 0.00520 | 65.0 |
| 4000K | 0.3818 | 0.3797 | 0.001420 | 0.00550 | 61.5 |
| 3000K | 0.4338 | 0.4030 | 0.01390 | 0.00680 | 53.2 |
| 2700K | 0.4577 | 0.4099 | 0.01350 | 0.00700 | 48.5 |

Standard White Chromaticity Regions Plotted On The CIE 1931 Curve



XHP35 Series Specifications

Thermal Interface Properties

| Property | Test Method | Value | Unit |
|----------------------|-------------|--------------------|-------|
| Color | - | Blue | - |
| Thickness | ASTM D374 | 0.3 | mm |
| Construction | - | Silicone / Ceramic | - |
| Temperature Range | EN344 | -50-200 | °C |
| Breakdown Voltage | ASTM D149 | >8.0 | Kv/mm |
| Flame Rating | UL94 | V-0 | - |
| Thermal Conductivity | ASTM D5470 | 3.0 | W/m-K |

Intended for connection to a class 2 power source with a maximum operating voltage of 50 Vdc

Note: Release liner must be removed for proper thermal performance. Do not remove thermal Interface Material.

Board Material Properties

| Property | Value | Unit |
|-------------------|-------|------|
| Solder Mask Color | White | - |
| Thickness | .062 | in |
| Construction | AL | - |
| Temperature | 130 | °C |
| Flame Rating | V-0 | - |
| Copper Thickness | 2 | oz |




XHP35 Series Specifications

Opulent Americas Rectangular 4 LED XHP35 Module



Schematic



1. Dual Poke-In Connectors accept 18-24 AWG solid or stranded wire
2. Recommended Mounting Hardware: 4x M3-.5 Socket Head Cap Screws

XHP35 Series Specifications

Opulent Americas Rectangular 8 LED XHP35 Module




Schematic



1. Dual Poke-In Connectors accept 18-24 AWG solid or stranded wire
2. Recommended Mounting Hardware: 6x M3-5 Socket Head Cap Screws

XHP35 Series Specifications

Opulent Americas Rectangular 12 LED XHP35 Module



Schematic



1. Dual Poke-In Connectors accept 18-24 AWG solid or stranded wire
2. Recommended Mounting Hardware: 5x M3-5 Socket Head Cap Screws



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331