Distinctive Characteristics

Brilliant illumination for highly visible status indication with LEDs and caps in red, green, or amber; subdued illumination for low light requirements with white cap over red, green, or amber LEDs.

Photo interrupter, rather than contacts, ensures high reliability and long life of 3 million operations minimum.

Rugged construction and smooth actuation allow repeated, rapid actuation force anywhere on cap surface.

Snap-in mounting for easy installation.

Connector socket with 6 pins for simple connection.

Well suited for gaming and vending machines, as well as equipment exposed to corrosive gases used in environments such as chemical or steel manufacturing plants.

Actual Size



Series FP01 Contactless Illuminated Pushbuttons

TYPICAL SWITCH ORDERING EXAMPLE

FP01 [1] [5] [C] [A] [C1] [F] [F] – [ ]

PHOTO TRANSISTOR

1	Single

SHAPE

C	Round

RECEPTACLE

C1	6-pin Socket

See Plug Options.

LEDS

C	Red
D	Amber
F	Green

PHOTO INTERRUPTER

5	Unshaded	(Shaded)

(Momentary Operating Function)

HOUSING

A	Black

ACTUATOR COLORS

B	White
C	Red
D	Amber
F	Green

PLUG OPTIONS

C2	Assembled Connector Plug with Wire Leads
C3	Unassembled Connector Plug and Pins
No Code	No Connector Plug

Contact factory for custom options.

DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

FP0115CAC1FF

ACTUATOR & INTERRUPTER

		Actuator Position		Photo Interrupter		Schematics
		Normal	Down	Unshaded	Shaded	
Model	1	▬	▬	5	Normally Unshaded with Momentary Shaded status	LED connector pins are 5 & 6; interrupter connector pins are 3-4 & 1-2.
FP0115	Single Photo Transistor	When shaded, the photo transistor momentarily activates electrical function which signals the external device to change its state.				

HOUSING SHAPE & COLOR

[C] **Round Shape**

[A] **Black Housing**

INTERNAL RECEPTACLE

[C1] **Receptacle**

Internal male connector socket



SWITCH SPECIFICATIONS

	Actuator Up	Actuator Down
Status of Photo Interrupter:	Unshaded	Shaded
Collector Current I_C:	0.8mA minimum	10μA maximum
Status of Photo Transistor:	On	Off
Output Condition of Photo Transistor:	I_F = 20mA & V_{CE} = 5V	

MECHANICAL SPECIFICATIONS

Total Travel:	.079″ (2.0mm)
Operating Force:	0.75 N (.169 lbf)
Mechanical Life:	3,000,000 operations minimum
Operating Temperature Range:	–25°C through +50°C (–13°F through +122°F)

MATERIALS

Actuator:	Polyacetal
Housing:	Polyamide

PHOTO INTERRUPTER SPECIFICATIONS

(Temperature @ 25°C)

Electrical & Optical Characteristics	Typical	Maximum	Condition
Input			
Forward Voltage V_F:	1.3V	1.6V	I_F = 50mA
Reverse Current I_R:		10μA	F_R = 5V
Transmission			
Collector-Emitter Saturation Voltage V_{CE} sat:		0.4V	I_F = 20mA & I_C = 0.1mA

Absolute Maximum Ratings

Input LED		Output Photo Transistor	
Forward Current I_F:	50mA	**Collector-Emitter Voltage V_{CEO}:**	30V
Reverse Voltage V_R:	5V	**Emitter-Collector Voltage V_{ECO}:**	4.5V
Power Dissipation P_D:	80mW	**Collector Current I_C:**	30mA
		Collector Dissipation P_C:	80mW

Circuit Design Considerations

Output of the infrared LED in the photo interrupter decreases approximately 50% after 100,000 hours.

Recommended load resistance (RL) is 40k ~ 120kΩ for the illustrated circuit.



EXTERNAL PLUG OPTIONS

C2 **AT021**
Assembled Connector Plug with Wire Leads

Connector plug body: JST model ZHR-6
Crimp connector pins: JST model SZH-002T-P0.5
Wire leads: 28-26AWG; 12-inch, unstripped;
Blue for Pin 1



C2 **AT022**
Unassembled Connector Plug and Pins

1 connector plug and 8 crimp connector pins only (no wire leads provided).

Matching wire leads: 28-26AWG



No Code

No Connector Plug

Recommended connector plug for assembly:
JST model number ZHR-6

Recommended crimp connector pins:
JST model SZH-002T-P0.5 for 28-26AWG wire leads or SZH-003T-P0.5 for 32-28AWG wire leads.

ACTUATOR COLORS

B White

C Red

D Amber

F Green

LED COLORS & SPECIFICATIONS

LEDs are an integral part of the switch and not available separately. The electrical specifications shown are determined at a basic temperature of 25°C.

If the source voltage exceeds the rated voltage, a ballast resistor is required.



$$R = \frac{E - V_F}{I_F}$$

Where: R = Resistor Value (Ohms)
E = Source Voltage (V)
V_F = Forward Voltage (V)
I_F = Forward Current (A)

Single Element LED		C	D	F
	Color	Red	Amber	Green
Forward Peak Current	I_{FM}	30mA	25mA	25mA
Continuous Forward Current	I_F	20mA	20mA	20mA
Forward Voltage	V_F	1.85V	2.0V	2.25V
Reverse Peak Voltage	V_{RM}	5V	5V	5V
Current Reduction Rate Above 25°C	ΔI_F	0.38mA /°C	0.28mA /°C	0.40mA /°C
Ambient Temperature Range		–25° ~ +50°C		

TYPICAL SWITCH DIMENSIONS



Recommended Panel Thickness Range:
.098" ~ .197"
(2.5mm ~ 5.0mm)

FP0115CAC1FF

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

NKK Switches:

AT021 AT022 AT021X001

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331