


# PLC-RPIT-120UC/21

Order No.: 2900304



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2900304>

PLC interface, consisting of PLC-BPIT.../21 basic terminal block with Push-In connection and pluggable miniature relay with power contact, for assembly on DIN rail NS 35/7.5, 1 PDT, input voltage 120 V AC/110 V DC



## Commercial data

|                          |                                                                                                        |
|--------------------------|--------------------------------------------------------------------------------------------------------|
| GTIN (EAN)               | <br>4 046356 507165 |
| sales group              | G226                                                                                                   |
| Pack                     | 10 pcs.                                                                                                |
| Customs tariff           | 85364900                                                                                               |
| Catalog page information | Page 82 (IF-2011)                                                                                      |

## Product notes

WEEE/RoHS-compliant since:  
05/05/2009



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### Coil side

|                             |                     |
|-----------------------------|---------------------|
| Nominal input voltage $U_N$ | 120 V AC (110 V DC) |
|                             | 110 V DC            |

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Nominal input current at $U_{IN}$ | 3.5 mA (at $U_N = 120$ V AC)      |
|                                   | 3 mA (at $U_N = 110$ V DC)        |
| Typical response time             | 6 ms                              |
| Typical release time              | 15 ms                             |
| Operating voltage display         | Yellow LED                        |
| Protective circuit                | Bridge rectifier Bridge rectifier |

#### Contact side

|                                       |                                                                                                                                                                                                                                               |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Contact type                          | Single contact, 1-PDT                                                                                                                                                                                                                         |
| Contact material                      | AgSnO                                                                                                                                                                                                                                         |
| Maximum switching voltage             | 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...) |
| Minimum switching voltage             | 5 V (at 100 mA)                                                                                                                                                                                                                               |
| Maximum inrush current                | (on request)                                                                                                                                                                                                                                  |
| Min. switching current                | 10 mA (at 12 V)                                                                                                                                                                                                                               |
| Limiting continuous current           | 6 A                                                                                                                                                                                                                                           |
| Interrupting rating (ohmic load) max. | 140 W (at 24 V DC)                                                                                                                                                                                                                            |
|                                       | 20 W (for 48 V DC)                                                                                                                                                                                                                            |
|                                       | 18 W (for 60 V DC)                                                                                                                                                                                                                            |
|                                       | 23 W (for 110 V DC)                                                                                                                                                                                                                           |
|                                       | 40 W (for 220 V DC)                                                                                                                                                                                                                           |
|                                       | 1500 VA (for 250 V AC)                                                                                                                                                                                                                        |

#### General data

|                                          |                         |
|------------------------------------------|-------------------------|
| Width                                    | 6.2 mm                  |
| Height                                   | 80 mm                   |
| Depth                                    | 94 mm                   |
| Test voltage relay winding/relay contact | 4 kV AC (50 Hz, 1 min.) |
| Ambient temperature (operation)          | -40 °C ... 60 °C        |
| Ambient temperature (storage/transport)  | -40 °C ... 85 °C        |
| Operating mode                           | 100% operating factor   |
| Mechanical service life                  | $2 \times 10^7$ cycles  |
| Inflammability class acc. to UL 94       | V0                      |
| Name                                     | Standards/regulations   |

|                        |                                               |
|------------------------|-----------------------------------------------|
| Standards/regulations  | IEC 60664                                     |
|                        | IEC 60664 A                                   |
|                        | DIN VDE 0110                                  |
|                        | DIN EN 50178/DIN VDE 0160 (in relevant parts) |
|                        | DIN EN 50178/VDE 0160                         |
|                        | IEC 60255/DIN VDE 0435 (in relevant parts)    |
| Pollution degree       | 3                                             |
| Surge voltage category | III                                           |
| Mounting position      | Any                                           |
| Assembly instructions  | In rows with zero spacing                     |

#### Connection data

|                                        |                      |
|----------------------------------------|----------------------|
| Connection method                      | Push-In connection   |
| Conductor cross section solid min.     | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.     | 2.5 mm <sup>2</sup>  |
| Conductor cross section stranded min.  | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded max.  | 2.5 mm <sup>2</sup>  |
| Conductor cross section AWG/kcmil min. | 26                   |
| Conductor cross section AWG/kcmil max  | 14                   |
| Stripping length                       | 8 mm                 |

#### Certificates / Approvals



Certification

CUL, CUL Listed, UL, UL Listed

#### Accessories

| Item            | Designation                 | Description                                                                                                                     |
|-----------------|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>Assembly</b> |                             |                                                                                                                                 |
| 0801762         | NS 35/ 7,5 CU UNPERF 2000MM | DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m                                               |
| 0801733         | NS 35/ 7,5 PERF 2000MM      | DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm |

|         |                              |                                                                                                                                                                                                                                                        |
|---------|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0801681 | NS 35/ 7,5 UNPERF 2000MM     | DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m                                                                                                                                                                       |
| 0801377 | NS 35/ 7,5 V2A UNPERF 2000MM | DIN rail, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver                                                                                                                                                                                 |
| 1201756 | NS 35/15 AL UNPERF 2000MM    | DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm                                                                                                                          |
| 1201895 | NS 35/15 CU UNPERF 2000MM    | DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m                                                                                                                                                         |
| 1201730 | NS 35/15 PERF 2000MM         | DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm                                                                                                                         |
| 1201714 | NS 35/15 UNPERF 2000MM       | DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m                                                                                                                                                                        |
| 1201798 | NS 35/15-2,3 UNPERF 2000MM   | DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m                                                                                                                                                          |
| 2966841 | PLC-ATP BK                   | Separating plate, 2 mm thick, required at the start and end of a PLC terminal strip. Furthermore, it is used for: visual separation of groups, safe isolation of different voltages of neighboring PLC relays in acc. with DIN VDE 0106-101, isolation |

**Bridges**

|         |                 |                                                                          |
|---------|-----------------|--------------------------------------------------------------------------|
| 2966812 | FBST 6-PLC BU   | Single plug-in bridge, Length: 6 mm, Number of positions: 2, Color: blue |
| 2966825 | FBST 6-PLC GY   | Single plug-in bridge, Length: 6 mm, Number of positions: 2, Color: gray |
| 2966236 | FBST 6-PLC RD   | Single plug-in bridge, Length: 6 mm, Number of positions: 2, Color: red  |
| 2967688 | FBST 8-PLC GY   | Single plug-in bridge, Length: 8 mm, Number of positions: 2, Color: gray |
| 2966692 | FBST 500-PLC BU | Continuous plug-in bridge, Length: 500 mm, Color: blue                   |
| 2966838 | FBST 500-PLC GY | Continuous plug-in bridge, Length: 500 mm, Color: gray                   |
| 2966786 | FBST 500-PLC RD | Continuous plug-in bridge, Length: 500 mm, Color: red                    |

**General**

|         |                   |                                                                                                                                                             |
|---------|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2900280 | PLC-BPIT-120UC/21 | 6.2 mm PLC basic terminal blocks with Push-In connection method, input voltage of 120 V AC (without relay or optocoupler)                                   |
| 2966508 | PLC-ESK GY        | Power terminal block, for the input of up to four potentials, for mounting on NS 35/7.5                                                                     |
| 2296061 | PLC-V8/D15B/OUT   | V8-OUTPUT adapter for eight 6.2 mm PLC interfaces (1 PDT, etc./see "Additional Products"). 15-pin D-SUB female connector, control logic: Positive switching |
| 2296058 | PLC-V8/D15S/OUT   | V8-OUTPUT adapter for eight 6.2 mm PLC interfaces (1 PDT, etc./see "Additional Products"). 15-pin D-SUB male connector, control logic: Positive switching   |

|         |                    |                                                                                                                                                                                               |
|---------|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2295554 | PLC-V8/FLK14/OUT   | V8-OUTPUT adapter for eight 6.2 mm PLC interfaces (1 PDT, etc./see "Supplementary Products"). 14-pos. flat-ribbon cable connection for the PLC system cabling, control logic: Plus switching  |
| 2304102 | PLC-V8/FLK14/OUT/M | V8-OUTPUT adapter for eight 6.2 mm PLC interfaces (1 PDT, etc./see "Supplementary Products"). 14-pos. flat-ribbon cable connection for the PLC system cabling, control logic: Minus switching |
| 2961118 | REL-MR- 60DC/21    | Pluggable miniature relays, with power contact, 1 PDT, input voltage 60 V DC                                                                                                                  |

#### Marking


|         |                        |                                                                                                                                                                                        |
|---------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1051016 | ZB 6,LGS:FORTL.ZAHLEN  | Zack marker strip, 10-section, printed horizontally: with the numbers 1 - 10, 11 - 20 and so on up to 491 - 500, color: white                                                          |
| 5060935 | ZB 6/WH-100:UNBEDRUCKT | Zack strip, unprinted: For individual labeling with M-PEN, ZB-T or CMS system, large batch, sufficient for labeling 1000 terminal blocks, for a terminal width of 6.2 mm, color: White |
| 1051003 | ZB 6:UNBEDRUCKT        | Zack strip, unprinted, strips with 10 labels for individual labeling with M-PEN or CMS system, for terminal block width: 6.2 mm, color: white                                          |

#### Tools


|         |               |                                                                                                                                                       |
|---------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1204517 | SZF 1-0,6X3,5 | Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip |
|---------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Diagrams/Drawings

##### Diagram




Interrupting rating



Interrupting rating

Circuit diagram

---



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331