



# Precision, Very Low Noise, Low Input Bias Current, Wide Bandwidth JFET Operational Amplifier

Enhanced Product

**AD8512-EP**

## FEATURES

- Fast settling time: 500 ns to 0.1%**
- Low offset voltage: 1.0 mV maximum at  $V_s = \pm 15$  V**
- Low offset voltage drift: 1.7  $\mu$ V/ $^{\circ}$ C typical**
- Low input bias current: 25 pA typical at  $V_s = \pm 15$  V**
- Dual-supply operation:  $\pm 5$  V to  $\pm 15$  V**
- Low noise: 8.0 nV/ $\sqrt{\text{Hz}}$  typical at  $f = 1$  kHz**
- Low distortion: 0.0005%**
- No phase reversal**
- Unity gain stable**

## ENHANCED PRODUCT FEATURES

- Supports defense and aerospace applications (AQEC standard)**
- Military temperature range ( $-55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ )**
- Controlled manufacturing baseline**
- 1 assembly/test site**
- 1 fabrication site**
- Product change notification**
- Qualification data available on request**

## APPLICATIONS

- Instrumentation**
- Multipole filters**
- Precision current measurement**
- Photodiode amplifiers**
- Military communication**
- Avionics**

## GENERAL DESCRIPTION

The AD8512-EP is a dual-precision JFET amplifier that features low offset voltage, input bias current, input voltage noise, and input current noise.

The combination of low offsets, low noise, and very low input bias currents makes these amplifiers especially suitable for high impedance sensor amplification and precise current measurements using shunts. The combination of dc precision, low noise, and fast settling time results in superior accuracy in flight instruments, electronic measurement, and aviation equipment. Unlike many competitive amplifiers, the AD8512-EP maintains its fast settling performance even with substantial capacitive loads. Unlike many older JFET amplifiers, the AD8512-EP does not suffer from output phase reversal when

## PIN CONFIGURATION




Figure 1.

input voltages exceed the maximum common-mode voltage range.

Fast slew rate and great stability with capacitive loads make the AD8512-EP suitable for high performance filters. Low input bias currents, low offset, and low noise result in a wide dynamic range of photodiode amplifier circuits. Low noise and distortion, high output current, and excellent speed make the AD8512-EP a great choice for military communication applications.

The AD8512-EP is available in an 8-lead narrow SOIC\_N package. The AD8512-EP is specified over a military temperature range of  $-55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ . Additional application and technical information can be found in the [AD8512](#) data sheet.

Rev. 0

[Document Feedback](#)

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.  
Tel: 781.329.4700 ©2018 Analog Devices, Inc. All rights reserved.  
[Technical Support](#) [www.analog.com](#)

## TABLE OF CONTENTS

Features .....	1	Absolute Maximum Ratings .....	5
Enhanced Product Features .....	1	Thermal Resistance .....	5
Applications.....	1	ESD Caution.....	5
Pin Configuration.....	1	Typical Performance Characteristics .....	6
General Description .....	1	Outline Dimensions.....	7
Revision History .....	2	Ordering Guide .....	7
Specifications.....	3		
Electrical Characteristics.....	4		

## REVISION HISTORY

8/2018—Revision 0: Initial Version

## SPECIFICATIONS

$V_S = \pm 5$  V,  $V_{CM} = 0$  V,  $T_A = 25^\circ\text{C}$ , unless otherwise noted.

Table 1.

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	$V_{OS}$			0.1	0.9	mV
		$-55^\circ\text{C} < T_A < +125^\circ\text{C}$		1.8		mV
Input Bias Current	$I_B$		21	75		pA
		$-55^\circ\text{C} < T_A < +85^\circ\text{C}$		0.7		nA
		$-55^\circ\text{C} < T_A < +125^\circ\text{C}$		7.5		nA
Input Offset Current	$I_{OS}$		5	50		pA
		$-55^\circ\text{C} < T_A < +85^\circ\text{C}$		0.3		nA
		$-55^\circ\text{C} < T_A < +125^\circ\text{C}$		0.5		nA
Input Capacitance				12.5		pF
Differential				11.5		pF
Common Mode					+2.5	
Input Voltage Range			-2.0			V
Common-Mode Rejection Ratio	CMRR	$V_{CM} = -2.0$ V to $+2.5$ V	86	100		dB
Large-Signal Voltage Gain	$A_{VO}$	$R_L = 2$ k $\Omega$ , $V_O = -3$ V to $+3$ V	65	107		V/mV
Offset Voltage Drift ( $T_C V_{OS}$ )	$\Delta V_{OS}/\Delta T$			1.7	12	$\mu\text{V}/^\circ\text{C}$
OUTPUT CHARACTERISTICS						
Output Voltage High	$V_{OH}$	$R_L = 10$ k $\Omega$	4.1	4.3		V
		$R_L = 2$ k $\Omega$	3.9	4.2		V
		$R_L = 600$ $\Omega$	3.7	4.1		V
Output Voltage Low	$V_{OL}$	$R_L = 10$ k $\Omega$ , $-55^\circ\text{C} < T_A < +125^\circ\text{C}$		-4.9	-4.7	V
		$R_L = 2$ k $\Omega$ , $-55^\circ\text{C} < T_A < +125^\circ\text{C}$		-4.9	-4.5	V
		$R_L = 600$ $\Omega$ , $-55^\circ\text{C} < T_A < +125^\circ\text{C}$		-4.8	-4.2	V
Output Current	$I_{OUT}$		$\pm 40$	$\pm 54$		mA
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	$V_S = \pm 4.5$ V to $\pm 18$ V	86	130		dB
Supply Current/Amplifier	$I_{SY}$	$V_O = 0$ V $-55^\circ\text{C} < T_A < +125^\circ\text{C}$		2.0	2.3	mA
					2.5	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	$R_L = 2$ k $\Omega$		20		V/ $\mu$ s
Gain Bandwidth Product	GBP			8		MHz
Settling Time	$t_s$	To 0.1%, 0 V to 4 V step, $G = +1$		0.4		$\mu$ s
Total Harmonic Distortion (THD) + Noise	THD + N	1 kHz, $G = +1$ , $R_L = 2$ k $\Omega$		0.0005		%
Phase Margin	$\varphi_M$			44.5		Degrees
NOISE PERFORMANCE						
Voltage Noise Density	$e_n$	$f = 10$ Hz		34		$\text{nV}/\sqrt{\text{Hz}}$
		$f = 100$ Hz		12		$\text{nV}/\sqrt{\text{Hz}}$
		$f = 1$ kHz		8.0	10	$\text{nV}/\sqrt{\text{Hz}}$
		$f = 10$ kHz		7.6		$\text{nV}/\sqrt{\text{Hz}}$
Peak-to-Peak Voltage Noise	$e_n$ p-p	0.1 Hz to 10 Hz bandwidth		2.4	5.2	$\mu\text{V}$ p-p

**ELECTRICAL CHARACTERISTICS**

$V_S = \pm 15$  V,  $V_{CM} = 0$  V,  $T_A = 25^\circ\text{C}$ , unless otherwise noted.

**Table 2.**

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	$V_{OS}$	$-55^\circ\text{C} < T_A < +125^\circ\text{C}$	0.1	1.0	1.8	mV
Input Bias Current	$I_B$	$-55^\circ\text{C} < T_A < +85^\circ\text{C}$ $-55^\circ\text{C} < T_A < +125^\circ\text{C}$	25	80	0.7	pA
Input Offset Current	$I_{OS}$	$-55^\circ\text{C} < T_A < +85^\circ\text{C}$ $-55^\circ\text{C} < T_A < +125^\circ\text{C}$	6	75	10	nA
Input Capacitance					0.3	nA
Differential				12.5		pF
Common Mode				11.5		pF
Input Voltage Range			-13.5		+13.0	V
Common-Mode Rejection Ratio	CMRR	$V_{CM} = -12.5$ V to $+12.5$ V	86	108		dB
Large-Signal Voltage Gain	$A_{VO}$	$R_L = 2$ k $\Omega$ , $V_{CM} = 0$ V, $V_O = -13.5$ V to $+13.5$ V	115	196		V/mV
Offset Voltage Drift	$\Delta V_{OS}/\Delta T$			1.7	12	$\mu\text{V}/^\circ\text{C}$
OUTPUT CHARACTERISTICS						
Output Voltage High	$V_{OH}$	$R_L = 10$ k $\Omega$ $R_L = 2$ k $\Omega$ $R_L = 600$ $\Omega$ $R_L = 600$ $\Omega$ , $-55^\circ\text{C} < T_A < +125^\circ\text{C}$	14.0 13.8 13.5 11.4	14.2 14.1 13.9		V
Output Voltage Low	$V_{OL}$	$R_L = 10$ k $\Omega$ , $-55^\circ\text{C} < T_A < +125^\circ\text{C}$ $R_L = 2$ k $\Omega$ , $-55^\circ\text{C} < T_A < +125^\circ\text{C}$ $R_L = 600$ $\Omega$ $R_L = 600$ $\Omega$ , $-55^\circ\text{C} < T_A < +125^\circ\text{C}$		-14.9 -14.8 -14.3	-14.6 -14.5 -13.8 -12.1	V
Output Current	$I_{OUT}$				$\pm 70$	mA
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	$V_S = \pm 4.5$ V to $\pm 18$ V	86			dB
Supply Current/Amplifier	$I_{SY}$	$V_O = 0$ V $-55^\circ\text{C} < T_A < +125^\circ\text{C}$		2.2	2.5	mA
					2.6	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	$R_L = 2$ k $\Omega$		20		$\text{V}/\mu\text{s}$
Gain Bandwidth Product	GBP			8		MHz
Settling Time	$t_s$	To 0.1%, 0 V to 10 V step, $G = +1$ To 0.01%, 0 V to 10 V step, $G = +1$		0.5 0.9		$\mu\text{s}$
Total Harmonic Distortion (THD) + Noise	THD + N	$1$ kHz, $G = +1$ , $R_L = 2$ k $\Omega$		0.0005		%
Phase Margin	$\Phi_M$			52		Degrees
NOISE PERFORMANCE						
Voltage Noise Density	$e_n$	$f = 10$ Hz $f = 100$ Hz $f = 1$ kHz $f = 10$ kHz		34 12 8.0 7.6	10	$\text{nV}/\sqrt{\text{Hz}}$ $\text{nV}/\sqrt{\text{Hz}}$ $\text{nV}/\sqrt{\text{Hz}}$ $\text{nV}/\sqrt{\text{Hz}}$
Peak-to-Peak Voltage Noise	$e_n$ p-p	0.1 Hz to 10 Hz bandwidth		2.4	5.2	$\mu\text{V}$ p-p

## ABSOLUTE MAXIMUM RATINGS

Table 3.

Parameter	Rating
Supply Voltage	$\pm 18\text{ V}$
Input Voltage	$\pm V_S$
Power Dissipation	See Figure 2
Storage Temperature Range	-65°C to +150°C
Operating Temperature Range	-55°C to +125°C
Junction Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 10 sec)	300°C
Electrostatic Discharge (Human Body Model)	2000 V

Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.

## THERMAL RESISTANCE

Thermal performance is directly linked to printed circuit board (PCB) design and operating environment. Careful attention to PCB thermal design is required.

$\theta_{JA}$  is the natural convection junction to ambient thermal resistance measured in a one cubic foot sealed enclosure.  $\theta_{JC}$  is the junction to case thermal resistance.

Table 4. Thermal Resistance

Package Type <sup>1</sup>	$\theta_{JA}$	$\theta_{JC}$	Unit
R-8	158	43	°C/W

<sup>1</sup> Thermal impedance simulated values are based on a JEDEC 2S2P thermal test board. See JEDEC JESD-51.




Figure 2. Maximum Power Dissipation vs. Ambient Temperature

## ESD CAUTION



**ESD (electrostatic discharge) sensitive device.** Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

## TYPICAL PERFORMANCE CHARACTERISTICS




Figure 3.  $T_c V_{OS}$  Distribution




Figure 5. Input Offset Current vs. Temperature




Figure 4. Input Bias Current vs. Temperature





Figure 6. Supply Current per Amplifier vs. Temperature

## OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MS-012-AA  
 CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS  
 (IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR  
 REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

Figure 7. 8-Lead Standard Small Outline Package [SOIC\_N]  
 Narrow Body (R-8)  
 Dimensions shown in millimeters and (inches)

012407-A

## ORDERING GUIDE

Model <sup>1</sup>	Temperature Range	Package Description	Package Option	Marking Code
AD8512TRZ-EP	-55°C to +125°C	8-Lead Standard Small Outline Package [SOIC_N]	R-8	DNL
AD8512TRZ-EP-R7	-55°C to +125°C	8-Lead Standard Small Outline Package [SOIC_N]	R-8	DNL

<sup>1</sup> Z = RoHS Compliant Part



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литер Н,  
помещение 100-Н Офис 331