DRAWING MADE IN THIRD ANGLE PROJECTION

1339780 ⇔ 1339780

/home/eb003653/edmmod

PART NUMBER	REV	FIRST USED	TERMINATOR	FEED TYPE	DESCRIPTION
1339780-1	A		-	BENCH & LEADMAKER	MECH POST FEED	HD-I APPLICATOR
7-1339780-1	A		-	BENCH & LEADMAKER	MECH POST FEED	-1 AND SPARE PARTS
7-1339780-7	A		-	-	-	SPARE PARTS KIT

CRIMP DATA ESCUBEDO TERMINAL AMP CRIMP SPECS △5

TERMINAL NAME: FASTON TYPE 4.8 SERIES.

CRIMP	SIZE	TYPE	RANGE
WIRE	2.03 [.080 IN]	F	0.50mm² - 1.00mm²
INSUL	3.05 [.120 IN]	F	1.80-2.50 [.071-.098 IN]

WIRE STRIP LENGTH 3.91-4.67 [.154-.184 IN]

APPL INSTRUCTION 408-8323

TERMINAL	-	-	FEED
APPL SPEC	NONE	-	17.50 [.689 IN]

TERMINALS APPLIED

AMP PN	MFR PN	-	-	-
1572818-1	4412.00	-	-	-
1572818-2	4412.02	-	-	-
1572818-3	4412.04	-	-	-
1572818-4	4412.30	-	-	-
1572818-5	4412.32	-	-	-
1572818-6	4412.70	-	-	-
-	-	-	-	-


WIRE SIZE mm² AWG	CRIMP HEIGHT	PIN PN AND LENGTH [IN]
1.00mm²	1.55 ±0.05 [.061 ±.002 IN]	354779-3 [.3005]
0.75mm²	1.45 ±0.05 [.057 ±.002 IN]	1-354779-1 [.3045]
0.50mm²	1.35 ±0.05 [.053 ±.002 IN]	2-354779-1 [.3090]
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

△1 RECOMMENDED SPARE PARTS.



2. GREASE RAM, CAM, CAM FOLLOWER AND FEED ROD LIGHTLY.
3. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.

△4 CUT TO LENGTH AT ASSEMBLY.

△5 ALL CRIMP DATA CALCULATED BY TYCO ELECTRONICS UK LTD.



VIEW B ROTATED 180°

POST-FEED 40 mm STROKE	POST-FEED 30 mm STROKE
	
LEADMAKER OR BENCH G	K TERMINATOR BENCH MACHINE

LOC A
DIST 66

-	1	1	1490525-1	DEPRESSOR, WIRE	73
-	1	1	1339780	PRINT, APPLICATOR LOG SHEET	72
-	1	1	1338705-2	DOCUMENTATION PACKAGE	71
-	3	3	2-23147-2	SPRING, DEPRESSOR	70
-	1	1	1490524-2	SPACER, DEPRESSOR	69
					68
-	1	1	461264-1	PLATE, IDENTIFICATION	67
-	2	2	21017-2	SCR,DRIVE(#2X.19)ID PLATE	66
-	1	1	1424350-1	HOLDER, PIN, WIRED	65
-	1	1	986950-1	WASHER, FLAT PRECISION	64
-	1	1	3-18031-0	SCR,SKT SET(M6X6)RAM	63
-	1	1	18023-9	SCR,SKT CAP(M4X6)CP DSC	62
					61
-	1	1	18024-7	SCR,BHC(M4X10)ANVIL	60
					59
-	2	2	1-18023-3	SCR,SHC(M4X16)HOLD DOWN	58
-	5	5	18023-9	SCR,SHC(M4X6)STRIP GUIDE	57
4	-	2	2	1-18023-2	SCR,SHC(M4X12)SLUG BLADE	56
					55
-	2	2	18029-1	NUT,HEX(M3)DRAG	54
-	2	2	986965-1	NUT,HEX SL(M4)DRAG STUD	53
-	2	2	2-18032-2	SCR,SKT SET(M3X10)DRAG	52
					51
					50
-	1	1	18024-3	SCR,BHC(M3X10)CAM	49
					48
-	1	1	1338676-1	CAM, POST-FEED 30 & 40 mm ST	47
-	1	1	1338662-1	APPLICATOR, BASIC (SUBASSY)	46
-	1	1	690191-1	PLUG, NYLON	45
-	1	1	1320998-1	RAM	44
-	1	1	690125-1	WASHER, LAMINATED	43
-	1	1	690124-1	WASHER, RAM	42
-	1	1	2-18024-6	SCREW,BHC(M8X25)CRIMPER	41
-	1	1	23241-1	BALL, STEEL	40
-	1	1	2-22278-7	SPRING, COMPRESSION	39
-	1	1	1320922-1	DISC, INSULATION	38
-	1	1	354777-1	WIRE DISC, PLASTIC	37
-	1	1	22480-5	WASHER, SPRING	36
-	1	1	690212-1	POST, RAM	35
					34
					33
-	9	9	18025-2	WASHER,LOCK(M4)SHEAR BL	32
-	2	2	1-18024-0	SCR,BHC(M4X20)SHEAR PL	31
					30
-	2	2	18024-8	SCR,BHC(M4X12)STRIPPER	29
-	1	1	3-690451-2	SPACER, STRIPPER	28
-	1	1	240639-1	STRIPPER	27
					26
-	2	2	1320906-1	DRAG, STUD	25
-	1	1	1320995-1	PLATE, STRIP GUIDE	24
-	1	1	240825-2	PLATE, STRIP HOLD DOWN	23
-	2	2	4-22281-1	SPRING, DRAG	22
					21
-	1	1	1338665-1	DRAG, STOCK	20
					19
-	2	2	1338663-4	GUIDE, LOWER STRIP	18
-	4	4	1-18024-8	SCR,BHC(M6X12)STRIP GD PL	17
-	1	1	1338708-1	SPACER, SLUG BLADE	16
					15
					14
-	1	1	690481-3	SPACER, HOLD DOWN	13
-	1	1	23846-1	SPRING, HOLD DOWN	12
1	-	1	1	240644-1	PLATE, REAR SHEAR	11
					10
1	-	1	1	690495-6	PLATE, FRONT SHEAR	9
1	1	2	1	2-1333216-5	ANVIL	8
1	-	1	1	690474-4	BLADE, SLUG	7
	-	1	1	2-455892-0	HOLD DOWN, TERMINAL	6
	-	1	1	1-240641-1	SPACER, SLUG BLADE	5
	-	1	1	238009-1	SPACER, BLOCK CRIMPER	4
1	1	2	1	4-1213077-7	CRIMPER, INSULATION	3
						2
1	1	2	1	1-456405-5	CRIMPER, WIRE	1

	-77	-71	-1	PART NO	DESCRIPTION	ITEM NO
				← REVISION OF EACH ASSY NO (WHEN BLANK, USE DWG REVISION)		
QTY REQD PER ASSY				PARTS LIST		

P	F	LTR	REVISION RECORD	APP	DATE
		A	SEE ECO-05-013159	LJL	NOV05

DIMENSIONS: mm [INCHES]
DO NOT SCALE PRINT.
TOLERANCES UNLESS OTHERWISE SPECIFIED:
1 PLC DEC ±-
2 PLC DEC ±-
3 PLC DEC ±-
ANGLES ± -
SURF TEXTURE: √
REMOVE BURRS, BREAK SHARP EDGES RO.38 MAX

MATL - | HT TR - | FIN -

DR 030CT05 L.LOFTHOUSE | APP 030CT05 F.BACKHURST
CHK - | REL 07NOV05 L.LOFTHOUSE

AMP Tyco Electronics Harrisburg, PA 17105-3608

NAME END FEED HD-I APPLICATOR | MACHINE REF HD-I APPL

SCALE - | D | DWG NO 1339780 | SHEET 1 OF 1 | REV A

CAGE CODE 00779 | CUSTOMER AND ASSEMBLY DRAWING | RESTRICTED TO -

LAYOUT 1339780
SET UP GAGE 458638-3

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION .20 .
© COPYRIGHT 20 BY AMP INCORPORATED. ALL RIGHTS RESERVED.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331