

# UHW

Miniature Sized, High Ripple Current,  
High Reliability



Smaller



Low Impedance




Long Life



Anti-Solvent  
Feature


- Lower impedance at high frequency range.
- Smaller case size and high ripple current.
- Compliant to the RoHS directive (2011/65/EU,(EU)2015/863).




## Specifications

| Item                          | Performance Characteristics                                                                                                                                                                             |                 |                                                                |      |             |      |             |      |             |      |      |       |   |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------------------------------------------------------------|------|-------------|------|-------------|------|-------------|------|------|-------|---|
| Category Temperature Range    | -40 to +105°C                                                                                                                                                                                           |                 |                                                                |      |             |      |             |      |             |      |      |       |   |
| Rated Voltage Range           | 6.3 to 100V                                                                                                                                                                                             |                 |                                                                |      |             |      |             |      |             |      |      |       |   |
| Rated Capacitance Range       | 8.2 to 15000μF                                                                                                                                                                                          |                 |                                                                |      |             |      |             |      |             |      |      |       |   |
| Capacitance Tolerance         | ±20% at 120Hz, 20°C                                                                                                                                                                                     |                 |                                                                |      |             |      |             |      |             |      |      |       |   |
| Leakage Current               | After 2 minutes' application of rated voltage at 20°C, leakage current is not more than 0.01CV (μA)                                                                                                     |                 |                                                                |      |             |      |             |      |             |      |      |       |   |
| Tangent of loss angle (tan δ) | Rated voltage (V)                                                                                                                                                                                       |                 | 6.3                                                            | 10   | 16          | 25   | 35          | 50   | 63          | 80   | 100  | 120Hz |   |
|                               | tan δ (MAX.)                                                                                                                                                                                            |                 | 0.21                                                           | 0.18 | 0.15        | 0.13 | 0.11        | 0.10 | 0.09        | 0.09 | 0.08 | 20°C  |   |
|                               | For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF.                                                                                                                             |                 |                                                                |      |             |      |             |      |             |      |      |       |   |
| Stability at Low Temperature  | Rated voltage (V)                                                                                                                                                                                       |                 | 6.3                                                            | 10   | 16          | 25   | 35          | 50   | 63          | 80   | 100  | 120Hz |   |
|                               | Impedance ratio (MAX.)                                                                                                                                                                                  | Z-25°C / Z+20°C | 2                                                              | 2    | 2           | 2    | 2           | 2    | 2           | 2    | 2    |       |   |
|                               |                                                                                                                                                                                                         | Z-40°C / Z+20°C | φD ≤ 6.3                                                       | 5    | 5           | 4    | 4           | 4    | 4           | 3    | 3    |       | 3 |
|                               |                                                                                                                                                                                                         | φ ≥ 8           | 3                                                              | 3    | 3           | 3    | 3           | 3    |             |      |      |       |   |
| Endurance                     | The following specifications shall be met when the capacitors are restored to 20°C after D.C. bias plus rated ripple current is applied at 105°C , the peak voltage shall not exceed the rated voltage. |                 |                                                                |      |             |      |             |      |             |      |      |       |   |
|                               | Case size                                                                                                                                                                                               |                 | φD ≤ 6.3                                                       |      | 8×11.5      |      | 8×15 , 8×20 |      | φD ≥ 10     |      |      |       |   |
|                               | Rated voltage (V)                                                                                                                                                                                       | 6.3V            | 6000 hours                                                     |      | 8000 hours  |      | 9000 hours  |      | 10000 hours |      |      |       |   |
|                               |                                                                                                                                                                                                         | 10 to 50V       | 7000 hours                                                     |      | 9000 hours  |      | 10000 hours |      | 10000 hours |      |      |       |   |
|                               |                                                                                                                                                                                                         | 63 to 100V      | 8000 hours                                                     |      | 10000 hours |      | 11000 hours |      | 12000 hours |      |      |       |   |
|                               | Capacitance change                                                                                                                                                                                      |                 | Within ±25% of the initial capacitance value (6.3V 10V : ±30%) |      |             |      |             |      |             |      |      |       |   |
|                               | tan δ                                                                                                                                                                                                   |                 | 200% or less than the initial specified value                  |      |             |      |             |      |             |      |      |       |   |
|                               | Leakage current                                                                                                                                                                                         |                 | Less than or equal to the initial specified value              |      |             |      |             |      |             |      |      |       |   |
| Marking                       | Printed with white color letter on black sleeve.                                                                                                                                                        |                 |                                                                |      |             |      |             |      |             |      |      |       |   |

## Radial Lead Type



## Type numbering system (Example : 16V 2200µF)



### ※ Configuration

| φ D        | Pb-free leadwire<br>Pb-free PET sleeve |
|------------|----------------------------------------|
| 5          | DD                                     |
| 6.3        | ED                                     |
| 8 - 10     | PD                                     |
| 12.5 to 18 | HD                                     |

- Please refer to page 20 about the end seal configuration.

## Frequency coefficient of rated ripple current

| Cap. (µF)     | Frequency | 120Hz | 1kHz | 10kHz | 10kHz or more |
|---------------|-----------|-------|------|-------|---------------|
| 8.2 to 33     |           | 0.40  | 0.70 | 0.90  | 1.00          |
| 39 to 180     |           | 0.40  | 0.75 | 0.90  | 1.00          |
| 220 to 560    |           | 0.50  | 0.85 | 0.94  | 1.00          |
| 680 to 1800   |           | 0.60  | 0.87 | 0.95  | 1.00          |
| 2200 to 3900  |           | 0.75  | 0.90 | 0.95  | 1.00          |
| 4700 to 15000 |           | 0.85  | 0.95 | 0.98  | 1.00          |

Please refer to page 20, 21, 22 about the formed or taped product spec.  
Please refer to page 4 for the minimum order quantity.

• Dimension table in next page.

UHW

## ■ Dimensions

| Cap.(μF)<br>Code |     | V (Code) |                             | 6.3 (0J)           |               |                                          | 10 (1A)            |               |                                          |      |
|------------------|-----|----------|-----------------------------|--------------------|---------------|------------------------------------------|--------------------|---------------|------------------------------------------|------|
|                  |     | Item     | Case size<br>φD × L<br>(mm) | Impedance (Ω) MAX. |               | Rated ripple<br>(mArms)<br>105°C /100kHz | Impedance (Ω) MAX. |               | Rated ripple<br>(mArms)<br>105°C /100kHz |      |
|                  |     |          |                             | 20°C /100kHz       | -10°C /100kHz |                                          | 20°C /100kHz       | -10°C /100kHz |                                          |      |
| 150              | 151 |          |                             |                    |               |                                          |                    |               |                                          |      |
| 220              | 221 |          | 5 × 11                      | 0.47               | 1.50          | 450                                      |                    |               |                                          |      |
| 330              | 331 |          |                             |                    |               |                                          | 6.3 × 11           | 0.20          | 0.66                                     | 700  |
| 470              | 471 |          | 6.3 × 11                    | 0.20               | 0.66          | 700                                      |                    |               |                                          |      |
| 560              | 561 |          |                             |                    |               |                                          | 8 × 11.5           | 0.10          | 0.36                                     | 1200 |
| 680              | 681 |          |                             |                    |               |                                          |                    |               |                                          |      |
| 820              | 821 |          | 8 × 11.5                    | 0.10               | 0.36          | 1200                                     | 8 × 15             | 0.054         | 0.17                                     | 1600 |
| 1000             | 102 |          | 8 × 15                      | 0.054              | 0.17          | 1600                                     | 10 × 12.5          | 0.048         | 0.15                                     | 1700 |
| 1200             | 122 |          | 10 × 12.5                   | 0.048              | 0.15          | 1700                                     | ▲8 × 20            | 0.038         | 0.12                                     | 1960 |
|                  |     |          |                             |                    |               |                                          | 10 × 16            | 0.030         | 0.090                                    | 2000 |
| 1500             | 152 |          | 8 × 20                      | 0.038              | 0.12          | 1960                                     | 10 × 16            | 0.030         | 0.090                                    | 2000 |
| 1800             | 182 |          | 10 × 16                     | 0.030              | 0.090         | 2000                                     | 10 × 20            | 0.020         | 0.060                                    | 2500 |
| 2200             | 222 |          | 10 × 20                     | 0.020              | 0.060         | 2500                                     | 10 × 25            | 0.017         | 0.051                                    | 2900 |
| 2700             | 272 |          | 10 × 20                     | 0.020              | 0.060         | 2500                                     | 12.5 × 20          | 0.017         | 0.051                                    | 2600 |
| 3300             | 332 |          | 10 × 25                     | 0.017              | 0.051         | 2900                                     | 12.5 × 20          | 0.017         | 0.051                                    | 2600 |
| 3900             | 392 |          | 12.5 × 20                   | 0.017              | 0.051         | 2600                                     | 12.5 × 25          | 0.015         | 0.045                                    | 3200 |
| 4700             | 472 |          | 12.5 × 25                   | 0.015              | 0.045         | 3200                                     | 12.5 × 31.5        | 0.012         | 0.036                                    | 3795 |
|                  |     |          |                             |                    |               |                                          | ▲16 × 20           | 0.015         | 0.045                                    | 3575 |
| 5600             | 562 |          | 12.5 × 31.5                 | 0.012              | 0.036         | 3795                                     | 12.5 × 35.5        | 0.011         | 0.033                                    | 4120 |
|                  |     |          | ▲12.5 × 25                  | 0.015              | 0.045         | 3200                                     | ▲16 × 25           | 0.013         | 0.039                                    | 3810 |
| 6800             | 682 |          | 12.5 × 31.5                 | 0.012              | 0.033         | 3795                                     |                    |               |                                          |      |
|                  |     |          | ▲16 × 20                    | 0.015              | 0.045         | 3575                                     | 16 × 25            | 0.013         | 0.039                                    | 3810 |
| 8200             | 822 |          | 16 × 25                     | 0.013              | 0.039         | 3810                                     | 16 × 31.5          | 0.011         | 0.033                                    | 4000 |
| 10000            | 103 |          | 16 × 25                     | 0.013              | 0.039         | 3810                                     | 16 × 31.5          | 0.011         | 0.033                                    | 4000 |
| 12000            | 123 |          | 16 × 31.5                   | 0.011              | 0.033         | 4000                                     | 16 × 35.5          | 0.010         | 0.030                                    | 4200 |
| 15000            | 153 |          | 16 × 35.5                   | 0.010              | 0.030         | 4200                                     |                    |               |                                          |      |

| Cap.(μF)<br>Code |     | V (Code) |                             | 16 (1C)            |               |                                          | 25 (1E)            |               |                                          |      |
|------------------|-----|----------|-----------------------------|--------------------|---------------|------------------------------------------|--------------------|---------------|------------------------------------------|------|
|                  |     | Item     | Case size<br>φD × L<br>(mm) | Impedance (Ω) MAX. |               | Rated ripple<br>(mArms)<br>105°C /100kHz | Impedance (Ω) MAX. |               | Rated ripple<br>(mArms)<br>105°C /100kHz |      |
|                  |     |          |                             | 20°C /100kHz       | -10°C /100kHz |                                          | 20°C /100kHz       | -10°C /100kHz |                                          |      |
| 68               | 680 |          |                             |                    |               |                                          |                    |               |                                          |      |
| 120              | 121 |          | 5 × 11                      | 0.47               | 1.50          | 450                                      |                    |               |                                          |      |
| 150              | 151 |          |                             |                    |               |                                          | 6.3 × 11           | 0.20          | 0.66                                     | 700  |
| 180              | 181 |          |                             |                    |               |                                          | 6.3 × 11           | 0.20          | 0.66                                     | 700  |
| 270              | 271 |          | 6.3 × 11                    | 0.20               | 0.66          | 700                                      |                    |               |                                          |      |
| 330              | 331 |          |                             |                    |               |                                          | 8 × 11.5           | 0.10          | 0.36                                     | 1200 |
| 390              | 391 |          |                             |                    |               |                                          | 8 × 15             | 0.054         | 0.17                                     | 1600 |
| 470              | 471 |          | 8 × 11.5                    | 0.10               | 0.36          | 1200                                     | 10 × 12.5          | 0.048         | 0.15                                     | 1700 |
| 560              | 561 |          | 8 × 15                      | 0.054              | 0.17          | 1600                                     | 8 × 20             | 0.038         | 0.12                                     | 1960 |
| 680              | 681 |          | 10 × 12.5                   | 0.048              | 0.15          | 1700                                     | 10 × 16            | 0.030         | 0.090                                    | 2000 |
| 820              | 821 |          | ▲8 × 20                     | 0.038              | 0.12          | 1960                                     | 10 × 20            | 0.020         | 0.060                                    | 2500 |
|                  |     |          | 10 × 16                     | 0.030              | 0.090         | 2000                                     | ▲10 × 16           | 0.030         | 0.090                                    | 2000 |
| 1000             | 102 |          | ▲8 × 20                     | 0.038              | 0.12          | 1960                                     |                    |               |                                          |      |
|                  |     |          | 10 × 16                     | 0.030              | 0.090         | 2000                                     | 10 × 20            | 0.020         | 0.060                                    | 2500 |
| 1200             | 122 |          | 10 × 20                     | 0.020              | 0.060         | 2500                                     |                    |               |                                          |      |
|                  |     |          | ▲10 × 16                    | 0.030              | 0.090         | 2000                                     | 10 × 25            | 0.017         | 0.051                                    | 2900 |
| 1500             | 152 |          | 10 × 20                     | 0.020              | 0.060         | 2500                                     | 12.5 × 20          | 0.017         | 0.051                                    | 2600 |
| 1800             | 182 |          | 10 × 25                     | 0.017              | 0.051         | 2900                                     | 12.5 × 25          | 0.015         | 0.045                                    | 3200 |
| 2200             | 222 |          | 12.5 × 20                   | 0.017              | 0.051         | 2600                                     | 12.5 × 25          | 0.015         | 0.045                                    | 3200 |
|                  |     |          |                             |                    |               |                                          | ▲16 × 20           | 0.015         | 0.045                                    | 3575 |
| 2700             | 272 |          | 12.5 × 25                   | 0.015              | 0.045         | 3200                                     | 12.5 × 31.5        | 0.012         | 0.036                                    | 3795 |
|                  |     |          |                             |                    |               |                                          | ▲16 × 20           | 0.015         | 0.045                                    | 3575 |
| 3300             | 332 |          | 12.5 × 25                   | 0.015              | 0.045         | 3200                                     | 12.5 × 35.5        | 0.011         | 0.033                                    | 4120 |
|                  |     |          | ▲16 × 20                    | 0.015              | 0.045         | 3575                                     | ▲16 × 25           | 0.013         | 0.039                                    | 3810 |
| 3900             | 392 |          | 12.5 × 31.5                 | 0.012              | 0.036         | 3795                                     |                    |               |                                          |      |
|                  |     |          | ▲16 × 20                    | 0.015              | 0.045         | 3575                                     | 16 × 25            | 0.013         | 0.039                                    | 3810 |
| 4700             | 472 |          | 12.5 × 35.5                 | 0.011              | 0.033         | 4120                                     |                    |               |                                          |      |
|                  |     |          | ▲16 × 25                    | 0.013              | 0.039         | 3810                                     | 16 × 31.5          | 0.011         | 0.033                                    | 4000 |
| 5600             | 562 |          | 16 × 25                     | 0.013              | 0.039         | 3810                                     | 16 × 35.5          | 0.010         | 0.030                                    | 4200 |
| 6800             | 682 |          | 16 × 31.5                   | 0.011              | 0.033         | 4000                                     |                    |               |                                          |      |
| 8200             | 822 |          | 16 × 35.5                   | 0.010              | 0.030         | 4200                                     |                    |               |                                          |      |

UHW

## ■ Dimensions

| Cap.(μF)<br><div>Code</div> |     | V (Code)<br><div>Item</div> | 35 (1V)                     |                    |              |                                         | 50 (1H)                     |                    |              |                                         |
|-----------------------------|-----|-----------------------------|-----------------------------|--------------------|--------------|-----------------------------------------|-----------------------------|--------------------|--------------|-----------------------------------------|
|                             |     |                             | Case size<br>φD × L<br>(mm) | Impedance (Ω) MAX. |              | Rated ripple<br>(mArms)<br>105℃ /100kHz | Case size<br>φD × L<br>(mm) | Impedance (Ω) MAX. |              | Rated ripple<br>(mArms)<br>105℃ /100kHz |
|                             |     |                             |                             | 20℃ /100kHz        | −10℃ /100kHz |                                         |                             | 20℃ /100kHz        | −10℃ /100kHz |                                         |
| 27                          | 270 |                             |                             |                    |              |                                         |                             |                    |              |                                         |
| 47                          | 470 | 5 × 11                      | 0.47                        | 1.50               | 450          | 5 × 11                                  | 0.47                        | 1.50               | 450          |                                         |
| 56                          | 560 |                             |                             |                    |              | 6.3 × 11                                | 0.20                        | 0.66               | 700          |                                         |
| 100                         | 101 | 6.3× 11                     | 0.20                        | 0.66               | 700          | 8 × 11.5                                | 0.10                        | 0.36               | 1200         |                                         |
| 120                         | 121 |                             |                             |                    |              | 8 × 11.5                                | 0.10                        | 0.36               | 1200         |                                         |
| 150                         | 151 |                             |                             |                    |              | 8 × 15                                  | 0.054                       | 0.17               | 1600         |                                         |
| 180                         | 181 | 8 × 11.5                    | 0.10                        | 0.36               | 1200         | 10 × 12.5                               | 0.048                       | 0.15               | 1700         |                                         |
| 220                         | 221 | 8 × 15                      | 0.054                       | 0.17               | 1600         | ▲10 × 12.5                              | 0.048                       | 0.15               | 1700         |                                         |
|                             |     |                             |                             |                    |              | 10 × 16                                 | 0.042                       | 0.126              | 1650         |                                         |
| 270                         | 271 | 8 × 15                      | 0.054                       | 0.17               | 1600         | ▲8 × 20                                 | 0.038                       | 0.12               | 1960         |                                         |
|                             |     | ▲10 × 12.5                  | 0.048                       | 0.15               | 1700         | 10 × 20                                 | 0.030                       | 0.090              | 2060         |                                         |
| 330                         | 331 | 10 × 12.5                   | 0.048                       | 0.15               | 1700         | 10 × 20                                 | 0.030                       | 0.090              | 2060         |                                         |
| 390                         | 391 | ▲8 × 20                     | 0.038                       | 0.12               | 1960         | 10 × 25                                 | 0.028                       | 0.084              | 2420         |                                         |
|                             |     | 10 × 16                     | 0.030                       | 0.090              | 2000         | ▲10 × 20                                | 0.030                       | 0.090              | 2060         |                                         |
| 470                         | 471 | 10 × 16                     | 0.030                       | 0.090              | 2000         | 10 × 25                                 | 0.028                       | 0.084              | 2420         |                                         |
|                             |     |                             |                             |                    |              | ▲12.5 × 20                              | 0.027                       | 0.081              | 2300         |                                         |
| 560                         | 561 | 10 × 20                     | 0.020                       | 0.060              | 2500         | 12.5 × 20                               | 0.027                       | 0.081              | 2300         |                                         |
| 680                         | 681 | 10 × 25                     | 0.017                       | 0.051              | 2900         | 12.5 × 25                               | 0.023                       | 0.069              | 2800         |                                         |
|                             |     | ▲10 × 20                    | 0.020                       | 0.060              | 2500         |                                         |                             |                    |              |                                         |
| 820                         | 821 | 10 × 25                     | 0.017                       | 0.051              | 2900         | 12.5 × 25                               | 0.023                       | 0.069              | 2800         |                                         |
|                             |     | ▲12.5 × 20                  | 0.017                       | 0.051              | 2600         | ▲16 × 20                                | 0.023                       | 0.069              | 3070         |                                         |
| 1000                        | 102 | 12.5 × 20                   | 0.017                       | 0.051              | 2600         | 12.5 × 31.5                             | 0.020                       | 0.060              | 3500         |                                         |
|                             |     |                             |                             |                    |              | ▲16 × 25                                | 0.021                       | 0.063              | 3270         |                                         |
| 1200                        | 122 | 12.5 × 25                   | 0.015                       | 0.045              | 3200         | 16 × 25                                 | 0.021                       | 0.063              | 3270         |                                         |
| 1500                        | 152 | 16 × 20                     | 0.015                       | 0.045              | 3575         | 12.5 × 35.5                             | 0.019                       | 0.057              | 3810         |                                         |
|                             |     |                             |                             |                    |              | ▲16 × 25                                | 0.021                       | 0.063              | 3270         |                                         |
| 1800                        | 182 | 12.5 × 31.5                 | 0.012                       | 0.036              | 3795         | 16 × 31.5                               | 0.019                       | 0.057              | 3430         |                                         |
|                             |     | ▲16 × 25                    | 0.013                       | 0.039              | 3810         |                                         |                             |                    |              |                                         |
| 2200                        | 222 | 12.5 × 35.5                 | 0.011                       | 0.033              | 4120         | 16 × 31.5                               | 0.019                       | 0.057              | 3430         |                                         |
|                             |     | ▲16 × 25                    | 0.013                       | 0.039              | 3810         |                                         |                             |                    |              |                                         |
| 2700                        | 272 |                             |                             |                    |              | 16 × 35.5                               | 0.018                       | 0.054              | 3600         |                                         |
| 3300                        | 332 | 16 × 31.5                   | 0.011                       | 0.033              | 4000         |                                         |                             |                    |              |                                         |
| 3900                        | 392 | 16 × 35.5                   | 0.010                       | 0.030              | 4200         |                                         |                             |                    |              |                                         |

▲ : In this case, [6] will be put at 12th digit of type numbering system.

UHW

## ■ Dimensions

| Cap.(μF) | Code | Item | 63 (1J)                     |                    |               |                                          | 80 (1K)                     |                    |               |                                          |
|----------|------|------|-----------------------------|--------------------|---------------|------------------------------------------|-----------------------------|--------------------|---------------|------------------------------------------|
|          |      |      | Case size<br>φD × L<br>(mm) | Impedance (Ω) MAX. |               | Rated ripple<br>(mArms)<br>105°C /100kHz | Case size<br>φD × L<br>(mm) | Impedance (Ω) MAX. |               | Rated ripple<br>(mArms)<br>105°C /100kHz |
|          |      |      |                             | 20°C /100kHz       | -10°C /100kHz |                                          |                             | 20°C /100kHz       | -10°C /100kHz |                                          |
| 12       | 120  |      |                             |                    |               |                                          | 5 × 11                      | 1.20               | 5.40          | 310                                      |
| 18       | 180  |      | 5 × 11                      | 1.20               | 5.40          | 310                                      |                             |                    |               |                                          |
| 27       | 270  |      |                             |                    |               |                                          | 6.3 × 11                    | 0.46               | 2.10          | 500                                      |
| 39       | 390  |      | 6.3 × 11                    | 0.46               | 2.10          | 500                                      |                             |                    |               |                                          |
| 47       | 470  |      | 6.3 × 11                    | 0.46               | 2.10          | 500                                      | 8 × 11.5                    | 0.29               | 1.30          | 950                                      |
| 68       | 680  |      | 8 × 11.5                    | 0.29               | 1.30          | 950                                      | 8 × 15                      | 0.20               | 0.90          | 1230                                     |
| 82       | 820  |      | 8 × 11.5                    | 0.29               | 1.30          | 950                                      | 10 × 12.5                   | 0.17               | 0.66          | 1280                                     |
| 100      | 101  |      | 8 × 15                      | 0.20               | 0.90          | 1230                                     | 8 × 20                      | 0.16               | 0.66          | 1580                                     |
| 120      | 121  |      | 8 × 15                      | 0.20               | 0.90          | 1230                                     | 10 × 16                     | 0.115              | 0.47          | 1040                                     |
|          |      |      | ▲10 × 12.5                  | 0.17               | 0.66          | 1280                                     |                             |                    |               |                                          |
|          |      |      | 8 × 20                      | 0.16               | 0.66          | 1580                                     |                             |                    |               |                                          |
| 150      | 151  |      | ▲10 × 12.5                  | 0.17               | 0.66          | 1280                                     |                             |                    |               |                                          |
| 180      | 181  |      | ▲8 × 20                     | 0.16               | 0.66          | 1580                                     | 10 × 20                     | 0.088              | 0.34          | 1430                                     |
|          |      |      | 10 × 16                     | 0.115              | 0.47          | 1200                                     | ▲12.5 × 15                  | 0.115              | 0.47          | 1430                                     |
| 220      | 221  |      |                             |                    |               |                                          | 10 × 25                     | 0.072              | 0.28          | 1620                                     |
| 270      | 271  |      | 10 × 20                     | 0.088              | 0.34          | 1570                                     | 10 × 31.5                   | 0.063              | 0.18          | 1750                                     |
|          |      |      |                             |                    |               |                                          | ▲12.5 × 20                  | 0.065              | 0.18          | 1750                                     |
| 330      | 331  |      | 10 × 25                     | 0.072              | 0.28          | 1990                                     |                             |                    |               |                                          |
| 390      | 391  |      | 10 × 31.5                   | 0.063              | 0.18          | 2050                                     | 12.5 × 25                   | 0.049              | 0.14          | 2210                                     |
|          |      |      | ▲12.5 × 20                  | 0.065              | 0.18          | 1990                                     |                             |                    |               |                                          |
|          |      |      |                             |                    |               |                                          |                             |                    |               |                                          |
| 470      | 471  |      |                             |                    |               |                                          | 12.5 × 31.5                 | 0.044              | 0.13          | 2400                                     |
|          |      |      |                             |                    |               |                                          | ▲16 × 20                    | 0.050              | 0.15          | 1950                                     |
| 560      | 561  |      | 12.5 × 25                   | 0.049              | 0.14          | 2460                                     | 12.5 × 35.5                 | 0.038              | 0.11          | 2600                                     |
|          |      |      |                             |                    |               |                                          | ▲18 × 20                    | 0.047              | 0.14          | 2270                                     |
| 680      | 681  |      | 12.5 × 31.5                 | 0.044              | 0.13          | 2760                                     | 12.5 × 40                   | 0.033              | 0.095         | 2860                                     |
|          |      |      | ▲16 × 20                    | 0.050              | 0.15          | 2380                                     | ▲16 × 25                    | 0.040              | 0.12          | 2430                                     |
| 820      | 821  |      | 12.5 × 35.5                 | 0.038              | 0.11          | 3040                                     | 16 × 31.5                   | 0.033              | 0.095         | 2640                                     |
|          |      |      | ▲18 × 20                    | 0.047              | 0.14          | 2460                                     | ▲18 × 25                    | 0.038              | 0.11          | 2500                                     |
| 1000     | 102  |      | 12.5 × 40                   | 0.033              | 0.095         | 3100                                     | 16 × 35.5                   | 0.030              | 0.086         | 2860                                     |
|          |      |      | ▲16 × 25                    | 0.040              | 0.12          | 2890                                     |                             |                    |               |                                          |
|          |      |      |                             |                    |               |                                          |                             |                    |               |                                          |
| 1200     | 122  |      | 16 × 31.5                   | 0.025              | 0.072         | 2930                                     | 16 × 40                     | 0.028              | 0.081         | 3510                                     |
|          |      |      | ▲18 × 25                    | 0.038              | 0.11          | 2930                                     | ▲18 × 31.5                  | 0.031              | 0.090         | 2860                                     |
| 1500     | 152  |      | 16 × 35.5                   | 0.023              | 0.066         | 3100                                     | 18 × 35.5                   | 0.028              | 0.081         | 3510                                     |
|          |      |      | ▲18 × 31.5                  | 0.024              | 0.069         | 3100                                     |                             |                    |               |                                          |
|          |      |      |                             |                    |               |                                          |                             |                    |               |                                          |
| 1800     | 182  |      | 16 × 40                     | 0.021              | 0.060         | 3510                                     | 18 × 40                     | 0.027              | 0.076         | 3860                                     |
|          |      |      | ▲18 × 35.5                  | 0.022              | 0.063         | 3510                                     |                             |                    |               |                                          |
| 2200     | 222  |      | 18 × 40                     | 0.020              | 0.057         | 3860                                     |                             |                    |               |                                          |

| Cap.(μF) | Code | Item | 100 (2A)                    |                    |               |                                          |
|----------|------|------|-----------------------------|--------------------|---------------|------------------------------------------|
|          |      |      | Case size<br>φD × L<br>(mm) | Impedance (Ω) MAX. |               | Rated ripple<br>(mArms)<br>105°C /100kHz |
|          |      |      |                             | 20°C /100kHz       | -10°C /100kHz |                                          |
| 8.2      | 8R2  |      | 5 × 11                      | 1.20               | 5.40          | 310                                      |
| 18       | 180  |      | 6.3 × 11                    | 0.46               | 2.10          | 500                                      |
| 33       | 330  |      | 8 × 11.5                    | 0.29               | 1.30          | 950                                      |
| 47       | 470  |      | 8 × 15                      | 0.20               | 0.90          | 1230                                     |
| 56       | 560  |      | 10 × 12.5                   | 0.17               | 0.66          | 1280                                     |
| 68       | 680  |      | 8 × 20                      | 0.16               | 0.66          | 1580                                     |
| 82       | 820  |      | 10 × 16                     | 0.115              | 0.47          | 1040                                     |
| 100      | 101  |      | 10 × 20                     | 0.088              | 0.34          | 1430                                     |
|          |      |      | ▲12.5 × 15                  | 0.115              | 0.47          | 1430                                     |
| 120      | 121  |      | 10 × 25                     | 0.072              | 0.28          | 1620                                     |
| 180      | 181  |      | 12.5 × 20                   | 0.065              | 0.18          | 1750                                     |
| 220      | 221  |      | 12.5 × 25                   | 0.049              | 0.14          | 2210                                     |
| 270      | 271  |      | 12.5 × 31.5                 | 0.044              | 0.13          | 2400                                     |
|          |      |      | ▲16 × 20                    | 0.050              | 0.15          | 1950                                     |
| 390      | 391  |      | 12.5 × 35.5                 | 0.038              | 0.11          | 2600                                     |
|          |      |      | ▲16 × 25                    | 0.040              | 0.12          | 2430                                     |
|          |      |      | ●18 × 20                    | 0.047              | 0.14          | 2270                                     |
| 470      | 471  |      | 12.5 × 40                   | 0.033              | 0.095         | 2860                                     |
|          |      |      | ▲18 × 25                    | 0.038              | 0.11          | 2500                                     |
| 560      | 561  |      | 16 × 31.5                   | 0.033              | 0.095         | 2640                                     |
| 680      | 681  |      | 16 × 35.5                   | 0.030              | 0.086         | 2860                                     |
|          |      |      | ▲18 × 31.5                  | 0.031              | 0.090         | 2860                                     |
| 820      | 821  |      | 16 × 40                     | 0.028              | 0.081         | 3510                                     |
|          |      |      | ▲18 × 35.5                  | 0.028              | 0.081         | 3510                                     |
| 1000     | 102  |      | 18 × 40                     | 0.027              | 0.076         | 3860                                     |

▲: In this case, [6] will be put at 12th digit of type numbering system.

●: In this case, [3] will be put at 12th digit of type numbering system.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331