

# R15

## Industrial Electromagnetic Relays



- Contacts AgNi
- For plug-in sockets, 35 mm rail mount or on panel mounting.
- Cadmium-free contacts-R15 DPDT, R15 3PDT, R15 4PDT relays
- WT (mechanical indicator and lockable front test button) - standard features of R15 DPDT, R15 3PDT relays in cover, for plug-in sockets.
- Relays may be provided with the test buttons (no latching) and plugs (see page 115).
- AUCOTEAM, GmbH Berlin - railway standards.



### Contact Data

| Number and type of contacts       |      | DPDT                                                    | 3PDT                                                    | 4PDT                                                    |
|-----------------------------------|------|---------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------|
| Contact material                  |      | AgNi                                                    | AgNi                                                    | AgCdO                                                   |
| Rated / max. switching voltage AC |      | 250 V / 440 V                                           | 250 V / 440 V                                           | 250 V / 440 V                                           |
| Min. switching voltage            |      | 10 V                                                    | 10 V                                                    | 10 V                                                    |
| Rated load (capacity)             | AC1  | 10 A / 250 V AC; 10 A / 277 V AC UL 508                 | 10 A / 250 V AC; 10 A / 277 V AC UL 508                 | 10 A / 250 V AC; 10 A / 277 V AC UL 508                 |
|                                   | AC15 | 3 A / 120 V; 1.5 A / 240 V (B300)                       | 3 A / 120 V; 1.5 A / 240 V (B300)                       | 3 A / 120 V; 1.5 A / 240 V (B300)                       |
|                                   | AC3  | 370 W (single-phase motor.<br>1/2 HP / 240 V AC UL 508) | 370 W (single-phase motor.<br>1/2 HP / 240 V AC UL 508) | 370 W (single-phase motor.<br>1/2 HP / 240 V AC UL 508) |
|                                   | DC1  | 10 A / 24 V DC (see Fig. 3)                             | 10 A / 24 V DC (see Fig. 3)                             | 10 A / 24 V DC (see Fig. 3)                             |
|                                   | DC13 | 0.22 A / 120 V; 0.1 A / 250 V (R300)                    | 0.22 A / 120 V; 0.1 A / 250 V (R300)                    | 0.22 A / 120 V; 0.1 A / 250 V (R300)                    |
| Min. switching current            |      | 5 mA                                                    | 5 mA                                                    | 10 mA                                                   |
| Max. inrush current               |      | 20 A                                                    | 20 A                                                    | 20 A                                                    |
| Rated current                     |      | 10A                                                     | 10A                                                     | 10A                                                     |
| Max. breaking capacity            | AC1  | 2500 VA                                                 | 2500 VA                                                 | 2500 VA                                                 |
|                                   |      | 0.3 W                                                   | 0.3 W                                                   | 0.5 W                                                   |
| Min. breaking capacity            |      |                                                         |                                                         |                                                         |
| Contact resistance                |      | ≤ 100 mΩ                                                | ≤ 100 mΩ                                                | ≤ 100 mΩ                                                |
| Max. operating frequency          |      |                                                         |                                                         |                                                         |
| • at rated load                   | AC1  | 1200 cycles/hour                                        | 1200 cycles/hour                                        | 1200 cycles/hour                                        |
|                                   |      | 12000 cycles/hour                                       | 12000 cycles/hour                                       | 12000 cycles/hour                                       |
| • no load                         |      |                                                         |                                                         |                                                         |

### Coil Data

|                                   |             |                                                      |                                                      |                                                      |
|-----------------------------------|-------------|------------------------------------------------------|------------------------------------------------------|------------------------------------------------------|
| Rated voltage                     | 50/60 Hz AC | 6 ... 240 V                                          | 6 ... 240 V                                          | 6 ... 240 V                                          |
|                                   | DC          | 6 ... 220 V                                          | 6 ... 220 V                                          | 6 ... 220 V                                          |
| Must release voltage              |             | AC: ≥ 0.15 U <sub>n</sub> ; DC: ≥ 0.1 U <sub>n</sub> | AC: ≥ 0.15 U <sub>n</sub> ; DC: ≥ 0.1 U <sub>n</sub> | AC: ≥ 0.15 U <sub>n</sub> ; DC: ≥ 0.1 U <sub>n</sub> |
| Operating range of supply voltage |             | see page 68                                          | see page 68                                          | see page 68                                          |
| Rated power consumption           |             | AC: 2.8 VA 50 Hz; 2.5 VA 60 Hz; DC: 1.5 W            | AC: 2.8 VA 50 Hz; 2.5 VA 60 Hz; DC: 1.5 W            | AC: 2.8 VA 50 Hz; 2.5 VA 60 Hz; DC: 1.5 W            |

### Insulation

|                             |  |                                           |                                           |                                           |
|-----------------------------|--|-------------------------------------------|-------------------------------------------|-------------------------------------------|
| Insulation rated voltage    |  | 250 V AC                                  | 250 V AC                                  | 250 V AC                                  |
| Rated surge voltage         |  | 2500 V 1.2 / 50 μs                        | 2500 V 1.2 / 50 μs                        | 2500 V 1.2 / 50 μs                        |
| Overvoltage category        |  | III                                       | III                                       | III                                       |
| Insulation pollution degree |  | 3                                         | 3                                         | 3                                         |
| Dielectric strength         |  |                                           |                                           |                                           |
| • between coil and contacts |  | 2500 V AC type of insulation: basic       | 2500 V AC type of insulation: basic       | 2500 V AC type of insulation: basic       |
|                             |  | 1500 V AC type of clearance: micro-disco. | 1500 V AC type of clearance: micro-disco. | 1500 V AC type of clearance: micro-disco. |
|                             |  | 2000 V AC type of insulation: basic       | 2000 V AC type of insulation: basic       | 2000 V AC type of insulation: basic       |
| Contact - coil distance     |  |                                           |                                           |                                           |
| • clearance                 |  | ≥ 3 mm                                    | ≥ 3 mm                                    | ≥ 3 mm                                    |
|                             |  | ≥ 4.2 mm                                  | ≥ 4.2 mm                                  | ≥ 3.2 mm                                  |
| • creepage                  |  |                                           |                                           |                                           |

### General Data


|                                    |  |                                        |                                        |                                        |
|------------------------------------|--|----------------------------------------|----------------------------------------|----------------------------------------|
| Operating / release time (typical) |  | AC: 12 ms / 10 ms; DC: 18 ms / 7 ms    | AC: 12 ms / 10 ms; DC: 18 ms / 7 ms    | AC: 12 ms / 10 ms; DC: 18 ms / 7 ms    |
| Electrical life                    |  |                                        |                                        |                                        |
| • resistive AC1                    |  | > 2 x 10 <sup>5</sup> ; 10 A. 250 V AC | > 2 x 10 <sup>5</sup> ; 10 A. 250 V AC | > 2 x 10 <sup>5</sup> ; 10 A. 250 V AC |
|                                    |  | see Fig. 2                             | see Fig. 2                             | see Fig. 2                             |
| • cos                              |  |                                        |                                        |                                        |
| Mechanical life (cycles)           |  | > 2 x 10 <sup>7</sup>                  | > 2 x 10 <sup>7</sup>                  | > 2 x 10 <sup>7</sup>                  |
| Dimensions (L x W x H)             |  | 35 x 35 x 54.4 mm                      | 35 x 35 x 54.4 mm                      | 35 x 42.5 x 54.5 mm                    |
| Weight                             |  | 83 g                                   | 83 g                                   | 95 g                                   |
| Ambient temperature                |  |                                        |                                        |                                        |
| • storage                          |  | -40...+85 °C                           | -40...+85 °C                           | -40...+85 °C                           |
|                                    |  | AC: -40...+55 °C DC: -40...+70 °C      | AC: -40...+55 °C DC: -40...+70 °C      | AC: -40...+55 °C DC: -40...+70 °C      |
| • operating                        |  |                                        |                                        |                                        |
| Cover protection category          |  | IP 40 PN-EN 60529                      | IP 40 PN-EN 60529                      | IP 40 PN-EN 60529                      |
| Environmental protection           |  | RTI PN-EN 116000-3                     | RTI PN-EN 116000-3                     | RTI PN-EN 116000-3                     |
| Shock resistance                   |  | 10 g                                   | 10 g                                   | 10 g                                   |
| Vibration resistance               |  | 5 g 10...150 Hz                        | 5 g 10...150 Hz                        | 5 g 10...150 Hz                        |
| Solder bath temperature            |  | max. 270 °C                            | max. 270 °C                            | max. 270 °C                            |
| Soldering time                     |  | max. 5 s                               | max. 5 s                               | max. 5 s                               |

# R15


## Industrial Electromagnetic Relays

### DPDT

#### CONNECTION DIAGRAM




#### DIMENSIONS




### 3PDT

#### CONNECTION DIAGRAM




#### DIMENSIONS




### 4PDT

#### CONNECTION DIAGRAM




#### DIMENSIONS




### LOAD CHARTS


Electrical life at AC resistive load.  
Switching frequency: 1200 cycles/hour Fig. 1



Electrical life reduction factor at AC inductive load Fig. 2



Max. DC breaking capacity  
A - resistive load DC1  
B - inductive load L/R = 40 ms Fig. 3



# R15

## Industrial Electromagnetic Relays

### R15 DPDT AC 50/60Hz & DC coil

| Part Number                   | Coil Voltage (V) | Coil Type  | Coil resistance at 20 °C in Ω | Coil operating range |                | Options* |    |     |
|-------------------------------|------------------|------------|-------------------------------|----------------------|----------------|----------|----|-----|
|                               |                  |            |                               | min. (at 20°C)       | max. (at 55°C) | -        | WT | WTL |
| ▶ <b>R15-2012-23-1012</b>     | 12               | DC         | 110                           | 9.6                  | 13.2           | x        |    |     |
| R15-2012-23-1012-WT           | 12               | DC         | 110                           | 9.6                  | 13.2           |          | x  |     |
| R15-2012-23-1012-WTL          | 12               | DC         | 110                           | 9.6                  | 13.2           |          |    | x   |
| ▶ <b>R15-2012-23-1024</b>     | 24               | DC         | 430                           | 19.2                 | 26.4           | x        |    |     |
| R15-2012-23-1024-WT           | 24               | DC         | 430                           | 19.2                 | 26.4           |          | x  |     |
| ▶ <b>R15-2012-23-1024-WTL</b> | 24               | DC         | 430                           | 19.2                 | 26.4           |          |    | x   |
| R15-2012-23-1110              | 110              | DC         | 9200                          | 88.0                 | 121.0          | x        |    |     |
| R15-2012-23-1110-WT           | 110              | DC         | 9200                          | 88.0                 | 121.0          |          | x  |     |
| R15-2012-23-1110-WTL          | 110              | DC         | 9200                          | 88.0                 | 121.0          |          |    | x   |
| ▶ <b>R15-2012-23-5024</b>     | 24               | AC 50/60Hz | 75                            | 19.2                 | 26.4           | x        |    |     |
| R15-2012-23-5024-WT           | 24               | AC 50/60Hz | 75                            | 19.2                 | 26.4           |          | x  |     |
| R15-2012-23-5024-WTL          | 24               | AC 50/60Hz | 75                            | 19.2                 | 26.4           |          |    | x   |
| ▶ <b>R15-2012-23-5120</b>     | 120              | AC 50/60Hz | 1910                          | 96.0                 | 132.0          | x        |    |     |
| R15-2012-23-5120-WT           | 120              | AC 50/60Hz | 1910                          | 96.0                 | 132.0          |          | x  |     |
| ▶ <b>R15-2012-23-5120-WTL</b> | 120              | AC 50/60Hz | 1910                          | 96.0                 | 132.0          |          |    | x   |
| ▶ <b>R15-2012-23-5230</b>     | 230              | AC 50/60Hz | 7080                          | 184.0                | 253.0          | x        |    |     |
| R15-2012-23-5230-WT           | 230              | AC 50/60Hz | 7080                          | 184.0                | 253.0          |          | x  |     |
| R15-2012-23-5230-WTL          | 230              | AC 50/60Hz | 7080                          | 184.0                | 253.0          |          |    | x   |

### R15 3PDT AC 50/60Hz & DC coil

| Part Number                   | Coil Voltage (V) | Coil Type  | Coil resistance at 20 °C in Ω | Coil operating range |                | Options* |    |     |
|-------------------------------|------------------|------------|-------------------------------|----------------------|----------------|----------|----|-----|
|                               |                  |            |                               | min. (at 20°C)       | max. (at 55°C) | -        | WT | WTL |
| ▶ <b>R15-2013-23-1012</b>     | 12               | DC         | 110                           | 9.6                  | 13.2           | x        |    |     |
| R15-2013-23-1012-WT           | 12               | DC         | 110                           | 9.6                  | 13.2           |          | x  |     |
| R15-2013-23-1012-WTL          | 12               | DC         | 110                           | 9.6                  | 13.2           |          |    | x   |
| ▶ <b>R15-2013-23-1024</b>     | 24               | DC         | 430                           | 19.2                 | 26.4           | x        |    |     |
| R15-2013-23-1024-WT           | 24               | DC         | 430                           | 19.2                 | 26.4           |          | x  |     |
| ▶ <b>R15-2013-23-1024-WTL</b> | 24               | DC         | 430                           | 19.2                 | 26.4           |          |    | x   |
| R15-2013-23-1110              | 110              | DC         | 9200                          | 88.0                 | 121.0          | x        |    |     |
| R15-2013-23-1110-WT           | 110              | DC         | 9200                          | 88.0                 | 121.0          |          | x  |     |
| R15-2013-23-1110-WTL          | 110              | DC         | 9200                          | 88.0                 | 121.0          |          |    | x   |
| ▶ <b>R15-2013-23-5024</b>     | 24               | AC 50/60Hz | 75                            | 19.2                 | 26.4           | x        |    |     |
| R15-2013-23-5024-WT           | 24               | AC 50/60Hz | 75                            | 19.2                 | 26.4           |          | x  |     |
| R15-2013-23-5024-WTL          | 24               | AC 50/60Hz | 75                            | 19.2                 | 26.4           |          |    | x   |
| ▶ <b>R15-2013-23-5120</b>     | 120              | AC 50/60Hz | 1910                          | 96.0                 | 132.0          | x        |    |     |
| R15-2013-23-5120-WT           | 120              | AC 50/60Hz | 1910                          | 96.0                 | 132.0          |          | x  |     |
| ▶ <b>R15-2013-23-5120-WTL</b> | 120              | AC 50/60Hz | 1910                          | 96.0                 | 132.0          |          |    | x   |
| ▶ <b>R15-2013-23-5230</b>     | 230              | AC 50/60Hz | 7080                          | 184.0                | 253.0          | x        |    |     |
| R15-2013-23-5230-WT           | 230              | AC 50/60Hz | 7080                          | 184.0                | 253.0          |          | x  |     |
| R15-2013-23-5230-WTL          | 230              | AC 50/60Hz | 7080                          | 184.0                | 253.0          |          |    | x   |

### R15 4PDT AC 50/60Hz & DC coil

| Part Number                 | Coil Voltage (V) | Coil Type | Coil resistance at 20 °C in Ω | Coil operating range |                | Options* |   |    |     |
|-----------------------------|------------------|-----------|-------------------------------|----------------------|----------------|----------|---|----|-----|
|                             |                  |           |                               | min. (at 20°C)       | max. (at 55°C) | -        | K | WT | WTL |
| R15-1014-23-1012            | 12               | DC        | 110                           | 9.6                  | 13.2           | x        |   |    |     |
| R15-1014-23-1012-K          | 12               | DC        | 110                           | 9.6                  | 13.2           |          | x |    |     |
| R15-1014-23-1012-L          | 12               | DC        | 110                           | 9.6                  | 13.2           |          |   | x  |     |
| R15-1014-23-1012-D          | 12               | DC        | 110                           | 9.6                  | 13.2           |          |   |    | x   |
| R15-1014-23-1024            | 24               | DC        | 430                           | 19.2                 | 26.4           | x        |   |    |     |
| R15-1014-23-1024-K          | 24               | DC        | 430                           | 19.2                 | 26.4           |          | x |    |     |
| ▶ <b>R15-1014-23-1024-L</b> | 24               | DC        | 430                           | 19.2                 | 26.4           |          |   | x  |     |
| R15-1014-23-1024-D          | 24               | DC        | 430                           | 19.2                 | 26.4           |          |   |    | x   |
| R15-1014-23-1110            | 110              | DC        | 9200                          | 88.0                 | 121.0          | x        |   |    |     |
| R15-1014-23-1110-K          | 110              | DC        | 9200                          | 88.0                 | 121.0          |          | x |    |     |
| R15-1014-23-1110-L          | 110              | DC        | 9200                          | 88.0                 | 121.0          |          |   | x  |     |
| R15-1014-23-1110-D          | 110              | DC        | 9200                          | 88.0                 | 121.0          |          |   |    | x   |
| R15-1014-23-3024            | 24               | AC 50Hz   | 72                            | 19.2                 | 26.4           | x        |   |    |     |
| R15-1014-23-3024-K          | 24               | AC 50Hz   | 72                            | 19.2                 | 26.4           |          | x |    |     |
| R15-1014-23-3024-L          | 24               | AC 50Hz   | 72                            | 19.2                 | 26.4           |          |   | x  |     |
| R15-1014-23-3024-D          | 24               | AC 50Hz   | 72                            | 19.2                 | 26.4           |          |   |    | x   |
| R15-1014-23-3120            | 120              | AC 50Hz   | 2300                          | 96.0                 | 132.0          | x        |   |    |     |
| R15-1014-23-3120-K          | 120              | AC 50Hz   | 2300                          | 96.0                 | 132.0          |          | x |    |     |
| R15-1014-23-3120-L          | 120              | AC 50Hz   | 2300                          | 96.0                 | 132.0          |          |   | x  |     |
| R15-1014-23-3120-D          | 120              | AC 50Hz   | 2300                          | 96.0                 | 132.0          |          |   |    | x   |
| R15-1014-23-3230            | 230              | AC 50Hz   | 7900                          | 184.0                | 253.0          | x        |   |    |     |
| R15-1014-23-3230-K          | 230              | AC 50Hz   | 7900                          | 184.0                | 253.0          |          | x |    |     |
| R15-1014-23-3230-L          | 230              | AC 50Hz   | 7900                          | 184.0                | 253.0          |          |   | x  |     |
| R15-1014-23-3230-D          | 230              | AC 50Hz   | 7900                          | 184.0                | 253.0          |          |   |    | x   |
| R15-1014-23-6120            | 120              | AC 60Hz   | 2000                          | 96.0                 | 132.0          | x        |   |    |     |
| R15-1014-23-6120-K          | 120              | AC 60Hz   | 2000                          | 96.0                 | 132.0          |          | x |    |     |
| ▶ <b>R15-1014-23-6120-L</b> | 120              | AC 60Hz   | 2000                          | 96.0                 | 132.0          |          |   | x  |     |
| R15-1014-23-6120-D          | 120              | AC 60Hz   | 2000                          | 96.0                 | 132.0          |          |   |    | x   |
| R15-1014-23-6230            | 230              | AC 60Hz   | 7000                          | 184.0                | 253.0          | x        |   |    |     |
| R15-1014-23-6230-K          | 230              | AC 60Hz   | 7000                          | 184.0                | 253.0          |          | x |    |     |
| R15-1014-23-6230-L          | 230              | AC 60Hz   | 7000                          | 184.0                | 253.0          |          |   | x  |     |
| R15-1014-23-6230-D          | 230              | AC 60Hz   | 7000                          | 184.0                | 253.0          |          |   |    | x   |

WT = with mechanical indicator + lockable front test button; WTL = with mechanical indicator + lockable front test button + light indicator (LED)  
 K = with test button without block function; L = with light indicator (LED); D = with surge suppression element (diode); other options available upon request

▶ **BOLD** - Regular stocked items.


### GZP8 for R15 DPDT

Screw terminals  
Max. tightening moment  
for the terminal: 0.5 Nm  
35 mm rail mount  
acc. to PN-EN 60715  
or on panel mounting  
73 x 38.2 x 27.2 mm Two poles  
12 A, 300 V AC




GZP8

#### CONNECTION DIAGRAM



#### DIMENSIONS



E22891



Time module COM3T




GZP-0035



GZP-0054


### PZ8 for R15 DPDT

Screw terminals  
Max. tightening moment  
for the terminal: : 0.7 Nm  
35 mm rail mount  
acc. to PN-EN 60715  
or on panel mounting  
68.2 x 38 x 24.2 mm  
Two poles  
10 A, 250 V AC




PZ8

#### CONNECTION DIAGRAM



#### DIMENSIONS



E105728



PZ11 0031


### GZP11 for R15 3PDT

Screw terminals  
Max. tightening moment  
for the terminal: : 0,5 Nm  
35 mm rail mount  
acc. to PN-EN 60715  
or on panel mounting  
73 x 38.2 x 27.2 mm  
Three poles  
12 A, 300 V AC




GZP11

#### CONNECTION DIAGRAM



#### DIMENSIONS



E22891



Time module COM3T



GZP-0035




GZP-0054

All accessories are sold separately.

## Industrial Electromagnetic Relays - Plug-in Sockets and Accessories

## PZ11 for R15 3PDT

Screw terminals  
Max. tightening moment  
for the terminal: : 0.7 Nm  
35 mm rail mount  
acc. to PN-EN 60715  
or on panel mounting  
68.2 x 38 x 24.2 mm  
Three poles  
10 A, 250 V AC




PZ11




PZ11 0031

## CONNECTION DIAGRAM




## DIMENSIONS



E105728

## GZ14U for R15 4PDT

Screw terminals  
Max. tightening moment  
for the terminal: : 0.7 Nm  
35 mm rail mount  
acc. to PN-EN 60715  
96.8 x 46.2 x 33.3 mm  
Four poles  
10 A, 250 V AC




GZ14ZU




GZ14 0737


## CONNECTION DIAGRAM



## DIMENSIONS




**See Relay Socket Combinations on pages 104-109**



All accessories are sold separately.

# Altech Custom Assemblies



**Altech provides quick turnaround  
and competitive prices on assemblies.**  
For complete assemblies contact Altech.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331