

Aluminum electrolytic capacitors

Single-ended capacitors

Series/Type: B43890

Date: December 2019

© TDK Electronics AG 2019. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without TDK Electronics' prior express consent is prohibited.



Single-ended capacitors

B43890

Extended useful life - 105 °C

Long-life grade capacitors

Applications

- Professional power supplies
- Not for automotive applications unless otherwise specified

Features

- High ripple current capability at high frequency
- Extra long useful life (12000 to 15000 h/105 °C)
- Compact dimensions
- RoHS-compatible

Construction

- Radial leads
- Charge-discharge proof, polar
- Aluminum case with insulating sleeve
- Minus pole marking on the insulating sleeve
- Stand-off rubber seal
- Case with safety vent

Delivery mode


Terminal configurations and packing:

- Bulk
- Taped, Ammo pack
- Cut
- Kinked
- PAPR (Protection Against Polarity Reversal): crimped leads, J leads, bent leads

Refer to chapter "Single-ended capacitors – Taping, packing and lead configurations" for further details.









Specifications and characteristics in brief

Rated voltage V _R	350 450 V DC								
Surge voltage V _S	1.1 · V _R								
Rated capacitance C _R	4.7 68 μF								
Capacitance tolerance	±20% ≙ M								
Dissipation factor $\tan\delta$	$\tan \delta (\text{max.}) = 0.24$								
(20 °C, 120 Hz)									
Leakage current I _{leak} (20 °C, 5 min)	$I_{leak} = 0.03 \mu\text{A} \cdot \left(\frac{C}{\mu}\right)$	$I_{leak} = 0.03 \mu\text{A} \cdot \left(\frac{C_R}{\mu F} \cdot \frac{V_R}{V}\right) + 15 \mu\text{A}$							
Self-inductance ESL	Diameter (mm)	≤ 12.5	16	18					
	ESL (nH)	20	26	34					
Useful life ¹⁾			Requirements:						
105 °C; V _R ; I _{AC,R}	> 12000 h for d = 1	l0 mm	\Delta C/C	≤ 40% of initial value					
	> 15000 h for d ≥ 1	2.5 mm	tan δ	≤ 3 times initial specified limit					
			I _{leak}	≤ initial specified limit					
Voltage endurance test			Post test requirements:						
105 °C; V _R	12000 h for d = 10	mm	\Delta C/C	≤ 25% of initial value					
	15000 h for d ≥ 12	.5 mm	tan δ	≤ 2 times initial specified limit					
			l _{leak}	≤ initial specified limit					
Vibration resistance test	To IEC 60068-2-6,	test Fc:							
				lacement amplitude max. 1.5 mm,					
	acceleration max.	•							
		amped by	the alum	inum case e.g. using our					
	standard fixture								
IEC climatic category	To IEC 60068-1:		/CC days	damar haat taat)					
Continual annuitientier	25/105/56 (-25 °C	,/+105 °C/	oo days (uamp neat test)					
Sectional specification	IEC 60384-4								

¹⁾ Refer to chapter "General technical information, 5 Useful life" on how to interpret useful life.






Extended useful life - 105 °C

Dimensional drawing

With stand-off rubber seal


Diameters (mm): 10, 12.5, 16, 18



Dimensions and weights

Dimensions (mm)			Approx. weight
d +0.5	1	a ±0.5	b	g
10	16 +1.0	5.0	0.60 ±0.05	1.9
10	20 +2.0	5.0	0.60 ±0.05	2.6
12.5	20 +2.0	5.0	0.60 ±0.05	3.6
12.5	25 +2.0	5.0	0.60 ±0.05	4.5
16	20 +2.0	7.5	0.80 ±0.05	5.5
16	25 +2.0	7.5	0.80 ±0.05	7.5
16	31.5 +2.0	7.5	0.80 ±0.05	7.8
18	20 +2.0	7.5	0.80 ±0.1	8.0
18	25 +2.0	7.5	0.80 ±0.1	9.0
18	31.5 +2.0	7.5	0.80 ±0.1	11.0
18	35 +2.0	7.5	0.80 ±0.1	13.0
18	40 +2.0	7.5	0.80 ±0.1	16.0







Overview of available types

Other voltage and capacitance ratings are available upon request.

V _R (V DC)	350	400	450
	Case dimensions d × I (mn	n)	
C _R (μF)			
4.7			10 × 16
6.8	10 × 16	10 × 16	10 × 20
10	10 × 20	10 × 20	12.5 × 20
15	12.5 × 20	12.5 × 20	12.5 × 25
22	12.5 × 25	12.5 × 25	16 × 20
33	16 × 20	16 × 25	18 × 20 16 × 31.5
33	10 ×20	10 ×23	18 × 25
47	16 × 31.5	16 × 31.5	18 × 31.5
68	18 × 31.5	18 × 35	18 × 40





Extended useful life - 105 °C

Technical data and ordering codes

C _R	Case dimensions	I _{AC,R}	Ordering code
120 Hz 20 °C	d×I	100 kHz 105 °C	(composition see below)
μF	mm	mA	
V _R = 350 V DC			
6.8	10 ×16	240	B43890A4685M***
10	10 × 20	318	B43890A4106M***
15	12.5 × 20	446	B43890A4156M***
22	12.5 × 25	590	B43890A4226M***
33	16 × 20	753	B43890A4336M***
47	16 × 31.5	1061	B43890A4476M***
68	18 × 31.5	1379	B43890A4686M***
V _R = 400 V DC			
6.8	10 × 16	240	B43890A9685M***
10	10 × 20	318	B43890A9106M***
15	12.5 × 20	446	B43890A9156M***
22	12.5 × 25	590	B43890A9226M***
33	16 × 25	818	B43890A9336M***
47	16 × 31.5	1061	B43890A9476M***
68	18 × 35	1438	B43890A9686M***
V _R = 450 V DC			
4.7	10 × 16	200	B43890A5475M***
6.8	10 × 20	262	B43890A5685M***
10	12.5 × 20	365	B43890A5106M***
15	12.5 × 25	487	B43890A5156M***
22	16 × 20	615	B43890A5226M***
22	18 × 20	664	B43890B5226M***
33	16 × 31.5	889	B43890A5336M***
33	18 × 25	880	B43890B5336M***
47	18 × 31.5	1147	B43890A5476M***
68	18 × 40	1517	B43890A5686M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (for $d \times I = 10 \times 20$ mm and \emptyset 12.5 ... 18 mm)

002 = for cut leads, bulk

 $003 = \text{ for crimped leads, blister (for } \emptyset 16 \dots 18 \text{ mm)}$

004 = for J leads, blister (for \emptyset 10 ... 18 mm, excluding d \times I =18 \times 40 mm)

 $008 = \text{ for taped leads, Ammo pack, lead spacing F} = 5.0 \text{ mm (for } \emptyset \text{ 10 ... 12.5 mm)}$

009 = for taped leads, Ammo pack, lead spacing F = 7.5 mm (for \varnothing 16 mm and d \times I = 18 \times 20 ... 18 \times 31.5 mm)


012 = for bent 90° leads, blister (for \varnothing 16 ... 18 mm)








Useful life¹⁾ depending on ambient temperature T_A under ripple current operating conditions d = 10 mm



Useful life $^{1)}$ depending on ambient temperature T_{A} under ripple current operating conditions $d\geq 12.5\ mm$




¹⁾ Refer to chapter "General technical information, 5 Useful life" on how to interpret useful life.






Extended useful life - 105 °C

Frequency factor of permissible ripple current I_{AC} versus frequency f









Taping

Single-ended capacitors are available taped in Ammo pack from diameter 8 to 18 mm as follows:

Lead spacing $F = 3.5 \text{ mm} (\emptyset \text{ d} = 8 \text{ mm})$


Lead spacing $F = 5.0 \text{ mm} (\emptyset \text{ d} = 8 \dots 12.5 \text{ mm})$

Lead spacing F = 7.5 mm ($\emptyset \text{ d} = 16 \dots 18 \text{ mm}$).

The dimensions for F, P_1 and 1 max. are specified with reference to the center of the terminal wires.

Lead spacing 3.5 mm (\emptyset d = 8 mm)

Last 3 digits of ordering code: 006



Dimensions in mm

\emptyset d	F	Н	W	W ₀	W ₁	W_2	Р	P ₀	P ₁	I ₁	t	Δh	D ₀
8	3.5	18.5	18.0	9.5	9.0	3.0	12.7	12.7	4.6	1.0	0.7	1.0	4.0
Toler- ance	+0.8	+1 0	+0.5	min	+0.5	may	+1.0	+0.3	+0.6	may	+0.2	may	+0.2
ance	-0.2	- 1.0				max.	_ 1.0			max.		illax.	∪.∠

Leads can also run straight through the taping area.






Extended useful life - 105 °C


Lead spacing 5.0 mm (\emptyset d = 8 mm)

Last 3 digits of ordering code: 008



Lead spacing 5.0 mm (\varnothing d = 10 ... 12.5 mm)

Last 3 digits of ordering code: 008




Dimensions in mm

\emptyset d	F	Н	W	W_0	W ₁	W_2	H _o	Р	P ₀	P ₁	I ₁	t	Δh	D ₀
8		20.0		9.5			16.0	12.7	12.7	3.85				
10	5.0	19.0	18.0	9.5	9.0	1.5	_	12.7	12.7	3.85	1.0	0.6	1.0	4.0
12.5		19.0		11.5			_	15.0	15.0	5.0				
Toler-	+0.8	+0.75	+0.5	min	+0.5	may	+0.5	±1.0	+0.2	+0.5	max.	+0.3	max.	±0.2
ance	-0.2			1111111.		max.	0.5	1.0	∪.∠	∪.5	max.	-0.2	max.	

Taping is available up to dimensions $d \times I = 12.5 \times 25$ mm.








Lead spacing 7.5 mm (\emptyset d = 16 ...18 mm)

Last 3 digits of ordering code: 009



Dimensions in mm

\emptyset d	F	Н	W	W _o	W ₁	W_2	Р	P ₀	P ₁	I ₁	t	ΔΡ	Δh	D ₀
16	7.5	18.5	10 0	10.5	0.0	1.5	20.0	15.0	2.75	1.0	0.7	0	0	4.0
18													U	
Toler- ance	±0.8	-0.5 +0.75	±0.5	min.	±0.5	max.	±1.0	±0.2	±0.5	max.	±0.2	±1.0	±1.0	±0.2

Taping is available up to dimensions $d \times I = 16 \times 31.5$ mm and 18×31.5 mm.





Extended useful life - 105 °C


Cut or kinked leads

Single-ended capacitors are available with cut or kinked leads. Other lead configurations also available upon request.

Cut leads


Last 3 digits of ordering code: 002

With stand-off rubber seal



KAL1085-I

With flat rubber seal



KAL1086-R

Case size	Dimensions (mm)
$d \times I (mm)$	a ±0.5
10 × 12.5	5.0
10 × 16	5.0
10 × 20	5.0
12.5 × 20	5.0
12.5 × 25	5.0
16 × 20	7.5
16 × 25	7.5
16 × 31.5	7.5
16 × 35.5	7.5
16 × 40	7.5
18 × 20	7.5
18 × 25	7.5
18 × 31.5	7.5
18 × 35	7.5
18 × 40	7.5




Extended useful life - 105 °C




Kinked leads

Last 3 digits of ordering code: 001

With stand-off rubber seal




KAL1081-K




KAL1083-2

With flat rubber seal



KAL1082-T

KAL1084-A



Case size Dimensions (mm) $d \times I (mm)$ a ±0.5 10×20 5.0 12.5×20 5.0 12.5×25 5.0 16×20 7.5 16×25 7.5 16×31.5 7.5 16×35.5 7.5 18×20 7.5 18×25 7.5 18×31.5 7.5 18×35 7.5 18×40 7.5





Extended useful life - 105 °C

PAPR leads (Protection Against Polarity Reversal)


These lead configurations ensure correct placement of the capacitor on the PCB with regard to polarity. PAPR leads are available for diameters from 10 mm up to 18 mm.

There are three configurations available: Crimped leads, J leads, bent 90° leads.

Crimped leads


Last 3 digits of ordering code: 003

With stand-off rubber seal




The series B41897 and B41898 have no sleeve nor minus pole marking, the positive pole is marked on the aluminum case side instead.

Suggestion for PCB hole diameter



Case size	Dimension	Dimensions (mm)								
$d \times I (mm)$	B ±0.2	C ±0.5	D ±0.1	E ±0.1	a ±0.5	∅b				
16 × 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05				
16 × 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05				
16 × 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05				
16 × 35.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05				
18 × 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1				
18 × 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1				
18 × 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1				
18 × 35	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1				
18 × 40	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1				









J leads

Last 3 digits of ordering code: 004







The series B41897 and B41898 have no sleeve nor minus pole marking, the positive pole is marked on the aluminum case side instead.

Suggestion for PCB hole diameter

Suggestion for PCB hole diameter, wire $\emptyset 0.6 \text{ mm}$



Suggestion for PCB hole diameter, wire $\emptyset 0.8 \text{ mm}$



Case size	Dimensions (Dimensions (mm)								
$d \times I (mm)$	C ±0.5	E ±0.5	J ±0.2	a ±0.5	Øb					
10 × 12.5	3.2	0.7	1.2	5.0	0.6 ±0.05					
10 × 16	3.2	0.7	1.2	5.0	0.6 ±0.05					
10 × 20	3.2	0.7	1.2	5.0	0.6 ±0.05					
12.5 × 20	3.2	0.7	1.2	5.0	0.6 ±0.05					
12.5 × 25	3.2	0.7	1.2	5.0	0.6 ±0.05					
16 × 20	3.5	0.7	1.6	7.5	0.8 ±0.05					
16 × 25	3.5	0.7	1.6	7.5	0.8 ±0.05					
16 × 31.5	3.5	0.7	1.6	7.5	0.8 ±0.05					
16 × 35.5	3.5	0.7	1.6	7.5	0.8 ±0.05					
16 × 40	3.5	0.7	1.6	7.5	0.8 ±0.05					
18 × 20	3.5	0.7	1.6	7.5	0.8 ±0.1					
18 × 25	3.5	0.7	1.6	7.5	0.8 ±0.1					
18 × 31.5	3.5	0.7	1.6	7.5	0.8 ±0.1					
18 × 35	3.5	0.7	1.6	7.5	0.8 ±0.1					







Extended useful life - 105 °C

Bent 90° leads for horizontal mounting pinning

Last 3 digits of ordering code: 012






The series B41897 and B41898 have no sleeve nor minus pole marking, the positive pole is marked on the aluminum case side instead.

Case size	Dimensions (mm)								
$d \times I (mm)$	C ±0.5	E ±0.5	F ±0.5	a ±0.5	Øb				
16 × 20	4.0	4.0	12.0	7.5	0.8 ±0.05				
16 × 25	4.0	4.0	12.0	7.5	0.8 ±0.05				
16 × 31.5	4.0	4.0	12.0	7.5	0.8 ±0.05				
16 × 35.5	4.0	4.0	12.0	7.5	0.8 ±0.05				
16 × 40	4.0	4.0	13.0	7.5	0.8 ±0.05				
18 × 20	4.0	4.0	13.0	7.5	0.8 ±0.1				
18 × 25	4.0	4.0	13.0	7.5	0.8 ±0.1				
18 × 31.5	4.0	4.0	13.0	7.5	0.8 ±0.1				
18 × 35	4.0	4.0	13.0	7.5	0.8 ±0.1				
18 × 40	4.0	4.0	13.0	7.5	0.8 ±0.1				

Bent leads for diameter 12.5 mm available upon request.








Packing units and box dimensions

Ammo pack



Case size d × I	Dimens	sions (mr	m)	Packing units
mm	A_{max}	B_{max}	C_{max}	pcs.
8 × 11.5	345	60	240	1000
10 × 12.5	345	60	280	750
10 × 16	345	65	200	500
10 × 20	345	65	200	500
12.5 × 20	345	65	260	500
12.5 × 25	345	70	260	500
16 × 20	325	65	285	300
16 × 25	325	65	285	300
16 × 31.5	325	80	275	300
18 × 20	325	65	285	250
18 × 25	325	65	285	250
18 × 31.5	325	80	275	250





Extended useful life - 105 $^{\circ}$ C

Overview of packing units and code numbers

								PAPR	
Case size	e size Stan- Taped,			Kinked	Cut	Crimped	J leads,	Bent 90°	
$d \times I$ dard, Am			Ammo pack			leads,	leads,	blister	leads,
	bulk				bulk	bulk	blister		blister
mm	pcs.	pcs.	pcs.			pcs.	pcs.	pcs.	pcs.
8 × 11.5	1000	1000			_	_	_	_	
10 × 12.5	1000	750			_	1000	_	900	
10 × 16	1000	500			_	1000	_	675	
10 × 20	500	500			500	500	_	500	
12.5 × 20	350	500			350	350	_	300	1)
12.5 × 25	250	500			500	500	_	225	1)
16 × 20	250	300			200	200	200	200	420
16 × 25	250	300			200	200	216	216	216
16 × 31.5	200	300			250	250	180	180	180
16 × 35.5	100	_			100	100	150	150	150
16 × 40	125	_			100	100	72	72	72
18 × 20	175	250			175	175	200	200	420
18 × 25	150	250			150	150	200	200	200
18 × 31.5	100	250			100	100	150	150	150
18 × 35	100	_			100	100	150	150	150
18 × 40	125	_			100	100	72	_	72
The last three	000	Code	F (mm)	d (mm)	001	002	003	004	012
digits of the		006	3.5	8					
complete		800	5	812.5					
ordering code		009	7.5	1618					
state the lead									
configuration									







Cautions and warnings

Personal safety

The electrolytes used have been optimized both with a view to the intended application and with regard to health and environmental compatibility. They do not contain any solvents that are detrimental to health, e.g. dimethyl formamide (DMF) or dimethyl acetamide (DMAC). Furthermore, some of the high-voltage electrolytes used are self-extinguishing.

As far as possible, we do not use any dangerous chemicals or compounds to produce operating electrolytes, although in exceptional cases, such materials must be used in order to achieve specific physical and electrical properties because no alternative materials are currently known. We do, however, restrict the amount of dangerous materials used in our products to an absolute minimum.

Materials and chemicals used in our aluminum electrolytic capacitors are continuously adapted in compliance with the TDK Electronics Corporate Environmental Policy and the latest EU regulations and guidelines such as RoHS, REACH/SVHC, GADSL, and ELV.

MDS (Material Data Sheets) are available on our website for all types listed in the data book. MDS for customer specific capacitors are available upon request.

MSDS (Material Safety Data Sheets) are available for our electrolytes upon request.

Nevertheless, the following rules should be observed when handling aluminum electrolytic capacitors: No electrolyte should come into contact with eyes or skin. If electrolyte does come into contact with the skin, wash the affected areas immediately with running water. If the eyes are affected, rinse them for 10 minutes with plenty of water. If symptoms persist, seek medical treatment. Avoid inhaling electrolyte vapor or mists. Workplaces and other affected areas should be well ventilated. Clothing that has been contaminated by electrolyte must be changed and rinsed in water.





Extended useful life - 105 °C

Product safety

The table below summarizes the safety instructions that must be observed without fail. A detailed description can be found in the relevant sections of seperate file chapter "General technical information".

Topic	Safety information	Reference chapter "General technical information"
Polarity	Make sure that polar capacitors are connected with the right polarity.	1 "Basic construction of aluminum electrolytic capacitors"
Reverse voltage	Voltages of opposite polarity should be prevented by connecting a diode.	3.1.6 "Reverse voltage"
Mounting position of screw-terminal capacitors	Screw terminal capacitors must not be mounted with terminals facing down unless otherwise specified.	11.1. "Mounting positions of capacitors with screw terminals"
Robustness of terminals	The following maximum tightening torques must not be exceeded when connecting screw terminals: M5: 2.5 Nm M6: 4.0 Nm	11.3 "Mounting torques"
Mounting of single-ended capacitors	The internal structure of single-ended capacitors might be damaged if excessive force is applied to the lead wires. Avoid any compressive, tensile or flexural stress. Do not move the capacitor after soldering to PC board. Do not pick up the PC board by the soldered capacitor. Do not insert the capacitor on the PC board with a hole space different to the lead space specified.	11.4 "Mounting considerations for single-ended capacitors"
Soldering	Do not exceed the specified time or temperature limits during soldering.	11.5 "Soldering"
Soldering, cleaning agents	Do not allow halogenated hydrocarbons to come into contact with aluminum electrolytic capacitors.	11.6 "Cleaning agents"
Upper category temperature	Do not exceed the upper category temperature.	7.2 "Maximum permissible operating temperature"
Passive flammability	Avoid external energy, e.g. fire.	8.1 "Passive flammability"







Topic	Safety information	Reference chapter "General
		technical information"
Active	Avoid overload of the capacitors.	8.2
flammability		"Active flammability"
Maintenance	Make periodic inspections of the capacitors.	10
	Before the inspection, make sure that the power supply is turned off and carefully discharge the	"Maintenance"
	capacitors.	
	Do not apply excessive mechanical stress to the capacitor terminals when mounting.	
Storage	Do not store capacitors at high temperatures or	7.3
Clorage	high humidity. Capacitors should be stored at +5 to +35 °C and a relative humidity of ≤ 75%.	"Shelf life and storage conditions"
		Reference chapter "Capacitors with screw terminals"
Breakdown strength	Do not damage the insulating sleeve, especially	"Screw terminals -
of insulating	when ring clips are used for mounting.	accessories"
sleeves		

Display of ordering codes for TDK Electronics products

The ordering code for one and the same product can be represented differently in data sheets, data books, other publications, on the company website, or in order-related documents such as shipping notes, order confirmations and product labels. The varying representations of the ordering codes are due to different processes employed and do not affect the specifications of the respective products.

Detailed information can be found on the Internet under www.tdk-electronics.tdk.com/orderingcodes.






Extended useful life - 105 $^{\circ}$ C

Symbols and terms

Symbol	English	German
С	Capacitance	Kapazität
C_R	Rated capacitance	Nennkapazität
C_{S}	Series capacitance	Serienkapazität
$C_{S,T}$	Series capacitance at temperature T	Serienkapazität bei Temperatur T
C_{f}	Capacitance at frequency f	Kapazität bei Frequenz f
d	Case diameter, nominal dimension	Gehäusedurchmesser, Nennmaß
d_{max}	Maximum case diameter	Maximaler Gehäusedurchmesser
ESL	Self-inductance	Eigeninduktivität
ESR	Equivalent series resistance	Ersatzserienwiderstand
ESR _f	Equivalent series resistance at frequency f	Ersatzserienwiderstand bei Frequenz f
ESR _T	Equivalent series resistance at temperature T	Ersatzserienwiderstand bei Temperatur T
f	Frequency	Frequenz
1	Current	Strom
I _{AC}	Alternating current (ripple current)	Wechselstrom
$I_{\rm AC,RMS}$	Root-mean-square value of alternating current	Wechselstrom, Effektivwert
$I_{AC,f}$	Ripple current at frequency f	Wechselstrom bei Frequenz f
I _{AC,max}	Maximum permissible ripple current	Maximal zulässiger Wechselstrom
$I_{AC,R}$	Rated ripple current	Nennwechselstrom
l _{leak}	Leakage current	Reststrom
I _{leak,op}	Operating leakage current	Betriebsreststrom
1	Case length, nominal dimension	Gehäuselänge, Nennmaß
I _{max}	Maximum case length (without terminals and mounting stud)	Maximale Gehäuselänge (ohne Anschlüsse und Gewindebolzen)
R	Resistance	Widerstand
R_{ins}	Insulation resistance	Isolationswiderstand
R_{symm}	Balancing resistance	Symmetrierwiderstand
Т	Temperature	Temperatur
ΔT	Temperature difference	Temperaturdifferenz
T_A	Ambient temperature	Umgebungstemperatur
T_C	Case temperature	Gehäusetemperatur
T_B	Capacitor base temperature	Temperatur des Gehäusebodens
t	Time	Zeit
Δt	Period	Zeitraum
t_{b}	Service life (operating hours)	Brauchbarkeitsdauer (Betriebszeit)







Symbol	English	German
V	Voltage	Spannung
V_{F}	Forming voltage	Formierspannung
V_{op}	Operating voltage	Betriebsspannung
V_{R}	Rated voltage, DC voltage	Nennspannung, Gleichspannung
V_S	Surge voltage	Spitzenspannung
X_{C}	Capacitive reactance	Kapazitiver Blindwiderstand
X_L	Inductive reactance	Induktiver Blindwiderstand
Z	Impedance	Scheinwiderstand
Z_T	Impedance at temperature T	Scheinwiderstand bei Temperatur T
$tan \ \delta$	Dissipation factor	Verlustfaktor
λ	Failure rate	Ausfallrate
ϵ_0	Absolute permittivity	Elektrische Feldkonstante
ϵ_{r}	Relative permittivity	Dielektrizitätszahl
ω	Angular velocity; $2 \cdot \pi \cdot f$	Kreisfrequenz; $2 \cdot \pi \cdot f$

Note

All dimensions are given in mm.



Important notes

The following applies to all products named in this publication:

- 1. Some parts of this publication contain statements about the suitability of our products for certain areas of application. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application. As a rule, we are either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether a product with the properties described in the product specification is suitable for use in a particular customer application.
- 2. We also point out that in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
- 3. The warnings, cautions and product-specific notes must be observed.
- 4. In order to satisfy certain technical requirements, some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous). Useful information on this will be found in our Material Data Sheets on the Internet (www.tdk-electronics.tdk.com/material). Should you have any more detailed questions, please contact our sales offices.
- 5. We constantly strive to improve our products. Consequently, the products described in this publication may change from time to time. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also reserve the right to discontinue production and delivery of products. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
- 6. Unless otherwise agreed in individual contracts, all orders are subject to our General Terms and Conditions of Supply.



Important notes

- 7. Our manufacturing sites serving the automotive business apply the IATF 16949 standard. The IATF certifications confirm our compliance with requirements regarding the quality management system in the automotive industry. Referring to customer requirements and customer specific requirements ("CSR") TDK always has and will continue to have the policy of respecting individual agreements. Even if IATF 16949 may appear to support the acceptance of unilateral requirements, we hereby like to emphasize that only requirements mutually agreed upon can and will be implemented in our Quality Management System. For clarification purposes we like to point out that obligations from IATF 16949 shall only become legally binding if individually agreed upon.
- 8. The trade names EPCOS, CeraCharge, CeraDiode, CeraLink, CeraPad, CeraPlas, CSMP, CTVS, DeltaCap, DigiSiMic, ExoCore, FilterCap, FormFit, LeaXield, MiniBlue, MiniCell, MKD, MKK, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, PowerHap, PQSine, PQvar, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, ThermoFuse, WindCap are trademarks registered or pending in Europe and in other countries. Further information will be found on the Internet at www.tdk-electronics.tdk.com/trademarks.

Release 2018-10

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EPCOS / TDK:

 B43890C5106M000
 B43890A9156M
 B43890A5685M
 B43890A5106M
 B43890C5226M
 B43890A9226M

 B43890A5686M
 B43890A5226M
 B43890A9476M
 B43890A4156M
 B43890A4226M
 B43890B5226M

 B43890B5336M
 B43890A5156M
 B43890A9336M
 B43890A9685M
 B43890A5475M
 B43890A9106M

 B43890A5685M8
 B43890A5475M8
 B43890A5156M2
 B43890B5226M9
 B43890A9106M8
 B43890A9685M8

 B43890C5226M000
 B43890C5226M000
 B43890A5156M2
 B43890A5106M
 B43890A9106M8
 B43890A9685M8



Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию.

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России, а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научноисследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,

Промышленная ул, дом № 19, литера Н,

помещение 100-Н Офис 331