

## Insulated Ultrafast Rectifier Module, 60 A


**SOT-227**

### FEATURES

- Two fully independent diodes
- Ceramic fully insulated package ( $V_{ISOL} = 2500 V_{AC}$ )
- Ultrafast reverse recovery
- Ultrasoft reverse recovery current shape
- Low forward voltage
- Optimized for power conversion: welding and industrial SMPS applications
- Industry standard outline
- Plug-in compatible with other SOT-227 packages
- Easy to assemble
- Direct mounting to heatsink
- UL approved file E78996 
- Compliant to RoHS directive 2002/95/EC
- Designed and qualified for industrial level


**RoHS**  
COMPLIANT

### PRODUCT SUMMARY

|                                                    |       |
|----------------------------------------------------|-------|
| $V_R$                                              | 200 V |
| $I_{F(AV)}$ at $T_C = 100\text{ }^{\circ}\text{C}$ | 60 A  |
| $t_{rr}$                                           | 27 ns |

### DESCRIPTION

The UFB60FA20P insulated modules integrate two state of the art Vishay Semiconductors ultrafast recovery rectifiers in the compact, industry standard SOT-227 package. The planar structure of the diodes, and the platinum doping life time control, provide a ultrasoft recovery current shape, together with the best overall performance, ruggedness and reliability characteristics.

These devices are thus intended for high frequency applications in which the switching energy is designed not to be predominant portion of the total energy, such as in the output rectification stage of welding machines, SMPS, dc-to-dc converters. Their extremely optimized stored charge and low recovery current reduce both over dissipation in the switching elements (and snubbers) and EMI/RFI.

### ABSOLUTE MAXIMUM RATINGS

| PARAMETER                                   | SYMBOL         | TEST CONDITIONS                          | MAX.        | UNITS              |
|---------------------------------------------|----------------|------------------------------------------|-------------|--------------------|
| Cathode to anode voltage                    | $V_R$          |                                          | 200         | V                  |
| Continuous forward current per diode        | $I_F$          | $T_C = 100\text{ }^{\circ}\text{C}$      | 30          | A                  |
| Single pulse forward current per diode      | $I_{FSM}$      | $T_C = 25\text{ }^{\circ}\text{C}$       | 250         |                    |
| Maximum power dissipation per module        | $P_D$          | $T_C = 100\text{ }^{\circ}\text{C}$      | 53          | W                  |
| RMS isolation voltage                       | $V_{ISOL}$     | Any terminal to case, $t = 1\text{ min}$ | 2500        | V                  |
| Operating junction and storage temperatures | $T_J, T_{Stg}$ |                                          | - 55 to 150 | $^{\circ}\text{C}$ |

**ELECTRICAL SPECIFICATIONS PER DIODE** ( $T_J = 25\text{ °C}$  unless otherwise specified)

| PARAMETER                          | SYMBOL   | TEST CONDITIONS                               | MIN. | TYP. | MAX. | UNITS         |
|------------------------------------|----------|-----------------------------------------------|------|------|------|---------------|
| Cathode to anode breakdown voltage | $V_{BR}$ | $I_R = 100\text{ }\mu\text{A}$                | 200  | -    | -    | V             |
| Forward voltage                    | $V_{FM}$ | $I_F = 30\text{ A}$                           | -    | 0.96 | 1.08 |               |
|                                    |          | $I_F = 30\text{ A}, T_J = 150\text{ °C}$      | -    | 0.78 | 0.86 |               |
| Reverse leakage current            | $I_{RM}$ | $V_R = V_R\text{ rated}$                      | -    | -    | 100  | $\mu\text{A}$ |
|                                    |          | $T_J = 150\text{ °C}, V_R = V_R\text{ rated}$ | -    | -    | 1.0  | $\text{mA}$   |
| Junction capacitance               | $C_T$    | $V_R = 200\text{ V}$                          | -    | 119  | -    | $\text{pF}$   |

**DYNAMIC RECOVERY CHARACTERISTICS PER DIODE** ( $T_J = 25\text{ °C}$  unless otherwise specified)

| PARAMETER               | SYMBOL    | TEST CONDITIONS                                                             | MIN. | TYP. | MAX. | UNITS |
|-------------------------|-----------|-----------------------------------------------------------------------------|------|------|------|-------|
| Reverse recovery time   | $t_{rr}$  | $I_F = 1.0\text{ A}, di_F/dt = 200\text{ A}/\mu\text{s}, V_R = 30\text{ V}$ | -    | -    | 27   | ns    |
|                         |           | $T_J = 25\text{ °C}$                                                        | -    | 31   | -    |       |
|                         |           | $T_J = 125\text{ °C}$                                                       | -    | 51   | -    |       |
| Peak recovery current   | $I_{RRM}$ | $T_J = 25\text{ °C}$                                                        | -    | 2.7  | -    | A     |
|                         |           | $T_J = 125\text{ °C}$                                                       | -    | 6.8  | -    |       |
| Reverse recovery charge | $Q_{rr}$  | $T_J = 25\text{ °C}$                                                        | -    | 41   | -    | nC    |
|                         |           | $T_J = 125\text{ °C}$                                                       | -    | 174  | -    |       |

**THERMAL - MECHANICAL SPECIFICATIONS**

| PARAMETER                                  | SYMBOL     | TEST CONDITIONS       | MIN. | TYP. | MAX. | UNITS                       |
|--------------------------------------------|------------|-----------------------|------|------|------|-----------------------------|
| Junction to case,<br>single leg conducting | $R_{thJC}$ |                       | -    | -    | 1.9  | $^{\circ}\text{C}/\text{W}$ |
| Junction to case,<br>both leg conducting   |            |                       | -    | -    | 0.95 | K/W                         |
| Case to heatsink                           | $R_{thCS}$ | Flat, greased surface | -    | 0.05 | -    |                             |
| Weight                                     |            |                       | -    | 30   | -    | g                           |
| Mounting torque                            |            |                       | -    | 1.3  | -    | Nm                          |




Fig. 1 - Maximum Forward Voltage Drop Characteristics (Per Diode)




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage




Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics (Per Diode)




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current (Per Leg)




Fig. 7 - Typical Reverse Recovery Time vs.  $dI_F/dt$




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 8 - Typical Stored Charge vs.  $dI_F/dt$

## Note

- (1) Formula used:  $T_C = T_J - (P_d + P_{dREV}) \times R_{thJC}$ ;  
 $P_d$  = Forward power loss =  $I_{F(AV)} \times V_{FM}$  at  $(I_{F(AV)}/D)$  (see fig. 6);  
 $P_{dREV}$  = Inverse power loss =  $V_{R1} \times I_R (1 - D)$ ;  $I_R$  at  $V_{R1}$  = Rated  $V_R$




Fig. 9 - Reverse Recovery Parameter Test Circuit




Fig. 10 - Reverse Recovery Waveform and Definitions

## ORDERING INFORMATION TABLE


**Device code**

|           |          |           |          |          |           |          |
|-----------|----------|-----------|----------|----------|-----------|----------|
| <b>UF</b> | <b>B</b> | <b>60</b> | <b>F</b> | <b>A</b> | <b>20</b> | <b>P</b> |
|-----------|----------|-----------|----------|----------|-----------|----------|

1 2 3 4 5 6 7

1 - Ultrafast rectifier  
 2 - Ultrafast Pt diffused  
 3 - Current rating (60 = 60 A)  
 4 - Circuit configuration (2 separate diodes, parallel pin-out)  
 5 - Package indicator (SOT-227 standard isolated base)  
 6 - Voltage rating (20 = 200 V)  
 7 - P = Lead (Pb)-free


## CIRCUIT CONFIGURATION



| LINKS TO RELATED DOCUMENTS |                                                                        |
|----------------------------|------------------------------------------------------------------------|
| Dimensions                 | <a href="http://www.vishay.com/doc?95036">www.vishay.com/doc?95036</a> |
| Packaging information      | <a href="http://www.vishay.com/doc?95037">www.vishay.com/doc?95037</a> |

## SOT-227

**DIMENSIONS** in millimeters (inches)



### Notes

- Dimensioning and tolerancing per ANSI Y14.5M-1982
- Controlling dimension: millimeter



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331