



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epitaxial Planar Die Construction
- Ideal for Low Power Amplification and Switching
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking: K4M/K2T

Maximum Ratings @ 25°C Unless Otherwise Specified

Symbol	Rating	Rating(PNP)	Unit
V_{CEO}	Collector-Emitter Voltage	40	V
V_{CBO}	Collector-Base Voltage	40	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	0.6	A
P_C	Collector Dissipation	0.2	W
T_J	Operating Junction Temperature	-55 to +150	°C
T_{STG}	Storage Temperature	-55 to +150	°C


Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units	
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage (I _C =-1mA _{DC} , I _B =0)	40	---	V _{dc}	
V _{(BR)CBO}	Collector-Base Breakdown Voltage (I _C =100μA _{DC} , I _E =0)	40	---	V _{dc}	
V _{(BR)EBO}	Collector-Emitter Breakdown Voltage (I _E =100μA _{DC} , I _C =0)	5	---	V _{dc}	
I _{CBO}	Collector Cutoff Current (V _{CB} =50V _{dc} , I _E =0)	---	0.1	μA _{dc}	
I _{EBO}	Emitter Cutoff Current (V _{EB} =-5V _{dc} , I _C =0)	---	0.1	μA _{dc}	
h _{FE}	DC Current Gain (I _C =0.1mA _{DC} , V _{CE} =1V _{dc})	30	---	---	
	(I _C =1mA _{DC} , V _{CE} =1V _{dc})	60	---		
	(I _C =10mA _{DC} , V _{CE} =1V _{dc})	100	----		
	(I _C =150mA _{DC} , V _{CE} =2V _{dc})	100	300		
	(I _C =500mA _{DC} , V _{CE} =2V _{dc})	20	---		
V _{CE(sat)}	Collector-Emitter Saturation Voltage (I _C =150mA _{DC} , I _B =15mA _{DC})	---	0.4	V _{dc}	
	(I _C =500mA _{DC} , I _B =50mA _{DC})	---	0.75		
V _{BE(sat)}	Base-Emitter Saturation Voltage (I _C =150mA _{DC} , I _B =15mA _{DC})	0.75	0.95	V _{dc}	
	(I _C =500mA _{DC} , I _B =50mA _{DC})	---	1.3		
f _T	Current Gain-Bandwidth Product (V _{CE} =10.0V _{dc} , I _C =20mA _{DC} , f=100MHz)	200	---	MHz	
C _{ob}	Output Capacitance (V _{CB} =10V _{dc} , f=1.0MHz, I _E =0)	---	8.5	pF	
t _d	Delay Time	V _{CC} =30V, I _C =150mA, V _{BE} =2.00V, I _{B1} =15.00mA		15	ns
t _r	Rise Time	---		20	ns
t _S	Storage Time	V _{CC} =30V, I _C =150mA, I _{B1} =I _{B2} =15mA		225	ns
t _f	Fall Time	---		30	ns


MMDT4403

PNP Plastic-Encapsulate Transistors

SOT-363



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.006	.014	0.15	0.35	
B	.045	.053	1.15	1.35	
C	.085	.096	2.15	2.45	
D	.026		0.65Nominal		
G	.047	.055	1.20	1.40	
H	.071	.087	1.80	2.20	
J	---	.004	---	0.10	
K	.035	.043	0.90	1.10	
L	.010	.018	0.26	0.46	
M	.003	.006	0.08	0.15	






Fig. 1, Max Power Dissipation vs Ambient Temperature




Fig. 2 Collector Emitter Saturation Voltage vs. Collector Current




Fig. 3 Base-Emitter Voltage vs. Collector Current




Fig. 4 DC Current Gain vs. Collector Current




Fig. 5 Gain Bandwidth Product vs. Collector Current




Fig. 6 Typical Capacitance

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel; 3Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331