Features

- **Fastest Propagation Speeds in the Industry $T_{PD\ (F\ grade)}$ = 2.5 ns, $T_{PD\ (G\ grade)}$ = 2.0 ns**
- **Maximum derating for capacitive loads 1.5ns/100 pF (F grade) and 1.1 ns/100 pF (G grade)**
- **Very low ground bounce < 0.6V @ V_{CC}=5.00 V, T_a=25°C**
- **Excellent noise rejection**
- **Typical output skew ≤0.25ns**
- **Bus Hold circuitry to retain last active state during Tri-State™**
- **Available in SSOP and TSSOP packages**


AT16244 Fast Logic™ 16-Bit Buffer/Line Driver

AT16244F AT16244G

Description

Atmel's Fast Logic 16-Bit Buffer/Line driver provides bus interface and signal buffering at the fastest speeds available in the industry. The Tri-state outputs can be set for either 4-bit, 8-bit, or 16-bit independent operation. The AT16244 also has bus-hold circuitry which retains the last state of the input whenever a high impedance level is detected, and eliminates the need for pull-up or pull-down resistors. Minimal ground bounce and high input noise rejection make this device excellent for use in all high speed interface applications.

Functional Block Diagram (1)




Note: 1. The function shown is repeated 3 additional times on each device.

Pin Configurations

Pin Names	Descriptions
$x\overline{OE}$	Output Enable Input (Active Low)
xAχ	Data Inputs
xYχ	Tri-State Outputs

SSOP/TSSOP



Top View

0755B

Function Table[1]

Inputs		Outputs
$x\overline{OE}$	$xA\chi$	$xY\chi$
L	L	L
L	H	H
H	X	Z

Note: 1. X = Don't Care, Z = High Impedance

Absolute Maximum Ratings*

Operating Temperature	0°C to +70°C
Storage Temperature	-65°C to +150°C
Voltage on any Pin with Respect to Ground	-2.0V to +7.0V[1]
Maximum Operating Voltage	6.0V

*NOTICE: Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Notes: 1. Minimum voltage is -0.6V dc which may undershoot to -2.0V for pulses of less than 20 ns. Maximum output pin voltage is V_{CC} +0.75V dc which may overshoot to +7.0V for pulses of less than 20 ns.

5.0 Volt DC Characteristics

Applicable over recommended operating range from T_a = 0°C to +70°C, V_{CC} = +5.0V +/- 5% (unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
ΔI_{CC}	Quiescent Power Supply Current	V_{CC} = Max, V_{IN} = 3.4V		0.8	1.2	mA
V_{IH}	Input High Voltage		2.0			V
V_{IL}	Input Low Voltage				0.8	V
I_{IH}	Input High Current (I/O Pins)	V_{IN} = V_{CC}			±15	µA
I_{IL}	Input Low Current (I/O Pins)	V_{IN} = GND			±15	µA
I_{OZ}	Output Leakage Current				±10	mA
V_{OH}(1)	Output High Voltage F Grade only	V_{CC} = 4.75V I_{OH} = -10 mA	2.7			V
V_{OH}(2)	Output High Voltage G Grade only	V_{CC} = 4.75V I_{OH} = -12 mA	2.7			V
V_{OL}	Output Low Voltage (F Grade)	I_{OL} = 10 mA			0.55	V
V_{OL}	Output Low Voltage (G Grade)	I_{OL} = 12 mA			0.55	V

Note: 1. F grade: At $V_{CC\ (max)}$, the value of $V_{OH(max)}$ = 3.75V and at $V_{CC(min)}$, $V_{OH(max)}$ = 3.25V
2. G grade: At $V_{CC\ (max)}$, the value of $V_{OH(max)}$ = 3.75V and at $V_{CC(min)}$, $V_{OH(max)}$ = 3.35V

AC Characteristics
AT16244F

Applicable over recommended operating range from T_a = 0°C to +70°C, V_{CC} = 5.0V +/- 5% (unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
t_{PHL} t_{PLH}	Propagation Delay	CL = 50 pF			2.5	ns
t_{PZH} t_{PZL}	Output Enable Time	CL = 50 pF			5.5	ns
t_{PHZ} t_{PLZ}	Output Disable Time	CL = 50 pF			6.0	ns
t_{SK}(1)	Output Skew	CL = 50 pF			0.5	ns
Δt_{PHL}(1) Δt_{PLH}	Propagation Delay vs Output Loading			1.3	1.5	ns/100 pF

Note: 1. This parameter is guaranteed but not 100% tested.


AT16244G

Applicable over recommended operating range from T_a = 0°C to +70°C, V_{CC} = 5.0V +/- 5% (unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
t_{PHL} t_{PLH}	Propagation Delay	CL = 50 pF			2.0	ns
t_{PZH} t_{PZL}	Output Enable Time	CL = 50 pF			5.5	ns
t_{PHZ} t_{PLZ}	Output Disable Time	CL = 50 pF			5.0	ns
t_{SK}(1)	Output Skew	CL = 50 pF			0.5	ns
Δt_{PHL}(1) Δt_{PLH}	Propagation Delay vs Output Loading			0.9	1.1	ns/100 pF

Note: 1. This parameter is guaranteed but not 100% tested.

Test Circuits(1,2)



Note: 1. Pulse Generator: Rate ≤ 1.0 MHz, $t_F \leq 2.5$ ns, $t_R \leq 2.5$ ns.
2. AC tests are done with a single bit switching, and timings need to be derated when multiple outputs are switching in the same direction simultaneously. This derating should not exceed 0.5 ns for 16 inputs switching simultaneously.

Switch Position


Test	Switch
Open Drain Disable Low Enable Low	Closed
All Other Tests	Open

Definitions:


C_L= Load capacitance; Includes jig and probe capacitance.

R_T=Termination resistance; Should be equal to Z_{OUT} of the Pulse Generator.


IOL Pull Down Current



Ground Bounce for High to Low Transitions(1)



Supply Bounce for Low to High Transitions(2)




Typical Values

Parameter	Value	Units
V_{OLP}	0.4	V
V_{OLV}	-0.26	V
V_{OHV}	V_{CC} - 0.13	V
V_{OHP}	V_{CC} + 0.6	V


Note: 1. When multiple outputs are switched at the same time, rapidly changing current on the ground and V_{CC} paths causes a voltage to develop across the parasitic inductance of the wire bond and package pins. This occurrence is called simultaneous switching noise. Atmel's AT16244 products have minimized this phenomenon as shown on the graph. Output data is for 15 outputs switching simultaneously at a frequency of 1 MHz. The ground data is measured on the one remaining output, which is set to logic low and will reflect any device ground movement.

2. As on the graph for Ground Bounce, a similar condition occurs for low to high transitions. Output data is for 15 outputs switching simultaneously at a frequency of 1 MHz. V_{CC} droop is measured on the one remaining output pin, which is set to a logic high. This output will reflect any movement on the device V_{CC}.

Propagation Delay Waveforms



Enable and Disable Waveforms



Ordering Information

T_{PD}	Ordering Code	Package	Operation Range
2.5 ns	AT16244F - 25YC AT16244F - 25XC	48Y 48X	Commercial
2.0 ns	AT16244G - 20YC AT16244G - 20XC	48Y 48X	Commercial

Package Type	
48X	48 Pin, Plastic Thin Shrink Small Outline Package (TSSOP)
48Y	48 Pin, Plastic Shrink Small Outline Package (SSOP)

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331