


anti-surge power type leaded resistor



features

- Excellent anti-surge characteristics
- Stable characteristics of moisture resistance up to high resistance range
- RCR50 (+1M Ω - 12M Ω), RCR50EN (1M Ω - 12M Ω) and RCR60 (1M Ω - 12M Ω) are discharge resistors recognized by UL1676 and c-UL(CSA-C22.2 No.1-M94)
- RCR25EN (100 Ω ~33M Ω), RCR50EN (100k Ω - 33M Ω) and RCR60 (470k Ω - 56M Ω) is approved by EN60065 14.1 safety
- Marking: Blue-gray body color with color-coded bands
- Products with lead-free terminations meet EU RoHS requirements. EU RoHS regulation is not intended for Pb-glass contained in electrode, resistor element and glass.
- Surface mount style "N" forming is suitable for automatic mounting

dimensions and construction



* Lead length changes depending on taping and forming.

Type	Dimensions inches (mm)					
	L	C (max.)	t (max.)	D	d (nom.)	I*
RCR16	.126 $\pm$.008 (3.2 $\pm$ 0.2)	.134 (3.4)	—	.067 $\pm$.008 (1.7 $\pm$ 0.2) -0.1	.018 (0.45)	.787 Min. (20.0 Min.)
RCR25 RCR25EN	.248 $\pm$.02 (6.3 $\pm$ 0.5)	.28 (7.1)	—	.098 $\pm$.02 (2.5 $\pm$ 0.5)	.024 (0.6)	
RCR50(+) RCR50EN	.374 $\pm$.039 (9.5 $\pm$ 1.0)	—	.118 (3.0)	.138 $\pm$.016 (3.5 $\pm$ 0.4)	.028 (0.7)	
RCR60	.374 $\pm$.039 (9.5 $\pm$ 1.0) -0.2	—	.118 (3.0)	.157 $\pm$.02 (4.0 $\pm$ 0.5)	.031 (0.8)	
RCR75	.472 $\pm$.039 (12 $\pm$ 1.0)	—	.118 (3.0)	.236 $\pm$.039 (6.0 $\pm$ 1.0) -0.4	.031 (0.8)	
RCR100	.610 $\pm$.039 (15.5 $\pm$ 1.0)	—	.118 (3.0)			

ordering information

New Part #	RCR	50	EN	C	T52	A	105	J
Type	RCR	Power Rating	Safety Appr. Marking	Termination Material	Taping and Forming	Packaging	Nominal Resistance	Tolerance
		16: 0.25W 25: 0.25W 50: 0.5W 60: 1W 75: 2W 100: 3W	RCR50+: + RCR25EN, RCR50EN: EN Blank: Others	C: SnCu	RCR16: T26, T52 RCR25, RCR25EN: T26, T52 RCR50(+, EN): T52 RCR60: T52 RCR75: T52 RCR100: T521, T631 L, M, N Forming	A: Ammo R: Reel TEB: Plastic embossed N forming	2 significant figures + 1 multiplier for $\pm$ 5% 3 significant figures + 1 multiplier for $\pm$ 1%	F: $\pm$ 1% J: $\pm$ 5%

applications and ratings

Part Designation	Power Rating @ 70°C	Minimum Dielectric Withstanding Voltage	Resistance Range E-24, E-96 (F±1%)	Resistance Range E-24 (J±5%)	Absolute Maximum Working Voltage	Absolute Maximum Overload Voltage	Operating Temperature Range
RCR16	0.25W	300V	100kΩ - 5.1MΩ	100kΩ - 5.1MΩ	500V	1000V	-55°C to +155°C
RCR25 NEW RCR25EN		700V	100kΩ - 9.1MΩ	100kΩ - 33MΩ	DC 1600V AC 1150V	DC 2000V AC 1500V	
RCR50	3.3Ω - 910kΩ		3.3Ω - 910kΩ	2000V	2500V		
						13MΩ - 33MΩ	
RCR50+	1MΩ - 9.1MΩ		1MΩ - 12MΩ				
RCR50EN	100kΩ - 9.1MΩ		100kΩ - 33MΩ				
RCR60	1.0W		100kΩ - 9.1MΩ	100kΩ - 56MΩ	4000V	5000V	
RCR75	2.0W	100kΩ - 9.1MΩ	100kΩ - 100MΩ	5000V			
RCR100	3.0W	1000V	100kΩ - 9.1MΩ		100kΩ - 33MΩ		


For further information on packaging, please refer to Appendix C.

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

1/03/14

environmental applications

Derating Curve




For resistors operated at an ambient temperature of 70°C or above, a power rating shall be derated in accordance with the above derating curve.

Notice of Surge Load

Surge withstanding load voltage for the resistors cannot be guaranteed when the undermentioned 4 items get to a remarkable overload in comparison with the conditions shown by surge withstanding voltage in Anti-surge characteristics. Please contact KOA in advance if such a case is anticipated.

1. Peak voltage to be applied
2. Pulse width
3. Conditions of protecting insulation around the resistor
4. Situation of proximity conductivity object

For example: In the figure, a metal wire is placed less than 5mm away from the resistor body, there is such a case that causes an electric discharge by a surge load 10kV and then destroys the outer coating.



Performance Characteristics

Parameter	Requirement $\Delta R \pm(\% + 0.05\Omega)$			Typical	Test Method				
	Limit								
Resistance	Within regulated tolerance			—	Measuring points are 10mm ± 1mm from the end cap				
T.C.R.	Type	T.C.R.	Resistance Range	—	Room temperature/100°C up				
	RCR16	±200ppm/°C	100kΩ - 5.1MΩ						
	RCR25 (EN)	±350ppm/°C	100kΩ - 33MΩ						
	RCR50 (+)	±500ppm/°C	3.3Ω - 91kΩ						
		±350ppm/°C	100kΩ - 33MΩ						
	RCR50EN	±350ppm/°C	100kΩ - 33MΩ						
	RCR60	±350ppm/°C	100kΩ - 56MΩ						
	RCR75	±350ppm/°C	100kΩ - 100MΩ						
RCR100	±200ppm/°C	100KΩ - 33MΩ							
Overload	1%			0.5%	Rated voltage x 2.5 or maximum overload voltage for 5 seconds, whichever is less				
Resistance to Solder Heat	1%			0.5%	260°C ± 5°C, 10 seconds ± 1 second or 350°C ± 10°C, 3.5 seconds ± 0.5 seconds				
Terminal Strength	No mechanical damage			—	Twist 360°, 5 times				
Rapid Change of Temperature	1%			0.5%	-55°C (30 minutes)/+155°C (30 minutes), 5 cycles				
Moisture Resistance	5%			2.5%	40°C ± 2°C, 90-95% RH, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle RCR16, 25, 50 (+), 60: W; RCR75, 100: Wx0.1				
Endurance @ 70°C	5%			2.5%	70°C ± 2°C, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle				
Resistance to Solvent	No visible damage to protective coating and marking			—	Isopropyl alcohol with ultrasonic washing, 2 minutes Power: 0.3W/cm², f: 28kHz, Temperature: 35°C ± 5°C				
Surge Withstanding	10%			2.5%	Discharge test: 2kV - 10kV, 0.01μF capacitor discharge pulse, 10 times (1 pulse/5 seconds maximum)				
					Type	RCR16	RCR25 RCR25EN	RCR50, RCR50+	RCR50EN, RCR60, RCR75, RCR100
					Applied Voltage	2kV	3kV	3.3Ω - 6.2Ω: 10kV	10kV
								6.8Ω - 10Ω: 7kV	
								11Ω - 9.1kΩ: 5kV	
								10kΩ - 91kΩ: 7kV	
			100kΩ - 33MΩ: 10kV						
EN60065 Test (RCR50EN, RCR60 only)	20%			—	Discharge test: 10kV, 1000pF capacitor discharge pulse, 50 times (1 pulse/5 seconds maximum)				



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331