

# SPECIFICATION CONTROL DRAWING

**55PC0241**

TITLE

FOUR CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, 600 VOLT

Date


10-22-05

Revision

B

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC0211



## CONSTRUCTION DETAILS

| PART NUMBER<br><u>1/</u> | CONDUCTOR<br>SIZE<br>(AWG) | DIAMETER<br>( in. ) |                 |                     | WEIGHT<br>( lbs/1000 ft. ) |                     |
|--------------------------|----------------------------|---------------------|-----------------|---------------------|----------------------------|---------------------|
|                          |                            | LOWER SPEC<br>LIMIT | TARGET<br>VALUE | UPPER SPEC<br>LIMIT | TARGET<br>VALUE            | UPPER SPEC<br>LIMIT |
| 55PC0241-24-*            | 24                         | .087                | .102            | .117                | 8.06                       | 8.38                |
| 55PC0241-22-*            | 22                         | .100                | .117            | .134                | 11.80                      | 12.19               |
| 55PC0241-20-*            | 20                         | .119                | .139            | .159                | 17.83                      | 18.32               |
| 55PC0241-18-*            | 18                         | .139                | .163            | .188                | 26.83                      | 27.56               |
| 55PC0241-16-*            | 16                         | .155                | .182            | .209                | 34.07                      | 34.92               |
| 55PC0241-14-*            | 14                         | .189                | .221            | .253                | 52.44                      | 53.64               |
| 55PC0241-12-*            | 12                         | .231                | .270            | .309                | 80.33                      | 81.99               |
| 55PC0241-10-*            | 10                         | .283                | .331            | .379                | 126.67                     | 129.46              |

## CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms) at sea level

INSULATION FLAWS:

Impulse Dielectric Test, 8.0 kV (peak)

PART NUMBER:

The "\*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors. Colors shown do not necessarily reflect the sequence of manufacturing.

1/ Example: AWG 22, black, red, orange and yellow component wires: 55PC0241-22-0/2/3/4

*Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.*

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx"). OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.  
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

**tyco**  
Electronics

**Raychem** Wire & Cable  
501 Oakside Avenue  
Redwood City, CA 94063-3800  
Phone: 1-800-227-8816  
Fax: 1-650-361-6297

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## TE Connectivity:

[55PC0241-16-2/4/5/6CS2970](#) [55PC0241-22-ST4CS2666](#) [55PC0241-16-2/4/5/6CS2502](#) [55PC0241-20-2/4/5/6CS2502](#) [55PC0241-20-9/93/95/96](#) [55PC0241-22-2/4/5/6CS2970](#) [55PC0241-16-3/5/6/9](#) [55PC0241-20-2/4/5/6CS2970](#) [55PC0241-12-2/4/5/6CS2502](#) [55PC0241-22-2/4/5/6CS2502](#) [55PC0241-22-3/5/6/9](#) [55PC0241-16-9/93/95/96](#)



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331