






Optocoupler, Phototriac Output, Non-Zero Crossing, 1.5 kV/ μ s dV/dt, 600 V



i179041-2



FEATURES

- 1500 V/ μ s dV/dt minimum 2000 V/ μ s typical
- 600 V blocking voltage
- 100 mA on-state current
- Low input trigger current
- 6 pin DIP package
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT

APPLICATIONS

- Household appliances
- Triac drive/AC motor drives
- Solenoid/valve controls
- Office automation equipment/machine
- Temperature (HVAC)/lighting controls
- Switching power supply

AGENCY APPROVALS



- UL-file E52744 system code H or J
- cUL - file no. E52744, equivalent to CSA bulletin 5A
- DIN EN 60747-5-2 (VDE 0884) available with option 1

DESCRIPTION

The VO3052 and VO3053 triac driver family consists of a GaAs infrared LED optically coupled to a monolithic photosensitive non-zero crossing triac detector chip.

The 600 V blocking voltage permits control of off-line voltages up to 240 V_{AC}, with a safety factor or more than two, and is sufficient for as much as 380 V.

ORDERING INFORMATION



| AGENCY CERTIFIED/PACKAGE | TRIGGER, CURRENT I _{FT} (mA) | |
|--------------------------|---------------------------------------|--------------|
| | 5 | 10 |
| UL, cUL | | |
| DIP-6 | VO3053 | VO3052 |
| DIP-6, 400 mil, option 6 | VO3053-X006 | VO3052-X006 |
| SMD-6, option 7 | VO3053-X007T | VO3052-X007T |
| SMD-6, option 9 | VO3053-X009T | - |
| VDE, UL, cUL | 5 | 10 |
| DIP-6, 400 mil, option 6 | - | VO3052-X016 |

| ABSOLUTE MAXIMUM RATINGS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | |
|--|----------------------|----------------|--------------|---------------|--------------------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | VALUE | UNIT |
| INPUT | | | | | |
| Reverse voltage | | | V_R | 6 | V |
| Forward current - continuous | | | I_F | 60 | mA |
| Power dissipation | | | P_{diss} | 100 | mW |
| OUTPUT | | | | | |
| Off state output terminal voltage | | VO3052, VO3053 | V_{DRM} | 600 | V |
| Peak non-repetitive surge current | PW = 100 ms, 120 pps | | I_{TSM} | 1 | A |
| Power dissipation | | | P_{diss} | 200 | mW |
| On-state RMS current | | | $I_{T(RMS)}$ | 100 | mA |
| COUPLER | | | | | |
| Isolation test voltage | t = 1 s | | V_{ISO} | 5300 | V_{RMS} |
| Total power dissipation | | | P_{tot} | 300 | mW |
| Operating temperature | | | T_{amb} | - 55 to + 100 | $^{\circ}\text{C}$ |
| Storage temperature | | | T_{stg} | - 55 to + 150 | $^{\circ}\text{C}$ |
| Soldering temperature ⁽¹⁾ | 10 s | | T_{sld} | 260 | $^{\circ}\text{C}$ |

Notes

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

⁽¹⁾ Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP) "Assembly Instructions" (www.vishay.com/doc?80054).

| THERMAL CHARACTERISTICS | | | | |
|---|----------------|-------|-----------------------------|--|
| PARAMETER | SYMBOL | VALUE | UNIT | |
| Maximum LED junction temperature | T_{jmax} | 125 | $^{\circ}\text{C}$ | |
| Maximum output die junction temperature | T_{jmax} | 125 | $^{\circ}\text{C}$ | |
| Thermal resistance, junction emitter to board | θ_{JEB} | 150 | $^{\circ}\text{C}/\text{W}$ | |
| Thermal resistance, junction emitter to case | θ_{JEC} | 139 | $^{\circ}\text{C}/\text{W}$ | |
| Thermal resistance, junction detector to board | θ_{JDB} | 78 | $^{\circ}\text{C}/\text{W}$ | |
| Thermal resistance, junction detector to case | θ_{JDC} | 103 | $^{\circ}\text{C}/\text{W}$ | |
| Thermal resistance, junction emitter to junction detector | θ_{JED} | 496 | $^{\circ}\text{C}/\text{W}$ | |
| Thermal resistance, case to ambient | θ_{CA} | 3563 | $^{\circ}\text{C}/\text{W}$ | |

Note

- The thermal model is represented in the thermal network below. Each resistance value given in this model can be used to calculate the temperatures at each node for a given operating condition. The thermal resistance from board to ambient will be dependent on the type of PCB, layout and thickness of copper traces. For a detailed explanation of the thermal model, please reference Vishay's Thermal Characteristics of Optocouplers application note.



| ELECTRICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | | |
|--|---|--------|--------------|------|------|------|------------------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| INPUT | | | | | | | |
| Reverse current | $V_R = 6\text{ V}$ | | I_R | | | 10 | μA |
| Forward voltage | $I_F = 30\text{ mA}$ | | V_F | | 1.2 | 1.5 | V |
| OUTPUT | | | | | | | |
| Leakage with LED off, either direction | $V_{DRM} = 600\text{ V}$ | | I_{DRM} | | 10 | 500 | nA |
| Critical rate of rise off-state voltage | $V_D = 400\text{ V}$ | | dV/dt_{cr} | 1500 | 2000 | | V/ μs |
| COUPLER | | | | | | | |
| LED trigger current, current required to latch output | | VO3053 | I_{FT} | | | 5 | mA |
| | | VO3052 | I_{FT} | | | 10 | mA |
| Peak on-state voltage, either direction | $I_{TM} = 100\text{ mA peak}$, $I_F = \text{rated } I_{FT}$ | | V_{TM} | | 1.7 | 3 | V |
| Holding current, either direction | | | I_H | | 200 | | μA |
| Coupling capacitance | 10 KHz | | C_{IO} | | 0.4 | | pF |

Note

- Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements.

| SAFETY AND INSULATION RATINGS | | | | | | |
|---|------------|-----------|-----------|------|--------------------|--|
| PARAMETER | SYMBOL | MIN. | TYP. | MAX. | UNIT | |
| Climatic classification (according to IEC 68 part 1) | | | 55/100/21 | | | |
| Pollution degree (DIN VDE 0109) | | | 2 | | | |
| Comparative tracking index | CTI | 175 | | | | |
| Peak transient overvoltage | V_{IOTM} | 8000 | | | V_{peak} | |
| Peak working insulation voltage | V_{IORM} | 890 | | | V_{peak} | |
| Isolation resistance at $T_{amb} = 100\text{ }^{\circ}\text{C}$, $V_{DC} = 500\text{ V}$ | R_{IO} | 10^{11} | | | Ω | |
| Isolation resistance at $T_{amb} = 25\text{ }^{\circ}\text{C}$, $V_{DC} = 500\text{ V}$ | R_{IO} | 10^{12} | | | Ω | |
| Partial discharge test voltage (method a, $V_{pd} = V_{IORM} \times 1.875$) | V_{pd} | 1669 | | | V_{peak} | |
| Safety rating - power | P_{SO} | | | 500 | mW | |
| Safety rating - input current | I_{SI} | | | 250 | mA | |
| Safety rating - temperature | T_{SI} | | | 175 | $^{\circ}\text{C}$ | |
| Clearance distance (Standard DIP-6) | | 7 | | | mm | |
| Creepage distance (Standard DIP-6) | | 7 | | | mm | |
| Clearance distance (400 mil DIP-6) | | 8 | | | mm | |
| Creepage distance (400 mil DIP-6) | | 8 | | | mm | |

Note

- According to DIN EN60747-5-5 (see figure 4). This optocoupler is suitable for safe electrical isolation only within the safety ratings. Compliance with the safety ratings shall be ensured by means of suitable protective circuits.

TYPICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)




Fig. 1 - Forward Voltage vs. Forward Current




Fig. 2 - Off-State Leakage Current vs. Temperature




Fig. 3 - On-State Current vs. V_{TM}




Fig. 6 - Normalized Holding Current vs. Temperature




Fig. 4 - Normalized Trigger Current vs. Temperature




Fig. 7 - Turn-on Time vs. Temperature




Fig. 5 - Turn-on Time vs. LED Current








Fig. 8 - Trigger Current vs. Pulse Width



PACKAGE DIMENSIONS in millimeters






i178014



Option 6

Option 7


Option 9



20802-24



PACKAGE MARKING



Notes

- The VDE logo is only marked on option1 parts.
- Tape and reel suffix (T) is not part of the package marking.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331