

**BSX62
BSX63**

NPN SILICON TRANSISTOR



TO-39 CASE

CentralTM
Semiconductor Corp.

DESCRIPTION:

The CENTRAL SEMICONDUCTOR BSX62, BSX63 types are NPN Silicon Transistors designed for general purpose applications where high collector current is required.

MARKING: FULL PART NUMBER

MAXIMUM RATINGS: (T_C=25°C)

	SYMBOL	BSX62	BSX63	UNITS
Collector-Base Voltage	V _{CB0}	60	80	V
Collector-Emitter Voltage	V _{CEO}	40	60	V
Emitter-Base Voltage	V _{EBO}		5.0	V
Collector Current	I _C		3.0	A
Power Dissipation	P _D		5.0	W
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 to +200		°C
Thermal Resistance	θ _{JC}	35		°C/W

ELECTRICAL CHARACTERISTICS: (T_C=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I _{CBO}	V _{CB} =40V (BSX62)			100	nA
I _{CBO}	V _{CB} =40V, T _C =150°C (BSX62)			100	μA
I _{CBO}	V _{CB} =60V (BSX63)			100	nA
I _{CBO}	V _{CB} =60V, T _C =150°C (BSX63)			100	μA
I _{EBO}	V _{EB} =5.0V			100	nA
V _{CE(SAT)}	I _C =1.0A, I _B =100mA			0.7	V
V _{CE(SAT)}	I _C =2.0A, I _B =200mA			0.8	V
V _{BE(SAT)}	I _C =1.0A, I _B =100mA			1.2	V
V _{BE(SAT)}	I _C =2.0A, I _B =200mA			1.3	V
V _{BE(ON)}	V _{CE} =1.0V, I _C =100mA			1.0	V
V _{BE(ON)}	V _{CE} =1.0V, I _C =1.0A			1.2	V
V _{BE(ON)}	V _{CE} =5.0V, I _C =2.0A			1.3	V
h _{FE}	V _{CE} =1.0V, I _C =1.0A (BSX62, 63-10)	63		160	
h _{FE}	V _{CE} =1.0V, I _C =1.0A (BSX62, 63-16)	100		250	
C _{ob}	V _{CB} =10V, I _E =0, f=1.0MHz			70	pF
f _T	V _{CE} =10V, I _C =200mA, f=100MHz	30			MHz
t _{on}	I _C =1.0A, I _{B1} =I _{B2} =50mA			300	ns
t _{off}	I _C =1.0A, I _{B1} =I _{B2} =50mA		4.0		μs

NPN SILICON TRANSISTOR

TO-39 CASE - MECHANICAL OUTLINE



SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A (DIA)	0.335	0.370	8.51	9.40
B (DIA)	0.315	0.335	8.00	8.51
C	-	0.040	-	1.02
D	0.240	0.260	6.10	6.60
E	0.500	-	12.70	-
F (DIA)	0.016	0.021	0.41	0.53
G (DIA)	0.200		5.08	
H	0.100		2.54	
I	0.028	0.034	0.71	0.86
J	0.029	0.045	0.74	1.14

TO-39 (REV: R1)

LEAD CODE:

- 1) EMITTER
- 2) BASE
- 3) COLLECTOR (case)

MARKING: FULL PART NUMBER

R0 (2-April 2008)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331