

## ReliaGATE 20-25

- **Reliable Performance**
- **Integrated 3G/LTE Cellular**
- **Truly Industrial**
- **Field Protocol Support**
- **Cloud Certified**
- **Open Platform**
- **Customizable**



### FEATURES

**Reliable Performance** - Powerful and efficient: single, dual and quad core Intel Atom E38xx, soldered-down eMMC storage and ECC memory for additional protection

**Integrated Cellular** - Certified 3G/LTE cellular modems can be integrated. It also supports Eurotech's ReliaCELL 10-20, the cellular module with global carrier precertifications

**Truly Industrial** - Extended operating temperature, a wide range power supply with surge and sag protection, isolated and protected DIO, protected USB and serial

**Field Protocol Support** - Native support for Modbus, S7 and OPC UA, the extensible, secure, and platform-independent industrial interoperability standard

**Cloud Certified** - Seamless integration with Eurotech Everyware Cloud, Microsoft Azure, Amazon Web Services IoT and other Cloud services

**Open Platform** - Provides a Java/OSGi gateway middleware, to free the developer from proprietary solutions

**Customizable** - Flexible: personalization and full customization options are available, ranging from branding ("skin" and color) to deep HW/SW configurations

The ReliaGATE 20-25 is a high-performance, globally certified, IoT gateway for industrial and lightly rugged applications.

It features up to four cores, soldered-down ECC RAM and storage, extended operating temperature support, wide range power supply, isolated and protected I/O interfaces, and customizable connectivity options.

The ReliaGATE 20-25 configuration options include GPS and LTE connectivity, both integrated and through the ReliaCELL 10-20 family of 2G/3G/LTE external modems with global carrier precertifications.

The ReliaGATE 20-25 comes with Everyware Software Framework (ESF), a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/OSGi middleware for IoT gateways.

Distributed and supported by Eurotech, ESF adds advanced security, diagnostics, provisioning and remote access. It supports ready-to-use field protocols (including Modbus, OPC-UA, S7), MQTT connectivity, web-based visual data flow programming and deep configuration.

ESF is also integrated with Everyware Cloud (EC), Eurotech's IoT Integration Platform (separately available), enabling advanced diagnostics, provisioning, and full remote device access and management.

The ReliaGATE 20-25 is Microsoft Azure certified and can also be integrated with 3rd party cloud services such as Amazon Web Services IoT.

Used stand-alone, or in conjunction with EC, the ReliaGATE 20-25 provides a fast go-to-market solution for projects of any size.

## ReliaGATE 20-25

## Specifications

HARDWARE CONFIGURATION		- □1	- □2	- □3	- □4	- □5	- □8
PROCESSOR	<b>CPU</b>	E3815, 1.46GHz, Single Core	E3827, 1.75GHz, Dual Core		E3845, 1.91GHz, Quad Core		
MEMORY	<b>RAM</b>	2GB, 1067MHz, (DDR3L-ECC)	2GB, 1333MHz, (DDR3L-ECC)		4GB, 1333MHz, (DDR3L-ECC)		
STORAGE	<b>Embedded</b>	8GB eMMC					
	<b>SATA</b>	1x SATA 2.0 - Internal Connector 1x 32GB mSATA (Included on -□4 Variants)					
	<b>Other</b>	1x microSD Slot (User Accessible)					
I/O INTERFACES	<b>Ethernet</b>	2x 10/100/1000Mbps - RJ45					
	<b>USB</b>	1x Host 3.0, 1x Host 2.0, 1x ReliaCELL (Noise and Surge Protected) - Type A					
	<b>Serial</b>	2x RS-232/RS-422/RS-485 (9 Wires, Noise and Surge Protected) - DB9 1x Serial Console TTL					
	<b>CAN 2.0B</b>	1x CAN bus with 5V (100mA) Power Out					
	<b>Digital I/O</b>	3x Digital Input 7 - 35VDC, 1KV Optoisolated - 3x Digital Output (40VDC), 20mA Sink					
	<b>Video</b>	1x mini DisplayPort					
	<b>Audio</b>	Factory Option					
	EXPANSION	<b>miniPCIe Slots</b>	Up to 3x Full/Half Size Mini PCIe (PCIe/USB/mSATA)				
RADIO INTERFACES	<b>Cellular</b>	Eurotech ReliaCELL 10-20					LTE Cat 4 (EU) 3G Fallback
	<b>GPS</b>	Eurotech ReliaCELL 10-20 Factory Option: Integrated GPS					
	<b>Wi-Fi / BT</b>	No	b/g/n, BLE	No	b/g/n, BLE		
OTHER	<b>RTC</b>	Yes (User Accessible Battery)					
	<b>Ext. Watchdog</b>	Yes					
	<b>EEPROM</b>	256kbit					
	<b>Sensors</b>	Temperature, Accelerometer					
	<b>LEDs</b>	1x Power, 3x miniPCIe Slot, 2x Programmable (Dual Color Green/Amber)					
	<b>Buttons</b>	1x Reset, 1x Programmable					
POWER	<b>Input</b>	7 - 35VDC (Nominal 12VDC), Surge and Sag Protection, Vehicle Ignition Input					
	<b>Consumption</b>	7W Idle	10W Idle		12W Idle		
ENVIRONMENT	<b>Operating Temp</b>	- 20 to +60°C	- 40 to +65°C				
	<b>Storage Temp</b>	- 40 to +85°C					
CERTIFICATIONS	<b>Regulatory</b>	CE, FCC, ISED					
	<b>Safety</b>	EN 62368, UL <sup>®</sup> 60950					
	<b>Environmental</b>	RoHS2; REACH					
	<b>Wi-Fi / BT Radio</b>	CE (RED), FCC					CE (RED)
	<b>Cellular Radio</b>	Eurotech ReliaCELL 10-20 Carrier Certifications					CE (RED)
	<b>IoT Platform</b>	Microsoft Azure Certified					
	<b>Ingress</b>	IP40					
MECHANICAL	<b>Enclosure</b>	Material: Anodized Aluminium - Color: Aluminum					
	<b>Dimensions</b>	192x131x52mm (WxDxH)					
SOFTWARE CONFIGURATION		- 3□			- 4□		
SOFTWARE	<b>OS</b>	Yocto Linux			Windows 10 IoT Enterprise		
	<b>SDK</b>	Yocto-based Eclipse Tooling, Oracle Java SE			-		
	<b>IoT Framework</b>	Everyware Software Framework (Java/OSGi)			-		

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies. § UL, NRTL listing Factory Option.

ETH\_ReliaGATE 20-25\_DS\_EN\_Rev 11\_11/2017



## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331