

MA4P MELF & HIPAX™ Series

High Power PIN Diodes

V14

Features

- ◆ High Power Handling
- ◆ Low Loss / Low Distortion
- ◆ Voltage Ratings up to 1000 Volts
- ◆ Passivated Chip for Low Leakage Current
- ◆ Low Theta (θ) Due to Full Face Chip Bonding
- ◆ Leadless Low Inductance MELF Packages
- ◆ Various Package Options
- ◆ Available as Chips
- ◆ Fully RoHS Compliant
- ◆ Non-Magnetic Packages Available for MRI

Description

M/A-COM Technology Solutions MELF and HIPAX PIN diode series are designed for usage in switch and attenuator applications requiring high power handling and low distortion. The MELF and HIPAX PIN diodes incorporate a fully passivated PIN diode chip resulting in an extremely low reverse bias leakage current. The semiconductor technology utilized in the MELF and HIPAX families draws on M/A-COM Tech's substantial experience in PIN diode design and wafer fabrication. The result is a device which has a thick I-region and long carrier lifetime while maintaining low series resistance and capacitance values. The chips of the MELF and HIPAX PIN diodes are enclosed in a rugged ceramic package and is full face bonded to metal pins on both the anode and cathode. The result is a low loss PIN diode with low thermal resistance due to symmetrical thermal paths. The parts are offered in either magnetic or non-magnetic, HIPAX (axial leaded) or **Metal Electrode Leadless Faced (MELF)** surface mount packages for MRI applications. The MELF is a rectangular SMQ, package which is designed for high volume tape and reel assembly. This easy to use package design makes automatic pick and place, indexing and assembly, extremely easy. The parallel flat surfaces are suitable for most key jaw or vacuum pick-up techniques. All of the solderable surfaces are tin plated and compatible with industry standard reflow and vapor phase soldering processes. See page 7 of Application Note [M538](#) on the [M/A-COM Technology Solutions](#) website for a typical solder reflow profile.

Package Styles



401 & 402



1072 & 1091

Applications

HIPAX PIN diodes are designed for use in a wide variety of switch and attenuator applications from HF through UHF frequencies and at power levels above 1kW, CW. The internal chip as well as each diode assembly has been comprehensively tested and characterized to ensure predictable and repeatable performance.

Design Recommendations

- ◆ Low Distortion Attenuators
 - MA4P4301B
- ◆ Surface Mount Switches
 - MA4P7101F
- ◆ Cellular Radio Antenna Switches
 - MA4P1200, MA4P1250

Absolute Maximum Ratings

 $T_{AMB} = +25^{\circ}\text{C}$ (Unless Otherwise Noted) ¹

Parameter	Absolute Maximum
D.C. Reverse Voltage (V_R)	(See Tables)
Operating Chip Junction Temperature	-55°C to +175°C
Storage Temperature	-55°C to +200°C
Installation Temperature	+280°C for 30 Seconds
ESD	Class 1A, HBM

Notes

1. Operation of this device above any one of these parameters may cause permanent damage.

¹ **ADVANCED:** Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
 • **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588
 Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

MA4P MELF & HIPAX™ Series

High Power PIN Diodes

V14

MA4P1000 Series Electrical Specifications @ $T_{AMB} = +25^{\circ}\text{C}$

Part Number (NM Indicates Non-Magnetic)	V_R Reverse Voltage V_{DC}		C_T Total Capacitance pF		R_S Series Resistance Ω		R_P Parallel Resistance k Ω
	<u>Condition</u> $I_R = 10 \mu\text{A}$		<u>Conditions</u> $f = 1 \text{ MHz}$ $V_R = 50 \text{ V}$		<u>Conditions</u> $f = 100 \text{ MHz}$ $I_F = 50 \text{ mA}$		<u>Conditions</u> $f = 100 \text{ MHz}$ $V_R = 0 \text{ V}$
	MINIMUM	MAXIMUM RATING	TYPICAL	MAXIMUM	TYPICAL	MAXIMUM	MINIMUM
MA4P1200 - 401T	50	100	1.2	1.5	0.5	0.75	5
MA4P1200NM - 401T	50	100	1.2	1.5	0.5	0.75	5
MA4P1250 -1072T	50	100	0.8	1.2	0.5	0.75	5
MA4P1250NM -1072T	50	100	0.8	1.2	0.5	0.75	5
MA4P1450 -1091T	50	100	1.8	2.5	0.5	0.75	5

Part Number (NM Indicates Non-Magnetic)	V_F Forward Voltage (Max. $I_{Forward} @ 1V \leq 1.5A$)		T_L Carrier Lifetime		Forward Bias Harmonic Distortion $R(2a/a) * R(3a/a)$		Reverse Bias Harmonic Distortion $R(2a/a) - R(3a/a)$	
	<u>Condition</u> $I_F = 50 \text{ mA}$		<u>Conditions</u> $I_F = 10 \text{ mA}$		<u>Conditions</u> $f = 100 \text{ MHz}$		<u>Conditions</u> $f = 100 \text{ MHz}$	
	TYPICAL	MAXIMUM RATING	MINIMUM	TYPICAL	MINIMUM	TYPICAL	MINIMUM	TYPICAL
MA4P1200 - 401T	0.85	1.0	2	8	80	90	60	70
MA4P1200NM - 401T	0.85	1.0	2	8	80	90	60	70
MA4P1250 -1072T	0.85	1.0	2	8	80	90	60	70
MA4P1250NM -1072T	0.85	1.0	2	8	80	90	60	70
MA4P1450 -1091T	0.85	1.0	2	8	80	90	60	70

*Notes:

- 1.) "NM" in the base part number signifies non-magnetic package.
- 2.) "T" suffix denotes tape and reel

Power Dissipation and Thermal Resistance Ratings @ $T_{AMB} = +25^{\circ}\text{C}$

Package Style	CONDITION	MA4P1200(NM)-401T		MA4P1250(NM)-1072T		MA4P1450-1091T	
		P _{DISS}	θ _{JC}	P _{DISS}	θ _{JC}	P _{DISS}	θ _{JC}
B Axial Lead	No Heatsink	1.5 W	15°C/W	—	—	—	—
	Lead Length 1/4"	5.5W		—	—	—	—
F MELF	No Heatsink			6W	15°C/W	10W	5°C/W
	Infinite Heatsink			18W		30W	

2

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• North America Tel: 800.366.2266 • Europe Tel: +353.21.244.6400

• India Tel: +91.80.4155721 • China Tel: +86.21.2407.1588

Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.


MA4P MELF & HIPAX™ Series

High Power PIN Diodes


V14

Typical Performance Curves @ $T_{AMB} = +25^{\circ}\text{C}$ MA4P1200 Series


Series Resistance @ 100 MHz vs. Forward Current




Capacitance vs. Frequency & Reverse Bias



Parallel Resistance vs. Frequency & Reverse Bias



Heatsink Temperature vs. Max. Power Dissipation



3

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588

Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.


MA4P MELF & HIPAX™ Series

High Power PIN Diodes


V14

Typical Performance Curves @ $T_{AMB} = +25^{\circ}\text{C}$ MA4P1250 Series


Series Resistance @ 100 MHz vs. Forward Current




Capacitance vs. Frequency & Reverse Bias



Parallel Resistance vs. Frequency & Reverse Bias



Carrier Lifetime vs. Forward Bias Current




MA4P MELF & HIPAX™ Series

High Power PIN Diodes


V14

Typical Performance Curves @ $T_{AMB} = +25^{\circ}\text{C}$ MA4P1450 Series


Series Resistance @ 100 MHz vs. Forward Current



Capacitance vs. Frequency and Reverse Bias



Parallel Resistance vs. Frequency and Reverse Bias



5

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588
Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

MA4P MELF & HIPAX™ Series

High Power PIN Diodes

V14

MA4P4000 - MA4P7100 Series Electrical Specifications @ $T_{AMB} = +25^{\circ}\text{C}$

Parameter	Symbol	Condition	MA4P4000 Series	MA4P4300 Series	MA4P7000 Series	MA4P7100 Series
Maximum Series Resistance	R_S	$I_F = 100 \text{ mA}$	0.5 Ω	1.0 Ω	0.9 Ω	0.5 Ω
Maximum Total Capacitance	C_T	$V_R = 100 \text{ V}$	2.2 pF	2.0 pF	0.7 pF	1.0 pF
Minimum Parallel Resistance	R_P	$V_R = 100 \text{ V}$	20 k Ω	50 k Ω	200 k Ω	100 k Ω
Minimum Carrier Lifetime	T_L	$I_F = 10 \text{ mA}$	20 μs	15 μs	5 μs	2.5 μs
Maximum Forward Voltage	V_F	$I_F = 100 \text{ mA}$	1.0 V	1.2 V	1.0 V	1.0 V
Maximum Reverse Current	I_R	At max. rated voltage	1 μA	1 μA	1 μA	1 μA
Nominal I-Region Width	μ	—	175 μm	300 μm	175 μm	100 μm

Maximum Reverse Voltage Rating (V_R)

Maximum Reverse Voltage Rating	MA4P4000 Series	MA4P4300 Series	MA4P7000 Series	MA4P7100 Series
100 Volts	MA4P4001B-402 MA4P4001BNM-402 MA4P4001F-1091T	MA4P4301B-402 MA4P4301F-1091T	MA4P7001F-1072T	MA4P7101B-401T MA4P7101F-1072T
200 Volts	MA4P4002B-402 MA4P4002F-1091T	MA4P4302B-402	MA4P7002B-401T MA4P7002F-1072T	MA4P7102B-401T MA4P7102F-1072T
400 Volts	—	—	—	MA4P7104B-401T MA4P7104F-1072T
600 Volts	MA4P4006F-1091T MA4P4006B-402	—	MA4P7006B-401T MA4P7006F-1072T	—

*Notes:

- 1.) "NM" in the base part number signifies non-magnetic package.
- 2.) "T" suffix denotes tape and reel

Package Style	Condition	MA4P4000 Series		MA4P4300 Series		MA4P7000 Series		MA4P7100 Series	
		P_{DISS}	θ_{JC}	P_{DISS}	θ_{JC}	P_{DISS}	θ_{JC}	P_{DISS}	θ_{JC}
B Axial Leaded	1/4" Lead Length	12 W	12.5°C/W	10 W	15°C/W	5 W	30°C/W	6 W	25°C/W
	No Heatsink	2.5 W	—	2.5 W	—	1.5 W	—	1.5 W	—
F MELF	Infinite Heatsink	7.5 W	20°C/W	5 W	30°C/W	10 W	15°C/W	11.5 W	13°C/W
Both B and F	Single 1 μs pulse	100 kW	—	100 kW	—	15 kW	—	15 kW	—
Both B and F	Single 100 μs pulse	5 kW	0.03°C/W	5 kW	0.03°C/W	300 W	0.5°C/W	300 W	0.5°C/W

6

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400

• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588

Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.


MA4P MELF & HIPAX™ Series

High Power PIN Diodes


V14

Typical Performance Curves @ $T_{AMB} = +25^{\circ}\text{C}$ MA4P4000, MA4P4300, MA4P7000, MA4P7100 Series


Series Resistance at 100 MHz vs. Forward Current
MA4P4000, MA4P4300 Series




Series Resistance at 100 MHz vs. Forward Current
MA4P7000, MA4P7100 Series



Thermal Resistance vs. Pulse Width
MA4P4000, MA4P4300, MA4P7000 & MA4P7100 Series



Carrier Lifetime vs. Forward Bias Current
MA4P4000, MA4P4300, MA4P7000 & MA4P7100 Series



7

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588

Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.


MA4P MELF & HIPAX™ Series

High Power PIN Diodes


V14

Typical Performance Curves @ $T_{AMB} = +25^{\circ}\text{C}$ MA4P4000, MA4P4300, MA4P7000, MA4P7100 Series


Capacitance vs. Frequency & Reverse Bias
MA4P4000 Series




Capacitance vs. Frequency & Reverse Bias
MA4P4300 Series



Capacitance vs. Frequency & Reverse Bias
MA4P7000 Series



Capacitance vs. Frequency & Reverse Bias
MA4P7100 Series



8 **ADVANCED:** Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588
Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.


MA4P MELF & HIPAX™ Series

High Power PIN Diodes


V14

Typical Performance Curves @ $T_{AMB} = +25^{\circ}\text{C}$ MA4P4000, MA4P4300, MA4P7000, MA4P7100 Series


Parallel Resistance vs. Reverse Bias & Frequency
MA4P4000 Series




Parallel Resistance vs. Reverse Bias & Frequency
MA4P4300 Series



Parallel Resistance vs. Reverse Bias & Frequency
MA4P7000 Series



Parallel Resistance vs. Reverse Bias & Frequency
MA4P7100 Series



9

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588

Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.


MA4P MELF & HIPAX™ Series

High Power PIN Diodes

V14


Case Styles

401 Axial Leaded Packages




401 Package (tape and reel only) 500 or 1000pcs/reel specify when ordering	Dimension	INCHES		MM	
		MIN.	MAX.	MIN.	MAX.
MA4P1200-401T MA4P1200NM-401T MA4P7002B-401T MA4P7006B-401T MA4P7101B-401T MA4P7102B-401T MA4P7104B-401T	A	—	0.130	—	3.30
	B	—	0.090	—	2.29
	C	0.975		24.77	—
	D	0.027	0.029	0.69	0.74

402 Axial Leaded Packages




402 Package (bulk only) 100pcs/bag	Dimension	INCHES		MM	
		MIN.	MAX.	MIN.	MAX.
MA4P4001B-402 MA4P4001BNM-402 MA4P4002B-402 MA4P4006B-402 MA4P4301B-402 MA4P4302B-402	A	—	0.230	—	5.84
	B	—	0.140	—	3.56
	C	0.975		24.77	—
	D	0.039	0.041	0.99	1.04

1091 MELF Surface Mount Packages



1091 Package (tape and reel only) 500pcs/reel	Dimension	INCHES		MM	
		MIN.	MAX.	MIN.	MAX.
MA4P1450-1091T MA4P4001F-1091T MA4P4002F-1091T MA4P4006F-1091T MA4P4301F-1091T	A	0.138	0.155	3.51	3.94
	B	0.181	0.191	4.57	4.85
	C	0.011	0.026	0.279	0.660

1072 MELF Surface Mount Packages



1072 Package (tape and reel only) 1500 or 5000pcs/reel specify when ordering	Dimension	INCHES		MM	
		MIN.	MAX.	MIN.	MAX.
MA4P1250-1072T MA4P1250NM-1072T MA4P7001F-1072T MA4P7002F-1072T MA4P7006F-1072T MA4P7101F-1072T MA4P7104F-1072T	A	0.080	0.095	2.032	2.413
	B	0.115	0.125	2.921	3.175
	C	0.008	0.023	0.203	0.584

10 ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588
Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

MA4P MELF & HIPAX™ Series

High Power PIN Diodes


V14

MELF Assembly Recommendations


- ◆ Devices may be soldered using standard 60Sn/40Pb or RoHS compliant solders. Axial leads and solderable surfaces of MELF devices are tin plated 50 µm thick to ensure an optimum connection.

Circuit Pad Layout for MELF Diodes

Dimension	Package Style 1072		Package Style 1091	
	inches	mm	inches	mm
A	0.093	2.36	0.150	3.81
B	0.050	1.27	0.050	1.27
C	0.060	1.52	0.100	2.54



MELF Internal Construction



Ordering Information

MELF diodes are available in tape and reel in quantities as shown in table below

Package Style	Quantity (7" Reel)	Bulk Devices Per Bag
1072T	1500 or 5000	N/A
1091T	500	N/A

Tape and reel information can be found on the M/A-COM website at <http://www.macomtech.com/Application Notes/pdf/M513.pdf>

11 ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
 • **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588
 Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

MA4P MELF & HIPAX™ Series


High Power PIN Diodes

V14


Axial Leaded HIPAX Assembly Recommendations

- ◆ Bends on case styles 401 and 402, axially leaded devices, must be made while holding the lead firm and forming the bend no closer than .060 inches from the body of the part. Bending the lead < 0.060 inches from the body of the part is not recommended and may cause internal damage to the chip. Appropriate fixturing should be used.
- ◆ Devices may be soldered using standard 60Sn/40Pb or any RoHS compliant solders. Axial leads are tin plated 50µm thick to ensure an optimum connection.
- ◆ For recommended Sn/Pb and RoHS soldering profiles see page 7 of Application Note [M538](#) on the M/A-COM Tech-

Case Style 401 & 402 Minimum Bend Distance



Case Style 401 & 402 Internal Construction



Ordering Information

Axial leaded diodes are available in tape and reel or bulk in quantities shown in the table below

Package Style	Quantity Per Reel	Bulk Devices Per Bag
401T	500 or 1000 (specify qty. when ordering)	N/A
402	N/A	100

Environmental Ratings

HIPAX PIN diodes are designed to meet most environmental and electrical requirements and may be ordered screened to MIL-STD-750 specifications as described in the table below.

TEST	METHOD	DESCRIPTION/ CONDITIONS
Moisture Resistance	1021	85°C, 85% Relative Humidity, 168 hrs
High Temperature Storage	1031	+175°C, 250 Hours
HTRB	1038	80% of rated V_R , 50°C, 96 Hours
Temperature Shock	1051	-65°C to +175°C, 20 Cycles
Fine Leak	1071 Cond. H	1×10^{-7} CC/Sec
Constant Acceleration	2006	20,000 G's
Solderability	2026	IPC/JDEC J-STD-02
Tension ¹	2036.3 Cond. A	2 Lbs., 30 Seconds
Lead Fatigue ¹	2036.3 Cond. E	3 Cycles, 8 oz., 90°,

Note:

- 1) Test applicable to HIPAX axially leaded devices only.

12 ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
 • **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588
 Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331