



LOC		DIST		REVISIONS						
AA		00		P	LTR	DESCRIPTION	DATE	DWN	APVD	
				A		PER ECO-09-012369	22MAY2009	GIP	ECW	
				B		ECO-09-013491	20AUG2009	LAM	EW	
				C		ECO-09-028526	04JAN2010	LAW	EW	



2-1926720-5 SHOWN

1. HOUSING: GLASS FILLED LIQUID CRYSTAL POLYMER, COLOR: BLACK, UL 94 V-O RATED
SIGNAL CONTACT: PHOSPHOR BRONZE
SIGNAL OVERMOLD: GLASS FILLED POLYESTER
POWER CONTACT: COPPER ALLOY
BOARD LOCK: PHOSPHOR BRONZE

2. SIGNAL CONTACT: 0.00127mm MIN NICKEL ALL OVER,
MATING AREA: 0.00076mm MIN GOLD OR 0.00008mm MIN GOLD OVER
0.00076mm MIN PALLADIUM-NICKEL
TAIL AREA: 0.0005mm MIN MATTE TIN

- POWER CONTACT: 0.00127mm MIN NICKEL ALL OVER,
MATING AREA: 0.00076mm MIN GOLD OR
0.00008mm MIN GOLD OVER 0.00076mm MIN PALLADIUM-NICKEL,
TAIL AREA: 0.0005mm MIN MATTE TIN

- BOARD LOCK: 0.00076mm MIN MATTE TIN OVER
0.00127mm MIN NICKEL.

3. CONTACT MATING AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT,
TECHNICAL REFERENCE: GR-1217-CORE, ISSUE 1, NOVEMBER 1995.

4. THIS CONNECTOR EMPLOYS UL RECOGNIZED Z-PACK 2mm HM SIGNAL CONTACTS

5. DATUMS AND BASIC DIMENSIONS TO BE ESTABLISHED BY CUSTOMER.

6. PC BOARD THICKNESS 1.4mm MIN, FOR WAVE SOLDER PC BOARD THICKNESS 2.62 MAX

7. SEE APPLICATION SPEC 114-13215 FOR PLATED THROUGH HOLE INFORMATION




8. SEE CUSTOMER DRAWING 1926721 OR 1926723 FOR MATING CONNECTOR

9. UNPLATED HOLES

2.375	4.250	48	25	7	4	63.85	68.96	8P X 25S X 8P	2-1926720-5
3.00	4.875	36	15	5	2	50.10	55.21	6P X 15S X 6P	1-1926720-6
3.00	4.875	24	15	1	2	28.10	33.21	2P X 15S X 2P	1926720-2
DIM H	DIM G	F SPACES	E PLACES	D SPACES	C SPACES	DIM B	DIM A	DESCRIPTION	PART NUMBER

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN P BRANDBERG 21NOV07	Tyco Electronics Harrisburg, PA 17105-3608	
mm		9 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ±		CHK N REESER 21NOV07	NAME	
		108-2325		APVD N REESER 21NOV07	ASSEMBLY, RIGHT ANGLE PLUG, POWER/SIGNAL/POWER, PASSIVE GUIDE, WITH BOARDLOCK, MINIPAK HDL	
MATERIAL SEE NOTE 1		FINISH SEE NOTE 2		PRODUCT SPEC	SIZE CAGE CODE DRAWING NO	
				APPLICATION SPEC	A100779C=1926720	
				114-13215	RESTRICTED TO	
				WEIGHT	-	
				CUSTOMER DRAWING	SCALE 4:1 SHEET 1 OF 3 REV C	


LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AA	00		-	SEE SHEET I	-	-	-



2-1926720-5 SHOWN

TYPICAL DIMENSIONS TO CENTERLINE UNLESS OTHERWISE SPECIFIED		DWN P. BRANDBERG 21NOV07	Tyco Electronics Harrisburg, PA 17105-3608	
DIMENSIONS:		CHK N. REESER 21NOV07	NAME ASSEMBLY, RIGHT ANGLE PLUG, POWER/SIGNAL/POWER, PASSIVE GUIDE, WITH BOARDLOCK, MINIPAK HDL	
mm		APVD N. REESER 21NOV07		
		PRODUCT SPEC	SIZE CAGE CODE DRAWING NO RESTRICTED TO	
		108-2325		
		APPLICATION SPEC		
		114-13215		
MATERIAL SEE NOTE 1		WEIGHT -	A100779C=1926720	
FINISH SEE NOTE 2		CUSTOMER DRAWING		SCALE 4:1 SHEET 2 OF 3 REV C

LOC	DIST	REVISIONS					
AA	00	F	LTR	DESCRIPTION	DATE	DWN	APVD
			-	SEE SHEET 1	-	-	-



2-1926720-5 SHOWN
RECOMMENDED PRINTED CIRCUIT BOARD LAYOUT ⁶
(AS VIEWED FROM COMPONENT SIDE)
SCALE 6:1

TYP. DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION IT IS SUBJECT TO THE TYCO ELECTRONICS CORPORATION CONTROL DOCUMENT ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		DWN P. BRANDBERG 21NOV07	Tyco Electronics Harrisburg, PA 17105-3608	
DIMENSIONS:		CHK N. REESER 21NOV07	NAME	
mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD N. REESER 21NOV07	ASSEMBLY, RIGHT ANGLE PLUG, POWER/SIGNAL/POWER, PASSIVE GUIDE, WITH BOARDLOCK, MINIPAK HDL	
	1 PLC ±	PRODUCT SPEC	SIZE CAGE CODE DRAWING NO RESTRICTED TO	
	2 PLC ±	108-2325		
	3 PLC ±	APPLICATION SPEC		
	4 PLC ±	114-13215		
ANGLES ±		WEIGHT -	A 100779 C-1926720 -	
MATERIAL	FINISH	CUSTOMER DRAWING	SCALE 4:1	SHEET 3 OF 3
SEE NOTE 1	SEE NOTE 2		REV C	



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331