


Applications

- Wireless Infrastructure
- AMPS, CDMA and TDMA
- General Purpose RF Filter
- 4G, Multi-Standard
- Band 1 Uplink
- Repeaters

Product Features

- 60 MHz Bandwidth
- High Attenuation
- Single-ended Operation
- 50 Ohm Impedance
- Small Size: 3.00 x 3.00 x 1.22 mm
- Ceramic Surface Mount Package (SMP)
- Hermetically Sealed
- RoHS Compliant, Pb-Free 

General Description


The 856678 is a Surface Acoustic Wave (SAW) based filter suitable for LTE Band 1 Uplink.

856678 is specifically designed to meet the high performance expectations of insertion loss and rejection for LTE downlink systems under all operating conditions.

This filter is housed in a compact, industry standard 3x3 mm footprint.

Low insertion loss, coupled with high attenuation makes this filter an ideal choice for Base Station Applications.


This filter is part of TriQuint's wide portfolio of RF filters.



SMP-12, 3.00 x 3.00 x 1.22 mm

Functional Block Diagram

Top View



Pin Configuration - Single Ended

| Pin No. | Label |
|---------|--------|
| 2 | Input |
| 5 | Output |
| 1,3,4,6 | Ground |

Ordering Information

| Part No. | Description |
|------------|---------------------|
| 856678 | 1950 MHz SAW Filter |
| 856678-EVB | Evaluation board |

Standard T/R size = 5000 units/reel

Absolute Maximum Ratings

| Parameter | Rating |
|---|---------------|
| Storage Temperature ⁽¹⁾ | -40 to +85 °C |
| Operable Temperature ⁽²⁾ | -30 to +85 °C |
| DC Voltage (instantaneous only on any port) | +5 V |

Notes:

1. Operation of this device outside the parameter ranges given may cause permanent damage.
2. Specifications are not guaranteed over all operable conditions.

Electrical Specifications ^(1,2,3)

Test conditions unless otherwise noted: ⁽²⁾ Temp= -30 °C to +85 °C







| Parameter ⁽³⁾ | Conditions | Min | Typ ⁽⁴⁾ | Max | Units |
|---|--|-------|--------------------|-----|--------|
| Center Frequency | | - | 1950 | - | MHz |
| Insertion Loss | 1920 – 1980 MHz | - | 1.8 | 3.0 | dB |
| Amplitude Variation | 1920 – 1980 MHz | | 0.45 | 1.6 | dB p-p |
| | 1920 – 1980 MHz (over any 5 MHz band) | | 0.25 | 0.8 | |
| Phase Ripple | 1920 – 1980 MHz | | 16 | 30 | Deg. |
| Absolute Delay | 1920 – 1980 MHz | | 11 | 50 | ns |
| Group Delay Variation | 1920 – 1980 MHz | | 6 | 30 | ns p-p |
| Stopband Attenuation (relative to zero dB) | 180 – 220 MHz | 20 | 49 | - | dB |
| | 1470 – 1500 MHz | 35 | 44.5 | - | |
| | 1500 – 1540 MHz | 35 | 40.5 | - | |
| | 1540 – 1570 MHz | 35 | 42 | - | |
| | 1570 – 1601 MHz | 35 | 45.5 | - | |
| | 1601 – 1670 MHz | 17 | 42 | - | |
| | 1814 – 1840 MHz | 20 | 33 | - | |
| | 1840 – 1878 MHz | 15 | 35.5 | - | |
| | 2025 – 2050 MHz | 3 | 11.5 | - | |
| | 2100 – 2170 MHz | 20 | 28 | - | |
| | 2490 – 3000 MHz | 25 | 44 | - | |
| | 3213 – 3755 MHz | 25 | 51.5 | - | |
| | 4925 – 5527 MHz | 25 | 41.5 | - | |
| Input/Output VSWR | 1920 – 1980 MHz | 1.5:1 | 2.2:1 | | - |
| Source Impedance ⁽⁵⁾ | single-ended | - | 50 | - | Ohms |
| Load Impedance ⁽⁵⁾ | single-ended | - | 50 | - | Ohms |

Notes:


1. All specifications are based on the test circuit shown below.
2. Production test is performed at room temp. to a guard-banded specification to ensure electrical compliance over temperature.
3. Electrical margin has been built into the design to account for variation due to temperature drift and manufacturing tolerances.
4. Typical values are based on average measurements at room temperature
5. This is the optimum impedance in order to achieve the performance shown.

Performance Plots

Test conditions unless otherwise noted: Temp= +25°C



Package Information, Marking and Dimensions



Package Style: SMP-12A

Body: Al_2O_3 ceramic
Lid: Kovar, Ni plated
Terminations: Au plating 0.5 - 1.0 μ m, over a 2-6 μ m Ni plating



The date code consists of JJJ = Julian day, Y = last digit of the year, and M = manufacturing site code

Notes:

1. All dimensions shown are typical in millimeters
2. All tolerances are ± 0.15 mm except overall length and width ± 0.10 mm
3. An asterisk (*) in front of the marking code indicates prototype.

Tape and Reel information

Standard T/R size = 5000 units/reel. All dimensions are in millimeters



Product Compliance Information

ESD Sensitivity Ratings



Caution! ESD-Sensitive Device

ESD Rating: Class 0A
Value: Passes ≤ 100 V
Test: Electrostatic Discharge Sensitivity Testing,
Human Body Model (HBM) - component level
Standard: ESDA/JEDEC JS-001-2012

ESD Rating: Class A
Value: Passes ≤ 50 V
Test: Machine Model (MM)
Standard: JEDEC Standard JESD22-A115

MSL Rating

Not applicable. Hermetic package.

Solderability

Compatible with both lead-free (260°C maximum reflow temperature) and tin/lead (245°C maximum reflow temperature) soldering processes.

Refer to [Soldering Profile](#) for recommended guidelines.

RoHS Compliance

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web: www.triquint.com
Email: info-sales@tqs.com

Tel: +1.407.886.8860
Fax: +1.407.886.7061

For technical questions and application information:

Email: flapplication.engineering@tqs.com

Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331