


# PolySwitch Resettable Devices
## Strap Battery Devices

**TE Circuit Protection, a pioneer of polymeric positive temperature coefficient resettable devices, has developed several material platforms to help protect battery applications. Each of these material platforms offers different performance characteristics, allowing the engineer greater design flexibility. PolySwitch devices for battery protection include SRP, LR4, VTP, VLP, VLR and MXP series, disc, and special application strap devices.**



### Benefits

- Many material platforms and device form factors give engineers more design flexibility
- Compatible with high-volume electronics assembly
- Assists in meeting regulatory requirements
- Low resistance devices increase battery operating time

### Features

- RoHS compliant
- Lead free versions of all devices are available
- Broad range of resettable devices available
- Current ratings from 1.1A to 13A
- Voltage ratings from 6V to 30V
- Agency recognition, UL, CSA, TÜV
- Fast time-to-trip
- Low resistance

### Applications

- Mobile phone and smart phone battery packs
- Tablet PC battery packs
- Mobile radio battery packs
- Computer battery packs
- Digital camera battery packs
- Portable media player battery packs
- Power tools (charge line)

## Application Selection Guide for Strap Battery Devices

The guide below lists PolySwitch strap battery devices which are typically used in these applications.
The following pages contain the specifications for the part numbers recommended below.
Once a device is selected, the user should evaluate and test each product for its intended application.

| | | PolySwitch Resettable Devices — Key Device Selection Criteria | | |
|---|---|---|---|---|
| **Protection Application** | **Additional Comments** | **Installation Method** | **Lowest Resistance** | **Lowest Thermal Cut-off** |
| Mobile phone battery packs | Li-ion | Surface Mount | refer to Surface-mount section of this catalog | |
| | | Prismatic | MXP370BD | VLR175F |
| Cordless phone battery packs | NiMH | Cylindrical | VLP210F | — |
| | | | SRP175F | |
| Mobile radio battery packs | NiMH | Cylindrical | LR4-380F | — |
| | | | SRP350F | |
| Computer battery packs | NiMH | Cylindrical | LR4-900F | — |
| | Li-ion | Cylindrical | LR4-1300SSF | — |
| | | Prismatic | Consult local Rep | Consult local Rep |
| Camcorder battery packs | NiMH or Li-ion | Prismatic | VLP270F | VTP210GF |
| | | | LR4-380F | — |
| PDA battery packs | Li-ion | Prismatic | VLP220F | VLR175F |
| Power tools (charge line) | NiCd, NiMH or Li-ion | Cylindrical | custom LR4 | custom VTP |

## Table B1 Product Series - Current Rating, Voltage Rating / Typical Resistance for Strap Battery Devices

| | VLR | VLP | VTP | MXP | SRP | LR4 |
|---|---|---|---|---|---|---|
| | Typical Activation Temperature | | | | | |
| **Hold Current (A)** | **85°C** | **90°C** | **90°C** | **120°C** | **125°C** | **125°C** |
| 1.10 | — | — | 16V/0.054Ω | — | — | — |
| 1.20 | — | 16V/0.053Ω | — | — | 15V/0.123Ω | — |
| 1.70 | 12V/0.025Ω | — | 16V/0.041Ω | — | — | — |
| 1.75 | 12V/0.024Ω | 16V/0.040Ω | 16V/0.040Ω | — | 15V/0.070Ω | — |
| 1.90 | — | — | — | 6V/0.010Ω | — | 15V/0.056Ω |
| 2.00 | — | — | — | — | 30V/0.045Ω | — |
| 2.10 | — | 16V/0.024Ω | 16V/0.024Ω | — | — | — |
| 2.20 | — | 16V/0.023Ω | — | — | — | — |
| 2.30 | 12V/0.015Ω | — | — | — | — | — |
| 2.60 | — | — | — | — | — | 15V/0.031Ω |
| 2.70 | — | 16V/0.015Ω | — | — | — | — |
| 3.50 | — | — | — | — | 30V/0.024Ω | — |
| 3.70 | — | — | — | 6V/0.013Ω | — | — |
| 3.80 | — | — | — | — | — | 15V/0.020Ω |
| 4.20 | — | — | — | — | 30V/0.018Ω | — |
| 4.50 | — | — | — | — | — | 20V/0.016Ω |
| 5.50 | — | — | — | — | — | 20V/0.013Ω |
| 6.00 | — | — | — | — | — | 20V/0.011Ω |
| 7.30 | — | — | — | — | — | 20V/0.009Ω |
| 9.00 | — | — | — | — | — | 20V/0.008Ω |
| 13.00 | — | — | — | — | — | 20V/0.006Ω |





RoHS Compliant, ELV Compliant

## Table B2 Thermal Derating for Strap Battery Devices [Hold Current (A) at Ambient Temperature (°C)]

| Part Number | Maximum Ambient Temperature -40°C Amps | -20°C | 0°C | 20°C | 25°C | 40°C | 50°C | 60°C | 70°C | 80°C | 85°C |
|---|---|---|---|---|---|---|---|---|---|---|---|
| **85°C Typical Activation VLR*** | | | | | | | | | | | |
| VLR170F | 3.5 | 2.9 | 2.4 | 1.84 | 1.70 | 1.2 | 1.0 | 0.7 | 0.3 | — | — |
| VLR170LF | 3.5 | 2.9 | 2.4 | 1.84 | 1.70 | 1.2 | 1.0 | 0.7 | 0.3 | — | — |
| VLR170UF | 3.5 | 2.9 | 2.4 | 1.84 | 1.70 | 1.2 | 1.0 | 0.7 | 0.3 | — | — |
| VLR175F | 3.5 | 2.9 | 2.4 | 1.87 | 1.75 | 1.3 | 1.0 | 0.8 | 0.3 | — | — |
| VLR175LF | 3.5 | 2.9 | 2.4 | 1.87 | 1.75 | 1.3 | 1.0 | 0.8 | 0.3 | — | — |
| VLR175UF | 3.5 | 2.9 | 2.4 | 1.87 | 1.75 | 1.3 | 1.0 | 0.8 | 0.3 | — | — |
| VLR230F | 5.0 | 4.2 | 3.4 | 2.52 | 2.30 | 1.7 | 1.3 | 0.9 | 0.4 | — | — |
| **90°C Typical Activation VLP*** | | | | | | | | | | | |
| VLP120UF | 2.4 | 2.1 | 1.8 | 1.30 | 1.20 | 1.0 | 0.7 | 0.6 | 0.3 | 0.2 | 0.1 |
| VLP175UF | 3.2 | 2.7 | 2.3 | 1.70 | 1.75 | 1.2 | 1.0 | 0.8 | 0.5 | 0.2 | 0.1 |
| VLP210F | 4.3 | 3.6 | 2.9 | 2.31 | 2.10 | 1.6 | 1.3 | 1.0 | 0.6 | 0.3 | 0.1 |
| VLP220F | 4.5 | 3.8 | 3.0 | 2.45 | 2.20 | 1.7 | 1.4 | 1.1 | 0.7 | 0.3 | 0.1 |
| VLP270F | 5.6 | 4.7 | 4.0 | 3.05 | 2.70 | 2.2 | 1.7 | 1.4 | 0.9 | 0.4 | 0.1 |
| **VTP*** | | | | | | | | | | | |
| VTP110F | 2.0 | 1.7 | 1.4 | 1.12 | 1.10 | 0.85 | 0.75 | 0.7 | 0.4 | 0.2 | 0.1 |
| VTP170F | 3.2 | 2.7 | 2.2 | 1.80 | 1.70 | 1.3 | 1.0 | 0.8 | 0.5 | 0.3 | 0.1 |
| VTP170SSF | 3.2 | 2.7 | 2.2 | 1.80 | 1.70 | 1.3 | 1.0 | 0.8 | 0.5 | 0.3 | 0.1 |
| VTP170XF | 3.2 | 2.7 | 2.2 | 1.80 | 1.70 | 1.3 | 1.0 | 0.8 | 0.5 | 0.3 | 0.1 |
| VTP170XSF | 3.2 | 2.7 | 2.2 | 1.80 | 1.70 | 1.3 | 1.0 | 0.8 | 0.5 | 0.3 | 0.1 |
| VTP175F | 3.2 | 2.7 | 2.2 | 1.84 | 1.75 | 1.3 | 1.0 | 0.8 | 0.5 | 0.3 | 0.1 |
| VTP175LF | 3.2 | 2.7 | 2.2 | 1.84 | 1.75 | 1.3 | 1.0 | 0.8 | 0.5 | 0.3 | 0.1 |
| VTP210GF | 4.1 | 3.5 | 2.9 | 2.26 | 2.10 | 1.6 | 1.3 | 1.0 | 0.7 | 0.4 | 0.1 |
| VTP210SF | 4.1 | 3.5 | 2.9 | 2.26 | 2.10 | 1.6 | 1.3 | 1.0 | 0.7 | 0.4 | 0.1 |
| **120°C Typical Activation MXP*** | | | | | | | | | | | |
| MXP190BB | — | — | 2.6 | — | 1.90 | — | — | 0.85 | — | — | — |
| MXP370BD | — | — | 5.0 | — | 3.70 | — | — | 1.90 | — | — | — |
| **125°C Typical Activation SRP** | | | | | | | | | | | |
| SRP120F | 1.9 | 1.7 | 1.5 | 1.20 | 1.17 | 1.0 | 0.9 | 0.8 | 0.6 | 0.5 | 0.4 |
| SRP120LF | 1.9 | 1.7 | 1.5 | 1.20 | 1.17 | 1.0 | 0.9 | 0.8 | 0.6 | 0.5 | 0.4 |
| SRP120SF | 1.9 | 1.7 | 1.5 | 1.20 | 1.17 | 1.0 | 0.9 | 0.8 | 0.6 | 0.5 | 0.4 |
| SRP175F | 2.5 | 2.2 | 2.0 | 1.75 | 1.68 | 1.4 | 1.3 | 1.2 | 1.0 | 0.9 | 0.8 |
| SRP175LF | 2.5 | 2.2 | 2.0 | 1.75 | 1.68 | 1.4 | 1.3 | 1.2 | 1.0 | 0.9 | 0.8 |
| SRP175SF | 2.5 | 2.2 | 2.0 | 1.75 | 1.68 | 1.4 | 1.3 | 1.2 | 1.0 | 0.9 | 0.8 |
| SRP200F | 3.1 | 2.8 | 2.5 | 2.00 | 1.97 | 1.7 | 1.5 | 1.4 | 1.2 | 1.0 | 0.9 |
| SRP350F | 5.3 | 4.8 | 4.3 | 3.50 | 3.44 | 3.0 | 2.7 | 2.5 | 2.1 | 1.8 | 1.7 |
| SRP420F | 6.3 | 5.7 | 5.1 | 4.20 | 4.11 | 3.6 | 3.3 | 3.0 | 2.6 | 2.2 | 2.1 |
| **LR4** | | | | | | | | | | | |
| LR4-190F | 2.8 | 2.5 | 2.3 | 1.9 | 1.86 | 1.6 | 1.5 | 1.4 | 1.2 | 1.1 | 1.0 |
| LR4-260F | 3.8 | 3.4 | 3.1 | 2.6 | 2.54 | 2.2 | 2.0 | 1.9 | 1.7 | 1.4 | 1.3 |
| LR4-260SF | 3.8 | 3.4 | 3.1 | 2.6 | 2.54 | 2.2 | 2.0 | 1.9 | 1.7 | 1.4 | 1.3 |
| LR4-380F | 5.4 | 4.9 | 4.4 | 3.8 | 3.64 | 3.3 | 3.0 | 2.8 | 2.5 | 2.3 | 2.1 |
| LR4-380XF | 5.4 | 4.9 | 4.4 | 3.8 | 3.64 | 3.3 | 3.0 | 2.8 | 2.5 | 2.3 | 2.1 |
| LR4-450F | 6.5 | 5.8 | 5.3 | 4.5 | 4.38 | 3.9 | 3.6 | 3.3 | 2.9 | 2.6 | 2.4 |
| LR4-550F | 7.6 | 6.9 | 6.2 | 5.5 | 5.32 | 4.7 | 4.3 | 4.0 | 3.6 | 3.2 | 3.0 |
| LR4-600F | 8.7 | 7.8 | 7.1 | 6.0 | 5.86 | 5.2 | 4.7 | 4.4 | 3.9 | 3.4 | 3.2 |
| LR4-600XF | 8.7 | 7.8 | 7.1 | 6.0 | 5.86 | 5.2 | 4.7 | 4.4 | 3.9 | 3.4 | 3.2 |
| LR4-730F | 10.5 | 9.5 | 8.6 | 7.3 | 7.13 | 6.3 | 5.7 | 5.4 | 4.7 | 4.2 | 4.0 |
| LR4-900F | 12.7 | 11.4 | 10.0 | 9.0 | 8.50 | 7.5 | 6.8 | 6.2 | 5.5 | 4.9 | 4.5 |
| LR4-1300SSF | 17.9 | 16.2 | 14.5 | 13.0 | 12.40 | 11.1 | 10.3 | 9.5 | 8.6 | 7.7 | 7.2 |


* Product electrical characteristics determined at 25°C.

RoHS Compliant, ELV Compliant

## Figure B1 Thermal Derating Curve for Strap Battery Devices

**A = LR4**
**B = SRP**
**C = VTP, VLP, MXP**
**D = VLR**

**Figure B1**




## Table B3 Electrical Characteristics for Strap Battery Devices

| Part Number | $I_H$ (A) | $I_T$ (A) | $V_{MAX}$ ($V_{DC}$) | $I_{MAX}$ (A) | $P_{D\ MAX}$ (W) | Max. Time-to-trip (A) | Max. Time-to-trip (s) | $R_{MIN}$ (Ω) | $R_{MAX}$ (Ω) | $R_{1MAX}$ (Ω) | Figure for Dimensions |
|---|---|---|---|---|---|---|---|---|---|---|---|
| **85°C Typical Activation VLR*** | | | | | | | | | | | |
| VLR170F | 1.70 | 4.1 | 12 | 100 | 1.4 | 8.50 | 5.0 | 0.018 | 0.032 | 0.064 | B3 |
| VLR170LF | 1.70 | 4.1 | 12 | 100 | 1.4 | 8.50 | 5.0 | 0.018 | 0.032 | 0.064 | B3 |
| VLR170UF | 1.70 | 4.1 | 12 | 100 | 1.4 | 8.50 | 5.0 | 0.018 | 0.032 | 0.064 | B5 |
| VLR175F | 1.75 | 4.2 | 12 | 100 | 1.4 | 8.75 | 5.0 | 0.017 | 0.031 | 0.062 | B3 |
| VLR175LF | 1.75 | 4.2 | 12 | 100 | 1.4 | 8.75 | 5.0 | 0.017 | 0.031 | 0.062 | B3 |
| VLR175UF | 1.75 | 4.2 | 12 | 100 | 1.4 | 8.75 | 5.0 | 0.017 | 0.031 | 0.062 | B5 |
| VLR230F | 2.30 | 5.0 | 12 | 100 | 2.5 | 10.00 | 5.0 | 0.012 | 0.018 | 0.036 | B3 |
| **90°C Typical Activation VLP*** | | | | | | | | | | | |
| VLP120UF | 1.20 | 3.6 | 16 | 60 | 1.6 | 7.00 | 5.0 | 0.039 | 0.067 | 0.134 | B5 |
| VLP175UF | 1.75 | 3.9 | 16 | 60 | 1.6 | 8.75 | 5.0 | 0.030 | 0.050 | 0.100 | B5 |
| VLP210F | 2.10 | 5.0 | 16 | 60 | 1.8 | 10.50 | 5.0 | 0.018 | 0.030 | 0.060 | B2 |
| VLP220F | 2.20 | 5.3 | 16 | 60 | 1.8 | 11.00 | 5.0 | 0.017 | 0.029 | 0.058 | B3 |
| VLP270F | 2.70 | 6.5 | 16 | 60 | 2.5 | 13.50 | 5.0 | 0.012 | 0.018 | 0.036 | B3 |
| **VTP*** | | | | | | | | | | | |
| VTP110F | 1.10 | 2.7 | 16 | 100 | 1.3 | 5.50 | 5.0 | 0.038 | 0.070 | 0.140 | B5 |
| VTP170F | 1.70 | 3.4 | 16 | 100 | 1.4 | 8.50 | 5.0 | 0.030 | 0.052 | 0.105 | B2 |
| VTP170SSF | 1.70 | 3.4 | 16 | 100 | 1.4 | 8.50 | 5.0 | 0.030 | 0.052 | 0.105 | B7 |
| VTP170XF | 1.70 | 3.4 | 16 | 100 | 1.4 | 8.50 | 5.0 | 0.030 | 0.052 | 0.105 | B3 |
| VTP170XSF | 1.70 | 3.4 | 16 | 100 | 1.4 | 8.50 | 5.0 | 0.030 | 0.052 | 0.105 | B4 |
| VTP175F | 1.75 | 3.6 | 16 | 100 | 1.4 | 8.75 | 5.0 | 0.029 | 0.051 | 0.102 | B3 |
| VTP175LF | 1.75 | 3.6 | 16 | 100 | 1.4 | 8.75 | 5.0 | 0.029 | 0.051 | 0.102 | B3 |
| VTP210GF | 2.10 | 4.7 | 16 | 100 | 1.5 | 10.00 | 5.0 | 0.018 | 0.030 | 0.060 | B3 |
| VTP210SF | 2.10 | 4.7 | 16 | 100 | 1.5 | 10.00 | 5.0 | 0.018 | 0.030 | 0.060 | B4 |
| **120°C Typical Activation MXP*** | | | | | | | | | | | |
| MXP190BB | 1.90 | 4.9 | 6 | 50 | 1.0 | 9.50 | 2.0 | 0.007 | 0.015 | 0.024 | B12 |
| MXP370BD | 3.70 | 9.0 | 6 | 50 | 1.3 | 18.50 | 5.0 | 0.004 | 0.010 | 0.016 | B12 |

* Product electrical characteristics determined at 25°C.



RoHS Compliant, ELV Compliant

## Table B3 Electrical Characteristics for Strap Battery Devices Cont'd

| Part Number | $I_H$ (A) | $I_T$ (A) | $V_{MAX}$ ($V_{DC}$) | $I_{MAX}$ (A) | $P_{D\ MAX}$ (W) | Max. Time-to-trip (A) | Max. Time-to-trip (s) | $R_{MIN}$ (Ω) | $R_{MAX}$ (Ω) | $R_{1MAX}$ (Ω) | Figure for Dimensions |
|---|---|---|---|---|---|---|---|---|---|---|---|
| **125°C Typical Activation SRP** | | | | | | | | | | | |
| SRP120F | 1.20 | 2.7 | 15 | 100 | 1.2 | 6.00 | 5.0 | 0.085 | 0.160 | 0.220 | B6 |
| SRP120LF | 1.20 | 2.7 | 15 | 100 | 1.2 | 6.00 | 5.0 | 0.085 | 0.160 | 0.220 | B6 |
| SRP120SF | 1.20 | 2.7 | 15 | 100 | 1.2 | 6.00 | 5.0 | 0.085 | 0.160 | 0.220 | B10 |
| SRP175F | 1.75 | 3.8 | 15 | 100 | 1.5 | 8.75 | 5.0 | 0.050 | 0.090 | 0.120 | B6 |
| SRP175LF | 1.75 | 3.8 | 15 | 100 | 1.5 | 8.75 | 5.0 | 0.050 | 0.090 | 0.120 | B6 |
| SRP175SF | 1.75 | 3.8 | 15 | 100 | 1.5 | 8.75 | 5.0 | 0.050 | 0.090 | 0.120 | B10 |
| SRP200F | 2.00 | 4.4 | 30 | 100 | 1.9 | 10.00 | 4.0 | 0.030 | 0.060 | 0.100 | B6 |
| SRP350F | 3.50 | 6.3 | 30 | 100 | 2.5 | 20.00 | 3.0 | 0.017 | 0.031 | 0.050 | B6 |
| SRP420F | 4.20 | 7.6 | 30 | 100 | 2.9 | 20.00 | 6.0 | 0.012 | 0.024 | 0.040 | B6 |
| **LR4** | | | | | | | | | | | |
| LR4-190F | 1.90 | 3.9 | 15 | 100 | 1.2 | 9.5 | 5.0 | 0.0390 | 0.0720 | 0.102 | B8 |
| LR4-260F | 2.60 | 5.8 | 15 | 100 | 2.5 | 13.0 | 5.0 | 0.0200 | 0.0420 | 0.063 | B8 |
| LR4-260SF | 2.60 | 5.8 | 15 | 100 | 2.5 | 13.0 | 5.0 | 0.0200 | 0.0420 | 0.063 | B9 |
| LR4-380F | 3.80 | 8.3 | 15 | 100 | 2.5 | 19.0 | 5.0 | 0.0130 | 0.0260 | 0.037 | B8 |
| LR4-380XF | 3.80 | 8.3 | 15 | 100 | 2.5 | 19.0 | 5.0 | 0.0130 | 0.0260 | 0.037 | B8 |
| LR4-450F | 4.50 | 8.9 | 20 | 100 | 2.3 | 22.5 | 5.0 | 0.0110 | 0.0200 | 0.028 | B8 |
| LR4-550F | 5.50 | 10.5 | 20 | 100 | 2.8 | 27.5 | 5.0 | 0.0090 | 0.0160 | 0.022 | B8 |
| LR4-600F | 6.00 | 11.7 | 20 | 100 | 2.8 | 30.0 | 5.0 | 0.0070 | 0.0140 | 0.019 | B8 |
| LR4-600XF | 6.00 | 11.7 | 20 | 100 | 2.8 | 30.0 | 5.0 | 0.0075 | 0.0140 | 0.019 | B8 |
| LR4-730F | 7.30 | 14.1 | 20 | 100 | 3.3 | 30.0 | 5.0 | 0.0060 | 0.0120 | 0.015 | B8 |
| LR4-900F | 9.00 | 16.7 | 20 | 100 | 3.8 | 45.0 | 5.0 | 0.0060 | 0.0100 | 0.014 | B8 |
| LR4-1300SSF | 13.00 | 21.2 | 20 | 100 | 4.5 | 50.0 | 10.0 | 0.0035 | 0.0065 | 0.009 | B11 |

* Product electrical characteristics determined at 25°C.

**Notes:**

$I_H$ : Hold current: maximum current device will pass without interruption in 20°C still air unless otherwise specified.
$I_T$ : Trip current: minimum current that will switch the device from low resistance to high resistance in 20°C still air unless otherwise specified.
$V_{MAX}$ : Maximum voltage device can withstand without damage at rated current.
$I_{MAX}$ : Maximum fault current device can withstand without damage at rated voltage.
$P_D$ : Power dissipated from device when in the tripped state in 20°C still air unless otherwise specified.
$R_{MIN}$ : Minimum resistance of device as supplied at 20°C unless otherwise specified.
$R_{MAX}$ : Maximum resistance of device as supplied at 20°C unless otherwise specified.
$R_{1MAX}$ : Maximum resistance, measured at 20°C unless otherwise specified, of device one hour after being tripped the first time.

## Figure B2-B12 Dimension Figures for Strap Battery Devices

**Figure B2**





**Figure B3**






**Figure B4**



## Figure B2-B12 Dimension Figures for Strap Battery Devices Cont'd

**Figure B5**





**Figure B6**





**Figure B7**





**Figure B8**





**Figure B9**





**Figure B10**





**Figure B11**






**Figure B12**




## Table B4 Dimensions for Strap Battery Devices in Millimeters (Inches)

| Part Number | A Min. | A Max. | B Min. | B Max. | C Min. | C Max. | D Min. | D Max. | E Min. | E Max. | F Min. | F Max. | Figure |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **85°C Typical Activation VLR** | | | | | | | | | | | | | |
| VLR170F | 20.8 | 23.2 | 3.5 | 3.9 | — | 0.8 | 4.5 | 6.5 | 4.5 | 6.5 | 2.4 | 2.6 | B3 |
| | (0.832) | (0.928) | (0.140) | (0.156) | — | (0.032) | (0.180) | (0.260) | (0.180) | (0.260) | (0.096) | (0.104) | |
| VLR170LF | 38.8 | 41.2 | 3.5 | 3.9 | — | 0.8 | 8.7 | 10.3 | 18.7 | 20.3 | 2.4 | 2.6 | B3 |
| | (1.552) | (1.648) | (0.140) | (0.156) | — | (0.032) | (0.348) | (0.412) | (0.748) | (0.812) | (0.096) | (0.104) | |
| VLR170UF | 20.8 | 23.2 | 3.5 | 3.7 | — | 0.07 | 5.3 | 6.7 | 5.3 | 6.7 | 2.4 | 2.6 | B5 |
| | (0.832) | (0.928) | (0.140) | (0.148) | — | (0.003) | (0.212) | (0.268) | (0.212) | (0.268) | (0.096) | (0.104) | |
| VLR175F | 23.0 | 24.5 | 2.9 | 3.3 | 0.5 | 0.8 | 4.7 | 7.2 | 3.8 | 5.4 | 2.4 | 2.6 | B3 |
| | (0.920) | (0.980) | (0.116) | (0.132) | (0.020) | (0.032) | (0.188) | (0.288) | (0.152) | (0.216) | (0.096) | (0.104) | |
| VLR175LF | 29.3 | 31.7 | 2.9 | 3.3 | — | 0.8 | 5.2 | 6.8 | 10 | 12.5 | 2.4 | 2.6 | B3 |
| | (1.172) | (1.268) | (0.116) | (0.132) | — | (0.032) | (0.208) | (0.272) | (0.400) | (0.500) | (0.096) | (0.104) | |
| VLR175UF | 23.0 | 24.5 | 2.9 | 3.1 | — | 0.7 | 5.2 | 7.5 | 4.3 | 5.7 | 2.4 | 2.6 | B5 |
| | (0.920) | (0.980) | (0.116) | (0.124) | — | (0.028) | (0.208) | (0.300) | (0.172) | (0.228) | (0.096) | (0.104) | |
| VLR230F | 20.9 | 23.1 | 4.9 | 5.3 | — | 0.8 | 4.1 | 5.8 | 4.1 | 5.8 | 3.9 | 4.1 | B3 |
| | (0.836) | (0.924) | (0.196) | (0.212) | — | (0.032) | (0.164) | (0.232) | (0.164) | (0.232) | (0.156) | (0.164) | |



RoHS Compliant, ELV Compliant

## Table B4 Dimensions for Strap Battery Devices in Millimeters (Inches) Cont'd

| Part Number | A Min. | A Max. | B Min. | B Max. | C Min. | C Max. | D Min. | D Max. | E Min. | E Max. | F Min. | F Max. | Figure |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **90°C Typical Activation** | | | | | | | | | | | | | |
| **VLP** | | | | | | | | | | | | | |
| VLP120UF | 10.9 | 11.8 | 4.4 | 4.6 | — | 0.7 | 5.5 | 6.5 | 1.65 | 1.9 | 2.3 | 2.5 | B5 |
| | (0.430) | (0.460) | (0.170) | (0.180) | — | (0.028) | (0.220) | (0.260) | (0.065) | (0.075) | (0.091) | (0.098) | |
| VLP175UF | 19.0 | 21.0 | 3.4 | 3.6 | — | 0.7 | 10.0 | 11.0 | 2.5 | 3.5 | 2.9 | 3.1 | B5 |
| | (0.750) | (0.830) | (0.130) | (0.140) | — | (0.030) | (0.390) | (0.430) | (0.100) | (0.140) | (0.110) | (0.120) | |
| VLP210F | 15.4 | 17.5 | 6.9 | 7.3 | 0.6 | 0.8 | 4.0 | 6.2 | 4.0 | 6.2 | 3.9 | 4.1 | B2 |
| | (0.616) | (0.700) | (0.276) | (0.292) | (0.024) | (0.032) | (0.160) | (0.248) | (0.160) | (0.248) | (0.156) | (0.164) | |
| VLP220F | 21.1 | 23.3 | 3.5 | 3.9 | 0.6 | 0.8 | 5.1 | 6.8 | 5.1 | 6.8 | 2.9 | 3.1 | B3 |
| | (0.844) | (0.932) | (0.140) | (0.156) | (0.024) | (0.032) | (0.204) | (0.272) | (0.204) | (0.272) | (0.116) | (0.124) | |
| VLP270F | 20.9 | 23.1 | 4.9 | 5.3 | 0.6 | 0.8 | 4.1 | 5.8 | 4.1 | 5.8 | 3.9 | 4.1 | B3 |
| | (0.836) | (0.924) | (0.196) | (0.212) | (0.024) | (0.032) | (0.164) | (0.232) | (0.164) | (0.232) | (0.156) | (0.164) | |
| **VTP** | | | | | | | | | | | | | |
| VTP110F | 23.6 | 25.6 | 2.7 | 2.9 | — | 0.7 | 7.0 | 8.0 | 7.0 | 8.0 | 2.3 | 2.5 | B5 |
| | (0.944) | (1.024) | (0.108) | (0.116) | — | (0.028) | (0.280) | (0.320) | (0.280) | (0.320) | (0.092) | (0.100) | |
| VTP170F | 15.4 | 17.5 | 7.0 | 7.4 | 0.5 | 0.8 | 4.0 | 6.2 | 4.0 | 6.2 | 3.9 | 4.1 | B2 |
| | (0.616) | (0.700) | (0.280) | (0.296) | (0.020) | (0.032) | (0.160) | (0.248) | (0.160) | (0.248) | (0.156) | (0.164) | |
| VTP170SSF | 15.4 | 17.5 | 7.0 | 7.4 | 0.5 | 0.8 | 4.0 | 6.2 | 4.0 | 6.2 | 3.9 | 4.1 | B7 |
| | (0.616) | (0.700) | (0.280) | (0.296) | (0.020) | (0.032) | (0.160) | (0.248) | (0.160) | (0.248) | (0.156) | (0.164) | |
| VTP170XF | 20.9 | 22.9 | 4.9 | 5.3 | 0.5 | 0.8 | 6.0 | 8.6 | 6.0 | 8.6 | 3.9 | 4.1 | B3 |
| | (0.836) | (0.916) | (0.196) | (0.212) | (0.020) | (0.032) | (0.240) | (0.344) | (0.240) | (0.344) | (0.156) | (0.164) | |
| VTP170XSF | 20.9 | 22.9 | 4.9 | 5.3 | 0.5 | 0.8 | 6.0 | 8.6 | 6.0 | 8.6 | 3.9 | 4.1 | B4 |
| | (0.836) | (0.916) | (0.196) | (0.212) | (0.020) | (0.032) | (0.240) | (0.344) | (0.240) | (0.344) | (0.156) | (0.164) | |
| VTP175F | 21.2 | 23.2 | 3.5 | 3.9 | — | 0.8 | 4.6 | 6.6 | 4.6 | 6.6 | 2.9 | 3.1 | B3 |
| | (0.848) | (0.928) | (0.140) | (0.156) | — | (0.032) | (0.184) | (0.264) | (0.184) | (0.264) | (0.116) | (0.124) | |
| VTP175LF | 25.8 | 28.2 | 3.5 | 3.9 | — | 0.8 | 5.7 | 7.3 | 8.7 | 10.3 | 2.4 | 2.6 | B3 |
| | (1.032) | (1.128) | (0.140) | (0.156) | — | (0.032) | (0.228) | (0.292) | (0.348) | (0.412) | (0.096) | (0.104) | |
| VTP210GF | 20.9 | 23.1 | 4.9 | 5.3 | — | 0.8 | 4.1 | 5.8 | 4.1 | 5.8 | 3.9 | 4.1 | B3 |
| | (0.836) | (0.924) | (0.196) | (0.212) | — | (0.032) | (0.164) | (0.232) | (0.164) | (0.232) | (0.156) | (0.164) | |
| VTP210SF | 20.9 | 23.1 | 4.9 | 5.3 | 0.6 | 0.8 | 4.1 | 5.8 | 4.1 | 5.8 | 3.9 | 4.1 | B4 |
| | (0.836) | (0.924) | (0.196) | (0.212) | (0.024) | (0.032) | (0.164) | (0.232) | (0.164) | (0.232) | (0.156) | (0.164) | |
| **120°C Typical Activation** | | | | | | | | | | | | | |
| **MXP** | | | | | | | | | | | | | |
| MXP190BB | 9.2 | 10.8 | 2.96 | 3.26 | 0.7 | 1.1 | 1.6 | 3.1 | 1.6 | 3.1 | 2.2 | 2.4 | B12 |
| | (0.368) | (0.432) | (0.118) | (0.130) | (0.028) | (0.044) | (0.064) | (0.124) | (0.064) | (0.124) | (0.088) | (0.096) | |
| MXP370BD | 10.5 | 11.3 | 2.96 | 3.26 | 0.7 | 1.1 | 5.0 | — | 2.0 | — | 2.2 | 2.4 | B12 |
| | (0.420) | (0.452) | (0.118) | (0.130) | (0.028) | (0.044) | (0.200) | — | (0.080) | — | (0.088) | (0.096) | |
| **125°C Typical Activation** | | | | | | | | | | | | | |
| **SRP** | | | | | | | | | | | | | |
| SRP120F | 19.9 | 22.1 | 4.9 | 5.2 | 0.6 | 1.0 | 5.5 | 7.5 | 5.5 | 7.5 | 3.9 | 4.1 | B6 |
| | (0.796) | (0.884) | (0.196) | (0.208) | (0.024) | (0.040) | (0.220) | (0.300) | (0.220) | (0.300) | (0.156) | (0.164) | |
| SRP120LF | 24.9 | 27.1 | 4.9 | 5.2 | 0.6 | 1.0 | 5.5 | 7.5 | 10.5 | 12.5 | 3.9 | 4.1 | B6 |
| | (0.996) | (1.084) | (0.196) | (0.208) | (0.024) | (0.040) | (0.220) | (0.300) | (0.420) | (0.500) | (0.156) | (0.164) | |
| SRP120SF | 19.9 | 22.1 | 4.9 | 5.2 | 0.6 | 1.0 | 5.5 | 7.5 | 5.5 | 7.5 | 3.9 | 4.1 | B10 |
| | (0.796) | (0.884) | (0.196) | (0.208) | (0.024) | (0.040) | (0.220) | (0.300) | (0.220) | (0.300) | (0.156) | (0.164) | |
| SRP175F | 20.9 | 23.1 | 4.9 | 5.2 | 0.6 | 1.0 | 4.1 | 5.5 | 4.1 | 5.5 | 3.9 | 4.1 | B6 |
| | (0.836) | (0.924) | (0.196) | (0.208) | (0.024) | (0.040) | (0.164) | (0.220) | (0.164) | (0.220) | (0.156) | (0.164) | |
| SRP175LF | 29.9 | 32.1 | 4.9 | 5.2 | 0.6 | 1.0 | 10.5 | 12.5 | 5.5 | 7.5 | 3.9 | 4.1 | B6 |
| | (1.196) | (1.284) | (0.196) | (0.208) | (0.024) | (0.040) | (0.420) | (0.500) | (0.220) | (0.300) | (0.156) | (0.164) | |
| SRP175SF | 20.9 | 23.1 | 4.9 | 5.2 | 0.6 | 1.0 | 4.1 | 5.5 | 4.1 | 5.5 | 3.9 | 4.1 | B10 |
| | (0.836) | (0.924) | (0.196) | (0.208) | (0.024) | (0.040) | (0.164) | (0.220) | (0.164) | (0.220) | (0.156) | (0.164) | |
| SRP200F | 21.3 | 23.4 | 10.2 | 11.0 | 0.5 | 1.1 | 5.0 | 7.6 | 5.0 | 7.6 | 4.8 | 5.4 | B6 |
| | (0.852) | (0.936) | (0.408) | (0.440) | (0.020) | (0.044) | (0.200) | (0.304) | (0.200) | (0.304) | (0.192) | (0.216) | |
| SRP350F | 28.4 | 31.8 | 13.0 | 13.5 | 0.5 | 1.1 | 6.3 | 8.9 | 6.3 | 8.9 | 6.0 | 6.6 | B6 |
| | (1.136) | (1.272) | (0.520) | (0.540) | (0.020) | (0.044) | (0.252) | (0.356) | (0.252) | (0.356) | (0.240) | (0.264) | |
| SRP420F | 30.6 | 32.4 | 12.9 | 13.6 | 0.5 | 1.1 | 5.0 | 7.5 | 5.0 | 7.5 | 6.0 | 6.7 | B6 |
| | (1.224) | (1.296) | (0.516) | (0.544) | (0.020) | (0.044) | (0.200) | (0.300) | (0.200) | (0.300) | (0.240) | (0.268) | |

## Table B4 Dimensions for Strap Battery Devices in Millimeters (Inches) Cont'd

| Part Number | A | | B | | C | | D | | E | | F | | Figure |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | |
| **LR4** | | | | | | | | | | | | | |
| LR4-190F | 19.9 | 22.1 | 4.9 | 5.5 | 0.6 | 1.0 | 5.5 | 7.5 | 5.5 | 7.5 | 3.9 | 4.1 | B8 |
| | (0.796) | (0.884) | (0.196) | (0.220) | (0.024) | (0.040) | (0.220) | (0.300) | (0.220) | (0.300) | (0.156) | (0.164) | |
| LR4-260F | 20.9 | 23.1 | 4.9 | 5.5 | 0.6 | 1.0 | 4.1 | 5.5 | 4.1 | 5.5 | 3.9 | 4.1 | B8 |
| | (0.836) | (0.924) | (0.196) | (0.220) | (0.024) | (0.040) | (0.164) | (0.220) | (0.164) | (0.220) | (0.156) | (0.164) | |
| LR4-260SF | 20.9 | 23.1 | 4.9 | 5.5 | 0.6 | 1.0 | 4.1 | 5.5 | 4.1 | 5.5 | 3.9 | 4.1 | B9 |
| | (0.836) | (0.924) | (0.196) | (0.220) | (0.024) | (0.040) | (0.164) | (0.220) | (0.164) | (0.220) | (0.156) | (0.164) | |
| LR4-380F | 24.0 | 26.0 | 6.9 | 7.5 | 0.6 | 1.0 | 4.1 | 5.5 | 4.1 | 5.5 | 4.9 | 5.1 | B8 |
| | (0.960) | (1.040) | (0.276) | (0.300) | (0.024) | (0.040) | (0.164) | (0.220) | (0.164) | (0.220) | (0.196) | (0.204) | |
| LR4-380XF | 32.2 | 35.8 | 4.9 | 5.5 | 0.6 | 1.0 | 5.5 | 7.5 | 5.5 | 7.5 | 3.9 | 4.1 | B8 |
| | (1.288) | (1.432) | (0.196) | (0.220) | (0.024) | (0.040) | (0.220) | (0.300) | (0.220) | (0.300) | (0.156) | (0.164) | |
| LR4-450F | 24.0 | 26 | 9.9 | 10.5 | 0.6 | 1.0 | 5.3 | 6.7 | 5.3 | 6.7 | 5.9 | 6.1 | B8 |
| | (0.960) | (1.040) | (0.396) | (0.420) | (0.024) | (0.040) | (0.212) | (0.268) | (0.212) | (0.268) | (0.236) | (0.244) | |
| LR4-550F | 35.0 | 37.0 | 6.9 | 7.5 | 0.6 | 1.0 | 5.3 | 6.7 | 5.3 | 6.7 | 4.9 | 5.1 | B8 |
| | (1.400) | (1.480) | (0.276) | (0.300) | (0.024) | (0.040) | (0.212) | (0.268) | (0.212) | (0.268) | (0.196) | (0.204) | |
| LR4-600F | 24.0 | 26.0 | 13.9 | 14.5 | 0.6 | 1.0 | 4.1 | 5.5 | 4.1 | 5.5 | 5.9 | 6.1 | B8 |
| | (0.960) | (1.040) | (0.556) | (0.580) | (0.024) | (0.040) | (0.164) | (0.220) | (0.164) | (0.220) | (0.236) | (0.244) | |
| LR4-600XF | 40.5 | 42.7 | 6.9 | 7.5 | 0.6 | 1.0 | 5.2 | 6.8 | 5.2 | 6.8 | 4.9 | 5.1 | B8 |
| | (1.620) | (1.708) | (0.276) | (0.300) | (0.024) | (0.040) | (0.208) | (0.272) | (0.208) | (0.272) | (0.196) | (0.204) | |
| LR4-730F | 27.1 | 29.1 | 13.9 | 14.5 | 0.6 | 1.0 | 4.1 | 5.5 | 4.1 | 5.5 | 5.9 | 6.1 | B8 |
| | (1.084) | (1.164) | (0.556) | (0.580) | (0.024) | (0.040) | (0.164) | (0.220) | (0.164) | (0.220) | (0.236) | (0.244) | |
| LR4-900F | 45.4 | 47.6 | 7.9 | 8.5 | 0.9 | 1.3 | 4.6 | 6.2 | 4.6 | 6.2 | 5.9 | 6.1 | B8 |
| | (1.816) | (1.904) | (0.316) | (0.340) | (0.036) | (0.052) | (0.184) | (0.248) | (0.184) | (0.248) | (0.236) | (0.244) | |
| LR4-1300SSF | 61.5 | 66.5 | 9.4 | 10.0 | 0.9 | 1.3 | 5.0 | 7.5 | 5.0 | 7.5 | 5.9 | 6.1 | B11 |
| | (2.460) | (2.660) | (0.376) | (0.400) | (0.036) | (0.052) | (0.200) | (0.300) | (0.200) | (0.300) | (0.236) | (0.244) | |

## Figure B13-B18 Typical Time-to-trip Curves at 20°C for Strap Battery Devices


**VLR (data at 25°C)**

A = VLR170F

B = VLR175F

C = VLR230F

**Figure B13**







RoHS Compliant, ELV Compliant

## Figure B13-B18 Typical Time-to-trip Curves at 20°C for Strap Battery Devices Cont'd

**VLP (data at 25°C)**

A = VLP120UF
B = VLP175UF
C = VLP210F
D = VLP220F
E = VLP270F


Figure B14




**VTP (data at 25°C)**

A = VTP110F
B = VTP170F
C = VTP175F
D = VTP210GF


Figure B15




**MXP (data at 25°C)**

A = MXP190BB
B = MXP370BD

Figure B16




## Figure B13-B18 Typical Time-to-trip Curves at 20°C for Strap Battery Devices Cont'd

**SRP**

A = SRP120F
B = SRP175F
C = SRP200F
D = SRP350F
E = SRP420F


**Figure B17**




**LR4**

A = LR4-190F
B = LR4-260F
C = LR4-380F
D = LR4-450F
E = LR4-550F
F = LR4-600F
G = LR4-730F
H = LR4-900F
I = LR4-1300SSF

**Figure B18**




## Table B5 Physical Characteristics and Environmental Specifications for Strap Battery Devices

**VLR**

**Physical Characteristics**

| | |
|---|---|
| Lead material | 0.125mm nominal thickness, quarter-hard nickel |
| Tape material | Polyester |

**Environmental Specifications**

| Test | Conditions | Resistance Change |
|---|---|---|
| Passive aging | -40°C, 1000 hours | ±5% typical |
| | 60°C, 1000 hours | ±20% typical |
| Humidity aging | 60°C/95% RH, 1000 hours | ±30% typical |
| Thermal shock | 85°C, -40°C (10 times) | ±5% typical |
| Vibration | MIL-STD-883D, Method 2026 | No change |


RoHS Compliant, ELV Compliant

## Table B5 Physical Characteristics and Environmental Specifications for Strap Battery Devices Cont'd

### VLP and VTP

#### Physical Characteristics

| | |
|---|---|
| Lead material | 0.125mm nominal thickness, quarter-hard nickel |
| Tape material | Polyester |

#### Environmental Specifications

| Test | Conditions | Resistance Change |
|---|---|---|
| Passive aging | -40°C, 1000 hours | ±5% typical |
| | 60°C, 1000 hours | ±10% typical |
| Humidity aging | 60°C/95% RH, 1000 hours | ±10% typical |
| Thermal shock | 85°C, -40°C (10 times) | ±5% typical |
| Vibration | MIL-STD-883D, Method 2026 | No change |

### MXP

#### Physical Characteristics

| | |
|---|---|
| Lead material | 0.1mm nominal thickness, half-hard nickel |
| Coating material | Epoxy |

#### Environmental Specifications

| Test | Conditions | Resistance Change |
|---|---|---|
| Passive aging | -40°C, 1000 hours | ±5% typical |
| | 60°C, 1000 hours | ±20% typical |
| Humidity aging | 60°C/95% RH, 1000 hours | ±30% typical |
| Thermal shock | 85°C, -40°C (10 times) | ±5% typical |
| Vibration | MIL-STD-883D, Method 2026 | No change |

### SRP

#### Physical Characteristics

| | |
|---|---|
| Lead material | 0.125mm nominal thickness, quarter-hard nickel |
| Tape material | Polyester |

#### Environmental Specifications

| Test | Conditions | Resistance Change |
|---|---|---|
| Passive aging | 70°C, 1000 hours | ±10% typical |
| Humidity aging | 85°C/85% RH, 7 days | ±5% typical |
| Vibration | MIL-STD-883C, Test Condition A | No change |

### LR4

#### Physical Characteristics

| | |
|---|---|
| Lead material | 0.125mm nominal thickness, quarter-hard nickel |
| Tape material | Polyester |

#### Environmental Specifications

| Test | Conditions | Resistance Change |
|---|---|---|
| Passive aging | 70°C, 1000 hours | ±10% typical |
| Humidity aging | 85°C/85% RH, 7 days | ±5% typical |
| Vibration | MIL-STD-883D, Method 2026 | No change |

**Note:** Storage conditions: 40°C max., 70% RH max.; devices should remain in original sealed bags prior to use. Devices may not meet specified values if these storage conditions are exceeded.

## Table B6 Packaging and Marking Information/Agency Recognition for Strap Battery Devices

| Part Number | Bag Quantity | Tape & Reel Quantity | Standard Package Quantity | Part Marking | Agency Recognition |
|---|---|---|---|---|---|
| **85°C Typical Activation VLR** | | | | | |
| VLR170F | 1,000 | — | 10,000 | R17 | UL, CSA,TÜV |
| VLR170LF | 1,000 | — | 10,000 | R17 | UL, CSA,TÜV |
| VLR170UF | 1,000 | — | 10,000 | — | UL, CSA,TÜV |
| VLR175F | 1,000 | — | 10,000 | R1X | UL, CSA,TÜV |
| VLR175LF | 1,000 | — | 10,000 | R1X | UL, CSA,TÜV |
| VLR175UF | 1,000 | — | 10,000 | — | UL, CSA,TÜV |
| VLR230F | 1,000 | — | 10,000 | R23 | UL, CSA,TÜV |
| **90°C Typical Activation VLP** | | | | | |
| VLP120UF | 1,000 | — | 10,000 | — | UL, CSA, TÜV |
| VLP175UF | 1,000 | — | 10,000 | — | UL, CSA, TÜV |
| VLP210F | 1,000 | — | 10,000 | W21 | UL, CSA, TÜV |
| VLP220F | 1,000 | — | 10,000 | W22 | UL, CSA, TÜV |
| VLP270F | 1,000 | — | 10,000 | W27 | UL, CSA, TÜV |
| **VTP** | | | | | |
| VTP110F | 1,000 | — | 10,000 | — | UL, CSA, TÜV |
| VTP170F | 1,000 | — | 10,000 | V17 | UL, CSA, TÜV |
| VTP170SSF | 1,000 | — | 10,000 | V17 | UL, CSA, TÜV |
| VTP170XF | 1,000 | — | 10,000 | V17 | UL, CSA, TÜV |
| VTP170XSF | 1,000 | — | 10,000 | V17 | UL, CSA, TÜV |
| VTP175F | 1,000 | — | 10,000 | V1X | UL, CSA, TÜV |
| VTP175LF | 1,000 | — | 10,000 | V1X | UL, CSA, TÜV |
| VTP210GF | 1,000 | — | 10,000 | V21 | UL, CSA, TÜV |
| VTP210SF | 1,000 | — | 10,000 | V21 | UL, CSA, TÜV |
| **120°C Typical Activation MXP** | | | | | |
| MXP190BB | 4,000 | — | 8,000 | — | UL, CSA, TÜV |
| MXP370BD | 2,000 | — | 4,000 | — | UL, CSA, TÜV |
| **125°C Typical Activation SRP** | | | | | |
| SRP120F | 1,000 | — | 10,000 | 120 | UL, CSA, TÜV |
| SRP120LF | 1,000 | — | 10,000 | 120 | UL, CSA, TÜV |
| SRP120SF | 2,000 | — | 10,000 | 120 | UL, CSA, TÜV |
| SRP175F | 2,000 | — | 10,000 | 175 | UL, CSA, TÜV |
| SRP175LF | 1,000 | — | 10,000 | 175 | UL, CSA, TÜV |
| SRP175SF | 2,000 | — | 10,000 | 175 | UL, CSA, TÜV |
| SRP200F | 1,000 | — | 10,000 | 200 | UL, CSA, TÜV |
| SRP350F | 500 | — | 10,000 | 350 | UL, CSA, TÜV |
| SRP420F | 500 | — | 10,000 | 420 | UL, CSA, TÜV |
| **LR4** | | | | | |
| LR4-190F | 2,000 | — | 10,000 | E19 | UL, CSA, TÜV |
| LR4-260F | 1,000 | — | 10,000 | E26 | UL, CSA, TÜV |
| LR4-260SF | 1,000 | — | 10,000 | E26 | UL, CSA, TÜV |
| LR4-380F | 1,000 | — | 10,000 | E38 | UL, CSA, TÜV |
| LR4-380XF | 1,000 | — | 10,000 | E38 | UL, CSA, TÜV |
| LR4-450F | 1,000 | — | 10,000 | E45 | UL, CSA, TÜV |
| LR4-550F | 1,000 | — | 10,000 | E55 | UL, CSA, TÜV |
| LR4-600F | 1,000 | — | 10,000 | E60 | UL, CSA, TÜV |
| LR4-600XF | 1,000 | — | 10,000 | E60 | UL, CSA, TÜV |
| LR4-730F | 1,000 | — | 10,000 | E73 | UL, CSA, TÜV |
| LR4-900F | 500 | — | 10,000 | E90 | UL, CSA, TÜV |
| LR4-1300SSF | 250 | — | 10,000 | EX3 | UL, CSA, TÜV |





RoHS Compliant, ELV Compliant


## Agency Recognition for Strap Battery Devices

| | |
|---|---|
| UL | File # E74889 |
| CSA | File # 78165C |
| TÜV | Certificate number available on request |

## Installation Guidelines for the Strap Family

- PPTC devices operate by thermal expansion of the conductive polymer. If devices are placed under pressure or installed in spaces that would prevent thermal expansion, they may not properly protect against damage caused by fault conditions. Designs must be selected in such a manner that adequate space is maintained over the life of the product.
- Twisting, bending, or placing the PPTC device in tension will decrease the ability of the device to protect against damage caused by electrical faults. No residual force should remain on device after installation. Mechanical damage to the PPTC device may affect device performance and should be avoided.
- Chemical contamination of PPTC devices should be avoided. Certain greases, solvents, hydraulic fluids, fuels, industrial cleaning agents, volatile components of adhesives, silicones, and electrolytes can have an adverse effect on device performance.
- PPTC strap devices are designed to be resistance welded to battery cells or to pack interconnect straps, yet some precautions must be taken when doing so. In order for the PPTC device to exhibit its specified performance, weld placement should be a minimum of 2mm from the edge of the PPTC device, weld splatter must not touch the PPTC device, and welding conditions must not heat the PPTC device above its maximum operating temperature.
- PPTC strap devices are not designed for applications where reflow onto flex circuits or rigid circuit boards is required.
- The polyester tape on PPTC strap devices is intended for marking and identification purposes only, not for electrical insulation.
- The coating on MXP devices is intended to prevent oxidization/aging of the devices. Damaging the coating or causing the coating to delaminate can have negative effects on device performance and should be avoided.
- MXP devices have small PPTC chip size and therefore have weaker peel strength between polymer and Ni-foil of the chip. Excessive mechanical force to the device may cause delamination of Ni-foil from polymer.

## Part Numbering System for Strap Battery Devices




## ⚠ Warning :

- Users should independently evaluate the suitability of and test each product selected for their own application.
- Operation beyond the maximum ratings or improper use may result in device damage and possible electrical arcing and flame.
- These devices are intended for protection against damage caused by occasional overcurrent or overtemperature fault conditions and should not be used when repeated fault conditions or prolonged trip events are anticipated.
- Contamination of the PPTC material with certain silicone-based oils or some aggressive solvents can adversely impact the performance of the devices.
- Device performance can be impacted negatively if devices are handled in a manner inconsistent with recommended electronic, thermal, and mechanical procedures for electronic components.
- PPTC devices are not recommended for installation in applications where the device is constrained such that its PTC properties are inhibited, for example in rigid potting materials or in rigid housings, which lack adequate clearance to accommodate device expansion.
- Operation in circuits with a large inductance can generate a circuit voltage (Ldi/dt) above the rated voltage of the device.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** sales@st-electron.ru

**Адрес:** 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331