Low Cost, Low Noise, CMOS, RRO Operational Amplifiers

Data Sheet

AD8691/AD8692/AD8694

FEATURES

Offset voltage: 400 µV typical
Low offset voltage drift: 6 µV/°C maximum (AD8692/AD8694)
Very low input bias currents: 1 pA maximum
Low noise: 8 nV/√Hz
Low distortion: 0.0006%
Wide bandwidth: 10 MHz
Unity-gain stable
Single-supply operation: 2.7 V to 6 V
Qualified for automotive applications

APPLICATIONS

Photodiode amplification
Battery-powered instrumentation
Medical instruments
Multipole filters
Sensors
Portable audio devices

GENERAL DESCRIPTION

The AD8691, AD8692, and AD8694 are low cost, single, dual, and quad rail-to-rail output, single-supply amplifiers featuring low offset and input voltages, low current noise, and wide signal bandwidth. The combination of low offset, low noise, very low input bias currents, and high speed make these amplifiers useful in a wide variety of applications. Filters, integrators, photodiode amplifiers, and high impedance sensors all benefit from this combination of performance features. Audio and other ac applications benefit from the wide bandwidth and low distortion of these devices.

Applications for these amplifiers include power amplifier (PA) controls, laser diode control loops, portable and loop-powered instrumentation, audio amplification for portable devices, and ASIC input and output amplifiers.

The small SC70 and TSOT package options for the AD8691 allow it to be placed next to sensors, thereby reducing external noise pickup.

The AD8691, AD8692, and AD8694 are specified over the extended industrial temperature range of −40°C to +125°C. The AD8691 single is available in 5-lead SC70 and 5-lead TSOT packages. The AD8692 dual is available in 8-lead MSOP and narrow SOIC surface-mount packages. The AD8694 quad is available in 14-lead TSSOP and narrow 14-lead SOIC packages.

See the Ordering Guide section for automotive grades.

PIN CONFIGURATIONS



Figure 1. 5-Lead TSOT



Figure 2. 5-Lead SC70



Figure 3. 8-Lead SOIC and 8-Lead MSOP



Figure 4. 14-Lead SOIC and 14-Lead TSSOP

Rev. F
Document Feedback

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 ©2004–2013 Analog Devices, Inc. All rights reserved.
Technical Support www.analog.com

TABLE OF CONTENTS

Features ... 1
Applications ... 1
General Description ... 1
Pin Configurations ... 1
Revision History ... 2
Specifications ... 3
Electrical Characteristics ... 3
Absolute Maximum Ratings ... 5
Thermal Characteristics ... 5
ESD Caution ... 5
Typical Performance Characteristics ... 6
Outline Dimensions ... 11
Ordering Guide ... 14
Automotive Products ... 14

REVISION HISTORY

9/13—Rev. E to Rev. F

Changes to Figure 3 and Figure 4 ... 1
Delete Figure 4 and Figure 5; Renumbered Sequentially ... 1
Changes to Ordering Guide ... 14

8/11—Rev. D to Rev. E

Changes to Figure 20 ... 8

11/10—Rev. C to Rev. D

Changes to Features Section and General Descriptions Section ... 1
Updated Outline Dimensions ... 11
Changes to Ordering Guide ... 14
Added Automotive Products Section ... 14

5/07—Rev. B to Rev. C

Change to Figure 1 ... 1
Changes to Large Signal Voltage Gain Values in Table 1 ... 3
Change to Phase Margin Symbol in Table 1 ... 3
Change to T_A Value for Table 2 ... 4
Changes to Large Signal Voltage Gain Values in Table 2 ... 4
Change to Phase Margin Symbol in Table 2 ... 4
Changes to Table 4 ... 5
Changes to Outline Dimensions ... 11
Changes to Ordering Guide ... 12

3/05—Rev. A to Rev. B

Added AD8694 ... Universal

1/05—Rev. 0 to Rev. A

Added AD8691 ... Universal
Changes to Features ... 1
Added Figure 1 and Figure 2 ... 1
Changes to Electrical Characteristics ... 3
Changes to Figure 6 caption ... 6
Changes to Figure 9 ... 6
Updated Outline Dimensions ... 11
Changes to Ordering Guide ... 11

10/04—Revision 0: Initial Version

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS

V_S = 2.7 V, V_{CM} = V_S/2, T_A = 25°C, unless otherwise noted.

Table 1.

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	V_{CM} = −0.3 V to +1.6 V		0.4	2.0	mV
		V_{CM} = −0.1 V to +1.6 V; −40°C < T_A < +125°C			3.0	mV
Input Bias Current	I_B			0.2	1	pA
		−40°C < T_A < +85°C			50	pA
		−40°C < T_A < +125°C			260	pA
Input Offset Current	I_{OS}			0.1	0.5	pA
		−40°C < T_A < +85°C			20	pA
		−40°C < T_A < +125°C			75	pA
Input Voltage Range			−0.3		+1.6	V
Common-Mode Rejection Ratio	CMRR	V_{CM} = −0.3 V to +1.6 V	68	90		dB
		V_{CM} = −0.1 V to +1.6 V; −40°C < T_A < +125°C	60	85		dB
Large Signal Voltage Gain	A_{VO}					
AD8691/AD8692		R_L = 2 kΩ, V_O = 0.5 V to 2.2 V	90	250		V/mV
AD8694		R_L = 2 kΩ, V_O = 0.5 V to 2.2 V	60			V/mV
Offset Voltage Drift	$\Delta V_{OS}/\Delta T$					
AD8691				2	12	µV/°C
AD8692/AD8694				1.3	6	µV/°C
INPUT CAPACITANCE						
Common-Mode Input Capacitance	C_{CM}			5		pF
Differential Input Capacitance	C_{DM}			2.5		pF
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	I_L = 1 mA	2.64	2.66		V
		−40°C < T_A < +125°C	2.6			V
Output Voltage Low	V_{OL}	I_L = 1 mA		25	40	mV
		−40°C < T_A < +125°C			60	mV
Short-Circuit Current	I_{SC}			±20		mA
Closed-Loop Output Impedance	Z_{OUT}	f = 1 MHz, A_V = 1		12		Ω
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	V_S = 2.7 V to 5.5 V	80	95		dB
		−40°C < T_A < +125°C	75	95		dB
Supply Current/Amplifier	I_{SY}	V_O = 0 V		0.85	0.95	mA
		−40°C < T_A < +125°C			1.2	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	R_L = 2 kΩ		5		V/µs
Settling Time	t_S	To 0.01%		1		µs
Gain Bandwidth Product	GBP			10		MHz
Phase Margin	$Ø_m$			60		Degrees
Total Harmonic Distortion + Noise	THD + N	G = 1, R_L = 600 Ω, f = 1 kHz, V_O = 250 mV p-p		0.003		%
NOISE PERFORMANCE						
Voltage Noise	$e_{n\ p-p}$	f = 0.1 Hz to 10 Hz		1.6	3.0	µV p-p
Voltage Noise Density	e_n	f = 1 kHz		8	12	nV/√Hz
	e_n	f = 10 kHz		6.5		nV/√Hz
Current Noise Density	i_n	f = 1 kHz		0.05		pA/√Hz

V_S = 5.0 V, V_{CM} = V_S/2, T_A = 25°C, unless otherwise noted.

Table 2.

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	V_{CM} = −0.3 V to +3.9 V		0.4	2.0	mV
		V_{CM} = −0.1 V to +3.9 V; −40°C < T_A < +125°C			3.0	mV
Input Bias Current	I_B			0.2	1	pA
		−40°C < T_A < +85°C			50	pA
		−40°C < T_A < +125°C			260	pA
Input Offset Current	I_{OS}			0.1	0.5	pA
		−40°C < T_A < +85°C			20	pA
		−40°C < T_A < +125°C			75	pA
Input Voltage Range			−0.3		+3.9	V
Common-Mode Rejection Ratio	CMRR	V_{CM} = −0.3 V to +3.9 V	70	95		dB
		V_{CM} = −0.1 V to +3.9 V; −40°C < T_A < +125°C	67	95		dB
Large Signal Voltage Gain	A_{VO}					
AD8691/AD8692		V_O = 0.5 V to 4.5 V, R_L = 2 kΩ, V_{CM} = 0 V	250	2000		V/mV
AD8694		V_O = 0.5 V to 4.5 V, R_L = 2 kΩ, V_{CM} = 0 V	150			V/mV
Offset Voltage Drift	$\Delta V_{OS}/\Delta T$					
AD8691				2	12	µV/°C
AD8692/AD8694				1.3	6	µV/°C
INPUT CAPACITANCE						
Common-Mode Input Capacitance	C_{CM}			5		pF
Differential Input Capacitance	C_{DM}			2.5		pF
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	I_L = 1 mA	4.96	4.98		V
		I_L = 10 mA	4.7	4.78		V
		−40°C to +125°C	4.6			V
Output Voltage Low	V_{OL}	I_L = 1 mA		20	40	mV
AD8691/AD8692		I_L = 10 mA		165	210	mV
AD8694		I_L = 10 mA		185	240	mV
AD8691/AD8692		−40°C to +125°C			290	mV
AD8694		−40°C to +125°C			370	mV
Short-Circuit Current	I_{SC}			±80		mA
Closed-Loop Output Impedance	Z_{OUT}	f = 1 MHz, A_V = 1		10		Ω
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	V_S = 2.7 V to 5.5 V	80	95		dB
		−40°C < T_A < +125°C	75	95		dB
Supply Current/Amplifier	I_{SY}	V_O = 0 V		0.95	1.05	mA
		−40°C < T_A < +125°C			1.3	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	R_L = 2 kΩ		5		V/µs
Settling Time	t_S	To 0.01%		1		µs
Full Power Bandwidth	BW_P	<1% distortion		360		kHz
Gain Bandwidth Product	GBP			10		MHz
Phase Margin	$Ø_m$			65		Degrees
Total Harmonic Distortion + Noise	THD + N	G = 1, R_L = 600 Ω, f = 1 kHz, V_O = 1 V p-p		0.0006		%
NOISE PERFORMANCE						
Voltage Noise	$e_{n\,p\text{-}p}$	f = 0.1 Hz to 10 Hz		1.6	3.0	µV p-p
Voltage Noise Density	e_n	f = 1 kHz		8	12	nV/√Hz
	e_n	f = 10 kHz		6.5		nV/√Hz
Current Noise Density	i_n	f = 1 kHz		0.05		pA/√Hz

ABSOLUTE MAXIMUM RATINGS

T_A = 25°C, unless otherwise noted.

Table 3.

Parameter	Rating
Supply Voltage	6 V
Input Voltage	V_{SS} − 0.3 V to V_{DD} + 0.3 V
Differential Input Voltage	±6 V
Output Short-Circuit Duration to GND	Observe derating curves
Storage Temperature Range	−65°C to +150°C
Operating Temperature Range	−40°C to +125°C
Junction Temperature Range	−65°C to +150°C
Lead Temperature (Soldering, 60 sec)	300°C

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL CHARACTERISTICS

θ_{JA} is specified for the worst-case conditions, that is, the device soldered in the circuit board for surface-mount packages.

Table 4. Thermal Resistance

Package Type	θ_{JA}	θ_{JC}	Unit
8-Lead MSOP (RM-8)	210	45	°C/W
8-Lead SOIC (R-8)	158	43	°C/W
5-Lead TSOT (UJ-5)	207	61	°C/W
5-Lead SC70 (KS-5)	376	126	°C/W
14-Lead TSSOP (RU-14)	180	35	°C/W
14-Lead SOIC (R-14)	120	36	°C/W

ESD CAUTION

ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

TYPICAL PERFORMANCE CHARACTERISTICS

V_S = +5 V or ±2.5 V, unless otherwise noted.



Figure 5. Input Offset Voltage Distribution



Figure 8. Input Bias Current vs. Temperature



Figure 6. AD8692/AD8694 Input Offset Voltage Drift Distribution



Figure 9. Supply Current vs. Supply Voltage



Figure 7. Input Offset Voltage vs. Common-Mode Voltage



Figure 10. Supply Current vs. Temperature



Figure 11. Output Voltage to Supply Rail vs. Load Current



Figure 14. Open-Loop Gain and Phase vs. Frequency



Figure 12. Output Voltage Swing vs. Temperature (I_L = 1 mA)



Figure 15. CMRR vs. Frequency



Figure 13. Output Voltage Swing vs. Temperature (I_L = 10 mA)



Figure 16. PSRR vs. Frequency



Figure 17. Closed-Loop Output Impedance vs. Frequency



Figure 20. Large Signal Transient Response



Figure 18. Small Signal Overshoot vs. Load Capacitance



Figure 21. Positive Overload Recovery



Figure 19. Small Signal Transient Response



Figure 22. Negative Overload Recovery



Figure 23. THD + N vs. Frequency



Figure 24. 0.1 Hz to 10 Hz Input Voltage Noise



Figure 25. Voltage Noise Density



Figure 26. AD8692/AD8694 Channel Separation

V_S = +2.7 V or ±1.35 V, unless otherwise noted.



Figure 27. Input Offset Voltage Distribution



Figure 30. Output Voltage Swing vs. Temperature (I_L = 1 mA)



Figure 28. Input Offset Voltage vs. Common-Mode Voltage



Figure 31. Large Signal Transient Response



Figure 29. Output Voltage to Supply Rail vs. Load Current

OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MO-187-AA

Figure 32. 8-Lead Mini Small Outline Package [MSOP]
(RM-8)
Dimensions shown in millimeters



COMPLIANT TO JEDEC STANDARDS MS-012-AA
CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS (IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

Figure 33. 8-Lead Standard Small Outline Package [SOIC_N]
Narrow Body (R-8)
Dimensions shown in millimeters and (inches)



Figure 34. 5-Lead Thin Shrink Small Outline Package [SC70]
(KS-5)
Dimensions shown in millimeters



Figure 35. 5-Lead Thin Small Outline Transistor Package [TSOT]
(UJ-5)
Dimensions shown in millimeters



COMPLIANT TO JEDEC STANDARDS MO-153-AB-1

Figure 36. 14-Lead Thin Shrink Small Outline Package [TSSOP]
(RU-14)
Dimensions shown in millimeters



COMPLIANT TO JEDEC STANDARDS MS-012-AB
CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS
(IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR
REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

Figure 37. 14-Lead Standard Small Outline Package [SOIC_N]
Narrow Body (R-14)
Dimensions shown in millimeters and (inches)

ORDERING GUIDE

Model[1, 2]	Temperature Range	Package Description	Package Option	Branding
AD8691AUJZ-R2	−40°C to +125°C	5-Lead TSOT	UJ-5	ACA
AD8691AUJZ-REEL	−40°C to +125°C	5-Lead TSOT	UJ-5	ACA
AD8691AUJZ-REEL7	−40°C to +125°C	5-Lead TSOT	UJ-5	ACA
AD8691AKSZ-R2	−40°C to +125°C	5-Lead SC70	KS-5	ACA
AD8691AKSZ-REEL	−40°C to +125°C	5-Lead SC70	KS-5	ACA
AD8691AKSZ-REEL7	−40°C to +125°C	5-Lead SC70	KS-5	ACA
AD8691WAUJZ-R7	−40°C to +125°C	5-Lead TSOT	UJ-5	ACA
AD8691WAUJZ-RL	−40°C to +125°C	5-Lead TSOT	UJ-5	ACA
AD8692ARMZ-R7	−40°C to +125°C	8-Lead MSOP	RM-8	APA
AD8692ARMZ-REEL	−40°C to +125°C	8-Lead MSOP	RM-8	APA
AD8692ARZ	−40°C to +125°C	8-Lead SOIC_N	R-8	
AD8692ARZ-REEL	−40°C to +125°C	8-Lead SOIC_N	R-8	
AD8692ARZ-REEL7	−40°C to +125°C	8-Lead SOIC_N	R-8	
AD8692WARMZ-REEL	−40°C to +125°C	8-Lead MSOP	RM-8	APA
AD8694ARUZ	−40°C to +125°C	14-Lead TSSOP	RU-14	
AD8694ARUZ-REEL	−40°C to +125°C	14-Lead TSSOP	RU-14	
AD8694WARUZ	−40°C to +125°C	14-Lead TSSOP	RU-14	
AD8694WARUZ-REEL	−40°C to +125°C	14-Lead TSSOP	RU-14	
AD8694ARZ	−40°C to +125°C	14-Lead SOIC_N	R-14	
AD8694ARZ-REEL	−40°C to +125°C	14-Lead SOIC_N	R-14	
AD8694ARZ-REEL7	−40°C to +125°C	14-Lead SOIC_N	R-14	
AD8694WAC-P3	−40°C to +125°C	Die		
AD8694WAC-P7	−40°C to +125°C	Die		

[1] Z = RoHS Compliant Part.
[2] W = Qualified for Automotive Applications.

AUTOMOTIVE PRODUCTS

The AD8691W/AD8692W/AD8694W models are available with controlled manufacturing to support the quality and reliability requirements of automotive applications. Note that these automotive models may have specifications that differ from the commercial models; therefore, designers should review the Specifications section of this data sheet carefully. Only the automotive grade products shown are available for use in automotive applications. Contact your local Analog Devices account representative for specific product ordering information and to obtain the specific Automotive Reliability reports for these models.

NOTES

NOTES

©2004–2013 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.
D04991-0-9/13(F)

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331