Bulletin PD-20785 07/04

International
IOR Rectifier

# 10BQ060PbF

## SCHOTTKY RECTIFIER 1 Amp

$I_{F(AV)}$ = 1.0Amp
$V_R$ = 60V

### Major Ratings and Characteristics

| Characteristics | 10BQ060 | Units |
|---|---|---|
| $I_{F(AV)}$ Rectangular waveform | 1.0 | A |
| $V_{RRM}$ | 60 | V |
| $I_{FSM}$ @tp = 5 µs sine | 700 | A |
| $V_F$ @1.0 Apk, $T_J$=125°C | 0.57 | V |
| $T_J$ range | - 55 to 150 | °C |


### Description/ Features

The 10BQ060 surface-mount Schottky rectifier has been designed for applications requiring low forward drop and very small foot prints on PC boards. Typical applications are in disk drives, switching power supplies, converters, free-wheeling diodes, battery charging, and reverse battery protection.

- Small foot print, surface mountable
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead-Free ("PbF" suffix)

### Case Styles

10BQ060PbF






SMB

## Voltage Ratings

| | Part number | 10BQ060PbF |
|---|---|---|
| $V_R$ | Max. DC Reverse Voltage (V) | 60 |
| $V_{RWM}$ | Max. Working Peak Reverse Voltage (V) | |

## Absolute Maximum Ratings

| | Parameters | 10BQ | Units | Conditions | |
|---|---|---|---|---|---|
| $I_{F(AV)}$ | Max. Average Forward Current | 1.0 | A | 50% duty cycle @ $T_L$ = 103 °C, rectangular wave form | |
| $I_{FSM}$ | Max. Peak One Cycle Non-Repetitive | 700 | A | 5µs Sine or 3µs Rect. pulse | Following any rated load condition and with rated $V_{RRM}$ applied |
| | Surge Current | 42 | | 10ms Sine or 6ms Rect. pulse | |
| $E_{AS}$ | Non- Repetitive Avalanche Energy | 2.0 | mJ | $T_J$ = 25 °C, $I_{AS}$ = 1A, L = 4mH | |
| $I_{AR}$ | Repetitive Avalanche Current | 1.0 | A | Current decaying linearly to zero in 1 µsec<br>Frequency limited by $T_J$ max. Va = 1.5 x Vr typical | |

## Electrical Specifications

| | Parameters | 10BQ | Units | Conditions | |
|---|---|---|---|---|---|
| $V_{FM}$ | Max. Forward Voltage Drop (1) | 0.6 | V | @ 1A | $T_J$ = 25 °C |
| | * See Fig. 1 | 0.76 | V | @ 2A | |
| | | 0.57 | V | @ 1A | $T_J$ = 125 °C |
| | | 0.69 | V | @ 2A | |
| $I_{RM}$ | Max. Reverse Leakage Current (1) | 0.1 | mA | $T_J$ = 25 °C | $V_R$ = rated $V_R$ |
| | * See Fig. 2 | 5.0 | mA | $T_J$ = 125 °C | |
| $C_T$ | Typical Junction Capacitance | 62 | pF | $V_R$ = 5$V_{DC}$ (test signal range 100kHz to 1MHz) 25°C | |
| $L_S$ | Typical Series Inductance | 2.0 | nH | Measured lead to lead 5mm from package body | |
| dv/dt | Max. Volatge Rate of Charge (Rated $V_R$) | 10000 | V/ µs | | |

(1) Pulse Width < 300µs, Duty Cycle < 2%

## Thermal-Mechanical Specifications

| | Parameters | 10BQ | Units | Conditions |
|---|---|---|---|---|
| $T_J$ | Max. Junction Temperature Range (*) | -55 to 150 | °C | |
| $T_{stg}$ | Max. Storage Temperature Range | -55 to 150 | °C | |
| $R_{thJL}$ | Max. Thermal Resistance Junction to Lead (**) | 36 | °C/W | DC operation |
| $R_{thJA}$ | Max. Thermal Resistance Junction to Ambient | 80 | °C/W | |
| wt | Approximate Weight | 0.10 (0.003) | g (oz.) | |
| | Case Style | SMB | | Similar DO-214AA |
| | Device Marking | IR1H | | |

(*) $\frac{dPtot}{dTj} < \frac{1}{Rth(j\text{-}a)}$ thermal runaway condition for a diode on its own heatsink

(**) Mounted 1 inch square PCB





Fig. 1 - Maximum Forward Voltage Drop Characteristics





Fig. 2 - Typical Peak Reverse Current Vs. Reverse Voltage





Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage





Fig. 4 - Max. Thermal Impedance $Z_{thJC}$ Characteristics (Per Leg)





Fig. 4 - Maximum Average Forward Current
Vs. Allowable Lead Temperature





Fig. 5 - Maximum Average Forward Dissipation
Vs. Average Forward Current






Fig. 6 - Maximum Peak Surge Forward Current Vs. Pulse Duration

**(2)** Formula used: $T_C = T_J - (Pd + Pd_{REV}) \times R_{thJC}$;
$Pd$ = Forward Power Loss = $I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);
$Pd_{REV}$ = Inverse Power Loss = $V_{R1} \times I_R (1 - D)$; $I_R @ V_{R1}$ = 80% rated $V_R$

## Outline Table




**Outline SMB**


Dimensions in millimeters and (inches)


For recommended footprint and soldering techniques refer to application note #AN-994

## Marking & Identification


Each device has 2 rows for identification. The first row designates the device as manufactured by International Rectifier, indicated by the letters "IR", and the Part Number (indicates the current, the voltage rating and Schottky Generation). The second row indicates the year, the week of manufacturing and the Site ID.



## Tape & Reel Information




Dimensions in millimetres and (inches)

## Ordering Information Table

**Device Code**

| 10 | B | Q | 060 | TR | PbF |
|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |

**1** - Current Rating

**2** - B = Single Lead Diode

**3** - Q = Schottky Q Series

**4** - Voltage Rating (060 = 60V)

**5** - • none = Box (1000 pieces)
• TR = Tape & Reel (3000 pieces)

**6** - • none = Standard Production
• PbF = Lead-Free

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level and Lead-Free.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
07/04

# Notice

The products described herein were acquired by Vishay Intertechnology, Inc., as part of its acquisition of International Rectifier's Power Control Systems (PCS) business, which closed in April 2007. Specifications of the products displayed herein are pending review by Vishay and are subject to the terms and conditions shown below.

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** sales@st-electron.ru

**Адрес:** 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331