



Features

- Surge withstand IEC 61000-4-5 1.2/50 μ s
- Low thermal resistant ceramic core
- E24 resistance values
- RoHS compliant*
- Wide power range (1-8 W)
- Coating material meets UL 94V-0 requirements

Applications

- Smart meters
- Renewable energy
- Industrial
- Power supplies/chargers
- Lighting
- Instruments/gauges
- White goods

WS Series High Surge Withstand Wirewound Resistor

Electrical Characteristics

| | |
|-------------------------------|-------------------------------------|
| Resistance Range | See Popular Resistance Values Table |
| Power Rating @ 70 °C | |
| WS1M, WS1A | 1 W |
| WS2M, WS2A | 2 W |
| WS3M, WS3A | 3 W |
| WS5M, WS5A | 5 W |
| WS7M, WS7A | 7 W |
| WS8M | 8 W |
| Tolerance | 5 % |
| Operating Temperature | -55 °C to +200 °C |
| Temperature Coefficient | ± 200 ppm/°C |
| Maximum Voltage | $\sqrt{P \cdot R}$ |

Popular Resistance Values

| Code | R Value |
|------|-------------|
| 15R0 | 15 Ω |
| 20R0 | 20 Ω |
| 22R0 | 22 Ω |
| 33R0 | 33 Ω |
| 47R0 | 47 Ω |

| Code | R Value |
|------|---------------|
| 68R0 | 68 Ω |
| 1500 | 150 Ω |
| 1001 | 1K Ω |
| 3301 | 3.3K Ω |

Other E24 resistance values available upon request.

Physical Characteristics

Resistor Low thermal resistant ceramic core
 Lead Wire Tin-plated copper wire
 Coating Material Meets UL 94V-0 requirements

Environmental Characteristics

| Test | Conditions | Specification |
|---------------------------|--|---|
| Short Time Overload | 10 times rated power for 5 seconds. | $\Delta R \leq \pm(5 \% \pm 0.05 \Omega)$ |
| Solderability | 245 ± 3 °C for 2.5 ± 0.5 seconds. | Over 95 % coverage |
| Resistance to Solder Heat | 260 ± 5 °C for 10 ± 1 seconds. | $\Delta R \leq \pm(1 \% + 0.05 \Omega)$ |
| Temperature Cycle | 5 cycles, -55 °C ± 3 °C for 30 minutes, Room temperature for 15 minutes, +155 ± 2 °C for 30 minutes, Room temperature for 15 minutes | $\Delta R \leq \pm(2 \% + 0.05 \Omega)$ |
| Dielectric Strength | Test voltage >500 Vrms for >1 minute. | Pass |
| Insulation Resistance | Test voltage >500 Vrms for 1 minute. | >10 ₉ Ω |
| Load Life Humidity | Rated continuous voltage for 1000 hours, 1.5 hours ON and 0.5 hours OFF at 90~95 % relative humidity and test temperature of 40 °C ± 2 °C. | $\Delta R \leq \pm(5 \% + 0.05 \Omega)$ |
| Load Life | Rated continuous voltage for 1000 hours, 1.5 hours ON and 0.5 hours OFF at a test temperature of 70 °C ± 2 °C. 1000 hours at rated power. | $\Delta R \leq \pm(5 \% + 0.05 \Omega)$ |
| Surge | IEC 61000-4-5 1.2/50 μ s exponential. | $\Delta R \leq \pm(5 \% + 0.05 \Omega)$ |

How to Order

WS 3 M 22R0 J

Product Series _____
 WS = Wirewound, High Surge Withstand

Power Rating _____
 1 = 1 Watt
 2 = 2 Watts
 3 = 3 Watts
 5 = 5 Watts
 7 = 7 Watts
 8 = 8 Watts

Pin Style _____
 A = Axial Standard Version
 M = Axial Miniaturized Version

Resistance Code _____
 • R < 100 ohms:
 "R" represents decimal point
 (example: 22R0 = 22 ohms)
 • R \geq 100 ohms:
 First three digits are significant,
 fourth digit represents number of
 zeros to follow
 (example: 1001 = 1K ohms)

Resistance Tolerance _____
 J = ± 5 %

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

WS Series High Surge Withstand Wirewound Resistor

BOURNS®

Product Dimensions



| Model | Dimensions | | | |
|-------|---|---------------------------------------|---|---|
| | L* | D | W | T |
| WS1M | $\frac{9.5 \pm 1.0}{(.374 \pm .004)}$ | $\frac{4.5 \pm 1.0}{(.177 \pm .004)}$ | $\frac{28.0 \pm 3.0}{(1.102 \pm .118)}$ | $\frac{0.65 \pm 0.05}{(.026 \pm .002)}$ |
| WS1A | $\frac{11.5 \pm 1.0}{(.453 \pm .004)}$ | $\frac{5.0 \pm 1.0}{(.197 \pm .004)}$ | $\frac{28.0 \pm 3.0}{(1.102 \pm .118)}$ | $\frac{0.65 \pm 0.05}{(.026 \pm .002)}$ |
| WS2M | $\frac{11.5 \pm 1.0}{(.453 \pm .004)}$ | $\frac{5.0 \pm 1.0}{(.197 \pm .004)}$ | $\frac{28.0 \pm 3.0}{(1.102 \pm .118)}$ | $\frac{0.65 \pm 0.05}{(.026 \pm .002)}$ |
| WS2A | $\frac{15.5 \pm 1.0}{(.610 \pm .004)}$ | $\frac{5.5 \pm 1.0}{(.217 \pm .004)}$ | $\frac{28.0 \pm 3.0}{(1.102 \pm .118)}$ | $\frac{0.75 \pm 0.05}{(.030 \pm .002)}$ |
| WS3M | $\frac{15.5 \pm 1.0}{(.610 \pm .004)}$ | $\frac{5.5 \pm 1.0}{(.217 \pm .004)}$ | $\frac{28.0 \pm 3.0}{(1.102 \pm .118)}$ | $\frac{0.75 \pm 0.05}{(.030 \pm .002)}$ |
| WS3A | $\frac{17.5 \pm 1.0}{(.689 \pm .004)}$ | $\frac{6.5 \pm 1.0}{(.256 \pm .004)}$ | $\frac{28.0 \pm 3.0}{(1.102 \pm .118)}$ | $\frac{0.75 \pm 0.05}{(.030 \pm .002)}$ |
| WS5M | $\frac{17.5 \pm 1.0}{(.689 \pm .004)}$ | $\frac{6.5 \pm 1.0}{(.256 \pm .004)}$ | $\frac{28.0 \pm 3.0}{(1.102 \pm .118)}$ | $\frac{0.75 \pm 0.05}{(.030 \pm .002)}$ |
| WS5A | $\frac{24.5 \pm 1.0}{(.965 \pm .004)}$ | $\frac{8.5 \pm 1.0}{(.335 \pm .004)}$ | $\frac{38.0 \pm 3.0}{(1.496 \pm .118)}$ | $\frac{0.75 \pm 0.05}{(.030 \pm .002)}$ |
| WS7M | $\frac{24.5 \pm 1.0}{(.965 \pm .004)}$ | $\frac{8.5 \pm 1.0}{(.335 \pm .004)}$ | $\frac{38.0 \pm 3.0}{(1.496 \pm .118)}$ | $\frac{0.75 \pm 0.05}{(.030 \pm .002)}$ |
| WS7A | $\frac{29.5 \pm 1.0}{(1.161 \pm .004)}$ | $\frac{8.5 \pm 1.0}{(.335 \pm .004)}$ | $\frac{38.0 \pm 3.0}{(1.496 \pm .118)}$ | $\frac{0.75 \pm 0.05}{(.030 \pm .002)}$ |
| WS8M | $\frac{29.5 \pm 1.0}{(1.161 \pm .004)}$ | $\frac{8.5 \pm 1.0}{(.335 \pm .004)}$ | $\frac{38.0 \pm 3.0}{(1.496 \pm .118)}$ | $\frac{0.75 \pm 0.05}{(.030 \pm .002)}$ |

Typical Part Marking

Resistors shall be marked with color coding. Colors shall be in accordance with JIS C 0802.



| Color | 1st Band | 2nd Band | Multiplier | Tol. |
|--------|----------|----------|------------|---------|
| Black | 0 | 0 | 1 Ω | |
| Brown | 1 | 1 | 10 Ω | ±1 % |
| Red | 2 | 2 | 100 Ω | ±2 % |
| Orange | 3 | 3 | 1K Ω | |
| Yellow | 4 | 4 | 10K Ω | |
| Green | 5 | 5 | 100K Ω | ±0.5 % |
| Blue | 6 | 6 | 1M Ω | ±0.25 % |
| Violet | 7 | 7 | 10M Ω | ±0.10 % |
| Grey | 8 | 8 | | ±0.05 % |
| White | 9 | 9 | | |
| Gold | | | 0.1 Ω | ±5 % |
| Silver | | | 0.01 Ω | ±10 % |

Power Derating Curve



Specifications are subject to change without notice. The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

WS Series High Surge Withstand Wirewound Resistor

BOURNS®

Packaging Specifications



| Model | O | P | A | B | C | Pkg. Style | Min. Order Qty. (Pcs.) | Pcs./Box |
|------------|-------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|---------------------------------------|------------|------------------------|------------|
| WS1M | $\frac{58 \pm 1}{(2.283 \pm .039)}$ | $\frac{5 \pm 0.3}{(.197 \pm .112)}$ | $\frac{75 \pm 5}{(2.953 \pm .197)}$ | $\frac{70 \pm 5}{(2.756 \pm .197)}$ | $\frac{255 \pm 5}{(10.039 \pm .197)}$ | Ammo Pack | 5,000 | 1,000 pcs. |
| WS1A, WS2M | $\frac{58 \pm 1}{(2.283 \pm .039)}$ | $\frac{5 \pm 0.3}{(.197 \pm .112)}$ | $\frac{80 \pm 5}{(3.150 \pm .197)}$ | $\frac{82 \pm 5}{(3.228 \pm .197)}$ | $\frac{255 \pm 5}{(10.039 \pm .197)}$ | | | |
| WS2A, WS3M | $\frac{65 \pm 5}{(2.559 \pm .197)}$ | $\frac{10 \pm 0.3}{(.393 \pm .112)}$ | $\frac{90 \pm 5}{(3.543 \pm .197)}$ | $\frac{119 \pm 5}{(4.685 \pm .197)}$ | $\frac{255 \pm 5}{(10.039 \pm .197)}$ | | | |
| WS3A, WS5M | $\frac{65 \pm 5}{(2.559 \pm .197)}$ | $\frac{10 \pm 0.3}{(.393 \pm .112)}$ | $\frac{90 \pm 5}{(3.543 \pm .197)}$ | $\frac{88 \pm 5}{(3.465 \pm .197)}$ | $\frac{255 \pm 5}{(10.039 \pm .197)}$ | | | |
| WS5A, WS7M | $\frac{90 \pm 5}{(3.543 \pm .197)}$ | $\frac{10 \pm 0.3}{(.393 \pm .112)}$ | $\frac{115 \pm 5}{(4.528 \pm .197)}$ | $\frac{124 \pm 5}{(4.882 \pm .197)}$ | $\frac{500 \pm 5}{(19.685 \pm .197)}$ | | 2,000 | 500 pcs. |

For WS7A and WS8M packaging specifications, please contact factory.

Surge Performance - 1.2/50 μ s Pulse Withstanding Curve



BOURNS®

Asia-Pacific:

Tel: +886-2 2562-4117
Fax: +886-2 2562-4116

EMEA:

Tel: +36 88 520 390
Fax: +36 88 520 211

The Americas:

Tel: +1-951 781-5500
Fax: +1-951 781-5700

www.bourns.com

03/15

Specifications are subject to change without notice. The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331