260-8Xi has all of the circuit protection features and advantages for which the 260 Series is famous...

And even more features than its predecessors. The yellow case color for enhanced visibility and user safety awareness is the trademark of the 260-8Xi. The durable ABS plastic case also provides high-impact resistance and increased drop protection in the toughest environments.

- *Instant Trend Information for Quick Positive "Yes/No" Checks*
- *Zero RFI Emission*
- *Audible Continuity Check*
- *Resettable Overload Circuit Protection Relay*
- *1.5 V and 9 V Batteries and Probe Test Leads With Alligator Clips*
- *Mirrored Scale for Parallax Reduction*



Specifications

DC VOLTAGE

Ranges	Accuracy	Sensitivity
250mV, 1V, 2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	2% of full scale	20KΩ per volt

AC VOLTAGE

Ranges	Accuracy	Sensitivity
2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	3% of full scale	5KΩ per volt

DECIBEL

5 Ranges: -20 to +50dB
Reference: 0dB= 1mW into 600Ω

AC CURRENT

Up to 250 AC amperes with AC Amp-Clamp Adapter Accessory 00541.

DC CURRENT

Ranges	Accuracy	Voltage Drop: (Nominal)
50µA, 1mA, 10mA, 100mA, 500mA, 10A	1.5% full scale 50 µA 2.0% of full scale, all others	250mV on 50 µA/1mA; 255mV on 10mA/10A; 300mV on 100mA; 500mV on 500mA

Specifications (Continued)

RESISTANCE

Ranges	Accuracy	Maximum Indication
Rx1		0-2KΩ
Rx100	2.5° of arc on Rx1	0-200KΩ
Rx10K	2.0° of arc on all others	0-20MΩ

BATTERIES: 1.5 V D, 9V (NEDA No. 13F, 1604A)
FUSE: F1 1A, 250V, type 3AG, quick acting Littelfuse® Type 312001; F2 2A, 600V Littelfuse® Type BLS or 2A 600V, Bussman® Type BBS.
SIZE: 5 1/4" x 7" x 3 1/8" (13.34 x 17.78 x 7.94 cm)
WEIGHT: 2 1/4 lbs. (1.02 Kg)
RATED CIRCUIT-TO-GROUND VOLTAGE: 1000V AC/DC Max

Specifications subject to change without notice.

Ordering Information

VOM	Catalog No.	ACCESSORIES	Catalog No.	ACCESSORIES	Catalog No.
260-8Xi, Yellow	12395	Probe Leads w/Screw-on Alligator Clip	00125	Case, Yellow Padded Polyester	00832
260-8XPi, Protected, Yellow	12396	Probe Set, Replaceable Tip, Banana	07538	Case, Black Padded Polyester	00834
		Lead Set, Alligator, Banana	07500	Case, Hard Leatherette Front Load	00805
		Clip Set, Alligator, Screw-On	00425	Case, Molded Plastic	45028
		150-2 Amp Clamp Adapter, AC	00541		

Additional accessories are on pages 22-24.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331