

## Aluminum Capacitors +85 °C, Large Can



## FEATURES

- Useful life: 2000 h at +85 °C
- The industry standard for large can aluminum capacitors
- Ideal for high wattage power supplies and energy storage applications
- Capacitance values to 2.2 F
- Largest CV available
- Highest voltage available
- Screw terminal
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT

## QUICK REFERENCE DATA

| DESCRIPTION                                 | VALUE                                                                                                                           |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Nominal case size<br>Ø D x L in inches (mm) | 1.375 x 1.625 (35.0 x 41.3)<br>to 3.00 x 8.675 (76.2 x 220.3)                                                                   |
| Operating temperature                       | -40 °C to +85 °C                                                                                                                |
| Rated capacitance<br>range, C <sub>R</sub>  | 100 µF to 2.2 F                                                                                                                 |
| Tolerance on C <sub>R</sub>                 | -10 % to 50 %                                                                                                                   |
| Rated voltage range, U <sub>R</sub>         | 6.3 WV <sub>DC</sub> to 450 WV <sub>DC</sub>                                                                                    |
| Termination                                 | Screw thread                                                                                                                    |
| Life validation test<br>at 85 °C            | 2000 h: ΔCAP ≤ 15 % from initial<br>measurement.<br>ΔESR ≤ 1.5 x initial specified limit<br>ΔDCL ≤ initial specified limit      |
| Shelf life at 85 °C                         | 500 h: ΔCAP ≤ 15 % from initial<br>measurement.<br>ΔESR ≤ 1.2 x initial specified limit.<br>ΔDCL ≤ 2 x initial specified limit. |
| DC leakage current                          | $I = k \sqrt{CV}$<br>k = 4.0 at +25 °C; k = 32.0 at +85 °C<br>I in µA, C in µF, V in Volts                                      |

## RIPPLE CURRENT MULTIPLIERS

| TEMPERATURE         |             |  |  |
|---------------------|-------------|--|--|
| AMBIENT TEMPERATURE | MULTIPLIERS |  |  |
| +85 °C              | 1.0         |  |  |
| +75 °C              | 1.4         |  |  |
| +65 °C              | 1.7         |  |  |
| +55 °C and below    | 2.0         |  |  |

| FREQUENCY (Hz)         |     |      |             |
|------------------------|-----|------|-------------|
| RATED WV <sub>DC</sub> | 120 | 400  | 1000 AND UP |
| 0 to 50                | 1.0 | 1.05 | 1.10        |
| 51 to 100              | 1.0 | 1.10 | 1.15        |
| 150 to 300             | 1.0 | 1.15 | 1.25        |
| 301 to 450             | 1.0 | 1.20 | 1.30        |

**DIMENSIONS** in inches (millimeters)

| LARGE CAN CAPACITORS |                    |                    |                        |               |                        |                                     |                       |
|----------------------|--------------------|--------------------|------------------------|---------------|------------------------|-------------------------------------|-----------------------|
| CASE CODE            | NOMINAL            |                    | WITH INSULATION SLEEVE |               |                        | TERMINAL SPACING<br>M ± 0.016 (0.4) | TYPICAL WEIGHT<br>(g) |
|                      | D<br>± 0.032 (0.8) | L<br>± 0.063 (1.6) | D<br>(Max.)            | L<br>(Max.)   | P TERMINAL<br>H (Max.) |                                     |                       |
| AN                   | 1.375 (35.0)       | 1.625 (41.0)       | 1.453 (36.9)           | 1.750 (44.5)  | 1.849 (47.0)           | 0.500 (12.7)                        | 43.0                  |
| AY                   | 1.375 (35.0)       | 1.875 (48.0)       | 1.453 (36.9)           | 2.000 (50.8)  | 1.099 (53.3)           | 0.500 (12.7)                        | 54.0                  |
| AA                   | 1.375 (35.0)       | 2.125 (54.0)       | 1.453 (36.9)           | 2.250 (57.2)  | 1.349 (59.7)           | 0.500 (12.7)                        | 63.0                  |
| AM                   | 1.375 (35.0)       | 2.625 (67.0)       | 1.453 (36.9)           | 2.750 (69.9)  | 1.849 (72.4)           | 0.500 (12.7)                        | 82.0                  |
| AB                   | 1.375 (35.0)       | 3.125 (79.0)       | 1.453 (36.9)           | 3.250 (82.6)  | 1.349 (85.1)           | 0.500 (12.7)                        | 105.0                 |
| AL                   | 1.375 (35.0)       | 3.625 (92.0)       | 1.453 (36.9)           | 3.750 (95.3)  | 1.849 (97.8)           | 0.500 (12.7)                        | 122.0                 |
| AC                   | 1.375 (35.0)       | 4.125 (105.0)      | 1.453 (36.9)           | 4.250 (108.0) | 1.349 (110.5)          | 0.500 (12.7)                        | 129.0                 |
| AD                   | 1.375 (35.0)       | 4.625 (117.0)      | 1.453 (36.9)           | 4.750 (120.7) | 1.849 (123.2)          | 0.500 (12.7)                        | 162.0                 |
| AE                   | 1.375 (35.0)       | 5.125 (130.0)      | 1.453 (36.9)           | 5.250 (133.4) | 1.349 (125.9)          | 0.500 (12.7)                        | 179.0                 |
| AF                   | 1.375 (35.0)       | 5.625 (143.0)      | 1.453 (36.9)           | 5.750 (146.1) | 1.849 (148.6)          | 0.500 (12.7)                        | 201.0                 |
| EN                   | 1.750 (44.0)       | 1.625 (41.0)       | 1.828 (46.4)           | 1.750 (44.5)  | 1.849 (47.0)           | 0.750 (19.1)                        | 71.0                  |

**DIMENSIONS** in inches (millimeters)


| LARGE CAN CAPACITORS |                    |                    |                        |               |                        |                                     |                       |
|----------------------|--------------------|--------------------|------------------------|---------------|------------------------|-------------------------------------|-----------------------|
| CASE CODE            | NOMINAL            |                    | WITH INSULATION SLEEVE |               |                        | TERMINAL SPACING<br>M ± 0.016 (0.4) | TYPICAL WEIGHT<br>(g) |
|                      | D<br>± 0.032 (0.8) | L<br>± 0.063 (1.6) | D<br>(Max.)            | L<br>(Max.)   | P TERMINAL<br>H (Max.) |                                     |                       |
| EY                   | 1.750 (44.0)       | 1.875 (48.0)       | 1.828 (46.4)           | 2.000 (50.8)  | 2.099 (53.3)           | 0.750 (19.1)                        | 88.0                  |
| EA                   | 1.750 (44.0)       | 2.125 (54.0)       | 1.828 (46.4)           | 2.250 (57.2)  | 2.349 (59.7)           | 0.750 (19.1)                        | 102.0                 |
| EM                   | 1.750 (44.0)       | 2.625 (67.0)       | 1.828 (46.4)           | 2.750 (69.9)  | 2.849 (72.4)           | 0.750 (19.1)                        | 133.0                 |
| EB                   | 1.750 (44.0)       | 3.125 (79.0)       | 1.828 (46.4)           | 3.250 (82.6)  | 3.349 (85.1)           | 0.750 (19.1)                        | 167.0                 |
| EL                   | 1.750 (44.0)       | 3.625 (92.0)       | 1.828 (46.4)           | 3.750 (95.3)  | 3.849 (97.8)           | 0.750 (19.1)                        | 198.0                 |
| EC                   | 1.750 (44.0)       | 4.125 (105.0)      | 1.828 (46.4)           | 4.250 (108.0) | 4.349 (110.5)          | 0.750 (19.1)                        | 230.0                 |
| ED                   | 1.750 (44.0)       | 4.625 (117.0)      | 1.828 (46.4)           | 4.750 (120.7) | 4.849 (123.2)          | 0.750 (19.1)                        | 252.0                 |
| EE                   | 1.750 (44.0)       | 5.125 (130.0)      | 1.828 (46.4)           | 5.250 (133.4) | 5.349 (135.9)          | 0.750 (19.1)                        | 269.0                 |
| EF                   | 1.750 (44.0)       | 5.625 (143.0)      | 1.828 (46.4)           | 5.750 (146.1) | 5.849 (148.6)          | 0.750 (19.1)                        | 318.0                 |
| BY                   | 2.000 (51.0)       | 1.875 (48.0)       | 2.078 (52.8)           | 2.000 (50.8)  | 2.099 (53.3)           | 0.875 (22.2)                        | 113.0                 |
| BA                   | 2.000 (51.0)       | 2.125 (54.0)       | 2.078 (52.8)           | 2.250 (57.2)  | 2.349 (59.7)           | 0.875 (22.2)                        | 133.0                 |
| BM                   | 2.000 (51.0)       | 2.625 (67.0)       | 2.078 (52.8)           | 2.750 (69.9)  | 2.849 (72.4)           | 0.875 (22.2)                        | 176.0                 |
| BB                   | 2.000 (51.0)       | 3.125 (79.0)       | 2.078 (52.8)           | 3.250 (82.6)  | 3.349 (85.1)           | 0.875 (22.2)                        | 213.0                 |
| BL                   | 2.000 (51.0)       | 3.625 (92.0)       | 2.078 (52.8)           | 3.750 (95.3)  | 3.849 (97.8)           | 0.875 (22.2)                        | 261.0                 |
| BC                   | 2.000 (51.0)       | 4.125 (105.0)      | 2.078 (52.8)           | 4.250 (108.0) | 4.349 (110.5)          | 0.875 (22.2)                        | 381.0                 |
| BD                   | 2.000 (51.0)       | 4.625 (117.0)      | 2.078 (52.8)           | 4.750 (120.7) | 4.849 (123.2)          | 0.875 (22.2)                        | 326.0                 |
| BE                   | 2.000 (51.0)       | 5.125 (130.0)      | 2.078 (52.8)           | 5.250 (133.4) | 5.349 (135.9)          | 0.875 (22.2)                        | 337.0                 |
| BF                   | 2.000 (51.0)       | 5.625 (143.0)      | 2.078 (52.8)           | 5.750 (146.1) | 5.849 (148.6)          | 0.875 (22.2)                        | 408.0                 |
| CB                   | 2.500 (64.0)       | 3.125 (79.0)       | 2.578 (65.5)           | 3.250 (82.6)  | n/a                    | 1.125 (28.6)                        | 329.0                 |
| CL                   | 2.500 (64.0)       | 3.625 (92.0)       | 2.578 (65.5)           | 3.750 (95.3)  | n/a                    | 1.125 (28.6)                        | 400.0                 |
| CC                   | 2.500 (64.0)       | 4.125 (105.0)      | 2.578 (65.5)           | 4.250 (108.0) | n/a                    | 1.125 (28.6)                        | 473.0                 |
| CD                   | 2.500 (64.0)       | 4.625 (117.0)      | 2.578 (65.5)           | 4.750 (120.7) | n/a                    | 1.125 (28.6)                        | 562.0                 |
| CE                   | 2.500 (64.0)       | 5.125 (130.0)      | 2.578 (65.5)           | 5.250 (133.4) | n/a                    | 1.125 (28.6)                        | 607.0                 |
| CF                   | 2.500 (64.0)       | 5.625 (143.0)      | 2.578 (65.5)           | 5.750 (146.1) | n/a                    | 1.125 (28.6)                        | 675.0                 |
| DB                   | 3.000 (76.0)       | 3.125 (79.0)       | 3.078 (78.2)           | 3.250 (82.6)  | n/a                    | 1.250 (31.8)                        | 496.0                 |
| DL                   | 3.000 (76.0)       | 3.625 (92.0)       | 3.078 (78.2)           | 3.750 (95.3)  | n/a                    | 1.250 (31.8)                        | 598.0                 |
| DC                   | 3.000 (76.0)       | 4.125 (105.0)      | 3.078 (78.2)           | 4.250 (108.0) | n/a                    | 1.250 (31.8)                        | 700.0                 |
| DD                   | 3.000 (76.0)       | 4.625 (117.0)      | 3.078 (78.2)           | 4.750 (120.7) | n/a                    | 1.250 (31.8)                        | 802.0                 |
| DE                   | 3.000 (76.0)       | 5.125 (130.0)      | 3.078 (78.2)           | 5.250 (133.4) | n/a                    | 1.250 (31.8)                        | 944.0                 |
| DF                   | 3.000 (76.0)       | 5.625 (143.0)      | 3.078 (78.2)           | 5.750 (146.1) | n/a                    | 1.250 (31.8)                        | 1004.0                |
| DJ                   | 3.000 (76.0)       | 8.625 (219.0)      | 3.078 (78.2)           | 8.750 (222.3) | n/a                    | 1.250 (31.8)                        | 1403.0                |

**DIMENSIONS** in inches (millimeters)

| BRACKETS (RoHS COMPLIANT)        |              |              |                           |                              |                              |                         |
|----------------------------------|--------------|--------------|---------------------------|------------------------------|------------------------------|-------------------------|
| TYPE                             | PART NUMBER  | A            | B                         | C                            | FIGURE NUMBER                |                         |
| 2 feet                           | 1245860035A  | 1.375 (34.9) | 1.781 (45.2)              | 2.218 (56.3)                 | 1                            |                         |
| 3 feet                           | 1245860036A  | 2.000 (50.8) | 2.500 (63.5)              | 2.875 (73.0)                 | 2                            |                         |
| 3 feet                           | 1245860037A  | 2.500 (63.5) | 3.000 (76.2)              | 3.375 (85.7)                 | 2                            |                         |
| 3 feet                           | 1245860038A  | 3.000 (76.2) | 3.500 (88.9)              | 3.875 (98.4)                 | 2                            |                         |
| SCREW INSERT TERMINAL DIMENSIONS |              |              |                           |                              |                              |                         |
| TERMINAL CODE                    | THREAD       | THREAD DEPTH | HEIGHT<br>J ± 0.032 (0.8) | DIAMETER<br>S ± 0.010 (0.25) | DIAMETER<br>T ± 0.010 (0.25) | NOTES                   |
| A                                | 10-32 NF-28  | 0.219 (5.6)  | 0.063 (1.6)               | 0.313 (8.0)                  | 0.438 (11.1)                 | All cases codes         |
| B                                | 10-32 NF-28  | 0.375 (9.5)  | 0.250 (6.4)               | 0.313 (8.0)                  | 0.438 (11.1)                 | All cases codes         |
| D                                | 1/4-28 NF-28 | 0.344 (8.7)  | 0.093 (2.4)               | 0.688 (17.5)                 | -                            | C and D dia. codes only |

## DIMENSIONS AND AVAILABLE FORMS

### Screw Insert Terminals



### ORDERING EXAMPLE

Electrolytic capacitor 36DY series: 36DY 683 F 6R3 AA 2 A

| DESCRIPTION |                                                  |
|-------------|--------------------------------------------------|
| CODE        | EXPLANATION                                      |
| 36DY        | Product type                                     |
| 683         | Capacitance value (68 000 $\mu$ F)               |
| F           | Tolerance (G = -10 % / +75 %; F = -10 % / +50 %) |
| 6R3         | Voltage rating at 85 °C (6.3 V)                  |
| AA          | Can size (see Dimensions table)                  |
| 2           | PVC insulating sleeve                            |
| A           | Terminal code (low insert 10-32 screw thread)    |

**ELECTRICAL DATA AND ORDERING INFORMATION**

| CAPACITANCE<br>( $\mu$ F)                         | PART NUMBER     | NOMINAL CASE SIZE<br>D x L   | MAX. ESR AT 25 °C<br>(m $\Omega$ )<br>120 Hz | MAX. RIPPLE AT +85 °C<br>(A)<br>120 Hz |
|---------------------------------------------------|-----------------|------------------------------|----------------------------------------------|----------------------------------------|
| <b>6.3 WV<sub>DC</sub> AT +85 °C, SURGE = 8 V</b> |                 |                              |                                              |                                        |
| 68 000.0                                          | 36DY683F6R3AA2A | 1.375 x 2.125 (35.0 x 54.0)  | 32.0                                         | 5.92                                   |
| 120 000.0                                         | 36DY124F6R3AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 20.0                                         | 8.70                                   |
| 220 000.0                                         | 36DY224F6R3BB2A | 2.000 x 3.125 (51.0 x 79.0)  | 11.2                                         | 14.4                                   |
| 560 000.0                                         | 36DY564F6R3BF2A | 2.000 x 5.625 (51.0 x 143.0) | 6.6                                          | 23.8                                   |
| 820 000.0                                         | 36DY824F6R3CF2A | 2.500 x 5.625 (64.0 x 143.0) | 4.1                                          | 34.4                                   |
| 1 000 000.0                                       | 36DY105F6R3DD2A | 3.000 x 4.625 (76.0 x 117.0) | 14.5                                         | 34.0                                   |
| <b>10 WV<sub>DC</sub> AT +85 °C, SURGE = 12 V</b> |                 |                              |                                              |                                        |
| 82 000.0                                          | 36DY823F010AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 19.8                                         | 8.65                                   |
| 150 000.0                                         | 36DY154F010AD2A | 1.375 x 4.625 (35.0 x 117.0) | 14.0                                         | 12.2                                   |
| 220 000.0                                         | 36DY224F010BL2A | 2.000 x 3.625 (51.0 x 92.0)  | 9.6                                          | 16.5                                   |
| 390 000.0                                         | 36DY394F010BF2A | 2.000 x 5.625 (51.0 x 143.0) | 6.7                                          | 23.7                                   |
| 470 000.0                                         | 36DY474F010CC2A | 2.500 x 4.125 (64.0 x 105.0) | 5.0                                          | 27.6                                   |
| 680 000.0                                         | 36DY684F010DC2A | 3.000 x 4.125 (76.0 x 105.0) | 5.0                                          | 30.9                                   |
| <b>15 WV<sub>DC</sub> AT +85 °C, SURGE = 18 V</b> |                 |                              |                                              |                                        |
| 47 000.0                                          | 36DY473F015AM2A | 1.375 x 2.625 (35.0 x 67.0)  | 25.0                                         | 7.19                                   |
| 68 000.0                                          | 36DY683F015AL2A | 1.375 x 3.625 (35.0 x 92.0)  | 17.5                                         | 9.79                                   |
| 100 000.0                                         | 36DY104F015AD2A | 1.375 x 4.625 (35.0 x 117.0) | 14.2                                         | 12.1                                   |
| 56 000.0                                          | 36DY563F015BA2A | 2.000 x 2.125 (51.0 x 54.0)  | 20.0                                         | 9.40                                   |
| 100 000.0                                         | 36DY104F015BB2A | 2.000 x 3.125 (51.0 x 79.0)  | 11.6                                         | 14.2                                   |
| 150 000.0                                         | 36DY154F015BC2A | 2.000 x 4.125 (51.0 x 105.0) | 8.7                                          | 18.3                                   |
| 220 000.0                                         | 36DY224F015BF2A | 2.000 x 5.625 (51.0 x 143.0) | 6.7                                          | 23.6                                   |
| 470 000.0                                         | 36DY474F015CF2A | 2.500 x 5.625 (64.0 x 143.0) | 4.2                                          | 34.0                                   |
| 680 000.0                                         | 36DY684F015DF2A | 3.000 x 5.625 (76.0 x 143.0) | 4.1                                          | 38.4                                   |
| <b>25 WV<sub>DC</sub> AT +85 °C, SURGE = 30 V</b> |                 |                              |                                              |                                        |
| 18 000.0                                          | 36DY183F025AM2A | 1.375 x 2.625 (35.0 x 67.0)  | 25.0                                         | 7.12                                   |
| 22 000.0                                          | 36DY223F025AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 21.0                                         | 8.42                                   |
| 47 000.0                                          | 36DY473F025AF2A | 1.375 x 5.625 (35.0 x 143.0) | 12.6                                         | 14.0                                   |
| 33 000.0                                          | 36DY333F025BM2A | 2.000 x 2.625 (51.0 x 67.0)  | 15.4                                         | 11.5                                   |
| 47 000.0                                          | 36DY473F025BB2A | 2.000 x 3.125 (51.0 x 79.0)  | 12.3                                         | 13.8                                   |
| 100 000.0                                         | 36DY104F025BF2A | 2.000 x 5.625 (51.0 x 143.0) | 7.2                                          | 22.8                                   |
| 120 000.0                                         | 36DY124F025CC2A | 2.500 x 4.125 (64.0 x 105.0) | 6.7                                          | 23.8                                   |
| 220 000.0                                         | 36DY224F025DE2A | 3.000 x 5.125 (76.0 x 130.0) | 4.5                                          | 35.3                                   |
| 390 000.0                                         | 36DY394F025DJ2A | 3.000 x 8.625 (76.0 x 219.0) | 3.5                                          | 49.5                                   |
| <b>40 WV<sub>DC</sub> AT +85 °C, SURGE = 50 V</b> |                 |                              |                                              |                                        |
| 4700.0                                            | 36DY472F040AN2A | 1.375 x 1.625 (35.0 x 41.0)  | 59.0                                         | 3.89                                   |
| 10 000.0                                          | 36DY103F040AM2A | 1.375 x 2.625 (35.0 x 67.0)  | 28.0                                         | 6.84                                   |
| 12 000.0                                          | 36DY123F040AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 23.0                                         | 8.10                                   |
| 15 000.0                                          | 36DY153F040AL2A | 1.375 x 3.625 (35.0 x 92.0)  | 19.4                                         | 9.30                                   |
| 10 000.0                                          | 36DY103F040BY2A | 2.000 x 1.875 (51.0 x 48.0)  | 30.0                                         | 7.40                                   |
| 27 000.0                                          | 36DY273F040BB2A | 2.000 x 3.125 (51.0 x 79.0)  | 12.8                                         | 13.5                                   |
| 33 000.0                                          | 36DY333F040BL2A | 2.000 x 3.625 (51.0 x 92.0)  | 10.9                                         | 15.5                                   |
| 39 000.0                                          | 36DY393F040BC2A | 2.000 x 4.125 (51.0 x 105.0) | 9.6                                          | 17.4                                   |
| 47 000.0                                          | 36DY473F040CB2A | 2.500 x 3.125 (64.0 x 79.0)  | 9.1                                          | 18.4                                   |
| 100 000.0                                         | 36DY104F040DC2A | 3.000 x 4.125 (76.0 x 105.0) | 5.4                                          | 29.7                                   |
| 8200.0                                            | 36DY822F040AM2A | 1.375 x 2.625 (35.0 x 67.0)  | 29.0                                         | 6.66                                   |
| 10 000.0                                          | 36DY103F040AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 24.0                                         | 7.79                                   |
| 15 000.0                                          | 36DY153F040AC2A | 1.375 x 4.125 (35.0 x 105.0) | 18.2                                         | 10.1                                   |

**ELECTRICAL DATA AND ORDERING INFORMATION**

| CAPACITANCE<br>( $\mu$ F)                           | PART NUMBER     | NOMINAL CASE SIZE<br>D x L   | MAX. ESR AT 25 °C<br>(m $\Omega$ )<br>120 Hz | MAX. RIPPLE AT +85 °C<br>(A)<br>120 Hz |
|-----------------------------------------------------|-----------------|------------------------------|----------------------------------------------|----------------------------------------|
| <b>50 WV<sub>DC</sub> AT +85 °C, SURGE = 65 V</b>   |                 |                              |                                              |                                        |
| 5600.0                                              | 36DY562F050AA2A | 1.375 x 2.125 (35.0 x 54.0)  | 40.0                                         | 5.25                                   |
| 8200.0                                              | 36DY822F050AM2A | 1.375 x 2.625 (35.0 x 67.0)  | 29.0                                         | 6.66                                   |
| 10 000.0                                            | 36DY103F050AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 24.0                                         | 8.60                                   |
| 47 000.0                                            | 36DY473F050BF2A | 2.000 x 5.625 (51.0 x 143.0) | 7.7                                          | 22.1                                   |
| 100 000.0                                           | 36DY104F050DE2A | 3.000 x 5.125 (76.0 x 130.0) | 4.8                                          | 34.2                                   |
| 180 000.0                                           | 36DY184F050DJ2A | 3.000 x 8.625 (76.0 x 219.0) | 3.6                                          | 48.8                                   |
| <b>60 WV<sub>DC</sub> AT +85 °C, SURGE = 75 V</b>   |                 |                              |                                              |                                        |
| 2700.0                                              | 36DY272F060AN2A | 1.375 x 1.625 (35.0 x 41.0)  | 69.0                                         | 3.62                                   |
| 4700.0                                              | 36DY472F060AA2A | 1.375 x 2.125 (35.0 x 54.0)  | 42.0                                         | 5.10                                   |
| 8200.0                                              | 36DY822F060AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 25.0                                         | 7.72                                   |
| 10 000.0                                            | 36DY103F060AL2A | 1.375 x 3.625 (35.0 x 92.0)  | 22.0                                         | 8.75                                   |
| 15 000.0                                            | 36DY153F060BB2A | 2.000 x 3.125 (51.0 x 79.0)  | 13.9                                         | 13.0                                   |
| 22 000.0                                            | 36DY223F060BL2A | 2.000 x 3.625 (51.0 x 92.0)  | 11.7                                         | 15.0                                   |
| 47 000.0                                            | 36DY473F060CD2A | 2.500 x 4.625 (64.0 x 117.0) | 6.6                                          | 25.1                                   |
| 100 000.0                                           | 36DY104F060DF2A | 3.000 x 5.625 (76.0 x 143.0) | 4.5                                          | 36.7                                   |
| <b>75 WV<sub>DC</sub> AT +85 °C, SURGE = 95 V</b>   |                 |                              |                                              |                                        |
| 1800.0                                              | 36DY182F075AN2A | 1.375 x 1.625 (35.0 x 41.0)  | 104.0                                        | 2.95                                   |
| 3300.0                                              | 36DY332F075AA2A | 1.375 x 2.125 (35.0 x 54.0)  | 62.0                                         | 4.19                                   |
| 5600.0                                              | 36DY562F075AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 36.0                                         | 6.45                                   |
| 6800.0                                              | 36DY682F075AL2A | 1.375 x 3.625 (35.0 x 92.0)  | 30.0                                         | 7.50                                   |
| 10 000.0                                            | 36DY103F075AD2A | 1.375 x 4.625 (35.0 x 117.0) | 24.0                                         | 9.26                                   |
| 12 000.0                                            | 36DY123F075BB2A | 2.000 x 3.125 (51.0 x 79.0)  | 18.8                                         | 11.1                                   |
| 18 000.0                                            | 36DY183F075BC2A | 2.000 x 4.125 (51.0 x 105.0) | 13.7                                         | 14.5                                   |
| 47 000.0                                            | 36DY473F075CF2A | 2.500 x 5.625 (64.0 x 143.0) | 6.7                                          | 26.9                                   |
| 47 000.0                                            | 36DY473F075DC2A | 3.000 x 4.125 (76.0 x 105.0) | 8.9                                          | 23.2                                   |
| 120 000.0                                           | 36DY124F075DJ2A | 3.000 x 8.625 (76.0 x 219.0) | 5.0                                          | 41.5                                   |
| <b>100 WV<sub>DC</sub> AT +85 °C, SURGE = 125 V</b> |                 |                              |                                              |                                        |
| 1800.0                                              | 36DY182F100AM2A | 1.375 x 2.625 (35.0 x 67.0)  | 56.0                                         | 4.82                                   |
| 4700.0                                              | 36DY472F100AC2A | 1.375 x 4.125 (35.0 x 105.0) | 32.0                                         | 7.68                                   |
| 4700.0                                              | 36DY472F100BM2A | 2.000 x 2.625 (51.0 x 67.0)  | 30.0                                         | 8.29                                   |
| 10 000.0                                            | 36DY103F100BC2A | 2.000 x 4.125 (51.0 x 105.0) | 16.3                                         | 13.3                                   |
| 10 000.0                                            | 36DY103F100CB2A | 2.500 x 3.125 (64.0 x 79.0)  | 14.8                                         | 14.5                                   |
| 18 000.0                                            | 36DY183F100DL2A | 3.000 x 3.625 (76.0 x 92.0)  | 11.2                                         | 19.7                                   |
| 33 000.0                                            | 36DY333F100DE2A | 3.000 x 5.125 (76.0 x 130.0) | 7.9                                          | 26.7                                   |
| <b>150 WV<sub>DC</sub> AT +85 °C, SURGE = 175 V</b> |                 |                              |                                              |                                        |
| 2700.0                                              | 36DY272F150AF2A | 1.375 x 5.625 (35.0 x 143.0) | 35.0                                         | 6.84                                   |
| 2200.0                                              | 36DY222F150BB2A | 2.000 x 3.125 (51.0 x 79.0)  | 57.0                                         | 5.22                                   |
| 5600.0                                              | 36DY562F150BF2A | 2.000 x 5.625 (51.0 x 143.0) | 22.0                                         | 10.66                                  |
| 10 000.0                                            | 36DY103F150CF2A | 2.500 x 5.625 (64.0 x 143.0) | 12.0                                         | 16.43                                  |
| 10 000.0                                            | 36DY103F150DC2A | 3.000 x 4.125 (76.0 x 105.0) | 17.0                                         | 13.68                                  |
| <b>200 WV<sub>DC</sub> AT +85 °C, SURGE = 250 V</b> |                 |                              |                                              |                                        |
| 1000.0                                              | 36DY102F200AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 84.0                                         | 1.5                                    |
| 1500.0                                              | 36DY152F200BM2A | 2.000 x 2.625 (51.0 x 67.0)  | 72.0                                         | 4.36                                   |
| 2200.0                                              | 36DY222F200BL2A | 2.000 x 3.625 (51.0 x 92.0)  | 49.0                                         | 5.97                                   |
| 2700.0                                              | 36DY272F200BC2A | 2.000 x 4.125 (51.0 x 105.0) | 40.0                                         | 6.95                                   |
| 3300.0                                              | 36DY332F200CB2A | 2.500 x 3.125 (64.0 x 79.0)  | 32.0                                         | 8.03                                   |
| 4700.0                                              | 36DY472F200CC2A | 2.500 x 4.125 (64.0 x 105.0) | 22.0                                         | 10.73                                  |
| 10 000.0                                            | 36DY103F200DE2A | 3.000 x 5.125 (76.0 x 130.0) | 14.0                                         | 16.36                                  |

**ELECTRICAL DATA AND ORDERING INFORMATION**

| CAPACITANCE<br>( $\mu$ F)                           | PART NUMBER     | NOMINAL CASE SIZE<br>D x L   | MAX. ESR AT 25 °C<br>(m $\Omega$ )<br>120 Hz | MAX. RIPPLE AT +85 °C<br>(A)<br>120 Hz |
|-----------------------------------------------------|-----------------|------------------------------|----------------------------------------------|----------------------------------------|
| <b>250 WV<sub>DC</sub> AT +85 °C, SURGE = 300 V</b> |                 |                              |                                              |                                        |
| 560.0                                               | 36DY561F250AM2A | 1.375 x 2.625 (35.0 x 67.0)  | 132.0                                        | 2.55                                   |
| 1000.0                                              | 36DY102F250AL2A | 1.375 x 3.625 (35.0 x 92.0)  | 74.0                                         | 3.89                                   |
| 2700.0                                              | 36DY272F250BD2A | 2.000 x 4.625 (51.0 x 117.0) | 34.0                                         | 7.90                                   |
| 3300.0                                              | 36DY332F250BF2A | 2.000 x 5.625 (51.0 x 143.0) | 29.0                                         | 9.44                                   |
| 2700.0                                              | 36DY272F250CB2A | 2.500 x 3.125 (64.0 x 79.0)  | 34.0                                         | 7.79                                   |
| 4700.0                                              | 36DY472F250DL2A | 3.000 x 3.625 (76.0 x 92.0)  | 24.0                                         | 10.99                                  |
| 10 000.0                                            | 36DY103F250DF2A | 3.000 x 5.625 (76.0 x 143.0) | 11.0                                         | 19.14                                  |
| <b>350 WV<sub>DC</sub> AT +85 °C, SURGE = 400 V</b> |                 |                              |                                              |                                        |
| 470.0                                               | 36DY471F350AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 272.0                                        | 1.91                                   |
| 1000.0                                              | 36DY102F350AF2A | 1.375 x 5.625 (35.0 x 143.0) | 128.0                                        | 3.58                                   |
| 1000.0                                              | 36DY102F350BL2A | 2.000 x 3.625 (51.0 x 92.0)  | 136.0                                        | 3.58                                   |
| 1800.0                                              | 36DY182F350BF2A | 2.000 x 5.625 (51.0 x 143.0) | 76.0                                         | 5.73                                   |
| 3300.0                                              | 36DY332F350DC2A | 3.000 x 4.125 (76.0 x 105.0) | 44.0                                         | 8.50                                   |
| 4700.0                                              | 36DY472F350DE2A | 3.000 x 5.125 (76.0 x 130.0) | 31.0                                         | 10.99                                  |
| <b>400 WV<sub>DC</sub> AT +85 °C, SURGE = 450 V</b> |                 |                              |                                              |                                        |
| 270.0                                               | 36DY271F400AM2A | 1.375 x 2.625 (35.0 x 67.0)  | 429.0                                        | 1.41                                   |
| 680.0                                               | 36DY681F400AE2A | 1.375 x 5.125 (35.0 x 130.0) | 170.0                                        | 2.98                                   |
| 1000.0                                              | 36DY102F400BC2A | 2.000 x 4.125 (51.0 x 105.0) | 123.0                                        | 3.96                                   |
| 2200.0                                              | 36DY222F400CD2A | 2.500 x 4.625 (64.0 x 117.0) | 55.0                                         | 7.09                                   |
| 2700.0                                              | 36DY272F400DC2A | 3.000 x 4.125 (76.0 x 105.0) | 48.0                                         | 8.14                                   |
| 6800.0                                              | 36DY682F400DJ2A | 3.000 x 8.625 (76.0 x 219.0) | 19.0                                         | 17.36                                  |
| <b>450 WV<sub>DC</sub> AT +85 °C, SURGE = 525 V</b> |                 |                              |                                              |                                        |
| 330.0                                               | 36DY331F450AB2A | 1.375 x 3.125 (35.0 x 79.0)  | 317.0                                        | 1.77                                   |
| 680.0                                               | 36DY681F450AE2A | 1.375 x 5.125 (35.0 x 130.0) | 164.0                                        | 3.13                                   |
| 1000.0                                              | 36DY102F450BC2A | 2.000 x 4.125 (51.0 x 105.0) | 113.0                                        | 4.13                                   |
| 2700.0                                              | 36DY272F450CF2A | 2.500 x 5.625 (64.0 x 143.0) | 42.0                                         | 8.78                                   |
| 3300.0                                              | 36DY332F450DD2A | 3.000 x 4.625 (76.0 x 117.0) | 36.0                                         | 10.20                                  |
| 5600.0                                              | 36DY562F450DJ2A | 3.000 x 8.625 (76.0 x 219.0) | 21.0                                         | 16.51                                  |

Statements about product lifetime are based on calculations and internal testing. They should only be interpreted as estimations. Also due to external factors, the lifetime in the field application may deviate from the calculated lifetime. In general, nothing stated herein shall be construed as a guarantee of durability.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331