

PXES-2590

9-Slot 3U PXI Express Chassis with AC – Up to 7 GB/s, All Hybrid



Introduction

The ADLINK PXES-2590 is a 9-slot PXI Express chassis equipped with advanced features and functions.

Compliant with PXI Express and cPCI Express specifications, the PXES-2590 offers one system slot, one system timing slot, and seven hybrid peripheral slots for versatile test and measurement applications requiring enhanced bandwidth. The hybrid-slot design accepts installation of CompactPCI, PXI, CompactPCI Express, and PXI Express modules into any peripheral slots in PXES-2590, maximizing flexibility. The PXES-2590 is built on a four-link PXI express chassis with 7 GB/s system bandwidth, and 2 GB/s slot bandwidth for all peripheral slots.



The PXES-2590 is implemented with a smart system monitoring controller, reporting full chassis status, including fan speed, system voltages, and internal temperature.

Equipped with an industrial grade AC power supply, the PXES-2590 still provides 400 W under 55°C, and delivers superior cooling capacity, from two 120 mm cooling fans on the rear of the chassis. Two BNC connectors for 10 MHz clock input/output on the rear panel increase chassis flexibility, enabling synchronization with supplementary devices. All in all, PXES-2590 is the best PXI Express platform choice for testing and measurement requirements.

Features

- PXI™-5 PXI Express hardware specification Rev.1.0 compliant
- 9-slot PXI Express chassis with one system slot, one system timing slot, and seven hybrid peripheral slots
- Four-link PXI Express chassis
- Up to 7 GB/s system bandwidth
- Up to 2 GB/s peripheral bandwidth for all slots
- 0°C to 55°C extended operating temperature range
- Intelligent chassis management
 - Automatic fan speed control
 - Chassis status monitoring and reporting
 - Remote chassis power on/off control
- BNC connectors for 10 MHz clock input/output
- Maximum total usable power is 400 W under 55°C
- Power, temperature, and fan monitoring LEDs

PXES-2590 Front View



PXES-2590 Hybrid Peripheral Slots

PXES-2590 Back View



10 MHz Ref clock input/output BNC connectors

FAN Speed Control Switch
Inhibit Enable/Disable Switch & Power rails monitoring port

Highlights

■ Portable LCD Monitor/Keyboard Accessory

In further support of the portability requirements of PXI/PXIe measurement systems, the PXES-2590 also provides an optional portable LCD monitor/keyboard accessory kit, allowing rack-cabinet PXI systems to be easily converted to fully portable PXI systems.

Accessory kit includes:

- 15 in. touch screen LCD monitor with 1024 x 768 resolution
- English keyboard and touchpad
- ADLINK factory or user installation
- VGA video connection
- No requirement for external power



Innovative Cooling Mechanism

The ADLINK PXES-2590 features an innovative heat dissipation solution. Two 185.9CFM cooling fans in the rear section of the chassis draw cool air through lower apertures, which is then exhausted through the back. This design generates uniform airflow for each PXI slot, delivering exceptional cooling.

When installed in a rack, the cooling design minimizes intake of hot air from the rear side, separating airflow for modules and power supplies, while isolating noise source (fan) from modules and maintaining a steady internal temperature.

Intelligent Chassis Management

The PXES-2590 has a built-in system monitoring controller that monitors and manages full chassis status, including internal temperature, fan speed, and DC voltages.



All Hybrid Peripheral Slots Design*

The ADLINK PXES-2590 features an all-hybrid peripheral slot design, with PXI Express, cPCI Express, PXI, and CompactPCI modules compatible with every slot.

Note:

1. ADLINK's PXI Express chassis accepts hybrid slot-compatible PXI-5 modules (with XJ4 connector). Legacy PXI-I boards (with J2 connector) need to be upgraded to hybrid slot-compatible PXI modules. A detailed list of ADLINK PXI hybrid slot-compatible modules is available online at: <http://www.adlinktech.com/PXI/pxi-breakthrough-bandwidth.php#FAQ>

2. Contact your ADLINK sales representative for assistance in upgrading ADLINK legacy PXI modules. If the PXI modules were purchased from a third party, please contact the original vendor.



• Backplane Link Configuration

Specifications

Power Supply

- AC Input
 - Input voltage range: 100 to 240 VAC
 - Input voltage frequency: 50 to 60 Hz
- DC Output
 - Maximum total usable power is 400 W

VDC	Maximum	Load Regulation	Maximum Ripple & Noise
+5 V	23.0 A	±3%	50 mV
+12 V	27.0 A	±3%	50 mV
+3.3 V	33.0 A	±3%	50 mV
-12 V	1.75 A	±3%	50 mV

Bus Interface

- Four-link capacity PXI Express chassis
- Up to 7 GB/s system bandwidth
- Up to 2 GB/s peripheral bandwidth for all slots

IO/Switch on Rear Panel

- BNC connectors for 10MHz clock input/output
- Fan speed selector switch
- Inhibit mode selector switch
- D-SUB9 for voltage monitoring and remote inhibit

Cooling

- Fans: 2 x 185.9 CFM fans
- Per-slot cooling capacity: 30 W

Physical

- Number of slots:
 - 1 system slot + 1 system timing hybrid slot
 - + 7 peripheral slots
- Dimensions:
 - 322 mm (W) x 190 mm (H) x 456 mm (D) (12.55" x 7.4" x 17.8")
- Weight: 9 kg (19.8 lbs)

Operating Environment

- Ambient temperature: 0°C to 55°C (32°F to 131°F)
- Relative humidity: 10% to 90%, non-condensing

Storage Environment

- Ambient temperature: -20°C to 70°C (-4°F to 158°F)
- Relative humidity: 10% to 90%, non-condensing

Shock and Vibration

- Functional shock: 30 G, half-sine, 11 ms pulse duration
- Random vibration:
 - Operating: 5 to 500 Hz, 0.3 Grms, 3 axes
 - Non-operating: 5 to 500 Hz, 2.46 Grms, 3 axes

Emissions Compliance

- EN 61326-I
- FCC Class A

CE Compliance

- Safety: EN 61010-I
- Immunity: EN 61326-I

Recommended System Controller

	PXES-2590
PXle-3975	✓

Ordering Information

PXES-2590

3U 9-slot PXI Express chassis with all-hybrid peripheral slots and universal AC power supply

PXES-2590/PMK-1524 with Trolley Case

3U 9-slot PXI Express chassis with all hybrid slots with factory-mounted 15" 24-bit monitor/ keyboard kit, pre-installed in trolley case for shipping.

Optional Accessories

PMK-1524

Portable LCD monitor/keyboard accessory kit for PXES-2590

Trolley Case

Trolley case for PXES-2590/PMK-1524, 570 x 270 x 390 mm, 5 kg

PXES-2590 Rack-mount Kit

Flexible rack-mount kit for PXES-2590



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331