# Phase Control Thyristors (Hockey PUK Version), 650 A

E-PUK (TO-200AB)

## FEATURES

- Center amplifying gate
- Metal case with ceramic insulator
- International standard case E-PUK (TO-200AB)
- Designed and qualified for industrial level
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

Pb-free RoHS COMPLIANT

## TYPICAL APPLICATIONS

- DC motor controls
- Controlled DC power supplies
- AC controllers

| PRIMARY CHARACTERISTICS | |
|---|---|
| $I_{T(AV)}$ | 650 A |
| $V_{DRM}/V_{RRM}$ | 400 V, 800 V, 1200 V, 1600 V, 1800 V, 2000 V |
| $V_{TM}$ | 2.18 V |
| $I_{GT}$ | 100 mA |
| $T_J$ | -40 °C to +125 °C |
| Package | E-PUK (TO-200AB) |
| Circuit configuration | Single SCR |

| MAJOR RATINGS AND CHARACTERISTICS | | | |
|---|---|---|---|
| PARAMETER | TEST CONDITIONS | VALUES | UNITS |
| $I_{T(AV)}$ | | 650 | A |
| | $T_{hs}$ | 55 | °C |
| $I_{T(RMS)}$ | | 1290 | A |
| | $T_{hs}$ | 25 | °C |
| $I_{TSM}$ | 50 Hz | 8000 | A |
| | 60 Hz | 8380 | |
| $I^2t$ | 50 Hz | 320 | $kA^2s$ |
| | 60 Hz | 292 | |
| $V_{DRM}/V_{RRM}$ | | 400 to 2000 | V |
| $t_q$ | Typical | 100 | µs |
| $T_J$ | | -40 to 125 | °C |

## ELECTRICAL SPECIFICATIONS

| VOLTAGE RATINGS | | | | |
|---|---|---|---|---|
| TYPE NUMBER | VOLTAGE CODE | $V_{DRM}/V_{RRM}$, MAXIMUM REPETITIVE PEAK AND OFF-STATE VOLTAGE V | $V_{RSM}$, MAXIMUM NON-REPETITIVE PEAK VOLTAGE V | $I_{DRM}/I_{RRM}$ MAXIMUM AT $T_J = T_J$ MAXIMUM mA |
| VS-ST300C..C | 04 | 400 | 500 | 50 |
| | 08 | 800 | 900 | |
| | 12 | 1200 | 1300 | |
| | 16 | 1600 | 1700 | |
| | 18 | 1800 | 1900 | |
| | 20 | 2000 | 2100 | |



For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| ABSOLUTE MAXIMUM RATINGS | | | | | | |
|---|---|---|---|---|---|---|
| **PARAMETER** | **SYMBOL** | **TEST CONDITIONS** | | | **VALUES** | **UNITS** |
| Maximum average on-state current at heatsink temperature | $I_{T(AV)}$ | 180° conduction, half sine wave double side (single side) cooled | | | 650 (320) | A |
| | | | | | 55 (75) | °C |
| Maximum RMS on-state current | $I_{T(RMS)}$ | DC at 25 °C heatsink temperature double side cooled | | | 1290 | A |
| Maximum peak, one-cycle non-repetitive surge current | $I_{TSM}$ | t = 10 ms | No voltage reapplied | Sinusoidal half wave, initial $T_J = T_J$ maximum | 8000 | |
| | | t = 8.3 ms | | | 8380 | |
| | | t = 10 ms | 100 % $V_{RRM}$ reapplied | | 6730 | |
| | | t = 8.3 ms | | | 7040 | |
| Maximum $I^2t$ for fusing | $I^2t$ | t = 10 ms | No voltage reapplied | | 320 | $kA^2s$ |
| | | t = 8.3 ms | | | 292 | |
| | | t = 10 ms | 100 % $V_{RRM}$ reapplied | | 226 | |
| | | t = 8.3 ms | | | 207 | |
| Maximum $I^2\sqrt{t}$ for fusing | $I^2\sqrt{t}$ | t = 0.1 to 10 ms, no voltage reapplied | | | 3200 | $kA^2\sqrt{s}$ |
| Low level value of threshold voltage | $V_{T(TO)1}$ | (16.7 % x π x $I_{T(AV)}$ < I < π x $I_{T(AV)}$), $T_J = T_J$ maximum | | | 0.97 | V |
| High level value of threshold voltage | $V_{T(TO)2}$ | (I > π x $I_{T(AV)}$), $T_J = T_J$ maximum | | | 0.98 | |
| Low level value of on-state slope resistance | $r_{t1}$ | (16.7 % x π x $I_{T(AV)}$ < I < π x $I_{T(AV)}$), $T_J = T_J$ maximum | | | 0.74 | mΩ |
| High level value of on-state slope resistance | $r_{t2}$ | (I > π x $I_{T(AV)}$), $T_J = T_J$ maximum | | | 0.73 | |
| Maximum on-state voltage | $V_{TM}$ | $I_{pk}$ = 1635 A, $T_J = T_J$ maximum, $t_p$ = 10 ms sine pulse | | | 2.18 | V |
| Maximum holding current | $I_H$ | $T_J$ = 25 °C, anode supply 12 V resistive load | | | 600 | mA |
| Typical latching current | $I_L$ | | | | 1000 | |

| SWITCHING | | | | |
|---|---|---|---|---|
| **PARAMETER** | **SYMBOL** | **TEST CONDITIONS** | **VALUES** | **UNITS** |
| Maximum non-repetitive rate of rise of turned-on current | dI/dt | Gate drive 20 V, 20 Ω, $t_r \leq 1$ µs<br>$T_J = T_J$ maximum, anode voltage ≤ 80 % $V_{DRM}$ | 1000 | A/µs |
| Typical delay time | $t_d$ | Gate current 1 A, $dI_g/dt$ = 1 A/µs<br>$V_d$ = 0.67 % $V_{DRM}$, $T_J$ = 25 °C | 1.0 | µs |
| Typical turn-off time | $t_q$ | $I_{TM}$ = 300 A, $T_J = T_J$ maximum, dI/dt = 40 A/µs,<br>$V_R$ = 50 V, dV/dt = 20 V/µs, gate 0 V 100 Ω, $t_p$ = 500 µs | 100 | |

| BLOCKING | | | | |
|---|---|---|---|---|
| **PARAMETER** | **SYMBOL** | **TEST CONDITIONS** | **VALUES** | **UNITS** |
| Maximum critical rate of rise of off-state voltage | dV/dt | $T_J = T_J$ maximum linear to 80 % rated $V_{DRM}$ | 500 | V/µs |
| Maximum peak reverse and off-state leakage current | $I_{RRM}$, $I_{DRM}$ | $T_J = T_J$ maximum, rated $V_{DRM}/V_{RRM}$ applied | 50 | mA |


For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| TRIGGERING | | | | | | |
|---|---|---|---|---|---|---|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES TYP. | VALUES MAX. | UNITS |
| Maximum peak gate power | $P_{GM}$ | $T_J = T_J$ maximum, $t_p \leq 5$ ms | | 10.0 | | W |
| Maximum average gate power | $P_{G(AV)}$ | $T_J = T_J$ maximum, f = 50 Hz, d% = 50 | | 2.0 | | W |
| Maximum peak positive gate current | $I_{GM}$ | $T_J = T_J$ maximum, $t_p \leq 5$ ms | | 3.0 | | A |
| Maximum peak positive gate voltage | + $V_{GM}$ | $T_J = T_J$ maximum, $t_p \leq 5$ ms | | 20 | | V |
| Maximum peak negative gate voltage | - $V_{GM}$ | | | 5.0 | | V |
| DC gate current required to trigger | $I_{GT}$ | $T_J$ = - 40 °C | Maximum required gate trigger/ current/voltage are the lowest value which will trigger all units 12 V anode to cathode applied | 200 | - | mA |
| | | $T_J$ = 25 °C | | 100 | 200 | mA |
| | | $T_J$ = 125 °C | | 50 | - | mA |
| DC gate voltage required to trigger | $V_{GT}$ | $T_J$ = - 40 °C | | 2.5 | - | V |
| | | $T_J$ = 25 °C | | 1.8 | 3.0 | V |
| | | $T_J$ = 125 °C | | 1.1 | - | V |
| DC gate current not to trigger | $I_{GD}$ | $T_J = T_J$ maximum | Maximum gate current/voltage not to trigger is the maximum value which will not trigger any unit with rated $V_{DRM}$ anode to cathode applied | 10.0 | | mA |
| DC gate voltage not to trigger | $V_{GD}$ | | | 0.25 | | V |

| THERMAL AND MECHANICAL SPECIFICATIONS | | | | |
|---|---|---|---|---|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
| Maximum operating junction temperature range | $T_J$ | | - 40 to 125 | °C |
| Maximum storage temperature range | $T_{Stg}$ | | - 40 to 150 | °C |
| Maximum thermal resistance, junction to heatsink | $R_{thJ\text{-}hs}$ | DC operation single side cooled | 0.09 | K/W |
| | | DC operation double side cooled | 0.04 | K/W |
| Maximum thermal resistance, case to heatsink | $R_{thC\text{-}hs}$ | DC operation single side cooled | 0.02 | K/W |
| | | DC operation double side cooled | 0.01 | K/W |
| Mounting force, ± 10 % | | | 9800 (1000) | N (kg) |
| Approximate weight | | | 83 | g |
| Case style | | See dimensions - link at the end of datasheet | E-PUK (TO-200AB) | |

| $\Delta R_{thJ\text{-}hs}$ CONDUCTION | | | | | | |
|---|---|---|---|---|---|---|
| CONDUCTION ANGLE | SINUSOIDAL CONDUCTION | | RECTANGULAR CONDUCTION | | TEST CONDITIONS | UNITS |
| | SINGLE SIDE | DOUBLE SIDE | SINGLE SIDE | DOUBLE SIDE | | |
| 180° | 0.010 | 0.011 | 0.007 | 0.007 | $T_J = T_J$ maximum | K/W |
| 120° | 0.012 | 0.012 | 0.012 | 0.013 | | |
| 90° | 0.015 | 0.015 | 0.016 | 0.017 | | |
| 60° | 0.022 | 0.022 | 0.023 | 0.023 | | |
| 30° | 0.036 | 0.036 | 0.036 | 0.037 | | |

**Note**

- The table above shows the increment of thermal resistance $R_{thJ\text{-}hs}$ when devices operate at different conduction angles than DC


For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - On-State Power Loss Characteristics




Fig. 6 - On-State Power Loss Characteristics



For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000




Fig. 7 - Maximum Non-Repetitive Surge Current
Single and Double Side Cooled




Fig. 8 - Maximum Non-Repetitive Surge Current
Single and Double Side Cooled




Fig. 9 - On-State Voltage Drop Characteristcs




Fig. 10 - Thermal Impedance $Z_{thJ-hs}$ Characteristics


For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000




Fig. 11 - Gate Characteristics

## ORDERING INFORMATION TABLE

**Device code**

| VS- | ST | 30 | 0 | C | 20 | C | 1 | - |
|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |

- **1** - Vishay Semiconductors product
- **2** - Thyristor
- **3** - Essential part number
- **4** - 0 = converter grade
- **5** - C = ceramic PUK
- **6** - Voltage code x 100 = $V_{RRM}$ (see Voltage Ratings table)
- **7** - C = PUK case E-PUK (TO-200AB)
- **8** - 0 = eyelet terminals (gate and auxiliary cathode unsoldered leads)
  1 = fast-on terminals (gate and auxiliary cathode unsoldered leads)
  2 = eyelet terminals (gate and auxiliary cathode soldered leads)
  3 = fast-on terminals (gate and auxiliary cathode soldered leads)
- **9** - Critical dV/dt:
  - None = 500 V/µs (standard value)
  - L = 1000 V/µs (special selection)

| LINKS TO RELATED DOCUMENTS | |
|---|---|
| Dimensions | www.vishay.com/doc?95075 |


For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# E-PUK (TO-200AB)

**DIMENSIONS** in millimeters (inches)







Quote between upper and lower pole pieces has to be considered after application of mounting force (see thermal and mechanical specification)



For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

*© 2017 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED*

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** sales@st-electron.ru

**Адрес:** 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331