



# Accessories

|                                        | Page          |
|----------------------------------------|---------------|
| <b>General information</b>             | <b>5 - 2</b>  |
| <b>Accessories - Luminous elements</b> | <b>5 - 3</b>  |
| Filament/neon lamp                     | 5 - 4         |
| LED                                    | 5 - 14        |
| <b>Other accessories</b>               | <b>5 - 19</b> |
| Accessories                            | 5 - 20        |

## General information

When selecting lamps, the button/lens colour of the device should be taken into account.

| transparent colours | Suitable for   |            |         |
|---------------------|----------------|------------|---------|
|                     | Filament lamps | Neon lamps | LED     |
| colourless          | limited        | good       | good    |
| red                 | good           | good       | good    |
| yellow              | good           | good       | good    |
| green               | good           | limited    | limited |
| blue                | limited        | limited    | good    |

**transparent** = clear, grooved on inside for better light diffusion

**translucent** = translucent but not clear

Operating life specifications of lamps refer to AC operation. For DC operation, these values are reduced by approximately 40%. (Operating life specifications: when not mounted).

Neon lamps: rated current tolerance +/- 30%

We recommend to combine coloured lenses with the corresponding LED colours in order to achieve a really intensive colour.

On the other hand, when combining e. g. a white LED with a coloured lens, this will produce a dim colour.

### LED Protective Diode

LED may be damaged when anode and cathode are connected in a wrong way. An integrated protective diode protects the LED against wrong polarization.

## CE-Conformity

Illumination like lamps and LED displays are exchangeable, overall available as merchandise and not steadily connected with the network – thus, the Low-voltage Directive 73/23/EEG does not apply.

### EMC

The components of this catalogue are within the meaning of the law concerning the electromagnetic conformity (= EMC) "basic components as f. ex. switches, signal lamps or like" and, therefore, do not all within the scope of the EMC.

### Declarations of Conformity

Declarations of conformity for lamps are not available.



## General Data

Luminous elements

## Content

|                                                              |               |
|--------------------------------------------------------------|---------------|
| <b>Filament/neon lamp</b>                                    | <b>5 - 4</b>  |
| Filament lamps, wedge base W 2 x 4.6d DIN 49846              | 5 - 4         |
| Filament lamps, Bi-Pin T 1 base                              | 5 - 5         |
| Filament lamps, Bi-Pin T ¼ base                              | 5 - 5         |
| Filament lamps T 4.5                                         | 5 - 6         |
| Filament lamps T 4.6                                         | 5 - 6         |
| Filament lamps, BA 9s base (MBC/MCC), shape G, DIN 72601     | 5 - 7         |
| Filament lamps, BA 9s base (MBC/MCC), shape A, DIN 49851     | 5 - 7         |
| Neon lamps, BA 9s base (MBC/MCC)                             | 5 - 8         |
| Neon lamps, BA 9s base (MBC/MCC), DIN 49850                  | 5 - 8         |
| Filament lamps, BA 15d base, DIN 49850                       | 5 - 8         |
| Filament lamps, BA 15d base, DIN 49852                       | 5 - 9         |
| Filament lamps, BA 15d base                                  | 5 - 9         |
| Filament lamps, E 10 (MES) base                              | 5 - 10        |
| Neon lamps, E 10 (MES) base                                  | 5 - 10        |
| Filament lamps, E 14 base, shape B, DIN 49850                | 5 - 10        |
| Filament lamps, E 14 base, shape A, DIN 49852                | 5 - 11        |
| Filament lamps, E 14 base                                    | 5 - 11        |
| Neon lamps, E 14 base, shape B                               | 5 - 12        |
| Filament lamps, tubular lamp, S 8.5 base, shape L, DIN 72601 | 5 - 12        |
| Filament lamps, tubular lamp, S 8.5 base, shape K, DIN 72601 | 5 - 12        |
| <b>LED</b>                                                   | <b>5 - 14</b> |
| LED W 2 x 4.6d superbright                                   | 5 - 14        |
| LED Bi-Pin T 1                                               | 5 - 15        |
| LED Bi-Pin T 1 superbright                                   | 5 - 15        |
| LED T 4.5                                                    | 5 - 16        |
| LED T 4.5 superbright                                        | 5 - 16        |
| LED BA 9s (MBC/MCC) superbright                              | 5 - 17        |
| LED 3 mm, without base                                       | 5 - 17        |

## Filament/neon lamp



### Typical accessories Filament/neon lamp

| Description                            | Photo                                                                                | Order no.                | Additional accessories see page |
|----------------------------------------|--------------------------------------------------------------------------------------|--------------------------|---------------------------------|
| Lamp extractor for lamp diameter 11 mm |  | <b>1.90.900.007/0000</b> | 5 - 20                          |

### Filament lamps, wedge base W 2 x 4.6d DIN 49846



| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 12 V          | 0.08 A        | 1.2 W       | 5 mm          | 20 mm  | 15000 h                  | <b>1.90.120.012/0000</b> | <b>1.90.900.003/0000</b>   |
| 24 - 30 V     | 0.04 A        | 1 W         | 5 mm          | 20 mm  | 1000 h                   | <b>1.90.120.005/0000</b> | <b>1.90.900.003/0000</b>   |
| 24 V          | 0.04 A        | 1.2 W       | 5 mm          | 20 mm  | 7000 h                   | <b>1.90.120.011/0000</b> | <b>1.90.900.003/0000</b>   |
| 48 V          | 0.025 A       | 1.2 W       | 5 mm          | 19 mm  | 2500 h                   | <b>1.90.120.010/0000</b> | <b>1.90.900.003/0000</b>   |
| 60 V          | 0.02 A        | 1.2 W       | 5 mm          | 19 mm  | 3300 h                   | <b>1.90.120.009/0000</b> | <b>1.90.900.003/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.  
 The lamps up to 30 V are provided with glass sockets, the other ones with plastic sockets.

### Filament lamps, Bi-Pin T 1 base



| Rated voltage | Rated current | Rated power  | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|--------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 24 - 28 V     | 0.016 A       | 0.4 - 0.56 W | -             | -      | 5000 h                   | <b>1.90.180.473/0000</b> | <b>1.90.900.001/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

### Filament lamps, Bi-Pin T ¼ base



| Rated voltage | Rated current | Rated power | Diameter max. | Length  | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|---------|--------------------------|--------------------------|----------------------------|
| 12 V          | 0.06 A        | 0.72 W      | 4.3 mm        | 10.5 mm | 10000 h                  | <b>1.90.180.474/0000</b> | <b>1.90.900.002/0000</b>   |
| 28 V          | 0.03 A        | 0.84 W      | 4.3 mm        | 10.5 mm | 5000 h                   | <b>1.90.180.475/0000</b> | <b>1.90.900.002/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

### Filament lamps T 4.5



| Rated voltage | Rated current | Rated power | Diameter max. | Length  | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|---------|--------------------------|--------------------------|----------------------------|
| 12 V          | 0.04 A        | 0.48 W      | 4.2 mm        | 16.5 mm | 10000 h                  | <b>1.90.100.022/0000</b> | <b>1.90.900.002/0000</b>   |
| 24 V          | 0.02 A        | 0.48 W      | 4.2 mm        | 16.5 mm | 8000 h                   | <b>1.90.100.023/0000</b> | <b>1.90.900.002/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

### Filament lamps T 4.6



| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 12 V          | 0.04 A        | 0.3 W       | 4 mm          | 22 mm  | 5000 h                   | <b>1.90.100.012/0000</b> | <b>1.90.900.002/0000</b>   |
| 24 V          | 0.02 A        | 0.5 W       | 4 mm          | 22 mm  | 5000 h                   | <b>1.90.100.013/0000</b> | <b>1.90.900.002/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, BA 9s base (MBC/MCC), shape G, DIN 72601**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 12 - 15 V     | 0.12 A        | 1.2 W       | 9 mm          | 24 mm  | 10000 h                  | <b>1.90.060.003/0000</b> | <b>1.90.900.006/0000</b>   |
| 24 - 30 V     | 0.04 A        | 1.2 W       | 9 mm          | 24 mm  | 7000 h                   | <b>1.90.060.014/0000</b> | <b>1.90.900.006/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, BA 9s base (MBC/MCC), shape A, DIN 49851**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 12 - 15 V     | 0.166 A       | 2 W         | 11 mm         | 29 mm  | 10000 h                  | <b>1.90.060.132/0000</b> | <b>1.90.900.007/0000</b>   |
| 24 - 30 V     | 0.083 A       | 2 W         | 11 mm         | 29 mm  | 10000 h                  | <b>1.90.060.133/0000</b> | <b>1.90.900.007/0000</b>   |
| 110 - 130 V   | 0.018 A       | 2 W         | 11 mm         | 30 mm  | 25000 h                  | <b>1.90.060.137/0000</b> | <b>1.90.900.007/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Neon lamps, BA 9s base (MBC/MCC)**


| Rated voltage | Rated current     | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|-------------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 220 AC V      | 0.0015 - 0.0018 A | -           | 10 mm         | 24 mm  | 1500 h                   | <b>1.90.560.002/0000</b> | <b>1.90.900.007/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Neon lamps, BA 9s base (MBC/MCC), DIN 49850**


| Rated voltage | Rated current     | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|-------------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| AC 220 V      | 0.0015 - 0.0018 A | -           | 10 mm         | 28 mm  | -                        | <b>1.90.560.102/0000</b> | <b>1.90.900.007/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, BA 15d base, DIN 49850**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 12 - 15 V     | 0.12 A        | 2 W         | 15.2/12.5 mm  | 31 mm  | 1000 h                   | <b>1.90.070.003/0000</b> | <b>1.90.900.008/0000</b>   |
| 24 - 30 V     | 0.08 A        | 2 W         | 15.2/12.5 mm  | 31 mm  | 1000 h                   | <b>1.90.070.004/0000</b> | <b>1.90.900.008/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, BA 15d base, DIN 49852**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 24 - 30 V     | 0.165 A       | 4 W         | 17 mm         | 57 mm  | 2000 h                   | <b>1.90.070.105/0000</b> | <b>1.90.900.009/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, BA 15d base**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 24 V          | 0.2 A         | 5 W         | 16 mm         | 36 mm  | 2000 h                   | <b>1.90.070.053/0000</b> | <b>1.90.900.009/0000</b>   |
| 220 - 260 V   | 0,02 - 0,03 A | 5 - 7 W     | 16 mm         | 36 mm  | 1000 h                   | 1.90.070.061/0000        | <b>1.90.900.009/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, E 10 (MES) base**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 24 - 30 V     | 0.083 A       | 2 W         | 11 mm         | 29 mm  | 1000 h                   | <b>1.90.010.033/0000</b> | <b>1.90.900.007/0000</b>   |
| 110 - 130 V   | 0.018 A       | 2 W         | 11 mm         | 30 mm  | 1000 h                   | <b>1.90.010.037/0000</b> | <b>1.90.900.007/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Neon lamps, E 10 (MES) base**


| Rated voltage | Rated current     | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|-------------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 220 AC V      | 0.0015 - 0.0018 A | -           | 10.4 mm       | 28 mm  | -                        | <b>1.90.510.012/0000</b> | <b>1.90.900.006/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, E 14 base, shape B, DIN 49850**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 24 - 30 V     | 0.083 A       | 2 W         | 14/12.5 mm    | 31 mm  | 1000 h                   | <b>1.90.020.033/0000</b> | <b>1.90.900.008/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, E 14 base, shape A, DIN 49852**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 24 - 30 V     | 0.165 A       | 4 W         | 17 mm         | 57 mm  | 1000 h                   | <b>1.90.020.105/0000</b> | <b>1.90.900.009/0000</b>   |
| 220 - 260 V   | 0.023 A       | 5 W         | 17 mm         | 57 mm  | 1000 h                   | <b>1.90.020.115/0000</b> | <b>1.90.900.009/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, E 14 base**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 24 V          | 0.2 A         | 5 W         | 16 mm         | 36 mm  | 2000 h                   | <b>1.90.020.053/0000</b> | <b>1.90.900.009/0000</b>   |
| 220 - 260 V   | 0,02 - 0,03 A | 5 - 7 W     | 16 mm         | 36 mm  | 1000 h                   | <b>1.90.020.061/0000</b> | <b>1.90.900.009/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Neon lamps, E 14 base, shape B**


| Rated voltage | Rated current     | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|-------------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 220 AC V      | 0.0014 - 0.0026 A | -           | 14.1/11.5 mm  | 31 mm  | -                        | <b>1.90.520.002/0000</b> | <b>1.90.900.008/0000</b>   |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, tubular lamp, S 8.5 base, shape L, DIN 72601**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 24 V          | -             | 3 W         | 11.5 mm       | 39 mm  | 200 h                    | <b>1.90.111.003/0000</b> | -                          |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.

**Filament lamps, tubular lamp, S 8.5 base, shape K, DIN 72601**


| Rated voltage | Rated current | Rated power | Diameter max. | Length | Medium operating life AC | Order no.                | Accessoires lamp extractor |
|---------------|---------------|-------------|---------------|--------|--------------------------|--------------------------|----------------------------|
| 24 V          | -             | 5 W         | 15.5 mm       | 44 mm  | 200 h                    | <b>1.90.111.103/0000</b> | -                          |

Ratings and operating life specifications generally refer to the lower rated voltage value. Operating life specifications of lamps refer to AC operation. With DC operation, these are reduced by about 40%.



## LED



## LED W 2 x 4.6d superbright



| Socket     | Colour | Forward voltage<br>typ. $U_F$ at $I_F$ | Max. current, $I_F$ | Light intensity | Order no.                | Accessoires lamp<br>extractor |
|------------|--------|----------------------------------------|---------------------|-----------------|--------------------------|-------------------------------|
| W 2 x 4.6d | red    | 24                                     | 12 mA               | 70 mcd          | <b>1.90.690.361/0000</b> | <b>1.90.900.003/0000</b>      |
| W 2 x 4.6d | green  | 24                                     | 12 mA               | 600 mcd         | <b>1.90.690.362/0000</b> | <b>1.90.900.003/0000</b>      |
| W 2 x 4.6d | yellow | 24                                     | 12 mA               | 80 mcd          | <b>1.90.690.363/0000</b> | <b>1.90.900.003/0000</b>      |
| W 2 x 4.6d | blue   | 24                                     | 12 mA               | 300 mcd         | <b>1.90.690.364/0000</b> | <b>1.90.900.003/0000</b>      |
| W 2 x 4.6d | white  | 24                                     | 12 mA               | 400 mcd         | <b>1.90.690.365/0000</b> | <b>1.90.900.003/0000</b>      |

All LEDs are provided with a protective diode. Operating temperature - 30 °C ... + 65 °C.  
For more intensive colours, please combine coloured lenses with suitable LED colours.

## LED Bi-Pin T 1



| Socket     | Colour | Forward voltage typ. $U_F$ at $I_F$ | Max. current, $I_F$ | Light intensity | Order no.                | Accessoires lamp extractor |
|------------|--------|-------------------------------------|---------------------|-----------------|--------------------------|----------------------------|
| Bi-Pin T 1 | red    | 2                                   | 10 mA               | 26-52 mcd       | <b>1.90.691.026/0000</b> | <b>1.90.900.001/0000</b>   |
| Bi-Pin T 1 | green  | 2                                   | 10 mA               | 9-33 mcd        | <b>1.90.691.027/0000</b> | <b>1.90.900.001/0000</b>   |
| Bi-Pin T 1 | yellow | 2                                   | 10 mA               | 26-52 mcd       | <b>1.90.691.028/0000</b> | <b>1.90.900.001/0000</b>   |

Voltage  $U_B$ : External resistor:  $R_V = (U_B - U_F) : I_F$

A suitable series resistor must be fitted externally.

Recommended resistor ratings:

- for 5 - 7 V = 270  $\Omega$  0.25 W

- for 12 - 14 V = 680  $\Omega$  0.50 W

- for 24 - 28 V = 1500  $\Omega$  1.00 W

Forward voltage  $U_F$ : 2 V (3 V max.)

Reverse voltage  $U_R$ : 5 V

Reverse current  $I_R$ : 100  $\mu$ A.

Forward current: 10 mA

Operating temperature: -20°C ... +60°C

Storage temperature: -30°C ... +80°C

Operating life: 100,000 h at  $T_U = 25^\circ\text{C}$

## LED Bi-Pin T 1 superbright



| Socket     | Colour | Forward voltage typ. $U_F$ at $I_F$ | Max. current, $I_F$ | Light intensity | Order no.                | Accessoires lamp extractor |
|------------|--------|-------------------------------------|---------------------|-----------------|--------------------------|----------------------------|
| Bi-Pin T 1 | red    | 24                                  | 11 mA               | 70 mcd          | <b>1.90.690.351/0000</b> | <b>1.90.900.001/0000</b>   |
| Bi-Pin T 1 | green  | 24                                  | 11 mA               | 600 mcd         | <b>1.90.690.352/0000</b> | <b>1.90.900.001/0000</b>   |
| Bi-Pin T 1 | yellow | 24                                  | 11 mA               | 80 mcd          | <b>1.90.690.353/0000</b> | <b>1.90.900.001/0000</b>   |
| Bi-Pin T 1 | blue   | 24                                  | 11 mA               | 300 mcd         | <b>1.90.690.354/0000</b> | <b>1.90.900.001/0000</b>   |
| Bi-Pin T 1 | white  | 24                                  | 11 mA               | 400 mcd         | <b>1.90.690.355/0000</b> | <b>1.90.900.001/0000</b>   |

All LEDs are provided with a protective diode. Operating temperature - 30 °C ... + 65 °C.

For more intensive colours, please combine coloured lenses with suitable LED colours.

## LED T 4.5



| Socket | Colour | Forward voltage typ. $U_F$ at $I_F$ | Max. current, $I_F$ | Light intensity | Order no.                | Accessoires lamp extractor |
|--------|--------|-------------------------------------|---------------------|-----------------|--------------------------|----------------------------|
| T 4.5  | red    | 2 - 3 V                             | 10 mA               | 26-52 mcd       | <b>1.90.692.001/0000</b> | -                          |
| T 4.5  | green  | 2 - 3 V                             | 10 mA               | 9-33 mcd        | <b>1.90.692.002/0000</b> | -                          |
| T 4.5  | yellow | 2 - 3 V                             | 10 mA               | 26-52 mcd       | <b>1.90.692.003/0000</b> | -                          |

Voltage  $U_B$ : External resistor:  $R_V = (U_B - U_F) : I_F$

A suitable series resistor must be fitted externally.

Recommended resistor ratings:

- for 5 - 7 V = 270  $\Omega$  0.25 W

- for 12 - 14 V = 680  $\Omega$  0.50 W

- for 24 - 28 V = 1500  $\Omega$  1.00 W

Forward voltage  $U_F$ : 2 V (3 V max.)

Reverse voltage  $U_R$ : 5 V

Reverse current  $I_R$ : 100  $\mu$ A.

Forward current: 10 mA

Operating temperature: -20°C ... +60°C

Storage temperature: -30°C ... +80°C

Operating life: 100,000 h at  $T_U = 25^\circ\text{C}$

## LED T 4.5 superbright



| Socket | Colour | Forward voltage typ. $U_F$ at $I_F$ | Max. current, $I_F$ | Light intensity | Order no.                | Accessoires lamp extractor |
|--------|--------|-------------------------------------|---------------------|-----------------|--------------------------|----------------------------|
| T 4.5  | red    | 24                                  | 13 mA               | 90 mcd          | <b>1.90.690.331/0000</b> | <b>1.90.900.004/0000</b>   |
| T 4.5  | green  | 24                                  | 13 mA               | 700 mcd         | <b>1.90.690.332/0000</b> | <b>1.90.900.004/0000</b>   |
| T 4.5  | yellow | 24                                  | 13 mA               | 100 mcd         | <b>1.90.690.333/0000</b> | <b>1.90.900.004/0000</b>   |
| T 4.5  | blue   | 24                                  | 13 mA               | 380 mcd         | <b>1.90.690.334/0000</b> | <b>1.90.900.004/0000</b>   |
| T 4.5  | white  | 24                                  | 13 mA               | 500 mcd         | <b>1.90.690.335/0000</b> | <b>1.90.900.004/0000</b>   |

All LEDs are provided with a protective diode. Operating temperature - 30 °C ... + 65 °C.

For more intensive colours, please combine coloured lenses with suitable LED colours.

## LED BA 9s (MBC/MCC) superbright



| Socket | Colour | Forward voltage typ. $U_F$ at $I_F$ | Max. current, $I_F$ | Light intensity | Order no.                | Accessoires lamp extractor |
|--------|--------|-------------------------------------|---------------------|-----------------|--------------------------|----------------------------|
| BA 9 s | red    | 24                                  | 15 mA               | 250 mcd         | <b>1.90.690.341/0000</b> | <b>1.90.900.007/0000</b>   |
| BA 9 s | green  | 24                                  | 15 mA               | 1000 mcd        | <b>1.90.690.342/0000</b> | <b>1.90.900.007/0000</b>   |
| BA 9 s | yellow | 24                                  | 15 mA               | 250 mcd         | <b>1.90.690.343/0000</b> | <b>1.90.900.007/0000</b>   |
| BA 9 s | blue   | 24                                  | 15 mA               | 450 mcd         | <b>1.90.690.344/0000</b> | <b>1.90.900.007/0000</b>   |
| BA 9 s | white  | 24                                  | 15 mA               | 600 mcd         | <b>1.90.690.345/0000</b> | <b>1.90.900.007/0000</b>   |

All LEDs are provided with a protective diode. Operating temperature - 30 °C ... + 65 °C.  
For more intensive colours, please combine coloured lenses with suitable LED colours.

## LED 3 mm, without base



| Socket         | Colour | Forward voltage typ. $U_F$ at $I_F$ | Max. current, $I_F$ | Light intensity | Order no.                | Accessoires lamp extractor |
|----------------|--------|-------------------------------------|---------------------|-----------------|--------------------------|----------------------------|
| without socket | red    | 1,6 V/1 mA                          | 30 mA               | -               | 1.90.690.228/0000        | -                          |
| without socket | yellow | 1,9 V/20 mA                         | 50 mA               | -               | <b>1.90.690.267/0000</b> | -                          |
| without socket | red    | 1,9 V/20 mA                         | 50 mA               | -               | <b>1.90.690.269/0000</b> | -                          |
| without socket | blue   | 3,6 V/20 mA                         | 30 mA               | -               | <b>1.90.690.282/0000</b> | -                          |
| without socket | green  | 3,5 V/20 mA                         | 30 mA               | -               | <b>1.90.690.285/0000</b> | -                          |
| without socket | white  | 3,6 V/20 mA                         | 30 mA               | -               | <b>1.90.690.295/0000</b> | -                          |

Processing information for 1.90.690.267/0000 and 1.90.690.269/0000  
The qualifications for the higher soldering temperatures on lead free soldering processes are as follows:  
Temperature stability according J-STD 020 C for reflow soldering 245°C and for wave soldering 245°C/10s.






## General Data

Other accessories

## Content

|                                                                                                     |               |
|-----------------------------------------------------------------------------------------------------|---------------|
| <b>Accessories</b>                                                                                  | <b>5 - 20</b> |
| Lamp extractor                                                                                      | 5 - 20        |
| Fixing spanner                                                                                      | 5 - 21        |
| RAFIX 22QR/FS - Fixing spanner for ring nut and front ring                                          | 5 - 21        |
| LUMOTAST FK/25 - Disassembly tool                                                                   | 5 - 22        |
| LUMOTAST FK/25 - Socket connector, 4-pin                                                            | 5 - 22        |
| LUMOTAST FK/25 - Flat ribbon cable, 10 cm, with socket connector and AMP 4-pin male quick connector | 5 - 22        |
| LUMOTAST FK/25 - Flat ribbon cable, 4-wire, length 1 m                                              | 5 - 23        |
| LUMOTAST FK/25 - Plug-in socket for PCB                                                             | 5 - 23        |
| Keylock switch - PCB plug-in socket                                                                 | 5 - 23        |
| LUMOTAST 75 IP40/65 - Protective cap                                                                | 5 - 24        |
| LUMOTAST 75 IP40/65 - Sealing cap                                                                   | 5 - 24        |
| Signal lamp Ø 22.3 mm - Sealing ring for IP 65                                                      | 5 - 24        |
| O-ring                                                                                              | 5 - 25        |
| Pushbutton 16.2 mm - Protection against contact                                                     | 5 - 25        |
| Signal lamps - Protection against contact                                                           | 5 - 25        |
| LUMOTAST 75 IP40/65 - Blanking cap, black, Ø 16.2 mm                                                | 5 - 26        |
| RAFIX 16 - Blanking cap with sealing and threaded ring, Ø 16.2 mm                                   | 5 - 26        |
| RAFIX 22 QR - Blanking cap, Ø 22.3 mm                                                               | 5 - 27        |
| RAFIX 22 FS - Blanking cap, Ø 22.3 mm                                                               | 5 - 27        |
| Emergency stop label, PVC adhesive, Ø 16.3 mm                                                       | 5 - 28        |
| Emergency stop label, Ø 22.3 mm                                                                     | 5 - 29        |
| Spacers, round                                                                                      | 5 - 30        |

# Accessories



## Lamp extractor



| Short text                                | Feature 1              | Feature 2 | Order no.                |
|-------------------------------------------|------------------------|-----------|--------------------------|
| Lamp extractor for lamp diameter 4 mm     | lamp diameter 4 mm     | -         | <b>1.90.900.001/0000</b> |
| Lamp extractor for lamp diameter 4 mm     | lamp diameter 4 mm     | -         | <b>1.90.900.002/0000</b> |
| Lamp extractor for lamp diameter 5 mm     | lamp diameter 5 mm     | -         | <b>1.90.900.003/0000</b> |
| Lamp extractor for lamp diameter 5-6 mm   | lamp diameter 5 - 6 mm | -         | <b>1.90.900.004/0000</b> |
| Lamp extractor for lamp diameter 7 mm     | lamp diameter 7mm      | -         | <b>1.90.900.005/0000</b> |
| Lamp extractor for lamp diameter 10.4 mm  | lamp diameter 10.4 mm  | -         | <b>1.90.900.006/0000</b> |
| Lamp extractor for lamp diameter 11 mm    | lamp diameter 11 mm    | -         | <b>1.90.900.007/0000</b> |
| Lamp extractor for lamp diameter 14 mm    | lamp diameter 14 mm    | -         | <b>1.90.900.008/0000</b> |
| Lamp extractor for lamp diameter 16-17 mm | lamp diameter 16-17 mm | -         | <b>1.90.900.009/0000</b> |

### Fixing spanner



| Short text                              | Feature 1 | Feature 2 | Order no.                |
|-----------------------------------------|-----------|-----------|--------------------------|
| Fixing spanner M 18, M 19               | -         | -         | <b>5.58.002.017/0105</b> |
| Fixing spanner M 20, M 22, for ring nut | -         | -         | <b>5.58.002.018/0105</b> |
| Fixing spanner M 15, M 16               | -         | -         | 5.58.002.019/0105        |
| Fixing spanner M 25, M 30               | -         | -         | <b>5.58.002.020/0105</b> |
| Fixing spanner M 9, M 10                | -         | -         | <b>5.58.002.025/0105</b> |
| Fixing spanner M 11, M 13               | -         | -         | <b>5.58.002.026/0105</b> |
| Fixing spanner M 8                      | -         | -         | <b>5.58.002.027/7705</b> |
| Fixing spanner, hexagon, for RAFIX 16   | -         | -         | 5.58.002.034/0100        |

### RAFIX 22QR/FS - Fixing spanner for ring nut and front ring




| Short text                                 | Feature 1 | Feature 2 | Order no.                |
|--------------------------------------------|-----------|-----------|--------------------------|
| Fixing spanner for ring nut and front ring | -         | -         | <b>5.05.800.062/0000</b> |

5

Others

### LUMOTAST FK/25 - Disassembly tool




| Short text                       | Feature 1 | Feature 2 | Order no.                |
|----------------------------------|-----------|-----------|--------------------------|
| Disassembly tool for LUMOTAST FK | -         | -         | <b>5.05.800.041/0000</b> |

### LUMOTAST FK/25 - Socket connector, 4-pin



| Short text              | Feature 1 | Feature 2 | Order no.                |
|-------------------------|-----------|-----------|--------------------------|
| Socket connector, 4-pin | -         | -         | <b>5.92.025.368/0000</b> |

### LUMOTAST FK/25 - Flat ribbon cable, 10 cm, with socket connector and AMP 4-pin male quick connector



| Short text                                                                                | Feature 1 | Feature 2 | Order no.                |
|-------------------------------------------------------------------------------------------|-----------|-----------|--------------------------|
| Cable (flat ribbon cable 10 cm with socket connector and male quick connector, AMP 4-pin) | -         | -         | <b>5.03.771.306/0000</b> |

5


Others

LUMOTAST FK/25 - Flat ribbon cable, 4-wire, length 1 m




| Short text                          | Feature 1 | Feature 2 | Order no.         |
|-------------------------------------|-----------|-----------|-------------------|
| Flat ribbon cable, 4-wire, 1 m long | -         | -         | 5.37.700.124/0000 |

LUMOTAST FK/25 - Plug-in socket for PCB



| Short text             | Feature 1 | Feature 2 | Order no.         |
|------------------------|-----------|-----------|-------------------|
| Plug-in socket for PCB | -         | -         | 5.00.645.036/0000 |

Keylock switch - PCB plug-in socket



| Short text                      | Feature 1 | Feature 2 | Order no.         |
|---------------------------------|-----------|-----------|-------------------|
| Plug-in socket for PCB mounting | -         | -         | 5.05.510.298/0000 |

**LUMOTAST 75 IP40/65 - Protective cap**


| Short text                          | Feature 1 | Feature 2 | Order no.         |
|-------------------------------------|-----------|-----------|-------------------|
| Protective cap (for 18 x 24 collar) | -         | -         | 5.05.800.027/0000 |
| Protective cap (for 18 x 18 collar) | -         | -         | 5.05.800.030/0000 |

**LUMOTAST 75 IP40/65 - Sealing cap**


| Short text                            | Feature 1  | Feature 2 | Order no.         |
|---------------------------------------|------------|-----------|-------------------|
| Sealing cap IP65 (for 18 x 24 collar) | 18 x 24 mm | -         | 5.05.200.008/0000 |
| Sealing cap IP65 (for 18 x 18 collar) | 18 x 18 mm | -         | 5.05.200.009/0000 |

**Signal lamp Ø 22.3 mm - Sealing ring for IP 65**


| Short text            | Feature 1 | Feature 2 | Order no.         |
|-----------------------|-----------|-----------|-------------------|
| Sealing ring for IP65 | -         | -         | 5.30.075.010/0100 |

## O-ring



| Short text                                          | Feature 1 | Feature 2 | Order no.         |
|-----------------------------------------------------|-----------|-----------|-------------------|
| O-ring, black, for blocking the operating stroke    | -         | -         | 5.30.120.009/0100 |
| O-ring for keylock switch                           | -         | -         | 5.30.120.015/0100 |
| O-ring, black, 17.0 x 1.5, for blocking RF 19H keys | -         | -         | 5.30.125.003/0100 |
| O-ring, black, 16.0 x 1, for blocking RF 19H keys   | -         | -         | 5.30.125.007/0100 |

## Pushbutton 16.2 mm - Protection against contact



| Short text                          | Feature 1 | Feature 2 | Order no.         |
|-------------------------------------|-----------|-----------|-------------------|
| Protection against contact to VBG 4 | -         | -         | 5.55.101.715/0200 |

## Signal lamps - Protection against contact



| Short text                          | Feature 1 | Feature 2 | Order no.         |
|-------------------------------------|-----------|-----------|-------------------|
| Protection against contact to VBG 4 | -         | -         | 5.50.240.063/0209 |
| Protection against contact to VBG 5 | -         | -         | 5.50.240.065/0200 |

5

Others

**LUMOTAST 75 IP40/65 - Blanking cap, black, Ø 16.2 mm**


| Short text                                                       | Feature 1 | Feature 2 | Order no.         |
|------------------------------------------------------------------|-----------|-----------|-------------------|
| Blanking cap, black, to cover spare holes, dimensions 18 x 18 mm | -         | -         | 5.52.006.020/0103 |
| Blanking cap, black, to cover spare holes, dimensions 18 x 24 mm | -         | -         | 5.52.006.021/0100 |
| Blanking cap, black, to cover spare holes, round 18 mm           | -         | -         | 5.52.006.022/0100 |

**RAFIX 16 - Blanking cap with sealing and threaded ring, Ø 16.2 mm**


| Short text                                                                           | Feature 1 | Feature 2 | Order no.                |
|--------------------------------------------------------------------------------------|-----------|-----------|--------------------------|
| Blanking cap complete with sealing disc and ring nut, square                         | -         | -         | <b>5.05.800.049/0100</b> |
| Blanking cap complete with sealing disc and ring nut, round                          | -         | -         | <b>5.05.800.050/0100</b> |
| Blanking cap complete with sealing disc and ring nut, square, alignable without gaps | -         | -         | <b>5.05.800.051/0100</b> |

**RAFIX 22 QR - Blanking cap, Ø 22.3 mm**


| Short text                          | Feature 1 | Feature 2 | Order no.                |
|-------------------------------------|-----------|-----------|--------------------------|
| Blanking cap IP65, ring nut, square | -         | -         | <b>5.05.800.065/0000</b> |
| Blanking cap IP65, ring nut, round  | -         | -         | <b>5.05.800.064/0000</b> |


**RAFIX 22 FS - Blanking cap, Ø 22.3 mm**


| Short text                                                                                                 | Feature 1 | Feature 2 | Order no.         |
|------------------------------------------------------------------------------------------------------------|-----------|-----------|-------------------|
| Blanking cap IP65, ring nut, square                                                                        | -         | -         | 5.05.800.068/0000 |
| Blanking cap IP65, ring nut, round                                                                         | -         | -         | 5.05.800.067/0000 |
| Blanking cap IP65, ring nut, round, high version,<br>can be used for covering mounted PCB contact blocks.  | -         | -         | 5.05.200.025/0000 |
| Blanking cap IP65, ring nut, square, high version,<br>can be used for covering mounted PCB contact blocks. | -         | -         | 5.05.200.026/0000 |

**Emergency stop label, PVC adhesive, Ø 16.3 mm**


| Short text                                                                                                    | Feature 1<br>Ø outward | Feature 2<br>Ø inward | Order no.                |
|---------------------------------------------------------------------------------------------------------------|------------------------|-----------------------|--------------------------|
| Adhesive label yellow, round 16.3 / 60 mm, without legend                                                     | 60 mm                  | 16.3 mm               | <b>5.76.204.400/0400</b> |
| Adhesive label yellow, round 16.3 / 60 mm, with legend „Not-Aus“                                              | 60 mm                  | 16.3 mm               | <b>5.76.204.401/0400</b> |
| Adhesive label yellow, round 16.3 / 60 mm, with legend „EMERGENCY STOP“                                       | 60 mm                  | 16.3 mm               | <b>5.76.204.403/0400</b> |
| Adhesive label yellow, round 16.3 / 60 mm, with legend „NOT-HALT, EMERGENCY STOP, ARRET D'URGENCE, EMERGENZA“ | 60 mm                  | 16.3 mm               | 5.76.204.106/0400        |
| Adhesive label yellow, round 16.3 / 60 mm, with legend 4 x „NOT-HALT“                                         | 60 mm                  | 16.3 mm               | 5.76.204.108/0400        |
| Adhesive label yellow, round 16.3 / 60 mm, with legend 4 x „NOT-AUS“                                          | 60 mm                  | 16.3 mm               | 5.76.204.110/0400        |
| Adhesive label yellow, round 16.3 / 60 mm, with legend 4 x „EMERGENCY STOP“                                   | 60 mm                  | 16.3 mm               | 5.76.204.112/0400        |
| Adhesive label yellow, round 16.3 / 40 mm, with legend „NOT-HALT, EMERGENCY STOP, ARRET D'URGENCE, EMERGENZA“ | 40 mm                  | 16.3 mm               | 5.76.204.114/0400        |
| Adhesive label yellow, round 16.3 / 40 mm, with legend 4 x „NOT-HALT“                                         | 40 mm                  | 16.3 mm               | 5.76.204.116/0400        |
| Adhesive label yellow, round 16.3 / 40 mm, with legend 4 x „NOT-AUS“                                          | 40 mm                  | 16.3 mm               | 5.76.204.118/0400        |
| Adhesive label yellow, round 16.3 / 40 mm, with legend 4 x „EMERGENCY STOP“                                   | 40 mm                  | 16.3 mm               | 5.76.204.120/0400        |


## Emergency stop label, Ø 22.3 mm



| Short text                                                                                                    | Feature 1<br>Ø outward | Feature 2<br>Ø inward | Order no.                |
|---------------------------------------------------------------------------------------------------------------|------------------------|-----------------------|--------------------------|
| Emergency stop label, yellow, round 60 mm, rigid PVC, with legend „Not-Aus“                                   | 60 mm                  | 22.3 mm               | <b>5.76.207.001/0400</b> |
| Emergency stop label, yellow, round 60 mm, rigid PVC, with legend „EMERGENCY-STOP/ARRET D'URGENCE“            | 60 mm                  | 22.3 mm               | <b>5.76.207.002/0400</b> |
| Adhesive label yellow, round 22.3 / 60 mm, without legend                                                     | 60 mm                  | 22.3 mm               | <b>5.76.204.100/0400</b> |
| Adhesive label yellow, round 22.3 / 60 mm, with legend 1 x „Not-Aus“                                          | 60 mm                  | 22.3 mm               | <b>5.76.204.101/0400</b> |
| Adhesive label yellow, round 22.3 / 60 mm, with legend 1 x „ARRET D'URGENCE“                                  | 60 mm                  | 22.3 mm               | 5.76.204.102/0400        |
| Adhesive label yellow, round 22.3 / 60 mm, with legend 1 x „EMERGENCY-STOP“                                   | 60 mm                  | 22.3 mm               | <b>5.76.204.103/0400</b> |
| Emergency stop label, yellow rectangular 36 x 64 mm, without legend                                           | 36 x 64 mm             | 22.3 mm               | 5.76.205.011/0400        |
| Adhesive label yellow, round 22.3 / 60 mm, with legend „NOT-HALT, EMERGENCY STOP, ARRET D'URGENCE, EMERGENZA“ | 60 mm                  | 22.3 mm               | 5.76.204.107/0400        |
| Adhesive label yellow, round 22.3 / 60 mm, with legend 4 x „NOT-HALT“                                         | 60 mm                  | 22.3 mm               | 5.76.204.109/0400        |
| Adhesive label yellow, round 22.3 / 60 mm, with legend 4 x „NOT-AUS“                                          | 60 mm                  | 22.3 mm               | 5.76.204.111/0400        |
| Adhesive label yellow, round 22.3 / 60 mm, with legend 4 x „EMERGENCY STOP“                                   | 60 mm                  | 22.3 mm               | 5.76.204.113/0400        |
| Adhesive label yellow, round 22.3 / 40 mm, with legend „NOT-HALT, EMERGENCY STOP, ARRET D'URGENCE, EMERGENZA“ | 40 mm                  | 22.3 mm               | 5.76.204.115/0400        |
| Adhesive label yellow, round 22.3 / 40 mm, with legend 4 x „NOT-HALT“                                         | 40 mm                  | 22.3 mm               | 5.76.204.117/0400        |
| Adhesive label yellow, round 22.3 / 40 mm, with legend 4 x „NOT-AUS“                                          | 40 mm                  | 22.3 mm               | 5.76.204.119/0400        |
| Adhesive label yellow, round 22.3 / 40 mm, with legend 4 x „EMERGENCY STOP“                                   | 40 mm                  | 22.3 mm               | 5.76.204.121/0400        |

Degree of protection: rigid PVC: IP40, adhesive foil: IP65

## Spacers, round



| Length   | Width | Overall height | Diameter | Colour                    | Order no.                |
|----------|-------|----------------|----------|---------------------------|--------------------------|
| 3.50 mm  | -     | -              | -        | blue transparent          | 5.30.759.023/0000        |
| 4 mm     | -     | -              | -        | green                     | 5.30.759.251/0000        |
| 4.25 mm  | -     | -              | -        | blue                      | 5.30.759.025/0000        |
| 4.50 mm  | -     | -              | -        | red                       | 5.30.759.026/0000        |
| 4.75 mm  | -     | -              | -        | blue transparent          | 5.30.759.027/0000        |
| 5 mm     | -     | -              | -        | black                     | 5.30.759.028/0000        |
| 5.25 mm  | -     | -              | -        | yellow orange transparent | 5.30.759.029/0000        |
| 5.50 mm  | -     | -              | -        | yellow                    | 5.30.759.030/0000        |
| 5.75 mm  | -     | -              | -        | green                     | 5.30.759.031/0000        |
| 6 mm     | -     | -              | -        | blue                      | <b>5.30.759.032/0000</b> |
| 6.2 mm   | -     | -              | -        | blue                      | <b>5.30.759.033/0000</b> |
| 6.25 mm  | -     | -              | -        | red                       | <b>5.30.759.034/0000</b> |
| 6.50 mm  | -     | -              | -        | blue transparent          | <b>5.30.759.035/0000</b> |
| 6.75 mm  | -     | -              | -        | black                     | <b>5.30.759.036/0000</b> |
| 7 mm     | -     | -              | -        | yellow orange transparent | <b>5.30.759.037/0000</b> |
| 7.25 mm  | -     | -              | -        | yellow                    | <b>5.30.759.038/0000</b> |
| 7.50 mm  | -     | -              | -        | green                     | <b>5.30.759.039/0000</b> |
| 7.75 mm  | -     | -              | -        | blue                      | <b>5.30.759.040/0000</b> |
| 8 mm     | -     | -              | -        | red                       | <b>5.30.759.041/0000</b> |
| 8.25 mm  | -     | -              | -        | blue transparent          | <b>5.30.759.042/0000</b> |
| 10.00 mm | -     | -              | -        | black                     | <b>5.30.759.043/0104</b> |

Required spacer length = Overall height of key - front panel thickness - 0.5 mm (area embossing).

5

Others

| Length   | Width | Overall height | Diameter | Colour                    | Order no.         |
|----------|-------|----------------|----------|---------------------------|-------------------|
| 8 mm     | -     | -              | -        | red                       | 5.30.759.116/0000 |
| 8.25 mm  | -     | -              | -        | blue transparent          | 5.30.759.117/0000 |
| 9 mm     | -     | -              | -        | blue                      | 5.30.759.254/0000 |
| 10.00 mm | -     | -              | -        | black                     | 5.30.759.124/0000 |
| 10.25 mm | -     | -              | -        | yellow orange transparent | 5.30.759.125/0000 |

Required spacer length = Overall height of key - front panel thickness - 0.5 mm (area embossing).



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331