


**DESCRIPTION**

The LX5530 is a power amplifier optimized for the FCC Unlicensed National Information Infrastructure (U-NII) band, HyperLAN2 and Japan WLAN applications in the 4.9 – 5.9 GHz frequency range. The PA is implemented as a three-stage monolithic microwave integrated circuit (MMIC) with active bias, on-chip input matching and output pre-matching. The device is manufactured with an InGaP/GaAs Heterojunction Bipolar Transistor (HBT) IC process (MOCVD). It operates with a single positive voltage supply of 3 – 5V, with high power gain of up to 33dB. When operated at 5V supply voltage, it provides up to +25dBm linear output power for 802.11a OFDM spectrum mask compliance, and low EVM of 3% for up to +23dBm output power in the 4.9-5.9GHz band.

The LX5530 also features an on-chip power detector at the output port of the PA to help reduce BOM cost and PCB space for implementation of power control in a typical wireless system. The power detector is integrated with a temperature-compensated bias network and provides very stable response across a wide range of output power levels, over temperature extremes from -40 to +85°C.

The LX5530 is available in a 16-pin 3mmx3mm micro-lead package (MLP). The compact footprint, low profile, and excellent thermal capability makes the LX5530 an ideal solution for broadband, high-gain power amplifier requirements for IEEE 802.11a, and the emerging 802.16 WiMAX applications.


**IMPORTANT:** For the most current data, consult MICROSEMI's website: <http://www.microsemi.com>

**BLOCK DIAGRAM**

**KEY FEATURES**

- Broadband 4.9 – 5.9GHz Operation
- Advanced InGaP HBT
- Single-Polarity 3 – 5V Supply
- Power Gain up to ~ 33dB for  $V_C=5V$ ,  $I_{CQ} = 250mA$
- Power Gain > ~28dB across 4.9-5.85GHz
- OFDM Mask Compliance Power  $P_{out} \sim +25dBm$  over 4.9-5.85GHz (ACPR ~ -50dBc @  $\pm 30MHz$  Offset)
- $P_{out}$  up to +23dBm with EVM ~3% ( $V_C = 5V$ )
- EVM < ~2.5% for  $P_{out} = +21dBm$  across 4.9-5.85GHz ( $V_C = 5V$ )
- EVM < ~2.5% for  $P_{out} = +19dBm$  across 4.9-5.85GHz ( $V_C = 4V$ )
- Total Current ~250mA for  $P_{out} = +20dBm$ , Duty Cycle = 99% ( $V_C = 4V$ )
- Complete On-Chip Input Match
- Simple Output Match for Optimal Broadband EVM
- On-Chip RF Decoupling
- Temperature-Compensated On-Chip Output Power Detector with Wide Dynamic Range
- Small Footprint: 3x3mm
- Low Profile: 0.9mm

**APPLICATIONS**

- FCC U-NII Wireless
- IEEE 802.11a
- HyperLAN2
- 5GHz Cordless Phone
- IEEE 802.16 WiMAX

**3X3MM MLP PACKAGE**

**PACKAGE ORDER INFO**

<b>LQ</b>	Plastic MLPQ
	16 pin
	RoHS Compliant / Pb-free
	<b>LX5530LQ</b>

Note: Available in Tape & Reel. Append the letters "TR" to the part number. (i.e. LX5530LQ-TR)



**Microsemi**

## INFORMATION

*Thank you for your interest in Microsemi® IPG products.*

The full data sheet for this device contains proprietary information.

To obtain a copy, please contact your local Microsemi sales representative. The name of your local representative can be obtained at the following link

<http://www.microsemi.com/contact/contactfind.asp>

**or**

Contact us directly by sending an email to:

[IPGdatasheets@microsemi.com](mailto:IPGdatasheets@microsemi.com)

Be sure to specify the data sheet you are requesting and include your company name and contact information and or vcard.

*We look forward to hearing from you.*



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331