Inline Holder for JCASE™ Style Fuses



Specifications

Maximum Voltage Rating:	58V
Maximum Current Rating:	See table below.
Cable Insulation	GXL, 125˚C
Operating Temperature Range:	-40˚C to +125˚C
Max. Fuse Insertion Force:	49N

This product is an In-line fuse holder for use with either standard or Low Profile JCASE™ fuses, 20A - 60A. It offers size and weight savings compared to MAXI™ fuseholders, and has an optional protective cover for splash resistance. Standard product will have two 102mm red wire leads. Wire length and insulation color can be customized upon request. Tinned wires also available upon request. All customizations have minimum order requirements. Contact Littelfuse sales representative for details.

There are two available mounting options: One version with mounting brackets, and one with a mounting hole through the body.

Part Number	Description	Cover	Mounting	Wire Size	Fuse Rating
0FHJ1001G	Standard JCASE Holder	None	Standard Thru-Hole	10AWG	40 A max
0FHJ1002G	Standard JCASE Holder	None	Standard Thru-Hole	8AWG	60 A max
0FHJ2001G	Standard JCASE Holder	None	Mounting Bracket	10AWG	40 A max
0FHJ2002G	Standard JCASE Holde	None	Mounting Bracket	8AWG	60 A max
FHJC1001G	Standard JCASE Holder	Yes	Standard Thru-Hole	10AWG	40 A max
FHJC1002G	Standard JCASE Holder	Yes	Standard Thru-Hole	8AWG	60 A max
FHJC2001G	Standard JCASE Holder	Yes	Mounting Bracket	10AWG	40 A max
FHJC2002G	Standard JCASE Holder	Yes	Mounting Bracket	8AWG	60 A max
HLJC1001G	Low Profile JCASE Holder	Yes	Standard Thru-Hole	10AWG	40 A max
HLJC1002G	Low Profile JCASE Holder	Yes	Standard Thru-Hole	8AWG	40 A max
HLJC2001G	Low Profile JCASE Holder	Yes	Mounting Bracket	10AWG	40 A max
HLJC2002G	Low Profile JCASE Holder	Yes	Mounting Bracket	8AWG	40 A max


*Note: XXXX1 Series includes 4.0mm diameter mounting thru-hole; XXXX2 Series includes mounting brackets

©2009 Littelfuse, Inc.

Specifications are subject to change without notice.
Please refer to www.littelfuse.com for current information.

Inline Holder for JCASE™ Style Fuses

"A"	"B"	"C"	"D"	LEAD "A" COLOR	LEAD "B" COLOR	INSULATION TYPE
102.0	102.0	9.0	9.0	RED	RED	GXL (STANDARD)



Standard hole only included with XXXX2000 series.

©2009 Littelfuse, Inc.

Specifications are subject to change without notice.
Please refer to www.littelfuse.com for current information.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331