


## Universal LED, $\varnothing$ 1.8 mm Tinted Diffused Miniplast Package

### Features

- Three colors
- For DC and pulse operation
- Luminous intensity categorized
- End-to-end stackable in centre-to-centre spacing of 0.1" (2.54 mm)
- Lead-free device



19229



### Applications

General indicating and lighting purposes

### Parts Table

| Part     | Color, Luminous Intensity                  | Angle of Half Intensity ( $\pm\phi$ ) | Technology   |
|----------|--|---------------------------------------|--------------|
| TLUO2400 | Red, $I_V > 1.6$ mcd                       | 20 °                                  | GaAsP on GaP |
| TLUO2401 | Red, $I_V = (4 \text{ to } 20)$ mcd        | 20 °                                  | GaAsP on GaP |
| TLUY2400 | Yellow, $I_V > 1$ mcd                      | 20 °                                  | GaAsP on GaP |
| TLUY2401 | Yellow, $I_V = (2.5 \text{ to } 12.5)$ mcd | 20 °                                  | GaAsP on GaP |
| TLUG2400 | Green, $I_V > 1.6$ mcd                     | 20 °                                  | GaP on GaP   |
| TLUG2401 | Green, $I_V = (4 \text{ to } 20)$ mcd      | 20 °                                  | GaP on GaP   |

### Absolute Maximum Ratings

$T_{amb} = 25$  °C, unless otherwise specified

TLUO240. , TLUY240. , TLUG240.

| Parameter                           | Test condition               | Part     | Symbol     | Value         | Unit |
|-------------------------------------|------------------------------|----------|------------|---------------|------|
| Reverse voltage                     |                              |          | $V_R$      | 6             | V    |
| DC Forward current                  |                              | TLUO2400 | $I_F$      | 30            | mA   |
|                                     |                              | TLUY2400 | $I_F$      | 30            | mA   |
|                                     |                              | TLUG2400 | $I_F$      | 30            | mA   |
| Surge forward current               | $t_p \leq 10$ $\mu$ s        |          | $I_{FSM}$  | 1             | A    |
| Power dissipation                   | $T_{amb} \leq 55$ °C         | TLUO2400 | $P_V$      | 100           | mW   |
|                                     |                              | TLUY2400 | $P_V$      | 100           | mW   |
|                                     |                              | TLUG2400 | $P_V$      | 100           | mW   |
| Junction temperature                |                              |          | $T_j$      | 100           | °C   |
| Operating temperature range         |                              |          | $T_{amb}$  | - 40 to + 100 | °C   |
| Storage temperature range           |                              |          | $T_{stg}$  | - 55 to + 100 | °C   |
| Soldering temperature               | $t \leq 3$ s, 2 mm from body |          | $T_{sd}$   | 260           | °C   |
|                                     | $t \leq 5$ s, 4 mm from body |          | $T_{sd}$   | 260           | °C   |
| Thermal resistance junction/ambient |                              | TLUO2400 | $R_{thJA}$ | 450           | K/W  |
|                                     |                              | TLUY2400 | $R_{thJA}$ | 450           | K/W  |
|                                     |                              | TLUG2400 | $R_{thJA}$ | 450           | K/W  |

### Optical and Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

#### Red

##### TLUO240.

| Parameter                        | Test condition                | Part     | Symbol      | Min | Typ.     | Max | Unit |
|----------------------------------|-------------------------------|----------|-------------|-----|----------|-----|------|
| Luminous intensity <sup>1)</sup> | $I_F = 10\text{ mA}$          | TLUO2400 | $I_V$       | 1.6 | 2        |     | mcd  |
|                                  |                               | TLUO2401 | $I_V$       | 4   | 5        | 20  | mcd  |
| Dominant wavelength              | $I_F = 10\text{ mA}$          |          | $\lambda_d$ | 612 |          | 625 | nm   |
| Peak wavelength                  | $I_F = 10\text{ mA}$          |          | $\lambda_p$ |     | 630      |     | nm   |
| Angle of half intensity          | $I_F = 10\text{ mA}$          |          | $\phi$      |     | $\pm 20$ |     | deg  |
| Forward voltage                  | $I_F = 20\text{ mA}$          |          | $V_F$       |     | 2        | 3   | V    |
| Reverse voltage                  | $I_R = 10\text{ }\mu\text{A}$ |          | $V_R$       | 6   | 15       |     | V    |
| Junction capacitance             | $V_R = 0, f = 1\text{ MHz}$   |          | $C_j$       |     | 50       |     | pF   |

<sup>1)</sup> in one Packing Unit  $I_{Vmin}/I_{Vmax} \leq 0.5$

#### Yellow

##### TLUY240.

| Parameter                        | Test condition                | Part     | Symbol      | Min | Typ.     | Max  | Unit |
|----------------------------------|-------------------------------|----------|-------------|-----|----------|------|------|
| Luminous intensity <sup>1)</sup> | $I_F = 10\text{ mA}$          | TLUY2400 | $I_V$       | 1   | 4        |      | mcd  |
|                                  |                               | TLUY2401 | $I_V$       | 2.5 | 8        | 12.5 | mcd  |
| Dominant wavelength              | $I_F = 10\text{ mA}$          |          | $\lambda_d$ | 581 |          | 594  | nm   |
| Peak wavelength                  | $I_F = 10\text{ mA}$          |          | $\lambda_p$ |     | 585      |      | nm   |
| Angle of half intensity          | $I_F = 10\text{ mA}$          |          | $\phi$      |     | $\pm 20$ |      | deg  |
| Forward voltage                  | $I_F = 20\text{ mA}$          |          | $V_F$       |     | 2.4      | 3    | V    |
| Reverse voltage                  | $I_R = 10\text{ }\mu\text{A}$ |          | $V_R$       | 6   | 15       |      | V    |
| Junction capacitance             | $V_R = 0, f = 1\text{ MHz}$   |          | $C_j$       |     | 50       |      | pF   |

<sup>1)</sup> in one Packing Unit  $I_{Vmin}/I_{Vmax} \leq 0.5$

#### Green

##### TLUG240.

| Parameter                        | Test condition                | Part     | Symbol      | Min | Typ.     | Max | Unit |
|----------------------------------|-------------------------------|----------|-------------|-----|----------|-----|------|
| Luminous intensity <sup>1)</sup> | $I_F = 10\text{ mA}$          | TLUG2400 | $I_V$       | 1.6 | 5        |     | mcd  |
|                                  |                               | TLUG2401 | $I_V$       | 4   | 12       | 20  | mcd  |
| Dominant wavelength              | $I_F = 10\text{ mA}$          |          | $\lambda_d$ | 562 |          | 575 | nm   |
| Peak wavelength                  | $I_F = 10\text{ mA}$          |          | $\lambda_p$ |     | 565      |     | nm   |
| Angle of half intensity          | $I_F = 10\text{ mA}$          |          | $\phi$      |     | $\pm 20$ |     | deg  |
| Forward voltage                  | $I_F = 20\text{ mA}$          |          | $V_F$       |     | 2.4      | 3   | V    |
| Reverse voltage                  | $I_R = 10\text{ }\mu\text{A}$ |          | $V_R$       | 6   | 15       |     | V    |
| Junction capacitance             | $V_R = 0, f = 1\text{ MHz}$   |          | $C_j$       |     | 50       |     | pF   |

<sup>1)</sup> in one Packing Unit  $I_{Vmin}/I_{Vmax} \leq 0.5$

## Typical Characteristics ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)




Figure 1. Power Dissipation vs. Ambient Temperature




Figure 4. Rel. Luminous Intensity vs. Angular Displacement




Figure 2. Forward Current vs. Ambient Temperature




Figure 5. Forward Current vs. Forward Voltage




Figure 3. Forward Current vs. Pulse Length




Figure 6. Forward Current vs. Forward Voltage




Figure 7. Rel. Luminous Intensity vs. Ambient Temperature




Figure 10. Relative Intensity vs. Wavelength




Figure 8. Rel. Lumin. Intensity vs. Forw. Current/Duty Cycle




Figure 11. Forward Current vs. Forward Voltage




Figure 9. Relative Luminous Intensity vs. Forward Current




Figure 12. Rel. Luminous Intensity vs. Ambient Temperature




Figure 13. Rel. Lumin. Intensity vs. Forw. Current/Duty Cycle




Figure 16. Forward Current vs. Forward Voltage




Figure 14. Relative Luminous Intensity vs. Forward Current




Figure 17. Rel. Luminous Intensity vs. Ambient Temperature




Figure 15. Relative Intensity vs. Wavelength




Figure 18. Specific Luminous Intensity vs. Forward Current




Figure 19. Relative Luminous Intensity vs. Forward Current





Figure 20. Relative Intensity vs. Wavelength

## Package Dimensions in mm





## **Ozone Depleting Substances Policy Statement**

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

**Vishay Semiconductor GmbH** has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

**Vishay Semiconductor GmbH** can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

**We reserve the right to make changes to improve technical design  
and may do so without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331