

# 3M™ Static Shielding Bag SCC 1000

## Static Shielding Bag ~ Metal-In

This transparent, metallized static shield bag helps provide a static safe environment for sensitive electronic devices. Four layer construction. Polyester dielectric and metal layer provide Faraday effect shielding of ESD and fields. Tribocharging is minimized by the specially processed polyethylene. Flat and zipper closure styles. Coded for QC traceability. These bags are tested to meet or exceed certain electrical and physical requirements of ANSI/ESD S541, EIA 625, and to be ANSI/ESD S20.20 program compliant.

## Specifications

| <b>Electrical Properties:</b>    | Typical Values                   | Test Method*             |
|----------------------------------|----------------------------------|--------------------------|
| Surface Resistivity / Resistance | ASTM D257 or                     | ANSI/ESD STM11.11        |
| Interior                         | <10 <sup>12</sup> ohms/square or | <10 <sup>11</sup> ohms   |
| Exterior                         | <10 <sup>12</sup> ohms/square or | <10 <sup>11</sup> ohms   |
| Metal                            | 100 ohms                         |                          |
| Static Shielding                 | < 30 volts                       | EIA 541                  |
| Static Shielding                 | < 10 nJ                          | ANSI/ESD STM11.31        |
| Static Decay                     | < 2 seconds                      | MIL-STD-3010 4046        |
| Charge Generation                |                                  |                          |
| PTFE                             | 0.09 nC/sq.in.                   | Modified Inclined Plane  |
| Quartz                           | 0.01 nC/sq.in.                   |                          |
| <b>Physical Properties:</b>      |                                  |                          |
| Tensile Strength                 | 4700 PSI                         | ASTM D 882               |
| Seam Strength                    | > 10 lbs                         | ASTM D 882               |
| Light Transmission               | 40 %                             | Tobias                   |
| Heat Sealing Conditions          |                                  |                          |
| Temperature                      | 250°F - 375° F                   |                          |
| Time                             | 0.5 - 3.5 seconds                |                          |
| Pressure                         | 30 - 70 PSI                      |                          |
| Thickness                        | 3 mils**                         | MIL-STD-3010 1003 +/-20% |
| Silicone or Amine Content        | Not detected                     | FTIR                     |

\*\* tolerance +/-15%

See 3M Data Sheets for these related items:

Static Warning Labels  
Heat Sealer

Open Top

ZipTop




Sizes on Page 2



## Material Structure

SCC 1000 open top and ZipTop static shielding bags are manufactured from industry approved Polyester/Metal/Polyethylene laminates. The polyester dielectric in concert with the metal layer provide Faraday Effect shielding of an Electrostatic Discharge (ESD). The metal layer prevents the penetration of damaging electrostatic fields. Tribocharging is minimized by the specially processed polyethylene.



## Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

## Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

\*This product is not on the Qualified Product Listing under the Defense Standardization Program.

P R O D U C T D A T A S H E E T

## SCC 1000 Static Shielding Bag METAL-IN

**PRODUCT**  
STATIC SHIELDING BAG, OPEN TOP AND ZIPTOP

**ITEM NUMBER**  
100(W")(L")

**DATASHEET**  
1100-A  
98-0799-1068-7

3M Electronic Solutions Division  
6801 River Place Blvd  
Austin, TX 78726-9000  
US and Canada: 866-722-3736  
Fax: 866-722-3735  
Intl: 919-718-0000; Fax: 919-774-8174  
email: 3Mstaticinfo@mmm.com; www.3Mstatic.com

3M is a trademark of 3M Company.  
All other trademarks herein are the property  
of their respective owners.



© 3M 2012. All rights reserved.


## 3M™ Static Shielding Bag SCC 1000

### Open Top Static Shielding Bag ~ Metal-In


| W"x L"   | P/N      | W"x L"  | P/N     | W"x L"  | P/N     |
|----------|----------|---------|---------|---------|---------|
| 2 x 3    | 10023    | 7 x 8   | 10078   | 12 x 18 | 1001218 |
| 2 x 4    | 10024    | 7 x 10  | 100710  | 12 x 24 | 1001224 |
| 2 x 6    | 10026    | 7 x 11  | 100711  | 12 x 25 | 1001225 |
| 3 x 5    | 10035    | 7 x 15  | 100715  | 12 x 30 | 1001230 |
| 4 x 4    | 10044    | 7 x 16  | 100716  | 14 x 16 | 1001416 |
| 4 x 6    | 10046    | 8 x 8   | 10088   | 14 x 18 | 1001418 |
| 4 x 8    | 10048    | 8 x 10  | 100810  | 14 x 20 | 1001420 |
| 4 x 24   | 100424   | 8 x 12  | 100812  | 14 x 30 | 1001430 |
| 4 x 26   | 100426   | 8 x 14  | 100814  | 15 x 18 | 1001518 |
| 4 x 30   | 100430   | 8 x 16  | 100816  | 16 x 18 | 1001618 |
| 5 x 6    | 10056    | 8 x 18  | 100818  | 16 x 20 | 1001620 |
| 5 x 7    | 10057    | 8 x 24  | 100824  | 16 x 24 | 1001624 |
| 5 x 8    | 10058    | 8 x 30  | 100830  | 16 x 30 | 1001630 |
| 5 x 10   | 100510   | 9 x 12  | 100912  | 18 x 18 | 1001818 |
| 6 x 8    | 10068    | 10 x 12 | 1001012 | 18 x 20 | 1001820 |
| 6 x 9    | 10069    | 10 x 14 | 1001014 | 18 x 24 | 1001824 |
| 6 x 10   | 100610   | 10 x 16 | 1001016 | 18 x 30 | 1001830 |
| 6 x 12   | 100612   | 10 x 18 | 1001018 | 20 x 20 | 1002020 |
| 6 x 14   | 100614   | 10 x 24 | 1001024 | 20 x 24 | 1002024 |
| 6 x 16   | 100616   | 10 x 26 | 1001026 | 22 x 24 | 1002224 |
| 6 x 18   | 100618   | 10 x 30 | 1001030 | 24 x 24 | 1002424 |
| 6 x 24   | 100624   | 11 x 14 | 1001114 | 24 x 30 | 1002430 |
| 6 x 26   | 100626   | 11 x 15 | 1001115 | 24 x 36 | 1002436 |
| 6 x 30   | 100630   | 12 x 12 | 1001212 | 30 x 24 | 1003024 |
| 6.5 x 10 | 1006.510 | 12 x 14 | 1001214 |         |         |
| 6.5 x 16 | 1006.516 | 12 x 16 | 1001216 |         |         |

- All standard sizes in-stock/same day shipment.
- Width is measured from inside seam to inside seam.
- Length is measured from the top edge to the bottom fold.
- Opening is in the "width" dimension.
- Custom bag sizes, custom printing, and custom hot stamping are available.
- Most sizes are packed 100 per case.  
Small sizes are packed 1000 or 500 per case.

### 3M SCC 1000 Open Top



### 3M SCC 1000 ZipTop



## 3M™ Static Shielding Bag SCC 1000 ZipTop™

### Recloseable Static Shielding Bag ~ Metal-In

| W"x L" | P/N    | W" x L" | P/N     | W" x L" | P/N     |
|--------|--------|---------|---------|---------|---------|
| 2 x 3  | 30023  | 6 x 24  | 300624  | 11 x 15 | 3001115 |
| 3 x 3  | 30033  | 6 x 30  | 300630  | 12 x 12 | 3001212 |
| 3 x 5  | 30035  | 7 x 15  | 300715  | 12 x 16 | 3001216 |
| 4 x 4  | 30044  | 8 x 8   | 30088   | 12 x 18 | 3001218 |
| 4 x 6  | 30046  | 8 x 10  | 300810  | 14 x 18 | 3001418 |
| 4 x 8  | 30048  | 8 x 12  | 300812  | 15 x 18 | 3001518 |
| 4 x 24 | 300424 | 9 x 12  | 300912  | 16 x 24 | 3001624 |
| 4 x 30 | 300430 | 10 x 10 | 3001010 | 18 x 18 | 3001818 |
| 5 x 8  | 30058  | 10 x 12 | 3001012 | 18 x 24 | 3001824 |
| 5 x 10 | 300510 | 10 x 14 | 3001014 | 20 x 24 | 3002024 |
| 6 x 8  | 30068  | 10 x 24 | 3001024 | 24 x 24 | 3002424 |
| 6 x 10 | 300610 | 10 x 30 | 3001030 |         |         |

## P R O D U C T D A T A S H E E T

### SCC 1000 Static Shielding Bag METAL-IN

**PRODUCT**  
STATIC SHIELDING BAG, OPEN TOP AND ZIPTOP

**ITEM NUMBER**  
100(W")(L")

**DATASHEET**  
1100-A  
98-0799-1068-7

3M Electronic Solutions Division  
6801 River Place Blvd  
Austin, TX 78726-9000  
US and Canada: 866-722-3736  
Fax: 866-722-3735  
Intl: 919-718-0000; Fax: 919-774-8174  
email: 3Mstaticinfo@mmm.com; www.3Mstatic.com

3M is a trademark of 3M Company.  
All other trademarks herein are the property  
of their respective owners.



© 3M 2012. All rights reserved.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331