

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0432550161

Status:

Active

Overview:

mlx

Description:

6.35mm (.250") Pitch MLX™ Power Connector Header, Vertical, with Plastic Polarizing Peg, 15 Circuits, Polyester 94V-0, Tin Plating, White (Translucent), Lead-free

Documents:

3D Model

Drawing (PDF)

Product Specification PSX-42002-0001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

UL

LR19980

E29179

General

Product Family

Series

Application

Comments

Overview

Product Name

PCB Headers

43255

Wire-to-Board

High Vibration Application

mlx

MLX™

Physical

Breakaway

Circuits (Loaded)

Circuits (maximum)

Color - Resin

Durability (mating cycles max)

First Mate / Last Break

Flammability

Glow-Wire Compliant

Guide to Mating Part

Keying to Mating Part

Lock to Mating Part

Mated Height (in)

Mated Height (mm)

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Number of Rows

Orientation

PC Tail Length (in)

PC Tail Length (mm)

PCB Locator

PCB Retention

PCB Thickness Recommended (in)

PCB Thickness Recommended (mm)

Packaging Type

Pitch - Mating Interface (in)

Pitch - Mating Interface (mm)

Pitch - Term. Interface (in)

Pitch - Term. Interface (mm)

Plating min: Mating (µin)

Plating min: Mating (µm)

Polarized to Mating Part

No

15

15

Natural

50

No

94V-2

Yes

Yes

Yes

Yes

1.195 In

30.35 mm

Phosphor Bronze

Tin

Tin

Nylon

3

Vertical

0.170 In

4.30 mm

Yes

Yes

0.062 In

1.57 mm

Bag

0.250 In

6.35 mm


0.250 In

6.35 mm

140

3.5

Yes



Series

image - Reference only

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
43255Series

Mates With
42021 MLX™ Power Crimp Housing Plug.
42024 MLX Crimp Terminal

Polarized to PCB	Yes
Shrouded	Fully
Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-55°C to +105°C
Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	9A
Voltage - Maximum	600V

Solder Process Data

Duration at Max. Process Temperature (seconds)	10
Lead-free Process Capability	Wave Capable (TH only)
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-43255-003
Product Specification	PSX-42002-0001

This document was generated on 05/24/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
	ITEM NO.	CIRCUIT SIZE	MATERIAL COLOR (SEE NOTE 1)	PIN (1) OR SOCKET (2) TERMINALS	TERMINAL PLATING (SEE NOTE 2)	TERMINAL LENGTH (SEE NOTE 3)	"A" DIM ±.015													
M	43255-0057	2	A	2	A	1	.17/(4,3)													
	43255-0058		A	2	B	1														
	43255-0059		B	1	A	1														
	43255-0060		B	1	B	1														
	43255-0061		A	2	A	2	.23/(5,8)													
	43255-0062		A	2	B	2														
L	43255-0063	3	B	1	A	2														
	43255-0064		B	1	B	2														
	43255-0065		A	2	A	1	.17/(4,3)													
	43255-0066		A	2	B	1														
	43255-0067		B	1	A	1														
	43255-0068		B	1	B	1														
K	43255-0069	4	A	2	A	2	.23/(5,8)													
	43255-0070		A	2	B	2														
	43255-0071		B	1	A	2														
	43255-0072		B	1	B	2														
	43255-0073		A	2	A	1	.17/(4,3)													
	43255-0074		A	2	B	1														
J	43255-0075	6	B	1	A	1														
	43255-0076		B	1	B	1														
	43255-0077		A	2	A	2	.23/(5,8)													
	43255-0078		A	2	B	2														
	43255-0079		B	1	A	2														
	43255-0080		B	1	B	2														
I	43255-0081	9	A	2	A	1	.17/(4,3)													
	43255-0082		A	2	B	1														
	43255-0083		B	1	A	1														
	43255-0084		B	1	B	1														
	43255-0085		A	2	A	2	.23/(5,8)													
	43255-0086		A	2	B	2														
H	43255-0087	12	B	1	A	2														
	43255-0088		B	1	B	2														
	43255-0089		A	2	A	1	.17/(4,3)													
	43255-0090		A	2	B	1														
	43255-0091		B	1	A	1														
	43255-0092		B	1	B	1														
G	43255-0093	15	A	2	A	2	.23/(5,8)													
	43255-0094		A	2	B	2														
	43255-0095		B	1	A	2														
	43255-0096		B	1	B	2														
	43255-0097		A	2	A	1	.17/(4,3)													
	43255-0098		A	2	B	1														
F	43255-0099	15	B	1	A	1														
	43255-0100		B	1	B	1														
	43255-0101		A	2	A	2	.23/(5,8)													
	43255-0102		A	2	B	2														
	43255-0103		B	1	A	2														
	43255-0104		B	1	B	2														
E	43255-0105	15	A	2	A	1	.17/(4,3)													
	43255-0106		A	2	B	1														
	43255-0107		B	1	A	1														
	43255-0108		B	1	B	1														
	43255-0109		A	2	A	2	.23/(5,8)													
	43255-0110		A	2	B	2														
	43255-0111		B	1	A	2														
	43255-0112		B	1	B	2														

RoHS COMPLIANT

EC NO: D2007-0146
DRAWN BY: CHOKKOSUDHIR
CHKD BY: SSUDHIR
APP: SSUDHIR

2006/11/03
2006/11/03
2006/11/03

QUALITY SYMBOLS
▽=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)
mm INCH
4 PLACES ± ±
3 PLACES ± ±
2 PLACES ± ±
1 PLACE ± ±
ANGULAR ± ±

DIMENSION STYLE
IN/MM
DRAWN BY: SSUDHIR
CHECKED BY: GJLOWE
APPROVED BY: GJLOWE
DATE: 2004/06/08
DATE: 2004/06/08
DATE: 2004/06/08

SCALE

INCH

DESIGN UNITS
INCH

THIRD ANGLE PROJECTION

HEADER HOUSING ASSEMBLY
0.84/(2.13) DIA. SERIES
COMPLIANT-POLARIZING PEG
MOLEX INCORPORATED

MATERIAL NO.
SEE CHART

DOCUMENT NO.
SDA-43255-00**

SHEET NO.
3 OF 4

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

SIZE
A1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

Rev. D 2004/04/02



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331