

AMP-200-EUR Series TRMS Clamp Meters

The Modern Evolution of the Professional Clamp Meter

Beha-Amprobe's AMP-210-EUR and AMP-220-EUR 600 A TRMS Clamp Meters offer a complete range of measuring functions for today's modern electrical environments. Both models feature True-RMS sensing, low pass filters and fast response processors for quick, error-free measurements. The Amp-Tip function allows for precise measurement of current down to the tenth of an Amp, enabling accurate current measurement of both large and small diameter wires.

AMP-200-EUR Series Features

- **True-RMS**
- **Low Pass Filter**
- **Amp-Tip Functions**
- **Non-Contact Voltage Detection (NCV)**
- **Audible Continuity and Diode Test**
- **Data Hold, Relative Zero**
- **Large LCD Backlit Display**
- **Safety Rated:**
CAT III 600 V



AMP-210-EUR
AC Clamp Meter



AMP-220-EUR
AC/DC Clamp Meter

AMP-200-EUR Series Product Details

True-RMS for accurate voltage measurements in noisy environments.

Low pass filter for current and voltage measurements on variable frequency drives.

Amp-Tip function for precise low current measurement of small diameter wires down to 0.1 Amp to help with electrical system troubleshooting.

Non-contact voltage detection (NCV)

Audible continuity and diode test

Data hold, relative zero, MAX/MIN/AVG mode

Large LCD backlit display

Safety rated
CAT III 600 V



Measurements:

Voltage
Up to 600 V AC/DC

AC current
Up to 600 A

DC Current
Up to 600 A
(AMP-220-EUR only)

Frequency
5.00 to 999.9 Hz

Resistance
Up to 60.00 k Ω

Capacitance
Up to 2500 μ F



AMP-200-EUR Series Applications



AMP-210-EUR AC Clamp Meter



AMP-220-EUR AC/DC Clamp Meter

- **Accurate measurement of current, voltage and frequency** on all electrical systems including distorted, non-sinusoidal signals (True-RMS function) and variable frequency drives (low-pass filter).
- **Capacitance measurement** for start and run motor capacitors.
- **Resistance and continuity** functions to verify quality of electrical connections and to check if motor and transformer coils are working properly.
- **Low pass filter** allows measurement of current and voltage on variable frequency drives (motors with speed controlled by frequency). Without this feature, the meter would provide erroneous readings when measuring voltage and current.

AMP-200-EUR and AMP-300-EUR Detailed Specifications

Model	AMP-210-EUR	AMP-220-EUR	AMP-310-EUR	AMP-320-EUR	AMP-330-EUR
	AC Clamp Meter Electrical	AC/DC Clamp Meter Electrical	AC Clamp Meter HVAC	AC/DC Clamp Meter Electrical Motor Maintenance	AC/DC 1000 A Clamp Meter Industrial Motor Maintenance
Safety Rating	CAT III 600 V	CAT III 600 V	CAT III 600 V	CAT III 600 V	CAT IV 600 V, CAT III 1000 V
Jaw Opening	1.18 in (30 mm)	1.37 in (35 mm)	1.18 in (30 mm)	1.37 in (35 mm)	2.0 in (51 mm)
AC Voltage (True-RMS)	Range: 0 to 600.0 V Accuracy: $\pm 1.0\% + 5\text{LSD}$ (50 to 60 Hz)		Range: 0 to 600.0 V Accuracy: $\pm 1.0\% + 5\text{LSD}$ (50 to 60 Hz)		Range: 0 to 1000 V Accuracy: $\pm 0.8\% + 5\text{LSD}$ (50 to 60 Hz) $\pm 1.5\% + 5\text{LSD}$ (20 to 200 Hz) $\pm 10\% + 5\text{LSD}$ (200 to 400 Hz)
DC Voltage	Range: 0 to 600.0 V Accuracy: $\pm 1.0\% + 5\text{LSD}$		Range: 0 to 600.0 V Accuracy: $\pm 1.0\% + 5\text{LSD}$		Range: 0 to 1000 V Accuracy: $\pm 0.8\% + 5\text{LSD}$
AC+DC Voltage	–	Range: 0 to 600.0 V Accuracy: $1.2\% \pm 7\text{LSD}$ (DC, 50 to 60 Hz)	–	Range: 0 to 600.0 V Accuracy: $1.2\% \pm 7\text{LSD}$ (DC, 50 to 60 Hz)	Range: 0 to 1000 V Accuracy: $\pm 1.0\% + 7\text{LSD}$ (50 to 60 Hz) $\pm 1.8\% + 7\text{LSD}$ (DC, 40 to 200 Hz) $\pm 12\% + 7\text{LSD}$ (200 to 400 Hz)
AC Current (True-RMS)	Range: 0 to 600.0 A Accuracy: $\pm 1.8\% + 5\text{LSD}$ (50 to 100 Hz) $\pm 2.0\% + 5\text{LSD}$ (100 to 400 Hz)		Range: 0 to 600.0 A Accuracy: $\pm 1.8\% + 5\text{LSD}$ (50 to 100 Hz) $\pm 2.0\% + 5\text{LSD}$ (100 to 400 Hz)		Range: 0 to 1000 A Accuracy: $\pm 1.8\% + 5\text{LSD}$ (40 to 100 Hz) $\pm 2.2\% + 5\text{LSD}$ (100 to 400 Hz)
DC Current	–	Range: 0 to 600.0 A Accuracy: $\pm 2.0\% + 5\text{LSD}$	–	Range: 0 to 600.0 A Accuracy: $\pm 2.0\% + 5\text{LSD}$	Range: 0 to 1000 A Accuracy: $\pm 1.8\% + 5\text{LSD}$
AC+DC Current	–	Range: 0 to 600.0 A Accuracy: $\pm 2.2\% + 7\text{LSD}$ (DC, 50 to 100 Hz) $\pm 2.7\% + 7\text{LSD}$ (100 to 400 Hz)	–	Range: 0 to 600.0 A Accuracy: $\pm 2.2\% + 7\text{LSD}$ (DC, 50 to 100 Hz) $\pm 2.7\% + 7\text{LSD}$ (100 to 400 Hz)	Range: 0 to 1000 A Accuracy: $\pm 2.2\% + 7\text{LSD}$ (DC, 40 to 100 Hz) $\pm 2.5\% + 7\text{LSD}$ (100 to 400 Hz)
Precise Low Current AC	Range: 0 to 60.00 A Accuracy: $\pm 1.5\% + 5\text{LSD}$ (50 to 60 Hz)		Range: 0 to 60.00 A Accuracy: $\pm 1.5\% + 5\text{LSD}$ (50 to 60 Hz)		Range: 0 to 60.00 A Accuracy: $\pm 1.5\% + 5\text{LSD}$ (0.00 to 20.00 A, 40 to 100 Hz) $\pm 2.0\% + 5\text{LSD}$ (0.00 to 20.00 A, 100 to 400 Hz) $\pm 3.0\% + 5\text{LSD}$ (20.00 to 60.00 A, 40 to 100 Hz) $\pm 3.0\% + 5\text{LSD}$ (20.00 to 60.00 A, 100 to 400 Hz)
Precise Low Current DC	–	Range: 0 to 60.00 A Accuracy: $\pm 2.0\% + 5\text{LSD}$	–	Range: 0 to 60.00 A Accuracy: $\pm 2.0\% + 5\text{LSD}$	Range: 0 to 60.00 A Accuracy: $\pm 1.5\% + 5\text{LSD}$ (0.00 to 20.00 A) $\pm 3.0\% + 5\text{LSD}$ (20.00 to 60.00 A)
Precise Low Current AC+DC	–	Range: 0 to 60.00 A Accuracy: $\pm 2.0\% + 5\text{LSD}$ (DC, 50 to 60 Hz)	–	Range: 0 to 60.00 A Accuracy: $\pm 2.0\% + 5\text{LSD}$ (DC, 50 to 60 Hz)	Range: 0 to 60.00 A Accuracy: $\pm 2.0\% + 7\text{LSD}$ (0.00 to 20.00 A, DC, 40 to 100 Hz) $\pm 2.2\% + 7\text{LSD}$ (0.00 to 20.00 A, 100 to 400 Hz) $\pm 3.0\% + 7\text{LSD}$ (20.00 to 60.00 A, DC, 40 to 100 Hz) $\pm 3.0\% + 7\text{LSD}$ (20.00 to 60.00 A, 100 to 400 Hz)
Frequency	Range: 5.00 to 999.9 Hz Accuracy: $\pm 1.0\% + 5\text{LSD}$ (600 V range) Range: 50.0 to 400.0 Hz Accuracy: $\pm 1.0\% + 5\text{LSD}$ (600 A range)		Range: 5.00 to 999.9 Hz Accuracy: $\pm 1.0\% + 5\text{LSD}$ (600 V range) Range: 50.0 to 400.0 Hz Accuracy: $\pm 1.0\% + 5\text{LSD}$ (600 A range)		Range: 5.00 to 999.9 Hz Accuracy: $\pm 1.0\% + 5\text{LSD}$ (1000 V range) Range: 40.0 to 400.0 Hz Accuracy: $\pm 1.0\% + 5\text{LSD}$ (1000 A range)
Resistance	Range: 0.0 to 60.00 k Ω Accuracy: $\pm 1.0\% + 5\text{LSD}$		Range: 0.0 to 60.00 k Ω Accuracy: $\pm 1.0\% + 5\text{LSD}$		
Capacitance	Range: 0.0 to 2500 μF Accuracy: $\pm 2.0\% + 4\text{LSD}$		Range: 0.0 to 2500 μF Accuracy: $\pm 2.0\% + 4\text{LSD}$		
Continuity Buzzer	ON $\leq 10 \Omega$ OFF $> 250 \Omega$		ON $\leq 10 \Omega$ OFF $> 250 \Omega$		
Non-Contact Voltage	20 to 440 V, 50/60 Hz		20 to 440 V, 50/60 Hz		
True-RMS	•	•	•	•	•
Low Pass Filter	•	•	•	•	•
Autoranging	•	•	•	•	•
Relative Zero	•	•	•	•	•
MAX/MIN/AVG	•	•	•	•	•
Diode Test	•	•	•	•	•
Data Hold	•	•	•	•	•
Backlight	•	•	•	•	•
Auto Power Off	•	•	•	•	•
AMP-300-EUR Series:					
DC Microamps	–	–	Range: 0.0 to 2000 μA Accuracy: $\pm 1.0\% + 5\text{LSD}$		
Temperature* (Type K thermocouple) *Error does not include Type-K thermocouple errors	–	–	Range: -40.0 to 752°F, -40.0 to 400°C Accuracy: -40.0 to 14.0°F ($\pm 1.0\% + 3.0^\circ\text{F}$), >14.0 to 99.9°F ($\pm 1.0\% + 1.5^\circ\text{F}$) 100 to 752°F ($\pm 1.0\% + 2^\circ\text{F}$), -40.0 to -10.0°C ($\pm 1.0\% + 1.5^\circ\text{C}$) >-10.0 to 99.9°C ($\pm 1.0\% + 0.8^\circ\text{C}$), 100 to 400°C ($\pm 1.0\% + 1^\circ\text{C}$)		
3-Phase and Motor Rotation Indication	–	–	Rotation-R for mains supply Rotation-M for motors		
Inrush Current	–	–	•	•	•
Peak Hold (Crest)	–	–	–	–	•
Work Light	–	–	–	–	•



Model	AMP-210-EUR	AMP-220-EUR	AMP-310-EUR	AMP-320-EUR	AMP-330-EUR
Display	3-5/6 digits 6000 counts	3-5/6 digits 6000 counts	3-5/6 digits 6000 counts	3-5/6 digits 6000 counts	3-5/6 digits 6000 counts
Polarity	Automatic	Automatic	Automatic	Automatic	Automatic
Update Rate	5 per second nominal	5 per second nominal	5 per second nominal	5 per second nominal	5 per second nominal
Operating Temperature	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	14 to 122°F (-10 to 50°C)
Relative Humidity	80% at 30°C, 50% at 40°C	80% at 30°C, 50% at 40°C	80% at 30°C, 50% at 40°C	80% at 30°C, 50% at 40°C	Non condensing at ≤10°C 90% at 10 to 30°C 75% at 30 to 40°C 45% at 40 to 50°C
Operating Altitude	0 to 2000 m	0 to 2000 m	0 to 2000 m	0 to 2000 m	0 to 2000 m
Pollution Degree	2	2	2	2	2
Storage Temperature	-4 to 140°F (-20°C to 60°C), < 80% RH	-4 to 140°F (-20°C to 60°C), < 80% RH	-4 to 140°F (-20°C to 60°C), < 80% RH	-4 to 140°F (-20°C to 60°C), < 80% RH	-4 to 140°F (-20°C to 60°C), < 80% RH
Temperature Coefficient	Nominal 0.15 x (specified accuracy)/ °C @ (0°C to 18°C or 28°C to 40°C)	Nominal 0.15 x (specified accuracy)/ °C @ (0°C to 18°C or 28°C to 40°C)	Nominal 0.15 x (specified accuracy)/ °C @ (0°C to 18°C or 28°C to 40°C)	Nominal 0.15 x (specified accuracy)/ °C @ (0°C to 18°C or 28°C to 40°C)	Nominal 0.10 x (specified accuracy)/ °C @ (0°C to 18°C or 28°C to 50°C)
Battery	Two AAA 1.5 V battery	Two AAA 1.5 V battery	Two AAA 1.5 V battery	Two AAA 1.5 V battery	Two AA 1.5 V battery
EMC	Meets EN 61326-1:2006	Meets EN 61326-1:2006	Meets EN 61326-1:2006	Meets EN 61326-1:2006	Meets EN 61326-1:2006
Safety Compliance	UL/IEC/EN 61010-1 ed. 3.0, IEC/EN 61010-2-033 ed. 1.0, CAN/CSA C22.2 NO. 61010-1 ed. 3.0, IEC/EN 61010-2-032 ed. 3.0 & IEC/EN 61010-031 ed. 1.1	UL/IEC/EN 61010-1 ed. 3.0, IEC/EN 61010-2-033 ed. 1.0, CAN/CSA C22.2 NO. 61010-1 ed. 3.0, IEC/EN 61010-2-032 ed. 3.0 & IEC/EN 61010-031 ed. 1.1	UL/IEC/EN 61010-1 ed. 3.0, IEC/EN 61010-2-033 ed. 1.0, CAN/CSA C22.2 NO. 61010-1 ed. 3.0, IEC/EN 61010-2-032 ed. 3.0 & IEC/EN 61010-031 ed. 1.1	UL/IEC/EN 61010-1 ed. 3.0, IEC/EN 61010-2-033 ed. 1.0, CAN/CSA C22.2 NO. 61010-1 ed. 3.0, IEC/EN 61010-2-032 ed. 3.0 & IEC/EN 61010-031 ed. 1.1	UL/IEC/EN 61010-1 ed. 3.0, IEC/EN 61010-2-033 ed. 1.0, CAN/CSA C22.2 NO. 61010-1 ed. 3.0, IEC/EN 61010-2-032 ed. 3.0 & IEC/EN 61010-031 ed. 1.1
Certification	UL (c/us) and CE	UL (c/us) and CE	UL (c/us) and CE	UL (c/us) and CE	UL (c/us) and CE
Dimensions (L x W x H):	8.62 x 3.03 x 1.46 in (219 x 77 x 37 mm)	8.82 x 3.03 x 1.46 in (224 x 77 x 37 mm)	8.62 x 3.03 x 1.46 in (219 x 77 x 37 mm)	8.82 x 3.03 x 1.46 in (224 x 77 x 37 mm)	10.16 x 3.70 x 1.73 in (258 x 94 x 44 mm)
Weight:	208 g (0.46 lb)	254 g (0.56 lb)	208 g (0.46 lb)	254 g (0.56 lb)	420 g (0.93 lb)

Accessories Included:					
User's Manual	•	•	•	•	•
Test Leads	•	•	•	•	•
Carrying Case	•	•	•	•	•
Batteries	AAA (2)		AAA (2)		AA (2)
Alligator Clip Set	–	–	•	•	•
Banana plug K-type Thermocouple	–	–	•	•	•



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331