

ZDT1048

SM-8 Dual NPN medium power high gain transistors


Summary

$BV_{CEO} > 17.5V$

$I_{C(cont)} = 5A$


$V_{CE(sat)} < 75mV @ 1A$

$P_D = 2.75W$



Description

Advanced process capability has been used to achieve this high performance device. Combining two NPN transistors in the SM-8 package provides a compact solution for the intended applications.



Features


- Dual NPN device
- Very low saturation voltage
- High gain
- SM 8 package

Applications

- CCFL invertors
- Royer circuits

Ordering information

DEVICE	Reel size (inches)	Tape width (mm)	Quantity per reel
ZDT1048TA	7	12	1000



Device marking

T1048

Absolute maximum ratings

Parameter	Symbol	Value	Unit
Collector-base voltage	V_{CBO}	50	V
Collector-emitter voltage	V_{CEO}	17.5	V
Emitter-base voltage	V_{EBO}	5	V
Peak pulse current	I_{CM}	20	A
Continuous collector current	I_C	5	A
Base current	I_B	500	mA
Operating and storage temperature range	$T_j; T_{stg}$	-55 to +150	°C

Thermal Characteristics

Parameter	Symbol	Value	Unit
Total power dissipation at $T_{amb} = 25^\circ\text{C}^*$	P_{tot}	2.25	W
Any single die "on"		2.75	W
Both die "on" equally			V
Derate above 25°C^*		18	mW/°C
Any single die "on"		22	mW/°C
Both die "on" equally			
Thermal resistance - junction to ambient*		55.6	°C/W
Any single die "on"		45.5	°C/W
Both die "on" equally			

* The power which can be dissipated assuming the device is mounted in a typical manner on a PCB with copper equal to 2 inches square.


Electrical characteristics (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated).

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	$V_{(BR)CBO}$	50	85		V	$I_C=100\mu\text{A}$
Collector-emitter breakdown voltage	V_{CES}	50	85		V	$I_C=100\mu\text{A}$
Collector-emitter breakdown voltage	V_{CEO}	17.5	24		V	$I_C=10\text{mA}$
Collector-emitter breakdown voltage	V_{CEV}	50	85		V	$I_C=100\mu\text{A}$, $V_{EB}=1\text{V}$
Emitter-base breakdown voltage	$V_{(BR)EBO}$	5	8.7		V	$I_E=100\mu\text{A}$
Collector cut-off current	I_{CBO}		0.3	10	nA	$V_{CB}=35\text{V}$
Emitter cut-off current	I_{EBO}		0.3	10	nA	$V_{EB}=4\text{V}$
Collector-emitter cut-off current	I_{CES}		0.3	10	nA	$I_{CES}=35\text{V}$
Collector-emitter saturation voltage	$V_{CE(sat)}$		27	45	mV	$I_C=0.5\text{A}$, $I_B=10\text{mA}$ (*)
			55	75	mV	$I_C=1\text{A}$, $I_B=10\text{mA}$ (*)
			120	160	mV	$I_C=2\text{A}$, $I_B=10\text{mA}$ (*)
			200	240	mV	$I_C=5\text{A}$, $I_B=100\text{mA}$ (*)
			200	300	mV	$I_C=5\text{A}$, $I_B=50\text{mA}$ (*)
Base-emitter saturation voltage	$V_{BE(sat)}$		1000	1100	mV	$I_C=5\text{A}$, $I_B=100\text{mA}$ (*)
Base-emitter turn on voltage	$V_{BE(on)}$		900	1000	mV	$I_C=5\text{A}$, $V_{CE}=2\text{V}$ (*)
Static forward current transfer ratio	h_{FE}	280	440	1200		$I_C=10\text{mA}$, $V_{CE}=2\text{V}$ (*)
		300	450			$I_C=0.5\text{A}$, $V_{CE}=2\text{V}$ (*)
		300	450			$I_C=1\text{A}$, $V_{CE}=2\text{V}$ (*)
		250	300			$I_C=5\text{A}$, $V_{CE}=2\text{V}$ (*)
		50	80			$I_C=20\text{A}$, $V_{CE}=2\text{V}$ (*)
Transition frequency	f_T		150		MHz	$I_C=50\text{mA}$, $V_{CE}=10\text{V}$ $f=50\text{MHz}$
Output capacitance	C_{obo}		60	80	pF	$V_{CB}=10\text{V}$, $f=1\text{MHz}$
Switching times	t_{on}		120		ns	$I_C=4\text{A}$, $I_B=40\text{mA}$, $V_{CC}=10\text{V}$
	t_{off}		250		ns	$I_C=4\text{A}$, $I_B=\pm 40\text{mA}$, $V_{CC}=10\text{V}$


NOTES:

(*) Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$


Typical characteristics




IC-Collector Current
 $V_{CE(sat)}$ v I_C




IC-Collector Current
 $V_{CE(sat)}$ v I_C




IC-Collector Current
 h_{FE} v I_C



IC-Collector Current
 $V_{BE(sat)}$ v I_C




IC-Collector Current
 $V_{BE(on)}$ v I_C



VCE - Collector Voltage
Safe Operating Area

Package outline - SM8



DIM	Millimeters			Inches			DIM	Millimeters			Inches		
	Min.	Max.	Typ.	Min.	Max.	Typ.		Min.	Max.	Typ.	Min.	Max.	Typ.
A	-	1.7	-	-	0.067	-	e1	-	-	4.59	-	-	0.1807
A1	0.02	0.1	-	0.0008	0.004	-	e2	-	-	1.53	-	-	0.0602
b	-	-	0.7	-	-	0.0275	He	6.7	7.3	-	0.264	0.287	-
c	0.24	0.32	-	0.009	0.013	-	Lp	0.9	-	-	0.035	-	-
D	6.3	6.7	-	0.248	0.264	-	α	-	15°	-	-	15°	-
E	3.3	3.7	-	0.130	0.145	-	β	-	-	10°	-	-	10°

Note: Controlling dimensions are in millimeters. Approximate dimensions are provided in inches

Definitions

Product change

Zetex Semiconductors reserves the right to alter, without notice, specifications, design, price or conditions of supply of any product or service. Customers are solely responsible for obtaining the latest relevant information before placing orders.

Applications disclaimer

The circuits in this design/application note are offered as design ideas. It is the responsibility of the user to ensure that the circuit is fit for the user's application and meets with the user's requirements. No representation or warranty is given and no liability whatsoever is assumed by Zetex with respect to the accuracy or use of such information, or infringement of patents or other intellectual property rights arising from such use or otherwise. Zetex does not assume any legal responsibility or will not be held legally liable (whether in contract, tort (including negligence), breach of statutory duty, restriction or otherwise) for any damages, loss of profit, business, contract, opportunity or consequential loss in the use of these circuit applications, under any circumstances.

Life support

Zetex products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Zetex Semiconductors plc. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body

or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Reproduction

The product specifications contained in this publication are issued to provide outline information only which (unless agreed by the company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned.

Terms and Conditions

All products are sold subjects to Zetex' terms and conditions of sale, and this disclaimer (save in the event of a conflict between the two when the terms of the contract shall prevail) according to region, supplied at the time of order acknowledgement.

For the latest information on technology, delivery terms and conditions and prices, please contact your nearest Zetex sales office.

Quality of product

Zetex is an ISO 9001 and TS16949 certified semiconductor manufacturer.

To ensure quality of service and products we strongly advise the purchase of parts directly from Zetex Semiconductors or one of our regionally authorized distributors. For a complete listing of authorized distributors please visit: www.zetex.com/salesnetwork

Zetex Semiconductors does not warrant or accept any liability whatsoever in respect of any parts purchased through unauthorized sales channels.

ESD (Electrostatic discharge)

Semiconductor devices are susceptible to damage by ESD. Suitable precautions should be taken when handling and transporting devices. The possible damage to devices depends on the circumstances of the handling and transporting, and the nature of the device. The extent of damage can vary from immediate functional or parametric malfunction to degradation of function or performance in use over time. Devices suspected of being affected should be replaced.

Green compliance

Zetex Semiconductors is committed to environmental excellence in all aspects of its operations which includes meeting or exceeding regulatory requirements with respect to the use of hazardous substances. Numerous successful programs have been implemented to reduce the use of hazardous substances and/or emissions.

All Zetex components are compliant with the RoHS directive, and through this it is supporting its customers in their compliance with WEEE and ELV directives.

Product status key:

"Preview"	Future device intended for production at some point. Samples may be available
"Active"	Product status recommended for new designs
"Last time buy (LTB)"	Device will be discontinued and last time buy period and delivery is in effect
"Not recommended for new designs"	Device is still in production to support existing designs and production
"Obsolete"	Production has been discontinued

Datasheet status key:

"Draft version"	This term denotes a very early datasheet version and contains highly provisional information, which may change in any manner without notice.
"Provisional version"	This term denotes a pre-release datasheet. It provides a clear indication of anticipated performance. However, changes to the test conditions and specifications may occur, at any time and without notice.
"Issue"	This term denotes an issued datasheet containing finalized specifications. However, changes to specifications may occur, at any time and without notice.

Zetex sales offices

Europe	Americas	Asia Pacific	Corporate Headquarters
Zetex GmbH Kustermann-park Balanstraße 59 D-81541 München Germany Telephone: (49) 89 45 49 49 0 Fax: (49) 89 45 49 49 49 europe.sales@zetex.com	Zetex Inc 700 Veterans Memorial Highway Hauppauge, NY 11788 USA Telephone: (1) 631 360 2222 Fax: (1) 631 360 8222 usa.sales@zetex.com	Zetex (Asia Ltd) 3701-04 Metroplaza Tower 1 Hing Fong Road, Kwai Fong Hong Kong Telephone: (852) 26100 611 Fax: (852) 24250 494 asia.sales@zetex.com	Zetex Semiconductors plc Zetex Technology Park, Chadderton Oldham, OL9 9LL United Kingdom Telephone: (44) 161 622 4444 Fax: (44) 161 622 4446 hq@zetex.com

© 2007 Published by Zetex Semiconductors plc



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331