
Phase Control SCR, 12.5 A



TO-220AB



DESCRIPTION/FEATURES

The 12TTS08 High Voltage Series of silicon controlled rectifiers are specifically designed for medium power switching and phase control applications. The glass passivation technology used has reliable operation up to 125 °C junction temperature.

Typical applications are in input rectification and crowbar (soft start) and these products are designed to be used with Vishay HPP input diodes, switches and output rectifiers which are available in identical package outlines.

Also available in SMD-220 package (series 12TTS..S)

This product has been designed and qualified for industrial level.

PRODUCT SUMMARY	
V_T at 8 A	1.2 V
I_{TSM}	140 A
V_{RRM}	800 V

OUTPUT CURRENT IN TYPICAL APPLICATIONS			
APPLICATIONS	SINGLE-PHASE BRIDGE	THREE-PHASE BRIDGE	UNITS
Capacitive input filter T_A = 55 °C, T_J = 125 °C, common heatsink of 1 °C/W	13.5	17	A

MAJOR RATINGS AND CHARACTERISTICS			
PARAMETER	TEST CONDITIONS	VALUES	UNITS
$I_{T(AV)}$	Sinusoidal waveform	8	A
$I_{T(RMS)}$		12.5	
V_{DRM}/V_{RRM}		800	V
I_{TSM}		140	A
V_T	8 A, T_J = 25 °C	1.2	V
dV/dt		150	V/µs
dI/dt		100	A/µs
T_J	Range	- 40 to 125	°C

VOLTAGE RATINGS			
PART NUMBER	V_{RRM}, MAXIMUM PEAK VOLTAGE V	V_{DRM}, MAXIMUM PEAK DIRECT VOLTAGE V	I_{RRM}/I_{DRM} AT 125 °C mA
12TTS08	800	800	1.0

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS
Maximum average on-state current	$I_{T(AV)}$	T_C = 108 °C, 180° conduction, half sine wave		8	A
Maximum RMS on-state current	$I_{T(RMS)}$			12.5	
Maximum peak, one-cycle, non-repetitive surge current	I_{TSM}	10 ms sine pulse, rated V_{RRM} applied, T_J = 125 °C		120	
		10 ms sine pulse, no voltage reapplied, T_J = 125 °C		140	
Maximum I^2t for fusing	I^2t	10 ms sine pulse, rated V_{RRM} applied, T_J = 125 °C		72	A^2s
		10 ms sine pulse, no voltage reapplied, T_J = 125 °C		100	
Maximum $I^2\sqrt{t}$ for fusing	$I^2\sqrt{t}$	t = 0.1 to 10 ms, no voltage reapplied, T_J = 125 °C		1000	$A^2\sqrt{s}$
Maximum on-state voltage drop	V_{TM}	8 A, T_J = 25 °C		1.2	V
On-state slope resistance	r_t	T_J = 125 °C		16.2	mΩ
Threshold voltage	$V_{T(TO)}$			0.87	V
Maximum reverse and direct leakage current	I_{RM}/I_{DM}	T_J = 25 °C	V_R = Rated V_{RRM}/V_{DRM}	0.05	mA
		T_J = 125 °C		1.0	
Typical holding current	I_H	Anode supply = 6 V, resistive load, initial I_T = 1 A		30	
Maximum latching current	I_L	Anode supply = 6 V, resistive load		50	
Maximum rate of rise of off-state voltage	dV/dt	T_J = 25 °C		150	V/µs
Maximum rate of rise of turned-on current	dI/dt			100	A/µs

TRIGGERING

PARAMETER	SYMBOL	TEST CONDITIONS	VALUES	UNITS
Maximum peak gate power	P_{GM}		8.0	W
Maximum average gate power	$P_{G(AV)}$		2.0	
Maximum peak positive gate current	+ I_{GM}		1.5	A
Maximum peak negative gate voltage	- V_{GM}		10	V
Maximum required DC gate current to trigger	I_{GT}	Anode supply = 6 V, resistive load, T_J = - 65 °C	20	mA
		Anode supply = 6 V, resistive load, T_J = 25 °C	15	
		Anode supply = 6 V, resistive load, T_J = 125 °C	10	
Maximum required DC gate voltage to trigger	V_{GT}	Anode supply = 6 V, resistive load, T_J = - 65 °C	1.2	V
		Anode supply = 6 V, resistive load, T_J = 25 °C	1	
		Anode supply = 6 V, resistive load, T_J = 125 °C	0.7	
Maximum DC gate voltage not to trigger	V_{GD}	T_J = 125 °C, V_{DRM} = Rated value	0.2	
Maximum DC gate current not to trigger	I_{GD}		0.1	mA

SWITCHING

PARAMETER	SYMBOL	TEST CONDITIONS	VALUES	UNITS
Typical turn-on time	t_{gt}	T_J = 25 °C	0.8	µs
Typical reverse recovery time	t_{rr}	T_J = 125 °C	3	
Typical turn-off time	t_q		100	

THERMAL AND MECHANICAL SPECIFICATIONS					
PARAMETER		**SYMBOL**	**TEST CONDITIONS**	**VALUES**	**UNITS**
Maximum junction and storage temperature range		T_J, T_{Stg}		- 40 to 125	°C
Maximum thermal resistance, junction to case		R_{thJC}	DC operation	1.5	°C/W
Maximum thermal resistance, junction to ambient		R_{thJA}		62	
Typical thermal resistance, case to heatsink		R_{thCS}	Mounting surface, smooth and greased	0.5	
Approximate weight				2	g
				0.07	oz.
Mounting torque	minimum			6 (5)	kgf · cm (lbf · in)
	maximum			12 (10)	
Marking device			Case style TO-220AB	12TTS08	




Fig. 1 - Current Ratings Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 3 - On-State Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristics

ORDERING INFORMATION TABLE

Device code

12	T	T	S	08	-
1	2	3	4	5	6

- 1 - Current ratings (12 = 12.5 A)
- 2 - Circuit configuration:
  T = Single thyristor
- 3 - Package:
  T = TO-220
- 4 - Type of silicon:
  S = Standard recovery rectifier
- 5 - Voltage rating (08 = 800 V)
- 6 - • None = Standard production
  • PbF = Lead (Pb)-free

LINKS TO RELATED DOCUMENTS	
Dimensions	http://www.vishay.com/doc?95222
Part marking information	http://www.vishay.com/doc?95225

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331