MJE4343 (NPN), MJE4353 (PNP)

High-Voltage - High Power Transistors

. . . designed for use in high power audio amplifier applications and high voltage switching regulator circuits.

Features

- High Collector−Emitter Sustaining Voltage −
  NPN PNP
  $V_{CEO(sus)}$ = 160 Vdc − MJE4343 MJE4353
- High DC Current Gain − @ I_C = 8.0 Adc h_{FE} = 35 (Typ)
- Low Collector−Emitter Saturation Voltage −
  $V_{CE(sat)}$ = 2.0 Vdc (Max) @ I_C
  = 8.0 Adc
- These are Pb−Free Devices

MAXIMUM RATINGS

Rating	Symbol	Max	Unit
Collector−Emitter Voltage	V_{CEO}	160	Vdc
Collector−Base Voltage	V_{CB}	160	Vdc
Emitter−Base Voltage	V_{EB}	7.0	Vdc
Collector Current − Continuous Peak (Note 1)	I_C	16 20	Adc
Base Current − Continuous	I_B	5.0	Adc
Total Power Dissipation @ T_C = 25°C	P_D	125	Watts
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−65 to +150	°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	1.0	°C/W

1. Pulse Test: Pulse Width ≤ 5.0 μs, Duty Cycle ≥ 10%.

ON Semiconductor®

http://onsemi.com

16 AMPS
POWER TRANSISTORS
COMPLEMENTARY
SILICON
160 VOLTS



SOT−93
CASE 340D
STYLE 1



TO−247
CASE 340L
STYLE 3

NOTE: Effective June 2012 this device will be available only in the TO−247 package. Reference FPCN# 16827.

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

© Semiconductor Components Industries, LLC, 2012

MARKING DIAGRAMS



MJE43x3	= Device Code
A	= Assembly Location
Y	= Year
WW	= Work Week
G	= Pb−Free Package

ORDERING INFORMATION

Device Order Number	Package Type	Shipping
MJE4343G	SOT−93 (Pb−Free)	30 Units / Rail
MJE4353G	SOT−93 (Pb−Free)	30 Units / Rail
MJE4343G	TO−247 (Pb−Free)	30 Units / Rail
MJE4353G	TO−247 (Pb−Free)	30 Units / Rail



Figure 1. Power Derating
Reference: Ambient Temperature

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector−Emitter Sustaining Voltage (Note 2) (I_C = 200 mAdc, I_B = 0)	$V_{CEO(sus)}$	160	−	Vdc
Collector−Emitter Cutoff Current (V_{CE} = 80 Vdc, I_B = 0)	I_{CEO}	−	750	μAdc
Collector−Emitter Cutoff Current (V_{CE} = Rated V_{CB}, $V_{EB(off)}$ = 1.5 Vdc) (V_{CE} = Rated V_{CB}, $V_{EB(off)}$ = 1.5 Vdc, T_C = 150°C)	I_{CEX}	− −	1.0 5.0	mAdc
Collector−Base Cutoff Current (V_{CB} = Rated V_{CB}, I_E = 0)	I_{CBO}	−	750	μAdc
Emitter−Base Cutoff Current (V_{BE} = 7.0 Vdc, I_C = 0)	I_{EBO}	−	1.0	mAdc
ON CHARACTERISTICS (Note 2)				
DC Current Gain (I_C = 8.0 Adc, V_{CE} = 2.0 Vdc) (I_C = 16 Adc, V_{CE} = 4.0 Vdc)	h_{FE}	15 8.0	35 (Typ) 15 (Typ)	−
Collector−Emitter Saturation Voltage (I_C = 8.0 Adc, I_B = 800 mA) (I_C = 16 Adc, I_B = 2.0 Adc)	$V_{CE(sat)}$	− −	2.0 3.5	Vdc
Base−Emitter Saturation Voltage (I_C = 16 Adc, I_B = 2.0 Adc)	$V_{BE(sat)}$	−	3.9	Vdc
Base−Emitter On Voltage (I_C = 16 Adc, V_{CE} = 4.0 Vdc)	$V_{BE(on)}$	−	3.9	Vdc
DYNAMIC CHARACTERISTICS				
Current−Gain − Bandwidth Product (Note 3) (I_C = 1.0 Adc, V_{CE} = 20 Vdc, f_{test} = 0.5 MHz)	f_T	1.0	−	MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 0.1 MHz)	C_{ob}	−	800	pF

2. Pulse Test: Pulse Width $\leq$ 300 μs, Duty Cycle $\geq$ 2.0%.
3. $f_T = |h_{fe}| \bullet f_{test}$.



R_B and R_C VARIED TO OBTAIN DESIRED CURRENT LEVELS
D_1 MUST BE FAST RECOVERY TYPE, e.g.:
1N5825 USED ABOVE $I_B \approx$ 100 mA
MSD6100 USED BELOW $I_B \approx$ 100 mA

Note: Reverse polarities to test PNP devices.

Figure 2. Switching Times Test Circuit



Figure 3. Typical Turn−On Time

TYPICAL CHARACTERISTICS



Figure 4. Turn−Off Time



Figure 5. On Voltages

DC CURRENT GAIN



Figure 6. MJE4340 Series (NPN)



Figure 7. MJE4350 Series (PNP)



Figure 8. Collector Saturation Region



Figure 9. Thermal Response



Figure 10. Maximum Forward Bias Safe Operating Area

REVERSE BIAS

For inductive loads, high voltage and high current must be sustained simultaneously during turn−off, in most cases, with the base to emitter junction reverse biased. Under these conditions the collector voltage must be held to a safe level at or below a specific value of collector current. This can be accomplished by several means such as active clamping, RC snubbing, load line shaping, etc. The safe level for these devices is specified as Reverse Bias Safe Operating Area and represents the voltage−current conditions during reverse biased turn−off. This rating is verified under clamped conditions so that the device is never subjected to an avalanche mode. Figure 11 gives RBSOA characteristics.

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 10 is based on T_C = 25°C; $T_{J(pk)}$ is variable depending on power level. Second breakdown pulse limits are valid for duty cycles to 10% but must be derated when $T_C \geq 25°C$. Second breakdown limitations do not derate the same as thermal limitations. Allowable current at the voltages shown on Figure 10 may be found at any case temperature by using the appropriate curve on Figure 9.



Figure 11. Maximum Reverse Bias Safe Operating Area

PACKAGE DIMENSIONS

SOT−93 (TO−218)
CASE 340D−02
ISSUE E



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	---	20.35	---	0.801
B	14.70	15.20	0.579	0.598
C	4.70	4.90	0.185	0.193
D	1.10	1.30	0.043	0.051
E	1.17	1.37	0.046	0.054
G	5.40	5.55	0.213	0.219
H	2.00	3.00	0.079	0.118
J	0.50	0.78	0.020	0.031
K	31.00 REF		1.220 REF	
L	---	16.20	---	0.638
Q	4.00	4.10	0.158	0.161
S	17.80	18.20	0.701	0.717
U	4.00 REF		0.157 REF	
V	1.75 REF		0.069	

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

TO−247
CASE 340L−02
ISSUE F



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	20.32	21.08	0.800	8.30
B	15.75	16.26	0.620	0.640
C	4.70	5.30	0.185	0.209
D	1.00	1.40	0.040	0.055
E	1.90	2.60	0.075	0.102
F	1.65	2.13	0.065	0.084
G	5.45 BSC		0.215 BSC	
H	1.50	2.49	0.059	0.098
J	0.40	0.80	0.016	0.031
K	19.81	20.83	0.780	0.820
L	5.40	6.20	0.212	0.244
N	4.32	5.49	0.170	0.216
P	---	4.50	---	0.177
Q	3.55	3.65	0.140	0.144
U	6.15 BSC		0.242 BSC	
W	2.87	3.12	0.113	0.123

STYLE 3:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

MJE4343/D

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331