

PBHV8560Z

600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor
13 March 2015 Product data sheet

1. General description

NPN high-voltage low V_{CEsat} Breakthrough In Small Signal (BISS) transistor in a SOT223 (SC-73) medium power Surface-Mounted Device (SMD) plastic package.

PNP complement: PBHV9560Z

2. Features and benefits

- Low collector-emitter saturation voltage V_{CEsat}
- High collector current capability
- High collector current gain h_{FE} at high I_C
- AEC-Q101 qualified

3. Applications

- Electronic ballast for fluorescent lighting
- LED driver for LED chain module
- LCD backlighting
- High Intensity Discharge (HID) front lighting
- Automotive motor management
- Hook switch for wired telecom
- Switch Mode Power Supply (SMPS)

4. Quick reference data

Table 1. Quick reference data

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
V _{CEO}	collector-emitter voltage	open base	-	-	600	V
I _C	collector current		-	-	0.5	Α
h _{FE}	DC current gain	V_{CE} = 10 V; I_{C} = 50 mA; T_{amb} = 25 °C	70	135	-	



600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor

5. Pinning information

Table 2. Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	В	base	4	2, 4
2	С	collector		1—
3	Е	emitter		. 1
4	С	collector	☐1 ☐2 ☐3 SC-73 (SOT223)	3 sym016

6. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
PBHV8560Z	SC-73	plastic surface-mounted package with increased heatsink; 4 leads	SOT223

7. Marking

Table 4. Marking codes

Type number	Marking code
PBHV8560Z	HV856Z

600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor


8. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
V_{CBO}	collector-base voltage	open emitter		-	600	V
V_{CEO}	collector-emitter voltage	open base		-	600	V
V_{CESM}	collector-emitter peak voltage	V _{BE} = 0 V		-	600	V
V_{EBO}	emitter-base voltage	open collector		-	6	V
I _C	collector current			-	0.5	Α
P _{tot}	total power dissipation	T _{amb} ≤ 25 °C	[1]	-	0.65	W
			<u>[2]</u>	-	1.4	W
T_{j}	junction temperature			-	150	°C
T _{amb}	ambient temperature			-55	150	°C
T _{stg}	storage temperature			-65	150	°C

- [1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.
- [2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6 cm².




600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor

Thermal characteristics


Table 6. **Thermal characteristics**

Symbol	Parameter	Conditions		Min	Тур	Max	Unit
fro	thermal resistance from junction to ambient	in free air	[1]	-	-	190	K/W
			<u>[2]</u>	-	-	89	K/W
R _{th(j-sp)}	thermal resistance from junction to solder point			-	-	20	K/W

- Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.
- Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6 cm².



Transient thermal impedance from junction to ambient as a function of pulse duration; typical values Fig. 2.



FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6 cm².

PBHV8560Z

Fig. 3. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values

All information provided in this document is subject to legal disclaimers. 4/13 **Product data sheet** 13 March 2015

© Nexperia B.V. 2017. All rights reserved


600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor

10. Characteristics

Table 7. Characteristics

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
I _{CBO}	collector-base cut-off	V _{CB} = 400 V; I _E = 0 A; T _{amb} = 25 °C	-	-	100	nA
	current	V _{CB} = 400 V; I _E = 0 A; T _j = 150 °C	-	-	10	μΑ
I _{CES}	collector-emitter cut-off current	V _{CE} = 400 V; V _{BE} = 0 V; T _{amb} = 25 °C	-	-	100	nA
I _{EBO}	emitter-base cut-off current	V _{EB} = 4 V; I _C = 0 A; T _{amb} = 25 °C	-	-	100	nA
h _{FE} DC current of	DC current gain	V _{CE} = 10 V; I _C = 50 mA; T _{amb} = 25 °C	70	135	-	
		V_{CE} = 10 V; I_{C} = 100 mA; $t_{p} \le 300 \ \mu s$; $\delta \le 0.02$; T_{amb} = 25 °C	70	135	-	
V _{CEsat}	collector-emitter	I_C = 50 mA; I_B = 5 mA; T_{amb} = 25 °C	-	50	100	mV
	saturation voltage	I_{C} = 100 mA; I_{B} = 20 mA; t_{p} ≤ 300 µs; δ ≤ 0.02 ; T_{amb} = 25 °C	-	50	100	mV
V_{BEsat}	base-emitter saturation voltage	I_{C} = 50 mA; I_{B} = 5 mA; pulsed; $t_{p} \le 300 \ \mu s; \ \delta \le 0.02 \ ; T_{amb}$ = 25 °C	-	-	950	mV
C _c	collector capacitance	V_{CB} = 20 V; I_{E} = 0 A; i_{e} = 0 A; f = 1 MHz; T_{amb} = 25 °C	-	7.5	-	pF
C _e	emitter capacitance	$V_{EB} = 0.5 \text{ V}; I_{C} = 0 \text{ A}; i_{c} = 0 \text{ A};$ $f = 1 \text{ MHz}; T_{amb} = 25 ^{\circ}\text{C}$	-	710	-	pF

600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor




$$V_{CE} = 10 V$$

(1)
$$T_{amb} = 100 \, ^{\circ}C$$

(2)
$$T_{amb} = 25 \, ^{\circ}C$$

$$(3) T_{amb} = -55 °C$$

Fig. 4. DC current gain as a function of collector current; typical values




$$T_{amb} = 25 \, ^{\circ}C$$

(1)
$$V_{CE} = 10 \text{ V}$$

(2)
$$V_{CE} = 25 \text{ V}$$


(3)
$$V_{CE} = 50 \text{ V}$$

Fig. 5. DC current gain as a function of collector current; typical values



 $T_{amb} = 25 \, ^{\circ}C$

Fig. 6. Collector current as a function of collectoremitter voltage; typical values




(1)
$$T_{amb} = -55 \, ^{\circ}C$$

(2)
$$T_{amb}$$
 = 25 °C

(3)
$$T_{amb} = 100 \, ^{\circ}C$$

Base-emitter voltage as a function of collector Fig. 7. current; typical values

600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor




$$I_C/I_B = 5$$

(1)
$$T_{amb} = -55$$
 °C

(2)
$$T_{amb}$$
 = 25 °C

(3)
$$T_{amb}$$
= 100 °C



$$I_C/I_B = 5$$


(1)
$$T_{amb} = 100 \, ^{\circ}C$$

(2)
$$T_{amb}$$
 = 25 °C

(3)
$$T_{amb} = -55 \, ^{\circ}C$$

Fig. 8. Base-emitter saturation voltage as a function of collector current; typical values






$$(1) I_{\rm C}/I_{\rm B} = 10$$

(2)
$$I_C/I_B = 5$$

(3)
$$I_C/I_B = 2.5$$

Fig. 10. Collector-emitter saturation voltage as a function of collector current; typical values



$$I_C/I_B = 5$$


(1)
$$T_{amb} = 100 \, ^{\circ}C$$

(2)
$$T_{amb}$$
 = 25 °C

(3)
$$T_{amb} = -55 \, ^{\circ}C$$

Fig. 11. Collector-emitter saturation resistance as a function of collector current; typical values

600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor




11. Test information

11.1 Quality information

This product has been qualified in accordance with the Automotive Electronics Council (AEC) standard Q101 - Stress test qualification for discrete semiconductors, and is suitable for use in automotive applications.

12. Package outline




PBHV8560Z

All information provided in this document is subject to legal disclaimers.

600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor

13. Soldering



600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor

14. Revision history

Table 8. Revision history

Data sheet ID	Release date	Data sheet status	Change notice	Supersedes
PBHV8560Z v.1	20150313	Product data sheet	-	-

600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor

15. Legal information

15.1 Data sheet status

Document status [1][2]	Product status [3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

- Please consult the most recently issued document before initiating or completing a design.
- [2] The term 'short data sheet' is explained in section "Definitions".
- The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nexperia.com.

15.2 Definitions

Preview — The document is a preview version only. The document is still subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

15.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nexperia.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the

PBHV8560Z

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor

grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of nonautomotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

15.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

600 V, 0.5 A NPN high-voltage low VCEsat (BISS) transistor

16. Contents

1	General description	1
2	Features and benefits	1
3	Applications	1
4	Quick reference data	1
5	Pinning information	2
6	Ordering information	2
7	Marking	2
8	Limiting values	3
9	Thermal characteristics	4
10	Characteristics	5
11	Test information	8
11.1	Quality information	8
12	Package outline	8
13	Soldering	9
14	Revision history	10
15	Legal information	11
15.1	Data sheet status	11
15.2	Definitions	11
15.3	Disclaimers	11
15.4	Trademarks	12

© Nexperia B.V. 2017. All rights reserved

For more information, please visit: http://www.nexperia.com For sales office addresses, please send an email to: salesaddresses@nexperia.com Date of release: 13 March 2015



Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию.

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России, а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научноисследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,

Промышленная ул, дом № 19, литера Н,

помещение 100-Н Офис 331