

Type SQ Series

Key Features

- Choice of Styles
- Bracketed Types Available
- Temp. Op. -55°C to +250°C
- Wide Value Range
- Stable TCR 300ppm/°C
- Custom Designs Welcome
- Inorganic Flame Proof Construction



This flexible range of Power Wirewound Resistors either have wire or power oxide film elements. The SQ series resistors are wound or deposited on a fine non - alkali ceramic core then embodied in a ceramic case and sealed with an inorganic silica filler. This design provides a resistor with high insulation resistance, low surface temperature, excellent T.C.R., and entirely fire proof construction. These resistors are ideally suited to a range of areas where low cost, and efficient thermal performance are important design criteria. Metal film cores adjusted by laser spiral are used where the resistor value is above that suited to wire. Similar performance is obtained although short time overload is slightly derated.

Characteristics - Electrical

| | Test Condition | Performance |
|--------------------------------------|--|-------------|
| Resistance Temp. Coefficient: | -55°C ~ 155°C | ± 300ppm/°C |
| *Short Time Overload: | 10 times rated power for 5 seconds | ± 2% |
| Rated Load: | Rated power for 30 minutes | ± 1% |
| Voltage Withstand: | 1000V AC 1 minute | no change |
| Insulation Resistance: | 500V megger | 1000 Meg |
| Temperature Cycle: | -30°C ~ 85°C for 5 cycles | ± 1% |
| Load Life: | 70°C on-off cycle for 1000 hours | ± 5% |
| Moisture-proof Load Life: | 40°C 95% RH on-off cycle 1000 hours | ± 5% |
| Incombustibility: | 16 times rated wattage for 5 minutes | No flame |
| Max. Overload Voltage: | 2 times max. working voltage | |
| *Metal Film Elements: | Short time overload 5 times rated power, 5 seconds | |

Type SQP - Horizontal



| Power Rating | Dimensions | | | | | Resistance Range | | Max. Working Voltage |
|--------------|------------|-------|---------|----------|---------|------------------|-------------|----------------------|
| | W ± 1 | H ± 1 | L ± 1.5 | d ± 0.05 | l ± 0.3 | Wire | Metal Film | |
| 2W | 7 | 7 | 18 | 0.65 | 23 | R10 - 82R | 83R - 10K | 150V |
| 3W | 8 | 8 | 22 | 0.8 | 35 | R10 - 180R | 181R - 33K | 350V |
| 5W | 10 | 9 | 22 | 0.8 | 35 | R10 - 180R | 181R - 100K | 350V |
| 7W | 10 | 9 | 35 | 0.8 | 35 | R10 - 430R | 431R - 100K | 500V |
| 10W | 10 | 9 | 48 | 0.8 | 35 | R10 - 470R | 471R - 100K | 750V |
| 15W | 12.5 | 11.5 | 48 | 0.8 | 35 | R50 - 600R | 601R - 150K | 1000V |
| 20W - 25W | 14 | 13.5 | 60 | 0.8 | 35 | R50 - 1K0 | 1.1K - 150K | 1000V |

Rated Continuous Working Voltage (RCWV)
 RCWV: $\sqrt{\text{Rated Power} \times \text{Resistance Value}}$ or Maximum Working Voltage listed above whichever is lower

Type SQ Series

Type SQH - Horizontal with Faston Connectors



| Power Rating | Dimensions | | | | | | | | Resistance Range | |
|--------------|------------|-------|---------|--------|--------|---------|----------|----------|------------------|------------|
| | W ± 1 | H ± 1 | L ± 1.5 | P | H1 ± 1 | D ± 0.5 | P1 ± 0.2 | P2 ± 0.2 | Wire | Metal Film |
| 10W | 10 | 10 | 48 | 32 ± 1 | 21 | 5 | 2.5 | 1.7 | R50 - 600R | 601R - 50K |
| 15W | 12.5 | 11.5 | 48 | 32 ± 1 | 21 | 5 | 2.5 | 1.7 | 1R0 - 600R | 601R - 50K |
| 20W | 14.5 | 13.5 | 60 | 42 ± 1 | 24 | 6 | 3.0 | 2.5 | 1R0 - 1K0 | 1K1 - 50K |
| 30W | 19 | 19 | 75 | 55 ± 2 | 31 | 7.5 | - | - | 1R0 - 2K0 | - |
| 40W | 19 | 19 | 90 | 67 ± 2 | 31 | 7.5 | - | - | 1R0 - 2K0 | - |

Type SQB - Horizontal with Faston Connectors and Bracket

| Power Rating | Dimensions | | | |
|--------------|------------|---------|---------|---------|
| | A ± 0.5 | B ± 0.5 | C ± 0.5 | G ± 0.5 |
| 10W | 8.0 | 5.0 | 12.0 | 3.0 |
| 15W | 8.0 | 5.5 | 12.0 | 3.0 |
| 20W | 8.0 | 5.5 | 12.0 | 3.0 |
| 30W | 10.5 | 8.0 | 18.0 | 3.5 |
| 40W | 10.5 | 8.0 | 18.0 | 3.5 |



Power Derating Curve



Load Against Temperature



Type SQM - Vertical



| Power Rating | Dimensions | | | | Resistance Range | |
|--------------|------------|-------|---------|---------|------------------|-------------|
| | W ± 1 | H ± 1 | S ± 1.5 | P ± 2.0 | Wire | Metal Film |
| 2W | 11 | 20 | 7 | 5 | R10 - 82R | 83R - 10K |
| 3W | 12 | 25 | 8 | 5 | R10 - 180R | 181R - 33K |
| 5W | 13 | 25 | 9 | 5 | R10 - 180R | 181R - 100K |
| 7W | 13 | 39 | 9 | 5 | R10 - 430R | 431R - 100K |
| 10W | 13 | 51 | 9 | 5 | R10 - 470R | 471R - 100K |
| 10WS | 16 | 35 | 12 | 7.5 | R10 - 360R | 361R - 100K |

N.B. Custom design versions in wire at low tolerances, better T.C.R., and higher ohmic values are available to special order. Please enquire.

Type SQ Series

Type SPS - Vertical Mounting with Stabilising Bracket



| Power Rating | Dimension | | Resistance Range | |
|--------------|-----------|---------|------------------|-------------|
| | L ± 1.5 | K ± 0.5 | Wire | Metal Film |
| 7W | 48 | 8.5 | R10 - 430R | 431R - 100K |
| 10W | 60 | 20 | R10 - 470R | 471R - 100K |

Type SQZ - Horizontal Pluggable



| Power Rating | Dimensions | | | | | | | | | | Resistance Range | |
|--------------|------------|-----|-------|-------|-----|----|----|-----|------|------|------------------|-------------|
| | W±1 | H±1 | L±1.5 | P±1.5 | P1 | P2 | P3 | P4 | H1±1 | H2±1 | Wire | Metal Film |
| 5W | 10 | 10 | 28 | 15 | 4.2 | 2 | 5 | 1.5 | 25 | 10.5 | R10 - 130R | 131R - 100K |
| 7W | 10 | 10 | 36 | 20 | 4.2 | 2 | 5 | 1.5 | 25 | 10.5 | R10 - 430R | 431R - 100K |
| 10W | 10 | 10 | 48 | 32 | 4.2 | 2 | 5 | 1.5 | 25 | 10.5 | R20 - 470R | 471R - 100K |
| 15W | 12.5 | 12 | 48 | 32 | 4.2 | 2 | 5 | 1.5 | 26 | 10.5 | 1R0 - 600R | 601R - 150K |
| 20W-25W* | 15 | 13 | 60 | 42 | 7 | 6 | 10 | 2.7 | 36 | 15.0 | 1R0 - 1K0 | 1K1 - 150K |

*NB: 20W & 25W Devices Terminations are not crimped

Type SQZ - Recommended PCB Hole Dimensions

| Power Rating | a | b | p |
|--------------|-----|-----|----|
| 5W | 2.0 | 0.8 | 15 |
| 7W | 2.0 | 0.8 | 20 |
| 10W | 2.0 | 0.8 | 32 |
| 15W | 2.0 | 0.8 | 32 |
| 20W_25W | 3.5 | 1.0 | 42 |



How to Order

| SQP | W | 20 | 1R0 | F |
|---|--------------------------------|---|---|---|
| Common Part | Element | Rated Power | Resistance Value | Resistance Tolerance |
| SQP - Axial Type SQZ - Pluggable Type SQM - Vertical Type SPS - Vertical Type SQH - Horizontal Type SQB - Horizontal Type (with bracket) | W - Wire R - Metal Film | 2 - 2 Watts 3 - 3 Watts 5 - 5 Watts etc | 0.1 ohm (1 milliohm) R10 1 ohm (1000 milliohms) 1R0 1K ohm (1000 ohms) 1K0 1M ohm (1000000 ohms) 1M0 | F - ±1% G - ±2% J - ±5% K - ±10% |

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks. Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this datasheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331