

## 9716 Multi-Conductor - High-Conductivity Copper Speaker Cable Parallel Zip Const

For more Information  
please call

1-800-Belden1

**General Description:**

16 AWG stranded (26x30) ETP high-conductivity copper conductors, PVC insulation, parallel: (1) tinned, (1) bare.

**Physical Characteristics (Overall)****Conductor**

AWG:

| # Conductors | AWG | Stranding | Conductor Material                   |
|--------------|-----|-----------|--------------------------------------|
| 1            | 16  | 26x30     | High Conductivity TC - Tinned Copper |
| 1            | 16  | 26x30     | High Conductivity BC - Bare Copper   |

Total Number of Conductors: 2

**Insulation**

Insulation Material:

| Insulation Material      | Wall Thickness (in.) |
|--------------------------|----------------------|
| PVC - Polyvinyl Chloride | .027                 |

**Outer Shield**

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded            |

**Outer Jacket**

Outer Jacket Material:

| Outer Jacket Material    |
|--------------------------|
| PVC - Polyvinyl Chloride |

**Overall Cable**

Overall Nominal Diameter: 0.115 x 0.230 in.

**Mechanical Characteristics (Overall)**

|                                   |                 |
|-----------------------------------|-----------------|
| Operating Temperature Range:      | -20°C To +60°C  |
| Non-UL Temperature Rating:        | 60°C            |
| Bulk Cable Weight:                | 25 lbs/1000 ft. |
| Max. Recommended Pulling Tension: | 78 lbs.         |
| Min. Bend Radius/Minor Axis:      | 2.250 in.       |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                       |           |
|---------------------------------------|-----------|
| EU Directive 2011/65/EU (ROHS II):    | Yes       |
| EU CE Mark:                           | Yes       |
| EU Directive 2000/53/EC (ELV):        | Yes       |
| EU Directive 2002/95/EC (RoHS):       | Yes       |
| EU RoHS Compliance Date (mm/dd/yyyy): | 0101/2004 |
| EU Directive 2002/96/EC (WEEE):       | Yes       |
| EU Directive 2003/11/EC (BFR):        | Yes       |
| CA Prop 65 (CJ for Wire & Cable):     | Yes       |
| MIL Order #39 (China RoHS):           | Yes       |

**Plenum/Non-Plenum**

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

**Electrical Characteristics (Overall)**

Nom. Inductance:

9716 Multi-Conductor - High-Conductivity Copper Speaker Cable Parallel Zip Const

Inductance (µH/ft)

.19

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

4.00

Max. Operating Voltage - Non-UL:

Voltage

300 V RMS

Max. Recommended Current:

Current

7.2 Amps per conductor @ 25°C

Put Ups and Colors:

| Item #        | Putup    | Ship Weight | Color              | Notes | Item Desc         |
|---------------|----------|-------------|--------------------|-------|-------------------|
| 9716 368U1000 | 1,000 FT | 27.000 LB   | CLEAR, TRANSPARENT |       | 2#16 PVC PARALLEL |
| 9716 3681000  | 1,000 FT | 26.000 LB   | CLEAR, TRANSPARENT | C     | 2#16 PVC PARALLEL |

Notes:  
C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 06-29-2011

© 2015 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331