

# MODM7AE70

## Ethernet Core Module

100 Version with RJ-45 | 200 Version with 10-pin header



# DATASHEET

### Key Points

- Use as a high-performance single board computer or add Ethernet connectivity to a new or existing design
- Customize with a development kit and begin writing application code immediately!
- Industrial temperature range (-40°C to 85°C)

### Device Connectivity

- 10/100Mbps Ethernet with IEEE1588 PTP frames and 802.3az Energy-efficient support
- Up to 2 USARTs, 5 UARTs, 3 I<sup>2</sup>C, and 4 SPI
- 11 Analog to Digital (ADC) Inputs
- 1 Digital to Analog (DAC) Output
- 53 digital I/Os
- 16-bit External Bus Interface

### Performance and memory

- 32-bit 300 MHz Processor
- 8MB SDRAM and 2MB Flash


### Companion development kit

*The following is available with the development kit:*

- Customize any aspect of operation including web pages, data filtering, or custom network applications
- Development software: NB Eclipse IDE, Graphical debugger, deployment tools, and examples
- Communication software: TCP/IP stack, HTTPS web server, FTP, E-mail, and flash file system
- System software: uC/OS RTOS, ANSI C/C++ compiler and linker
- Security software: Embedded SSL/TLS & SSH libraries

*The following optional software modules are not included with kit and are sold separately:*

- SNMP



## Specifications

### Processor and Memory

Microchip® SAM E70 32-bit ARM® Cortex®-M7 processor running at 300 MHz clock speed with 8MB SDRAM, 2MB embedded flash, 384Kb embedded multi-port SRAM, and 1KB embedded low-power backup RAM<sup>1</sup>.

Single and double precision hardware Floating Point Unit (FPU), DSP Instructions, Thumb®-2 Instruction Set.

1. While the RAM is usable, it is unsuitable for low-power backup due to the power consumption of the module's components.

### Network Interface

10/100 BaseT with RJ-45 connector (100 Version)

10-pin header (200 Version)

### Data I/O Interface (P1 and P2)

- Up to 7 Asynchronous Serial Ports: 2 UARTs, 5 Two-wire UARTs
- Up to 53 digital I/O
- Up to 3 Two-Wire Interfaces (TWIHS)(I2C-compatible)
- Up to 4 SPI interface
- SD/MMC flash card ready
- 16-bit external bus interface
- Image Sensor Interface (ISI)
- Quad SPI Interface
- 11 Analog to Digital (ADC) Inputs
- 1 Digital to Analog (DAC) Output

### SPI Configurations

The SPI interfaces are available from the following:

- 1 dedicated SPI
- 1 Quad SPI that can be configured to run as a native SPI or QSPI
- 2 from USART0 and USART1 that can be configured as SPI

### Serial Configurations

The UARTs can be configured in the following ways:

- USART0/1
- ISO7816
- IrDA®
- RS-422/485
- Manchester

Note: USART0/1 supports SPI. USART1 supports Modem and LON mode.

### Additional Peripherals

- Ethernet AVB support with IEEE802.1AS Time-stamping and IEEE802.1Qav credit-based traffic-shaping hardware support.
- Two master Controller Area Networks (MCAN) with Flexible Data Rate (CAN-FD) with SRAM-based mailboxes, time- and event-triggered transmission.
- Serial Synchronous Controller (SSC) with I2S and TDM support.
- High-speed Multimedia Card Interface (HSMCI) (SDIO/SD Card/e.MMC)
- Nine 16-bit Timer/Counters, can be chained to create 32 bit and 48 bit timer/counters. Functions include capture, compare, interrupt generation, frequency measurement, event counting, interval measurement, quadrature decoder, pulse generation, waveform generation, synchronization with PWM peripheral, delay timing pulse width modulation, 2-bit Gray Up/Down Counter for stepper motor control. Each channel has

three external clock inputs, five internal clock inputs and two multi-purpose input/output signals.<sup>1</sup>

- 12-bit 1Msps-per-channel Digital-to-Analog Controller (DAC) with differential and oversampling modes.
- One Analog Comparator (ACC) with flexible input selection, selectable input hysteresis.
- Watchdog Timer
- Three Two-Wire Interfaces (TWIHS) (I2C-compatible). Two-wire bus, made up of one clock line and one data line with speeds of up to 400 kbps in Fast mode, and up to 3.4 Mbps in High-speed slave mode. Easily interface to EEPROM and I<sup>2</sup>C-compatible devices, such as a Real-Time Clock (RTC), Dot Matrix/Graphic LCD Controller
- Dedicated SPI. Note that USARTs 0 and 1 can also be used as SPI interfaces, as can the Quad SPI when in single bit mode.
- Seventeen 16-bit PWMs with complementary outputs, Dead Time Generator, fault inputs motor control and an external trigger.
- Two Analog Front-End Controllers (AFEC). The AFEC is based on an Analog Front-End cell (AFE) integrating a 12-bit Analog-to-Digital Converter (ADC), a Programmable Gain Amplifier (PGA), a Digital-to-Analog Converter (DAC) and two 6-to-1 analog multiplexers, making possible the conversions of 12 analog lines or two simultaneous conversions of 6 analog lines. The AFEC supports a 12-bit resolution mode which can be extended up to a 16-bit resolution by digital averaging. Up to 2Msps conversion rate. Automatic correction of gain and offset errors.
- Parallel Capture Interface consisting of clock, data and enable signals to continuously read data from peripherals such as a CMOS digital image sensor, a high-speed parallel ADC, a DSP synchronous port in synchronous mode, etc.
- Up to 53 GPIO lines. Each has several input or output modes such as pull-up or pull-down, input Schmitt triggers, multi-drive (open-drain), glitch filters, debouncing or input change interrupt. Each GPIO line also has an on-die serial resistor for impedance matching, reducing overshoot, undershoot and EMI.
- Temperature sensor internal to processor.

## LEDs

Link and Speed (100 Version only, on RJ-45)

## Physical Characteristics

Dimensions (inches): 2.60" x 2.00"

Weight: 1 oz.

Mounting Holes: 2 x 0.125" dia.

## Power

DC Input Voltage: 3.3V @ 100mA typical, 250mA max

Low power modes are able to reduce power draw, with consumption dependant on enabled peripherals.

## Environmental Operating Temperature

-40° to 85° C

## RoHS Compliance

The Restriction of Hazardous Substances guidelines ensure that electronics are manufactured with fewer environment harming materials.

<sup>1</sup> Some timer I/O is unavailable due to SDRAM and Ethernet interfaces. Please consult the pinout for further details.

## Part Numbers

### **MODM7AE70 Ethernet Core Module (100 Version, with RJ-45)**

Part Number: MODM7AE70-100IR

### **MODM7AE70 Ethernet Core Module (200 Version, with 10-pin header)**

Part Number: MODM7AE70-200IR

### **MOD7AE70 LC Development Kit**

Part Number: NNDK-MODM7AE70LC-KIT

Kit includes all the hardware and software you need to customize the included platform hardware. See NetBurner Store product page for package contents. Note: Includes the MOD-DEV-70 development board.

### **SNMP V1 (Module License Version)**

Part Number: NBLIC-SNMP

Available as an option if you are using a development kit.

## Ordering Information

E-mail: [sales@netburner.com](mailto:sales@netburner.com)

Online Store: [www.NetBurner.com](http://www.NetBurner.com)

Telephone: 1-800-695-6828

## Pinout and Signal Description

The 200 version board has a 10-pin header instead of an RJ-45 jack. This header enables you to relocate the jack to another location or to add a different jack with power over ethernet (PoE) capabilities to your module. Table 1 provides descriptions of the pin functions of the 10-pin header.

Table 1: Pinout and Signal Descriptions for Ethernet Connector <sup>(1)</sup>

Pin	Signal	Description
1	TX-	Transmit -
2	TX+	Transmit +
3	VCC <sup>1</sup>	2.5V
4	RX+	Recieve +
5	RX-	Recieve -
6	VCC <sup>1</sup>	2.5V
7	GND	Ground
8	N/C	Not Connected
9	LED	Link LED
10	LED	Speed LED

Note:

1. Ethernet magnetics center tap voltage provided by NetBurner device.

# MODM7AE70

The module has two dual in-line 50 pin headers which enable you to connect to one of our standard NetBurner Carrier Boards, or a board you create on your own. Table 2-3 provides descriptions of pin function of the module header. Most pins have a Primary and Alternate function. In the Primary function mode you can select one of up to four peripheral functions, A through D.

Table 2: Pinout and Signal Descriptions for P1 Connector <sup>(1)</sup>

Pin	Port	GPIO	P1 Connector				Alternate
			Peripheral A Peripheral C	Peripheral B Peripheral D			
1	GND						
2	GND						
3	VCC_3V						
4	PC8	X	Lower Byte Write Access (NWR0) / Write Enable (NWE)	Timer 7 Line A (TIOA7)			
5 <sup>1</sup>	PA22	X	SSC Receive Clock (100K pull-up at reset)(RK) Bus Chip Select 2 (NCS2)	PWM 0 External Trigger (PWMC0_PWMEXTRG1)		Parallel Capture Clock Input (PIODCCLK) <sup>1</sup>	
6 <sup>1</sup>	PC14	X	Bus Chip Select 0 (NCS0) CAN 1 Transmit (CANTX1)	Timer 8 Clock (TCLK8)			
7 <sup>1</sup>	PD19	X	Bus Chip Select 3 (NCS3) Serial Port 6 TX (UTXD4) <sup>5</sup>				
8 <sup>1</sup>	PC11	X	Read Signal (NRD)	Timer 8 Line A (TIOA8)			
9	PD15		NWR1/NBS1				
10	PA20		A16/BA0				
11						Transfer in Progress (TIP) footnote <sup>2</sup>	
12	PC0		D0				
13	PC13	X	External Wait Signal (NWAIT)	PWM 0 Channel 3 Output High (PWMC0_PWMH3)		AFE 1 ADC Input 1 (AFE1_AD1) <sup>3</sup>	
14	PC2		D2				
15	PC1		D1				
16	PC4		D4				

**Note:**

1. When the External Bus Interface (EBI) peripheral is enabled, this signal is locked to EBI functionality. Trying to use this signal while it is in use by the EBI peripheral can damage the module.

# MODM7AE70

P1 Connector					
Pin	Port	GPIO	Peripheral A	Peripheral B	Alternate
			Peripheral C	Peripheral D	
17	PC3		D3		
18	PC6		D6		
19	PC5		D5		
20	PE0		D8		
21	PC7		D7		
22	PE2		D10		
23	PE1		D9		
24	PE4		D12		
25	PE3		D11		
26	PA15		D14		
27	PE5		D13		
28	NRST				
29	PA16		D15		
30	NRST				
31	PA6	X	Serial Port 3 TX (UTXD1) <sup>5</sup>	Programmable Clock Channel 0 Output (PCK0)	
32	PC18		A0/NBS0		
33	PC19	X	A1	PWM 0 Channel 2 Output High (PWMC0_PWMH2)	
34	PC20		A2		

# MODM7AE70

P1 Connector					
Pin	Port	GPIO	Peripheral A	Peripheral B	Alternate
			Peripheral C	Peripheral D	
35	PC21		A3		
36	PC22		A4		
37	PC23		A5		
38	PC24		A6		
39	PC25		A7		
40	PC26		A8		
41	PC27		A9		
42	PC28		A10		
43	PC29		A11		
44	PC30	X	A12	Timer 5 Line B (TIOB5)	AFE 1 ADC Input 5 (AFE1_AD5)(5) <sup>3</sup>
45	PC31		A13		
46	PA18		A14		
47	PA19	X	A15	PWM 0 Channel 0 Output Low (PWMC0_PWML0) Sound Controller 1 Master Clock (I2SC1_MCK)	AFE 0 ADC Input 8 (AFE0_AD8) Wakeup Pin 9 (WKUP9) <sup>4</sup>
48	VCC_V3				
49	GND				
50	GND				

**Note:**

1. To select this extra function, refer to Section 32.5.14 "Parallel Capture Mode".
2. Logical AND of PA.22, PC.14, PD.19. Typically used to control the enable of an external data bus buffer.
3. To select this extra function, refer to Section 50.5.1 "I/O Lines".
4. Analog input has priority over WKUPx pin. To select the analog input, refer to Section 50.5.1 "I/O Lines". WKUPx can be used if the PIO controller defines the I/O line as "input".
5. See Table 5 for Serial Port to USART/UART mapping.



# MODM7AE70

Table 3: Pinout and Signal Descriptions for P2 Connector <sup>(1)</sup>

P2 Connector							
Pin	Port	GPIO	Peripheral A		Peripheral B		Alternate
			Peripheral C		Peripheral D		
1	GND						
2	VCC_3V						
3	PB0	X	PWM0 Channel 0 Output High (PWM0_PWMH0)				AFE0 ADC Input 10 (AFE0_AD10) RTCOUNT
4	PB1	X	Serial Port 0 RX (RXD0) <sup>10</sup>				
5	VREFP	X	PWM0 Channel 1 Output High (PWM0_PWMH1)				AFE1 ADC Input 0 (AFE1_AD0) RTCOUNT1
6	PC12	X	Serial Port 0 TX (TXD0) <sup>10</sup>				
7	PD30	X	ADC Voltage Reference				
8	PA17	X	CAN 1 Receive (CANRX1)				AFE1 ADC Input 3 (AFE1_AD3) <sup>5</sup>
9	PA2	X	Serial Port 5 TX (UTXD3) <sup>10</sup>				AFE0 ADC Input 0 (AFE0_AD0) <sup>5</sup>
10	PD18	X	QSPI Data 2 Quad Mode (QI2)				AFE0 ADC Input 6 (AFE0_AD6) <sup>5</sup>
11	PB13	X	PWM0 Chan 3 Output High (PWM0_PWMH3)				Wakeup Pin 2 (WKUP2) <sup>1</sup>
12	PA5	X	PWM0 Channel 1 Output High (PWM0_PWMH1)				
	PB5	X	DAC Trigger Input (DATRG)				
13	PA8	X	PWM1 Channel 3 Output High (PWM1_PWMH3)				
14	GND		Serial Port 6 RX (URXD4) <sup>10</sup>				
15	PD24	X	PWM0 Channel 2 Output Low (PWM0_PWML2)				
16	PA28	X	Serial Port 0 Serial Clock (SCK0)				
17	PA26	X	PWM1 Channel 3 Output Low (PWM1_PWML3)				
			Serial Port 3 RX (URXD1) <sup>10</sup>				
			Two-wire Channel 1 Clock (TWCK1)				
			PWM1 Channel 3 Output High (PWM1_PWMH3)				
			PWM0 Channel 0 Output Low (PWM0_PWML0)				
			Timer 11 Clock Input (TCLK11)				
			Serial Port 1 DSR (100K pull-up at reset)(DSR1) <sup>10</sup>				
			Multimedia Card Slot A Data Command (MCCDA)				
			Serial Port 1 DCD (100K pull-up at reset)(DCD1) <sup>10</sup>				
			Multimedia Card Slot A Data 2 (MCDA2)				
			PWM0 Channel 0 Output Low (PWM0_PWML0)				
			Timer 1 Clock (TCLK1)				
			PWM1 Fault Input 2 (PWM1_PWMF2)				
			Timer 2 Line A (TIOA2)				
			PWM1 Fault Input 1 (PWM1_PWMF1)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Timer 1 Clock (TCLK1)				
			PWM1 Fault Input 2 (PWM1_PWMF2)				
			Timer 2 Line A (TIOA2)				
			PWM1 Fault Input 1 (PWM1_PWMF1)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				
			SSC Receive Frame sync (RF)				
			Image Sensor Horizontal Sync (ISI_HSYNC)				
			Image Sensor Channel 4 Data Input (ISI_D4)				
			PWM0 Channel 0 Output Low (PWM0_PWMLO)				
			SSC Transmit Data (TD)				
			AFE0 ADC External Trigger (AFE0_ADTRG)				

# MODM7AE70

P2 Connector							
Pin	Port	GPIO	Peripheral A		Peripheral B		Alternate
			Peripheral A	Peripheral C	Peripheral B	Peripheral D	
18	PA27	X	Serial Port 1 DTR (100K pull-up at reset)(DTR1) <sup>10</sup> Multimedia Card Slot A Data 3 (MCDA3)		Timer 2 Line B (TIOB2) Image Sensor Data Input 7 (ISI_D7)		
19	PA1	X	PWM 0 Channel 0 Output Low (PWMC0_PWML0) A18		Timer 0 Line B (TIOB0) Sound Controller 0 Serial Clock (#2SC0_CK)		Wakeup Pin 1 (WKUP1) <sup>1</sup>
20	PA29	X	Serial Port 1 RI (100K pull-up at reset)(RI1) <sup>10</sup>		Timer 2 Clock (TCLK2)		
21	PA21	X	Serial Port 1 RX (RXD1) <sup>10</sup> PWM 1 Chan 0 Fault Input (PWMC1_PWMF10)		Programmable Clock Output 1 (PCK1)		AFE 0 ADC Input 1 (AFE0_AD1)(6) Parallel Capture Enable 2 (PIODCEN2) <sup>8</sup>
22	PB4	X	Two-wire Channel 1 Data (TWD1)		PWM 0 Channel 2 Output High (PWMC0_PWMH2) Serial Port 1 TX (TXD1) <sup>10</sup>		Test Data In (TDI) <sup>9</sup>
23	PD28	X	Serial Port 5 RX (URXD3) <sup>10</sup> Two-Wire 2 Clock (TWCK2)		CAN 1 Receive (CANRX1) Image Sensor Data Input 9 (ISI_D9)		Wakeup Pin 5 (WKUP5) <sup>1</sup>
24	PD31	X	QSPI Quad Mode Data 3 (QIO3) Programmable Clock 2 Output (PCK2)		Serial Port 5 TX (UTXD3) <sup>10</sup> Image Sensor Data Input 11 (ISI_D11)		
25	PD22	X	PWM 0 Channel 2 Output High (PWMC0_PWMH2) Timer 11 Line B (TIOB11)		SPI 0 Clock (SPI0_SPCCK) Image Sensor Date Input 0 (ISI_D0)		
26	PD27	X	PWM 0 Channel 3 Output Low (PWMC0_PWML3) Two-Wire 2 Serial Data (TWD2)		SPI 0 Chip Select 3 (SPI0_NPCS3) Image Sensor Date Input 8 (ISI_D8)		
27	PD20	X	PWM 0 Channel 0 Output High (PWMC0_PWMH0) TSU Timer Comparison Valid 1588 (GTSUCOMP)		SPI 0 Master In Slave Out (SPI0_MISO)		
28	PD21	X	PWM 0 Channel 1 Output High (PWMC0_PWMH1) Timer 11 Line A (TIOA11)		SPI 0 Master Out Slave In (SPI0_MOSI) Image Sensor Data Input 1 (ISI_D1)		
29	PB2	X	CAN 0 Transmit (CANTX0) Serial Port 0 CTS (CTS0) <sup>10</sup>		SPI 0 Chip Select 0 (SPI0_NPCS0) CAN 1 Transmit (CANTX1)		AFE 0 ADC Input 5 (AFE0_AD5)
30	PD12	X	GMAC Receive Data 3 (GRX3) SPI 0 Chip Select 2 (SPI0_NPCS2)		Image Sensor Data Input 6 (ISI_D6) PWM 0 Chan 0 Output High (PWMC0_PWMH0)		
31	PA23	X	Serial Port 1 Serial Clock (100K pull-up at reset) (SCK1) A19		PWM 1 Channel 2 Output Low (PWMC1_PWML2) PWM 0 Chan 1 Output High (PWMC0_PWMH1)		
32	PA24	X	Serial Port 1 RTS (RTS1) <sup>10</sup> A20		Image Sensor Data Clock (ISI_PCK) PWM 0 Chan 2 Output High (PWMC0_PWMH2)		
33	PA25	X	Serial Port 1 CTS (CTS1) <sup>10</sup> A23		Multimedia Card Clock (MCCCK) Image Sensor Channel 3 Data Input (ISI_D3)		Wakeup Pin 6 (WKUP6)
34	PA9	X	Serial Port 2 RX (URXD0) <sup>10</sup> PWM 0 Fault Input 0 (100k pull-up reset) (PWMC0_PWM-FI0)				Parallel Capture Data 3 (PIODC3) <sup>3</sup>

# MODM7AE70

P2 Connector							
Pin	Port	GPIO	Peripheral A		Peripheral B		Alternate
			Peripheral C		Peripheral D		
35	PA10	X	Serial Port 2 TX (UTXD0) <sup>10</sup>		PWM 0 External Trigger 0 (PWMC0_PWMEXTRG0)		Parallel Capture Data 4 (PIODC4) <sup>2</sup>
36	PA30	X	SSC Receive Data (100k pull-up at reset) (RD)		PWM 1 Chan 0 Trigger Input (PWMC1_PWMEXTRG0)		Wakeup Pin 11 (WKUP11)
37	PD11	x	PWMC0_PWML2		Sounds Controller 0 Data Output (I2SC0_DO)		
38	PB3	X	Multimedia Card Slot A Data 0 (MCDA0)		PWM 0 Channel 0 Output High (PWMC0_PWMH0)		AFE 0 ADC Input 2 (AFE0_AD2)/WKUP12 <sup>6</sup>
39	PA3	X	GMAC Receive Data 2 (GRX2)		Image Sensor Data Input 5 (ISL_D5)		Parallel Capture Data 0 (PIODC0)
40	PA31	X	TSU Timer Comparison Valid 1588 (GTSUCOMP)		Programmable Clock Output 2 (PCK2)		
41	PD25	X	CAN 0 Receive (CANRX0)		Image Sensor Clock Output 2 (PCK2)		
42	PA4	X	Serial Port 0 RTS (RTS0) <sup>10</sup>		Image Sensor Data Input 2 (ISL_D2)		
43	PA13	X	Serial Port 0 Data (TWD0)		LON Chan 1 Collision Detect (LONCOL1)		
44	PD26	X	Programmable Clock Output 2 (PCK2)				
45	PA14	X	SPI 0 Chip Select 1 (SPI0_NPCS1)		Programmable Clock Output 2 (PCK2)		
46	GND		Multimedia Card Slot A Data 1 (MCDA1)		PWM 1 Channel 2 Output High (PWMC1_PWMH2)		
47	PA12	X	PWM 0 Channel 1 Output Low (PWMC0_PWML1)		SPI0 Chip Select 1 (SPI0_NPCS1)		
48	PA11	X	Serial Port 4 RX (URXD2) <sup>10</sup>		Image Sensor Vertical Sync (ISL_VSYNC)		
49	GND		Two-Wire 0 Clock (TWCK0)		Timer 0 Clock (TCLK0)		Wakeup Pin 3 (WKUP3)
50	VCC_3V		Serial Port 3 TX (UTXD1) <sup>10</sup>				Parallel Capture Data 1 (PIODC1)
			QSPI MOSI Single Bit Mode, Data 0 Quad Mode (QIO0)		PWM 0 Channel 2 Output High (PWMC0_PWMH2)		Parallel Capture Data 7 (PIODC7) <sup>2</sup>
			PWM 1 Chan 1 Output Low (PWMC1_PWML1)				
			PWM 0 Channel 2 Output Low (PWMC0_PWML2)		SSC Transmt Data (TD)		
			Serial Port 4 TX (UTXD2) <sup>10</sup>		Serial Port 3 TX (UTXD1) <sup>10</sup>		
			QSPI Serial Clock (QSCK)		PWM 0 Channel 3 Output High (PWMC0_PWMH3)		Wakeup Pin 8 (WKUP8)
			PWM 1 Chan 1 Output High (PWMC1_PWMH1)				Parallel Capture Date En 1 (PIODCEN1) <sup>3</sup>
			QSPI MISO Single Bit Mode, Data 1 Quad Mode (QIO1)		PWM 0 Channel 1 Output High (PWMC0_PWMH1)		Parallel Capture Data 6 (PIODC6) <sup>2</sup>
			PWM 1 Chan 0 Output High (PWMC1_PWMH0)				
			QPI Chip Select (QCS)		PWM 0 Channel 0 Output High (PWMC0_PWMH0)		Wakeup Pin 7 (WKUP7)
			PWM 1 Chan 0 Output Low (PWMC1_PWML0)				Parallel Capture Data 5 (PIODC5) <sup>3</sup>

**Note:**

1. WKUPx can be used if the PIO Controller defines the I/O line as "input".
2. To select this extra function, refer to Section 32.5.14 "Parallel Capture Mode".
3. PIODCEN1/PIODCx has priority over WKUPx. Refer to Section 32.5.14 "Parallel Capture Mode".
4. Refer to Section 22.4.2 "Slow Clock Generator".
5. To select this extra function, refer to Section 50.5.1 "I/O Lines".
6. Analog input has priority over WKUPx pin. To select the analog input, refer to Section 50.5.1 "I/O Lines". WKUPx can be used if the PIO controller defines the I/O line as "input".

# MODM7AE70

7. DAC0 is selected when DACC\_CHER.CH0 is set. DAC1 is selected when DACC\_CHER.CH1 is set. Refer to Section 51.7.4 “DAC Channel Enable Register”.
8. Analog input has priority over WKUPx pin. To select the analog input, refer to Section 50.5.1 “I/O Lines”. To select PIOCEN2, refer to Section 32.5.14 “Parallel Capture Mode”.
9. Refer to the System I/O Configuration Register in Section 18. “Bus Matrix (MATRIX)”.
10. See Table 5 for Serial Port to USART/UART mapping.

**Table 4: Pinout and Signal Descriptions for P3, USB Connector**

Pin	Signal	GPIO	Description
1	VCCUSB		USB VBUS Enable <sup>1</sup>
2	USB.D_N		USB Data Negative
3	USB.ID	X	USB ID Line
4	USB.D_P		USB Data Positive

Note:

1. Voltage divided for 5V signal tolerance.

## Serial Port to USART/UART Mapping

This table details the mapping of the NetBurner software serial port number to the processor hardware signal name. The SAME70 processor provides both USART and UART serial ports. In addition to functioning as a UART, the USART ports can be configured for ISO7816, IrDA®, RS-485, SPI, Manchester and Modem modes; USART1 supports LON mode. Please refer to the SAME70 processor manual for details on the USARTs. USART 2 is available in custom and chip based designs, but is not fully pinned out on the MODM7AE70.

**Table 5: Serial Port to USART/UART Mapping for P1 and P2 Connector**

Serial Port Number	Hardware Module	
	USART	UART
0	0	
1	1	
2		0
3		1
4		2
5		3
6		4



## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331