

# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

Series 14-9159



AVX developed the 9159 Series of SMT connectors for co-planar PCB mating for the challenging Solid State Lighting (SSL) market. These connectors needed to be small, low in height, carry up to 5 Amps/contact and then function up to 125C for extended periods. This application has been very unique to the SSL market where PCB's are stacked end-to-end to create linear strip lighting in everything from office to transportation applications where products are exposed to harsh mechanical and environmental environments.

The IDC cable plug connector allows for 22-24AWG discrete or cabled wires to be easily and reliability terminated into a 9159 standard interface socket connector. This will allow power and signals to be connectors onto a PCB socket connector while providing positive latching. The wire assembly support block allows for 2 through 6 wires to be terminated all in one step with any standard bench top press. IDC covers provide both through (daisy chain applications) and wire stop termination options.

### APPLICATIONS

- Provides Wire-to-Board capabilities to standard 9159 2-Piece connector system
- In conjunction with the IDC socket WTB connector (24-9159), these connectors provide maximum flexibility to bring power and signal wires onto or off of any board level 9159 connector
- Reference application notes 201-01-123
- Reference Product Specification 201-01-119

### FEATURES AND BENEFITS

- Mates with standard 9159 horizontal socket, keeping same BTB connector system
- Economical and reliable IDC wire termination
- Gold plated BeCu contact system for high reliability in harsh environments
- Integrally molded latch offers positive latching after mating

### ELECTRICAL

- Current Rating: 5 Amps / Contact
- Voltage Rating: 125 VAC

### ENVIRONMENTAL

- Operating Temperature: -40°C to +125°C

### MECHANICAL

- Insulator Material: Nylon: UL94VO
- Contact Material: Phosphor Bronze
- Plating: Gold / Tin over Nickel
- Durability: 10 Cycles

### HOW TO ORDER

**14**

Prefix  
Right Angle  
Wired Plug  
IDC Terminations

**9159**

Series

**XXX**

Number of Ways

| Code                    | No of Ways | Details |
|-------------------------|------------|---------|
| <b>THROUGH WIRE CAP</b> |            |         |
| 002                     | 2          | Page 25 |
| 003                     | 3          | Page 26 |
| 004                     | 4          | Page 27 |
| 005                     | 5          | Page 28 |
| 006                     | 6          | Page 29 |
| <b>WIRE STOP CAP</b>    |            |         |
| 002                     | 2          | Page 30 |
| 003                     | 3          | Page 31 |
| 004                     | 4          | Page 32 |
| 005                     | 5          | Page 33 |
| 006                     | 6          | Page 34 |

**1**

2 Part  
PCB Strip  
Connector  
2 Part  
Wired IDC  
Strip  
Connector

**X**

Wire Gauge  
2 = 22AWG  
3 = 24AWG

**2**

Wire  
Insulation  
Diameter  
ø1.10mm  
to ø1.60mm

**X**

Color Options

| Code | Color | Availability |
|------|-------|--------------|
| 1    | White | Standard     |

**X**

Cap Options

| Code | Cap Option   | Description                                          |
|------|--------------|------------------------------------------------------|
| 0    | Through Wire | Allows wires to be terminated at any point           |
| 9    | Wire Stop    | Terminates end of wire. End protected with Stop Face |

**6**

Plating Option

| Code | Contact                       |
|------|-------------------------------|
| 6    | Gold on Contact<br>Tin on IDC |




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

Series 14-9159


### PLUG-WIRED – 2 WAY THROUGH WIRE CAP



**NOTES:**



1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.  
FOR WIRE ASSEMBLY REFER TO APPLICATION NOTES 201-01-123.
2. THROUGH WIRE CAP, FOR TERMINATION OF WIRE IN ANY POSITION.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge               | Code<br>(Page 24) | Dimension A | Wire Insulation<br>Diameter |
|--------------------------|-------------------|-------------|-----------------------------|
| 22AWG<br>(Stranded Wire) | 122               | 0.47        | 1.10 to 1.60                |
| 24AWG<br>(Stranded Wire) | 132               | 0.37        | 1.10 to 1.60                |



### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

### Series 14-9159


#### PLUG-WIRED – 3 WAY THROUGH WIRE CAP



#### NOTES:



1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.  
FOR WIRE ASSEMBLY REFER TO APPLICATION NOTES 201-01-123.
2. THROUGH WIRE CAP, FOR TERMINATION OF WIRE IN ANY POSITION.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge               | Code<br>(Page 24) | Dimension A | Wire Insulation<br>Diameter |
|--------------------------|-------------------|-------------|-----------------------------|
| 22AWG<br>(Stranded Wire) | 122               | 0.47        | 1.10 to 1.60                |
| 24AWG<br>(Stranded Wire) | 132               | 0.37        | 1.10 to 1.60                |



#### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

### Series 14-9159


#### PLUG-WIRED – 4 WAY THROUGH WIRE CAP



#### NOTES:



1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.  
FOR WIRE ASSEMBLY REFER TO APPLICATION NOTES 201-01-123.
2. THROUGH WIRE CAP, FOR TERMINATION OF WIRE IN ANY POSITION.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge               | Code<br>(Page 24) | Dimension A | Wire Insulation<br>Diameter |
|--------------------------|-------------------|-------------|-----------------------------|
| 22AWG<br>(Stranded Wire) | 122               | 0.47        | 1.10 to 1.60                |
| 24AWG<br>(Stranded Wire) | 132               | 0.37        | 1.10 to 1.60                |



#### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

### Series 14-9159





#### PLUG-WIRED – 5 WAY THROUGH WIRE CAP



#### NOTES:



1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.  
FOR WIRE ASSEMBLY REFER TO APPLICATION NOTES 201-01-123.
2. THROUGH WIRE CAP, FOR TERMINATION OF WIRE IN ANY POSITION.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge               | Code<br>(Page 24) | Dimension A | Wire Insulation<br>Diameter |
|--------------------------|-------------------|-------------|-----------------------------|
| 22AWG<br>(Stranded Wire) | 122               | 0.47        | 1.10 to 1.60                |
| 24AWG<br>(Stranded Wire) | 132               | 0.37        | 1.10 to 1.60                |



#### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap



Series 14-9159



### PLUG-WIRED – 6 WAY THROUGH WIRE CAP



**NOTES:**



1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.  
FOR WIRE ASSEMBLY REFER TO APPLICATION NOTES 201-01-123.
2. THROUGH WIRE CAP, FOR TERMINATION OF WIRE IN ANY POSITION.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge               | Code<br>(Page 24) | Dimension A | Wire Insulation<br>Diameter |
|--------------------------|-------------------|-------------|-----------------------------|
| 22AWG<br>(Stranded Wire) | 122               | 0.47        | 1.10 to 1.60                |
| 24AWG<br>(Stranded Wire) | 132               | 0.37        | 1.10 to 1.60                |



### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

### Series 14-9159


#### PLUG-WIRED – 2 WAY WIRE STOP CAP



#### NOTES:


1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.
2. WIRE STOP CAP, WITH STOP FACE ON ONE SIDE TO PROTECT END OF WIRE.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. SHOWN WITH WIRE ENTRY FROM UNDERSIDE, CAP CAN BE ASSEMBLED FOR EITHER TOP OR UNDERSIDE WIRE ENTRY.
10. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge               | Code<br>(Page 24) | Dimension A | Wire Insulation<br>Diameter |
|--------------------------|-------------------|-------------|-----------------------------|
| 22AWG<br>(Stranded Wire) | 122               | 0.47        | 1.10 to 1.60                |
| 24AWG<br>(Stranded Wire) | 132               | 0.37        | 1.10 to 1.60                |



#### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

### Series 14-9159




#### PLUG-WIRED – 3 WAY WIRE STOP CAP



#### NOTES:



1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.  
FOR WIRE ASSEMBLY REFER TO APPLICATION NOTES 201-01-123.
2. WIRE STOP CAP, WITH STOP FACE ON ONE SIDE TO PROTECT END OF WIRE.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. SHOWN WITH WIRE ENTRY FROM UNDERSIDE, CAP CAN BE ASSEMBLED FOR EITHER TOP OR UNDERSIDE WIRE ENTRY.
10. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge               | Code<br>(Page 24) | Dimension A | Wire Insulation<br>Diameter |
|--------------------------|-------------------|-------------|-----------------------------|
| 22AWG<br>(Stranded Wire) | 122               | 0.47        | 1.10 to 1.60                |
| 24AWG<br>(Stranded Wire) | 132               | 0.37        | 1.10 to 1.60                |



#### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

### Series 14-9159




#### PLUG-WIRED – 4 WAY WIRE STOP CAP



#### NOTES:



1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.  
FOR WIRE ASSEMBLY REFER TO APPLICATION NOTES 201-01-123.
2. WIRE STOP CAP, WITH STOP FACE ON ONE SIDE TO PROTECT END OF WIRE.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. SHOWN WITH WIRE ENTRY FROM UNDERSIDE, CAP CAN BE ASSEMBLED FOR EITHER TOP OR UNDERSIDE WIRE ENTRY.
10. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge               | Code<br>(Page 24) | Dimension A | Wire Insulation<br>Diameter |
|--------------------------|-------------------|-------------|-----------------------------|
| 22AWG<br>(Stranded Wire) | 122               | 0.47        | 1.10 to 1.60                |
| 24AWG<br>(Stranded Wire) | 132               | 0.37        | 1.10 to 1.60                |



#### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

### Series 14-9159




#### PLUG-WIRED – 5 WAY WIRE STOP CAP



#### NOTES:



1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.  
FOR WIRE ASSEMBLY REFER TO APPLICATION NOTES 201-01-123.
2. WIRE STOP CAP, WITH STOP FACE ON ONE SIDE TO PROTECT END OF WIRE.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. SHOWN WITH WIRE ENTRY FROM UNDERSIDE, CAP CAN BE ASSEMBLED FOR EITHER TOP OR UNDERSIDE WIRE ENTRY.
10. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge               | Code<br>(Page 24) | Dimension A | Wire Insulation<br>Diameter |
|--------------------------|-------------------|-------------|-----------------------------|
| 22AWG<br>(Stranded Wire) | 122               | 0.47        | 1.10 to 1.60                |
| 24AWG<br>(Stranded Wire) | 132               | 0.37        | 1.10 to 1.60                |



#### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

### Series 14-9159


#### PLUG-WIRED – 6 WAY WIRE STOP CAP



#### NOTES:



1. FOR MORE INFORMATION REFER TO PRODUCT SPEC 201-01-119.  
FOR WIRE ASSEMBLY REFER TO APPLICATION NOTES 201-01-123.
2. WIRE STOP CAP, WITH STOP FACE ON ONE SIDE TO PROTECT END OF WIRE.
3. CAP ACTS AS WIRE ASSEMBLY TOOL. WIRE PREFIT TO CAP, NARROW SLOT TO GRIP WIRE, PERMANENT ASSEMBLY.
4. GENERAL TOLERANCE  $\pm 0.20$  UNLESS SPECIFIED.
5. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0. COLOR REFER TO PAGE 24.
6. CONTACT MATERIAL: COPPER ALLOY, PLATING NICKEL BASE ALL OVER, GOLD ON CONTACT, TIN ON IDC.
7. PACKING IN TAPE AND REEL. QTY PER REEL 700, POCKET CONTAINS 1 CONNECTOR AND 1 CAP.
8. WIRE GAUGE OPTIONS, SEE TABLE.
9. SHOWN WITH WIRE ENTRY FROM UNDERSIDE, CAP CAN BE ASSEMBLED FOR EITHER TOP OR UNDERSIDE WIRE ENTRY.
10. ASSEMBLY AIDS, REFER TO PAGE 35.

| Wire Gauge            | Code (Page 24) | Dimension A | Wire Insulation Diameter |
|-----------------------|----------------|-------------|--------------------------|
| 22AWG (Stranded Wire) | 122            | 0.47        | 1.10 to 1.60             |
| 24AWG (Stranded Wire) | 132            | 0.37        | 1.10 to 1.60             |



#### PACKING DETAILS

#### CAP AND CONNECTOR SUPPLIED TOGETHER (2 PARTS)




# IDC Plug: WTB

## Through Wire Cap/Wire Stop Cap

Series 14-9159


### PLUG-WIRED – ASSEMBLY SUPPORT BLOCK



**NOTES:**

1. BLOCK TO SUPPORT 9159 IDC WIRED CONNECTORS DURING ASSEMBLY OF CAP/WIRE.
2. PART NUMBER 06-9159-7026-01-000, MATERIAL ALUMINUM.  
PART NUMBER 06-9159-7026-02-000, MATERIAL NYLON 46.
3. CAN BE USED WITH EITHER THE PLUG OR SOCKET CONNECTORS, USE THE CORRECT SLOT AS IDENTIFIED.
4. FOR FULL WIRE ASSEMBLY DETAILS REFER TO APPLICATION NOTES 201-01-123.
5. ONLY A SIMPLE FLAT BOTTOMED TOOL REQUIRED TO PUSH THE CAP DOWN (NOT SUPPLIED.)
6. ALL DIMENSIONS  $\pm 0.20$  UNLESS TOLERANCED.
7. 06-9159-7026-02-000 HAS RIBS TO HELP LOCATE CONTACT/INSULATOR SUB-ASSEMBLY.

### PLUG-WIRED – WIRE INSERTION TOOL



**WIRE INSERTION TOOL 06-9159-7027-01-000**

**NOTES:**


1. TOOL 06-9159-7027-01-000 TO INSERT WIRES INTO CAP.
2. FOR USE WITH UNIVERSAL HANDLE 06-7000-7720-01-000.
3. CAN BE USED WITH BOTH THROUGH WIRE AND WIRE STOP CAPS.
4. REFER TO APPLICATION NOTES 201-01-123 FOR FURTHER DETAILS.

# IDC Plug: WTB


## Through Wire Cap/Wire Stop Cap

Series 14-9159


PLUG-WIRED – ASSEMBLY



THROUGH WIRE



WIRED STOP  
WIRE ENTRY UNDERSIDE



WIRED STOP  
WIRE ENTRY TOP



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331