DUAL N-CHANNEL ENHANCEMENT MODE FIELD EFFECT TRANSISTOR

NEW PRODUCT

Features

- Dual N-Channel MOSFET
- Low On-Resistance
- Low Gate Threshold Voltage
- Low Input Capacitance
- Fast Switching Speed
- Low Input/Output Leakage
- Ultra-Small Surface Mount Package
- **Lead Free By Design/RoHS Compliant (Note 3)**
- **"Green" Device (Note 4)**
- **Qualified to AEC-Q101 Standards for High Reliability**


Mechanical Data

- Case: SOT-563
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminal Connections: See Diagram (Note 1)
- Terminals: Finish - Matte Tin annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Marking Information: See Page 2
- Ordering Information: See Page 2
- Weight: 0.003 grams (approximate)


SOT-563



TOP VIEW



2N7002VC
(ASK Marking Code)



2N7002VAC
(AYK Marking Code)

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Value	Units
Drain-Source Voltage		V_{DSS}	60	V
Drain-Gate Voltage $R_{GS} \leq 1.0M\Omega$		V_{DGR}	60	V
Gate-Source Voltage (Note 2)	Continuous Pulsed	V_{GSS}	±20 ±40	V
Drain Current (Note 2)	Continuous	I_D	280	mA
Drain Current (Note 2)	Pulsed	I_{DM}	1.5	A

Thermal Characteristics @T_A = 25°C unless otherwise specified

Characteristic	Symbol	Value	Units
Total Power Dissipation	P_d	150	mW
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	833	°C/W
Operating and Storage Temperature Range	T_j, T_{STG}	-55 to +150	°C

Electrical Characteristics @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 5)							
Drain-Source Breakdown Voltage		BV_{DSS}	60	70	—	V	V_{GS} = 0V, I_D = 10mA
Zero Gate Voltage Drain Current	@ T_C = 25°C @ T_C = 125°C	I_{DSS}	—	—	1.0 500	μA	V_{DS} = 60V, V_{GS} = 0V
Gate-Body Leakage		I_{GSS}	—	—	±100	nA	V_{GS} = ±20V, V_{DS} = 0V
ON CHARACTERISTIC (Note 5)							
Gate Threshold Voltage		$V_{GS(th)}$	1.0	—	2.5	V	V_{DS} = V_{GS}, I_D = 250μA
Static Drain-Source On-Resistance		$R_{DS\ (ON)}$	— —	— —	7.5 13.5	Ω	V_{GS} = 5V, I_D = 0.05A, V_{GS} = 10V, I_D = 0.5A, T_j = 125°C
On-State Drain Current		$I_{D(ON)}$	0.5	1.0	—	A	V_{GS} = 10V, V_{DS} = 7.5V
Forward Transconductance		g_{FS}	80	—	—	mS	V_{DS} = 10V, I_D = 0.2A
DYNAMIC CHARACTERISTICS							
Input Capacitance		C_{iss}	—	—	50	pF	V_{DS} = 25V, V_{GS} = 0V, f = 1.0MHz
Output Capacitance		C_{oss}	—	—	25	pF	
Reverse Transfer Capacitance		C_{rss}	—	—	5.0	pF	
SWITCHING CHARACTERISTICS							
Turn-On Delay Time		$t_{D(ON)}$	—	—	20	ns	V_{DD} = 30V, I_D = 0.2A, R_L = 150Ω, V_{GEN} = 10V, R_{GEN} = 25Ω
Turn-Off Delay Time		$t_{D(OFF)}$	—	—	20	ns	

Notes:
1. Package is non-polarized. Parts may be on reel in orientation illustrated, 180° rotated, or mixed (both ways).
2. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch; pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at http://www.diodes.com/datasheets/ap02001.pdf.
3. No purposefully added Lead.
4. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
5. Short duration pulse test used to minimize self-heating effect.

© Diodes Incorporated

NEW PRODUCT





Fig. 1, Derating Curve - Total

Ordering Information (Note 6)


Part Number	Case	Packaging
2N7002VC-7	SOT-563	3000/Tape & Reel
2N7002VAC-7	SOT-563	3000/Tape & Reel

Notes: 6. For packaging details, go to our website at http://www.diodes.com/datasheets/ap02007.pdf.

Marking Information



ASK = 2N7002VC Product Type Marking Code (See Note 1)
YM = Date Code Marking
Y = Year ex: R = 2004
M = Month ex: 9 = September




AYK = 2N7002VAC Product Type Marking Code (See Note 1)
YM = Date Code Marking
Y = Year ex: R = 2004
M = Month ex: 9 = September

Date Code Key

Year	2004	2005	2006	2007	2008	2009	2010	2011	2012
Code	R	S	T	U	V	W	X	Y	Z

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

Package Outline Dimensions




SOT-563			
Dim	Min	Max	Typ
A	0.15	0.30	0.20
B	1.10	1.25	1.20
C	1.55	1.70	1.60
D		0.50	
G	0.90	1.10	1.00
H	1.50	1.70	1.60
K	0.55	0.60	0.60
L	0.10	0.30	0.20
M	0.10	0.18	0.11
All Dimensions in mm			

© Diodes Incorporated

NEW PRODUCT

Suggested Pad Layout



Dimensions	Value (in mm)
Z	2.2
G	1.2
X	0.375
Y	0.5
C	1.7
E	0.5

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

© Diodes Incorporated

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331