THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
DW	—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	RELEASED.	19APR'12	JC	WK





RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05





NOTES:
1. MATERIAL:
   1.1 HOUSING: LCP, UL 94V-0, BLACK COLOR.
   1.2 CONTACT: PHOSPHOR BRONZE.
   1.3 SHELL: PHOSPHOR BRONZE.
   1.4 PANEL: PHOSPHOR BRONZE.
   1.5 REAR SHELL: SPCC.
2. FINISH:
   2.1 CONTACT
   GOLD FLASH ON THE CONTACT AREA,
   2.54um [100u"] MIN. MATTE-TIN PLATING ON THE SOLDERING AREA.
   1.27um [50u"] MIN. NICKEL UNDERPLATING OVERALL.
   2.2 SHELL: 2.54um [100u"] MIN. NICKEL PLATING.
   2.3 PANEL: 1.27um [50u"] MIN. NICKEL PLATING.
   2.4 REAR SHELL: 1.27um [50u"] MIN. NICKEL PLATING.
3. RECOMMENDED P.C.B THICKNESS : 1.60mm
4. REFLOW SOLDER CAPABLE TO 260°C PER TE CONNECTIVITY SPEC. 109-201, CONDITION B.
5. LOW HALOGEN SPECIFICATION:
   CHLORINE(Cl): 900ppm MAX.
   BROMINE(Br): 900ppm MAX.
   CHLORINE(Cl)+BROMINE(Br): 1500ppm MAX.



MOUNTING PANEL CUTOUT

2041495-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± -
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	± -
ANGLES	± 3°

MATERIAL: SEE NOTE
FINISH: SEE NOTE

DWN	J. CHEN 19APR2012
CHK	S. CHIEN 19APR2012
APVD	W. KODAMA 19APR2012
PRODUCT SPEC	108-57519
APPLICATION SPEC	—
WEIGHT	9.55 GRAMS

TE Connectivity

NAME: TRIPLE STACKED USB, A TYPE RECEPTACLE, R/A DIP CONN.

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-2041495	—

CUSTOMER DRAWING | SCALE — | SHEET 1 OF 2 | REV A

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
DW	—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			













10.55	9.55	100	10	1000
G/W (KG)	N/W (KG)	PCS/ TRAY	TRAY/ CARTON	PCS/ CARTON

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL –

FINISH –

DWN –
CHK –
APVD –
PRODUCT SPEC –
APPLICATION SPEC –
WEIGHT –

TE Connectivity

NAME
TRIPLE STACKED USB, A TYPE RECEPTACLE, R/A DIP CONN.

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-2041495	—

CUSTOMER DRAWING | SCALE — | SHEET 2 OF 2 | REV A

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331