

TWA-E Series



CECC Wet Electrolytic Tantalum Capacitor



The TWA-E series is an axial leaded wet electrolytic tantalum capacitor manufactured in EU in accordance with CECC 30 202-001. High capacitance cathode system allows high level of CV (Capacitance/Voltage) in DSCC compatible case sizes.

This design includes a welded tantalum can and header assembly that provides a hermetic seal to withstand harsh shock and vibration requirements of MIL-PRF-39006.

Customized capacitance and voltage packages are possible and welcomed. Contact the factory about design possibilities beyond those contained in this datasheet.

OUTLINE DIMENSIONS



CASE DIMENSIONS: millimeters (inches)

| DSCC Case Size | AVX Case Size | L +0.79 (0.031) -0.41 (0.016) | D | | E ±6.35 (0.250) |
|----------------|---------------|-------------------------------------|--|-------------------------------|--------------------|
| | | | Without Insulating Sleeve ±0.41 (0.016) | With Insulating Sleeve Max | |
| T1 | A | 11.51 (0.453) | 4.78 (0.188) | 5.56 (0.219) | 38.10 (1.500) |
| T2 | B | 16.28 (0.641) | 7.14 (0.281) | 7.92 (0.312) | 57.15 (2.250) |
| T3 | D | 19.46 (0.766) | 9.52 (0.375) | 10.31 (0.406) | 57.15 (2.250) |
| T4 | E | 26.97 (1.062) | 9.52 (0.375) | 10.31 (0.406) | 57.15 (2.250) |

VOLTAGE RATINGS (Operating Temperature -55°C to 125°C)

| Voltage (DC) | | | | | | | | |
|----------------------------|-------|------|------|------|----|------|-----|-----|
| Rated Voltage: (V_R) | 85°C | 25 | 30 | 50 | 60 | 75 | 100 | 125 |
| Derated Voltage: (V_C) | 125°C | 15 | 20 | 30 | 40 | 50 | 65 | 85 |
| Surge Voltage: (V_S) | 85°C | 28.8 | 34.5 | 57.5 | 69 | 86.3 | 115 | 144 |



TWA-E Series



CECC Wet Electrolytic Tantalum Capacitor

HOW TO ORDER

AVX PART NUMBER:

| | | | | | | | | | | | |
|------------|-----------|--|---|--------------|--|----------------------------|---|---------------------------|--------------------------------|--|--------------------------------------|
| TWA | D | 337 | * | 050 | □ | B | E | Z | 0 | ^ | 00 |
| Type | Case Size | Capacitance Code pF code: 1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow) | Capacitance Tolerance K = ±10% M = ±20% | Voltage Code | Insulation Sleeve C = Without Sleeve S = With Sleeve | Packaging B = Tray Pack | Inspection Level E = In accordance with CECC testing | Reliability Z = Non-ER | Qualification Level 0 = N/A | Termination Finish 0 = Sn/Pb 60/40 7 = Matte tin | Custom Test Options 00 = Standard |




LEAD-FREE
LEAD-FREE COMPATIBLE COMPONENT
For RoHS compliant products, please select correct termination style.

RIPPLE CURRENT MULTIPLIERS vs. Frequency, temperature and applied voltage^{1/2/}

| Frequency of Applied Ripple Current | | 120Hz | | | | 800Hz | | | | 1kHz | | | |
|-------------------------------------|---------|------------------------------------|------|------|------|-------|------|------|------|------|------|------|------|
| | | Ambient Still Air Temperature (°C) | | | | | | | | | | | |
| | | ≤55 | 85 | 105 | 125 | ≤55 | 85 | 105 | 125 | ≤55 | 85 | 105 | 125 |
| % of | 100% | 0.60 | 0.39 | – | – | 0.71 | 0.43 | – | – | 0.72 | 0.45 | – | – |
| 85°C | 90% | 0.60 | 0.46 | – | – | 0.71 | 0.55 | – | – | 0.72 | 0.55 | – | – |
| Rated Peak | 80% | 0.60 | 0.52 | 0.35 | – | 0.71 | 0.62 | 0.42 | – | 0.72 | 0.62 | 0.42 | – |
| | 70% | 0.60 | 0.58 | 0.44 | – | 0.71 | 0.69 | 0.52 | – | 0.72 | 0.70 | 0.52 | – |
| Voltage | 66-2/3% | 0.60 | 0.60 | 0.46 | 0.27 | 0.71 | 0.71 | 0.55 | 0.32 | 0.72 | 0.72 | 0.55 | 0.32 |

| Frequency of Applied Ripple Current | | 10kHz | | | | 40kHz | | | | 100kHz | | | |
|-------------------------------------|---------|------------------------------------|------|------|------|-------|------|------|------|--------|------|------|------|
| | | Ambient Still Air Temperature (°C) | | | | | | | | | | | |
| | | ≤55 | 85 | 105 | 125 | ≤55 | 85 | 105 | 125 | ≤55 | 85 | 105 | 125 |
| % of | 100% | 0.88 | 0.55 | – | – | 1.00 | 0.63 | – | – | 1.10 | 0.69 | – | – |
| 85°C | 90% | 0.88 | 0.67 | – | – | 1.00 | 0.77 | – | – | 1.10 | 0.85 | – | – |
| Rated Peak | 80% | 0.88 | 0.76 | 0.52 | – | 1.00 | 0.87 | 0.59 | – | 1.10 | 0.96 | 0.65 | – |
| | 70% | 0.88 | 0.85 | 0.64 | – | 1.00 | 0.97 | 0.73 | – | 1.10 | 1.07 | 0.80 | – |
| Voltage | 66-2/3% | 0.88 | 0.88 | 0.68 | 0.40 | 1.00 | 1.00 | 0.77 | 0.45 | 1.10 | 1.10 | 0.85 | 0.50 |

1/ At 125°C the rated voltage of the capacitors decreases to 66 2/3 of the 85°C rated voltage.

2/ The peak of the applied ac ripple voltage plus the applied dc voltage must not exceed the dc voltage rating of the capacitors.

CECC Wet Electrolytic Tantalum Capacitor

CAPACITANCE AND RATED VOLTAGE, V_R (VOLTAGE CODE) RANGE (LETTER DENOTES CASE SIZE)

| Capacitance | | Rated Voltage DC (V_R) to 85°C | | | | | | |
|---------------|------|------------------------------------|-----|------|-----|------|------|------|
| μF | Code | 25V | 30V | 50V | 60V | 75V | 100V | 125V |
| 15 | 156 | | | | | | | A* |
| 22 | 226 | | | | | | A* | |
| 33 | 336 | | | | | A* | | |
| 47 | 476 | | | A* | | | | B* |
| 68 | 686 | A | | | | | B | |
| 100 | 107 | | | | B | B | | D |
| 120 | 127 | | | B | | | | D* |
| 150 | 157 | | | B | | | D | E |
| 220 | 227 | | B | | | D*,E | E | E |
| 330 | 337 | B | | D*,E | | E | E | |
| 470 | 477 | | | D,E | | E | | |
| 560 | 567 | D* | | | E | | | |
| 680 | 687 | E | D,E | E | | E | | |
| 750 | 757 | D,E | D,E | | | E | E* | |
| 1000 | 108 | D,E | E | D*,E | | | | |
| 1500 | 158 | E | | | | | | |
| 2200 | 228 | | | | E | | | |
| 3000 | 308 | | | E | | | | |
| 4700 | 478 | E | | | | | | |

Released codes

Engineering samples - please contact manufacturer

*Codes under development

CECC Wet Electrolytic Tantalum Capacitor

RATINGS & PART NUMBER REFERENCE

| AVX Part Number | Cap (µF) 25°C at 120Hz | DC Rated Voltage (V) at 85°C | ESR Max (ohms) at 120Hz | DC Leakage max (µA) | | TANG δ Max +25°C (%) | Impedance max (Ohms) -55°C at 120Hz | Maximum Capacitance Change (%) | | | AC Ripple (mA rms) 85°C at 40kHz | Case Size | |
|---|------------------------------|------------------------------------|-------------------------------|---------------------|-----------------|-------------------------|---|-----------------------------------|-------|--------|--|-----------|------|
| | | | | +25°C | +85 & +125°C | | | -55°C | +85°C | +125°C | | AVX | DSCC |
| 25 VDC at 85°C 15 VDC at 125°C | | | | | | | | | | | | | |
| TWAA686*025□BEZO^00 | 68 | 25 | 2.5 | 0.6 | 3 | 12 | 45 | -40 | 12 | 15 | 850 | A | T1 |
| TWAB337*025□BEZO^00 | 330 | 25 | 1.3 | 2 | 20 | 30 | 25 | -60 | 10 | 15 | 1550 | B | T2 |
| TWAE687*025□BEZO^00 | 680 | 25 | 0.75 | 3 | 12 | 45 | 12 | -50 | 8 | 15 | 2100 | E | T4 |
| TWAD757*025□BEZO^00 | 750 | 25 | 1 | 3 | 25 | 45 | 15 | -50 | 8 | 15 | 2000 | D | T3 |
| TWAE757*025□BEZO^00 | 750 | 25 | 0.75 | 3.5 | 16 | 50 | 9 | -55 | 10 | 18 | 2200 | E | T4 |
| TWAD108*025□BEZO^00 | 1000 | 25 | 1 | 4 | 30 | 45 | 15 | -50 | 8 | 15 | 2300 | D | T3 |
| TWAE108*025□BEZO^00 | 1000 | 25 | 0.7 | 4 | 20 | 60 | 9 | -55 | 10 | 18 | 2400 | E | T4 |
| TWAE158*025□BEZO^00 | 1500 | 25 | 0.5 | 6 | 24 | 65 | 7 | -65 | 15 | 20 | 2850 | E | T4 |
| TWAE478*025□BEZO^00 | 4700 | 25 | 0.25 | 18 | 92 | 90 | 1.8 | -74 | 32 | 34 | 5700 | E | T4 |
| 30 VDC at 85°C 20 VDC at 125°C | | | | | | | | | | | | | |
| TWAB227*030□BEZO^00 | 220 | 30 | 2 | 1.9 | 10 | 15 | 30 | -40 | 8 | 15 | 1200 | B | T2 |
| TWAD687*030□BEZO^00 | 680 | 30 | 1 | 3.3 | 25 | 45 | 15 | -50 | 8 | 15 | 1900 | D | T3 |
| TWAE687*030□BEZO^00 | 680 | 30 | 0.8 | 4.5 | 18 | 45 | 10 | -60 | 8 | 15 | 2100 | E | T4 |
| TWAD757*030□BEZO^00 | 750 | 30 | 1 | 3.6 | 30 | 45 | 15 | -50 | 8 | 15 | 2000 | D | T3 |
| TWAE757*030□BEZO^00 | 750 | 30 | 0.8 | 5 | 20 | 45 | 10 | -65 | 10 | 18 | 2200 | E | T4 |
| TWAE108*030□BEZO^00 | 1000 | 30 | 0.7 | 5 | 20 | 55 | 7 | -70 | 10 | 18 | 2500 | E | T4 |
| 50 VDC at 85°C 30 VDC at 125°C | | | | | | | | | | | | | |
| TWAA476*050□BEZO^00 | 47 | 50 | 2 | 1 | 5 | 9 | 35 | -25 | 8 | 15 | 850 | A | T1 |
| TWAB127*050□BEZO^00 | 120 | 50 | 2 | 2 | 10 | 14 | 30 | -45 | 8 | 15 | 1200 | B | T2 |
| TWAB157*050□BEZO^00 | 150 | 50 | 2 | 2 | 10 | 16 | 25 | -50 | 8 | 15 | 1400 | B | T2 |
| TWAD337*050□BEZO^00 | 330 | 50 | 0.85 | 3 | 25 | 25 | 15 | -50 | 8 | 15 | 1650 | D | T3 |
| TWAE337*050□BEZO^00 | 330 | 50 | 0.8 | 2.5 | 25 | 24 | 15 | -50 | 8 | 15 | 1900 | E | T4 |
| TWAD477*050□BEZO^00 | 470 | 50 | 1 | 3 | 25 | 35 | 11 | -50 | 8 | 15 | 2100 | D | T3 |
| TWAE477*050□BEZO^00 | 470 | 50 | 0.75 | 3 | 30 | 32 | 10 | -50 | 8 | 15 | 2200 | E | T4 |
| TWAE687*050□BEZO^00 | 680 | 50 | 0.7 | 5 | 40 | 42 | 8 | -58 | 10 | 20 | 2750 | E | T4 |
| TWAD108*050□BEZO^00 | 1000 | 50 | 1.2 | 15 | 125 | 100 | 15 | -90 | 100 | 140 | 3800 | D | T3 |
| TWAE108*050□BEZO^00 | 1000 | 50 | 0.7 | 11 | 110 | 45 | 20 | -70 | 30 | 40 | 3200 | E | T4 |
| TWAE308*050□BEZO^00 | 3000 | 50 | 0.3 | 30 | 150 | 80 | 3.5 | -80 | 60 | 85 | 3100 | E | T4 |
| 60 VDC at 85°C 40 VDC at 125°C | | | | | | | | | | | | | |
| TWAB107*060□BEZO^00 | 100 | 60 | 2.5 | 1.7 | 10 | 12 | 30 | -40 | 8 | 15 | 1100 | B | T2 |
| TWAE567*060□BEZO^00 | 560 | 60 | 0.8 | 5 | 40 | 45 | 10 | -58 | 8 | 15 | 2750 | E | T4 |
| TWAE228*060□BEZO^00 | 2200 | 60 | 0.5 | 30 | 150 | 80 | 3.5 | -80 | 60 | 85 | 3000 | E | T4 |
| 75 VDC at 85°C 50 VDC at 125°C | | | | | | | | | | | | | |
| TWAA336*075□BEZO^00 | 33 | 75 | 2.5 | 1 | 5 | 8 | 66 | -25 | 5 | 9 | 1050 | A | T1 |
| TWAB107*075□BEZO^00 | 100 | 75 | 2.5 | 2 | 10 | 12 | 24 | -35 | 6 | 10 | 1400 | B | T2 |
| TWAD227*075□BEZO^00 | 220 | 75 | 1.2 | 3 | 30 | 24 | 20 | -45 | 6 | 10 | 1500 | D | T3 |
| TWAE227*075□BEZO^00 | 220 | 75 | 1.1 | 2.5 | 30 | 22 | 20 | -50 | 6 | 10 | 1800 | E | T4 |
| TWAE337*075□BEZO^00 | 330 | 75 | 1 | 3 | 40 | 30 | 12 | -50 | 6 | 10 | 2200 | E | T4 |
| TWAE477*075□BEZO^00 | 470 | 75 | 0.9 | 5 | 50 | 38 | 12 | -55 | 6 | 10 | 2750 | E | T4 |
| TWAE687*075□BEZO^00 | 680 | 75 | 0.9 | 11 | 110 | 45 | 10 | -70 | 30 | 40 | 2750 | E | T4 |
| TWAE757*075□BEZO^00 | 750 | 75 | 0.7 | 12 | 120 | 60 | 10 | -70 | 30 | 40 | 3800 | E | T4 |
| 100 VDC at 85°C 65 VDC at 125°C | | | | | | | | | | | | | |
| TWAA226*100□BEZO^00 | 22 | 100 | 3.5 | 1 | 5 | 7 | 125 | -18 | 3 | 10 | 1400 | A | T1 |
| TWAB686*100□BEZO^00 | 68 | 100 | 2.5 | 2 | 10 | 13 | 37 | -30 | 4 | 12 | 1650 | B | T2 |
| TWAD157*100□BEZO^00 | 150 | 100 | 1.6 | 3 | 25 | 22 | 22 | -35 | 6 | 12 | 2100 | D | T3 |
| TWAE227*100□BEZO^00 | 220 | 100 | 1.2 | 5 | 50 | 24 | 15 | -40 | 6 | 12 | 2750 | E | T4 |
| TWAE337*100□BEZO^00 | 330 | 100 | 0.8 | 6 | 60 | 30 | 10 | -45 | 7 | 20 | 3600 | E | T4 |
| TWAE757*100□BEZO^00 | 750 | 100 | 0.7 | 20 | 200 | 45 | 10 | -40 | 20 | 50 | 6700 | E | T4 |
| 125 VDC at 85°C 85 VDC at 125°C | | | | | | | | | | | | | |
| TWAD107*125□BEZO^00 | 100 | 125 | 1.8 | 3 | 25 | 18 | 35 | -35 | 5 | 12 | 2100 | D | T3 |
| TWAE157*125□BEZO^00 | 150 | 125 | 1.6 | 5 | 50 | 35 | 20 | -35 | 6 | 16 | 2750 | E | T4 |
| TWAE227*125□BEZO^00 | 220 | 125 | 1.4 | 10 | 50 | 25 | 12 | -40 | 8 | 15 | 3600 | E | T4 |

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5RMS with DC bias of 2.2V. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the rights to supply higher voltage rating in the same case size, to the same reliability standards.



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331