Inolux Surface Mount High Power Ultraviolet LED
IN-K2PUV

DISCLAIMER....3
LABEL SPECIFICATIONS....4
RADIOMETRIC POWER AND FORWARD VOLTAGE....5
PRODUCT CHARACTERISTICS....6
ABSOLUTE MAXIMUM RATINGS....6
ELECTRO-OPTICAL CHARACTERISTICS....6
PACKAGE OUTLINE DIMENSION....7
RECOMMENDED SOLDERING PATTERN FOR REFLOW SOLDERING....7
CHARACTERISTIC CURVES....8
THERMAL DESIGN....9
PACKING INFORMATION....11
REVISION HISTORY....12

DISCLAIMER

INOLUX reserves the right to make changes without further notice to any products herein to improve reliability, function or design. INOLUX does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

LIFE SUPPORT POLICY

INOLUX's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of INOLUX or INOLUX Technologies. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.

2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Label Specifications

INOLUX P/N:

I N - K 2 P U V -X X X X

Series Name	Substrate / Emitting Color	Customer Code
IN-K2 **Inolux K2 package**	**K2** **UV@390-420nm**	**XXXX** **Customer Product Code**

Lot No.:

1	2	3	4	5	6	7	8	9	10
E	1	A	1	A	2	2	L	1	2
Code 1 2		Code 3	Code 4	Code 5	Code 6	Code 7	Code 8	Code 9	Code 10
		Mfg. Year	Mfg. Month	Mfg. Date	Consecutive number		Special code		
Internal Tracing Code		2010-A 2011-B 2012-C 2013-D . .	1:Jan. 2:Feb. .... A:Oct. B:Nov. C:Dec.	1:A 2:B 3:C ... 26:Z 27:7 28:8 29:9 30:3 31:4	01~ZZ		000~ZZZ		

Radiometric Power and Forward Voltage

(Tj =25 °C)

Part Number	Color	Performance at Test Current 700mA			
		Min. Radiometric Power (mW)		V_f	
		Min	Max	Min	Max
IN-K2PUV	UV	340	440	3.0	4.3

Part Number	Color	Performance at Test Current 350mA			
		Min. Radiometric Power (mW)		V_f	
		Min	Max	Min	Max
IN-K2PUV	UV	200	260	2.8	4.0

Note:

1. Radiometric Power is measured with an accuracy of ±10%
2. The forward voltage is measured with an accuracy of ±0.1V

Product Characteristics

Absolute Maximum Ratings

(Tj =25 °C)

Parameter	Rating
DC Forward Current (mA)	350~700mA
LED Junction Temperature	150°C
LED Operating Temperature	-40°C ~ 110°C
Storage Temperature	-40°C ~ 110°C
Soldering Temperature	Max. 260°C / Max. 10 sec. (JEDEC 020c)
ESD Sensitivity	2,000V HBM (JESD-22A-114-B)
Preconditioning	Acc. to JEDEC Level 2

Notes:

1. Never operate the LEDs in reverse bias.
2. Do not drive at rated current for more than 5 seconds without proper thermal management.
3. When the LEDs are illuminating, operating current should be decided after considering the packages maximum temperature.
4. Caution: These devices emit high intensity UV/NUV light. Necessary precautions must be taken during operation. Do not look directly into the light or look through the optical system when in operation. Protective eyewear should be worn at all times during operation.
5. Lens discoloration may occur with prolonged exposure to UV/NUV light. Lens material will need to be tested for UV/NUV light compatibility and durability.

Electro-Optical Characteristics

(T_j 25 °C)

Part Number	Color	Peak Wavelength (λp)		2Θ1/2	Temperature Coefficient of Vf (mV/°C)	Thermal Resistance Junction to Pad
		Min	Max		ΔVF /ΔTJ	(°C/W) $RΘ_{J-L}$
IN-K2PUV	UV	390	420	120	-3	10

Notes:

1. The peak/dominant wavelength is measured with an accuracy of ±1nm.

Package Outline Dimension
Recommended Soldering Pattern for Reflow Soldering

Unit: mm Tolerance: +/-0.13

Outline Dimension	Solder Pattern
	
Soldering terminals may shift in the x, y direction.	Unit: mm

Characteristic Curves

Relative Spectral Power Distribution, Ta=25 °C

UV



Typical Forward L-I Characteristics

UV



Typical Forward I-V Characteristics

UV



Thermal Design

Thermal design of the end product is important. The thermal resistance between the junction and the solder point (RΘJ-S) and the end product should be designed to minimize the thermal resistance from the solder point to ambient in order to optimize the emitter life and optical characteristics. The maximum operation current is determined by the plot of Allowable Forward Current vs. Ambient Temperature.



The junction temperature can be correlated to the thermal resistance between the junction and ambient (Rja) by the following equation.

Tj=Ta + Rja*W

Tj: LED junction temperature

Ta: Ambient temperature

Rja: Thermal resistance between the junction and ambient

W: Input power (I_F*V_F)

Reflow Soldering

The LEDs can be soldered using the parameter listed below. As a general guideline, the users are suggested to follow the recommended soldering profile provided by the manufacturer of the solder paste. Although the recommended soldering conditions are specified in the list, reflow soldering at the lowest possible temperature is preferred for the LEDs.



Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Average Ramp-up Rate (Ts_{max} to Tp)	3℃/second max.	3℃/second max.
Preheat - Temperature Min(Ts_{min}) - Temperature Max(Ts_{max}) - Time(ts_{min} to ts_{max})	 100℃ 150℃ 60-120 seconds	 150℃ 200℃ 60-180 seconds
Time maintained above: - Temperature(T_L) - Time(t_L)	 183℃ 60-150 seconds	 217℃ 60-150 seconds
Peak/classification Temperature(Tp)	215℃	240℃
Time within 5℃ of actual Peak Temperature(tp)	10-30 seconds	20-40 seconds
Ramp-Down Rate	6℃/second max.	6℃/second max.
Time 25℃ to Peak Temperature	6 minutes max.	8 minutes max.

Packing Information

The carrier tape is conformal to EIA-481D





	Dimensions (L*W*H)	Emitter Quantity
Tube	424*16.7*10.0 mm	50 EA

Note : All Dimensions are in millimeter

Revision History

Changes since last revision	Page	Version No.	Revision Date
Initial release		1.0	04-19-2014

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331