



Standard RF Shields

PROTOTYPE KIT



Now we offer two kits to choose from! Kits are in stock and are ready-to-ship!

PRODUCT FEATURES

- Variable shield heights of 0.25" (6.35mm), 0.50" (12.7mm) or 0.75" (19.05mm)
- Quick & easy shielding solution; Shields are ready to order; no tooling needed
- Brass material with tin plating offer excellent shielding and solderability characteristics
- No pre-set through-pins to interfere with custom boards
- Easy form-by-hand bend lines assist creating formed shield --No tooling required!

MATERIAL SPECS

- 0.015" (0.381mm) brass CDA 26000 ½ hard
- Finish: Bright tin plate (per Mil-T-10727, Type I Bright)
- Dimensions are outside (formed) dimensions
- Fotofab standard shields are RoHS compliant
- Made in the USA with materials produced in the USA

PRODUCT NOTES

- Parts are designed to be formed by hand without the use of tools.
- To create a wall height of 0.50" or 0.25" simply break away each 0.25" section by bending wall back and forth at the bend line
- Create 90° bend by forming shield wall into the lid so that bend line remains on the inside of shield



For current pricing, or to order by credit card, please visit www.fotofab.com/standard-order.php
To order by fax or email, please send PO to (773) 463-3387 or orders@fotofab.com
Contact sales@fotofab.com with any additional questions

Information furnished by Fotofab is believed to be accurate and reliable. However, no responsibility is assumed by Fotofab for its use, nor any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice.

Fotofab
3758 Belmont Ave
Chicago, IL 60618

p. 773-463-6211
f. 773-463-33787
www.fotofab.com





Standard RF Shields

PROTOTYPE KIT


Prototype Kit: Standard Size Shields

P/N: Prototype Kit, Standard

Prototype Kit, Standard				
Dimensions: in (mm)				
Quantity per kit	A	B	C	
2	0.500 (12.70)	0.500 (12.70)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
2	0.500 (12.70)	0.750 (19.05)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
2	0.500 (12.70)	1.000 (25.40)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
2	0.750 (19.05)	0.750 (19.05)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
2	0.750 (19.05)	1.125 (28.58)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
4	0.750 (19.05)	1.500 (38.10)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
2	1.000 (25.40)	1.000 (25.40)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
2	1.000 (25.40)	1.500 (38.10)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
2	1.000 (25.40)	2.000 (50.80)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
1	1.500 (38.10)	1.500 (38.10)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
1	1.500 (38.10)	2.250 (57.15)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
1	1.500 (38.10)	3.000 (76.20)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
1	2.000 (50.80)	2.000 (50.80)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
1	2.000 (50.80)	3.000 (76.20)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
1	2.000 (50.80)	4.000 (101.60)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
1	2.500 (63.50)	2.500 (63.50)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
1	2.500 (63.50)	3.750 (95.25)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	
1	2.500 (63.50)	5.000 (127.00)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)	

Kit includes 29 shields total

For more information, visit www.fotofab.com



Each 0.025" section can be easily broken away to create shield heights of 0.25", 0.50" or 0.75"

Information furnished by Fotofab is believed to be accurate and reliable. However, no responsibility is assumed by Fotofab for its use, nor any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice.

Fotofab
3758 Belmont Ave
Chicago, IL 60618

p. 773-463-6211
f. 773-463-33787
www.fotofab.com

© 2006 Fotofab / All rights reserved.





Standard RF Shields

PROTOTYPE KIT


Prototype Kit: Small Size Shields

P/N: Prototype Kit, Small

Prototype Kit, Small			
Dimensions: in (mm)			
Quantity per kit	A	B	C
3	0.500 (12.70)	0.500 (12.70)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
3	0.500 (12.70)	0.750 (19.05)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
3	0.500 (12.70)	1.000 (25.40)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
2	0.750 (19.05)	0.750 (19.05)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
3	0.750 (19.05)	1.125 (28.58)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
2	0.750 (19.05)	1.500 (38.10)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
2	1.000 (25.40)	1.000 (25.40)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
2	1.000 (25.40)	1.500 (38.10)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
2	1.500 (38.10)	3.000 (76.20)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
4	1.000 (25.40)	1.333 (33.86)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
4	0.600 (15.24)	0.900 (22.86)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
4	0.400 (10.16)	0.400 (10.16)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
4	0.600 (15.24)	0.600 (15.24)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
4	0.500 (12.70)	1.333 (33.86)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)
4	0.750 (19.05)	1.333 (33.86)	Select from: 0.25 (6.35), 0.50 (12.70) or 0.75 (19.05)

Kit includes 46 shields total

For more information, visit www.fotofab.com



Each 0.025" section can be easily broken away to create shield heights of 0.25", 0.50" or 0.75"

Information furnished by Fotofab is believed to be accurate and reliable. However, no responsibility is assumed by Fotofab for its use, nor any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice.

Fotofab
3758 Belmont Ave
Chicago, IL 60618

p. 773-463-6211
f. 773-463-33787
www.fotofab.com

© 2006 Fotofab / All rights reserved.





**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331