



Is Now Part of



**ON Semiconductor®**

To learn more about ON Semiconductor, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at [www.onsemi.com](http://www.onsemi.com). Please email any questions regarding the system integration to [Fairchild\\_questions@onsemi.com](mailto:Fairchild_questions@onsemi.com).

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

**FDFM2N111****Integrated N-Channel PowerTrench® MOSFET and Schottky Diode****General Description**

FDFM2N111 combines the exceptional performance of Fairchild's PowerTrench MOSFET technology with a very low forward voltage drop Schottky barrier rectifier in a MicroFET package.


This device is designed specifically as a single package solution for Standard Buck Converter. It features a fast switching, low gate charge MOSFET with very low on-state resistance.

**Applications**

- Standard Buck Converter

**Features**

- 4 A, 20 V     $R_{DS(ON)} = 100\text{m}\Omega$  @  $V_{GS} = 4.5\text{ V}$   
 $R_{DS(ON)} = 150\text{m}\Omega$  @  $V_{GS} = 2.5\text{ V}$
- Low Profile - 0.8 mm maximum - in the new package  
 MicroFET 3x3 mm

**Absolute Maximum Ratings**  $T_A = 25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Ratings	Units
$V_{DSS}$	Drain-Source Voltage	20	V
$V_{GSS}$	Gate-Source Voltage	$\pm 12$	V
$I_D$	Drain Current -Continuous	(Note 1a)	A
	-Pulsed	10	
$V_{RRM}$	Schottky Repetitive Peak Reverse voltage	20	V
$I_O$	Schottky Average Forward Current	(Note 1a)	A
$P_D$	Power dissipation (Steady State)	(Note 1a)	W
	Power dissipation (Steady State)	(Note 1b)	
$T_J, T_{STG}$	Operating and Storage Junction Temperature Range	-55 to +150	$^\circ\text{C}$

**Thermal Characteristics**

$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	(Note 1a)	70	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	(Note 1b)	150	$^\circ\text{C/W}$

**Package Marking and Ordering Information**

Device Marking	Device	Reel Size	Tape Width	Quantity
2N111	FDFM2N111	7inch	12mm	3000 units

### Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
<b>Off Characteristics</b>						
$B_{VDSS}$	Drain-Source Breakdown Voltage	$I_D = 250\mu\text{A}, V_{GS} = 0\text{V}$	20	-	-	V
$\Delta B_{VDSS}$ $\Delta T_J$	Breakdown Voltage Temperature Coefficient	$I_D = 250\mu\text{A},$ Referenced to $25^\circ\text{C}$	-	12	-	$\text{mV}/^\circ\text{C}$
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{GS} = 0\text{V}, V_{DS} = 16\text{V}$	-	-	1	$\mu\text{A}$
$I_{GSS}$	Gate-Body Leakage,	$V_{GS} = \pm 12\text{V}, V_{DS} = 0\text{V}$	-	-	$\pm 100$	nA

### On Characteristics (Note 2)

$V_{GS(\text{TH})}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	0.6	1.0	1.5	V
$\Delta V_{GS(\text{TH})}$ $\Delta T_J$	Gate Threshold Voltage Temperature Coefficient	$I_D = 250\mu\text{A},$ Referenced to $25^\circ\text{C}$	-	-3	-	$\text{mV}/^\circ\text{C}$
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$I_D = 4.0\text{A}, V_{GS} = 4.5\text{V}$	-	54	100	$\text{m}\Omega$
		$I_D = 3.3\text{A}, V_{GS} = 2.5\text{V}$	-	83	150	
		$I_D = 4.0\text{A}, V_{GS} = 4.5\text{V},$ $T_J = 125^\circ\text{C}$	-	74	147	
$I_{D(\text{ON})}$	On-State Drain Current	$V_{GS} = 2.5\text{V}, V_{DS} = 5\text{V}$	10	-	-	A
$g_{FS}$	Forward Transconductance	$I_D = 4\text{A}, V_{DS} = 5\text{V}$	-	9.7	-	S

### Dynamic Characteristics

$C_{ISS}$	Input Capacitance	$V_{DS} = 10\text{V}, V_{GS} = 0\text{V},$ $f = 1\text{MHz}$	-	273	-	pF
$C_{OSS}$	Output Capacitance		-	63	-	pF
$C_{RSS}$	Reverse Transfer Capacitance		-	37	-	pF
$R_G$	Gate Resistance	$V_{GS} = 0\text{V}, f = 1\text{MHz},$	-	1.6	-	$\Omega$

### Switching Characteristics (Note 2)

$t_{d(\text{ON})}$	Turn-On Delay Time	$V_{DD} = 10\text{V}, I_D = 1\text{A}$ $V_{GS} = 4.5\text{V}, R_{\text{GEN}} = 6\Omega$	-	6	12	ns
$t_r$	Turn-On Rise Time		-	7	14	ns
$t_{d(\text{OFF})}$	Turn-Off Delay Time		-	11	20	ns
$t_f$	Turn-Off Fall Time		-	1.7	3.4	ns
$Q_g$	Total Gate Charge	$V_{DS} = 10\text{V}, I_D = 4.0\text{A},$ $V_{GS} = 4.5\text{V}$	-	2.7	3.8	nC
$Q_{gs}$	Gate-Source Charge		-	0.6	-	nC
$Q_{gd}$	Gate-Drain Charge		-	0.9	-	nC

### Drain-Source Diode Characteristics and Maximum Ratings

$I_S$	Maximum Continuous Drain-Source Diode Forward Current	-	-	1.4	A	
$V_{SD}$	Drain-Source Diode Forward Voltage	$V_{GS} = 0\text{V}, I_S = 1.4\text{ A}$ (Note 2)	-	0.8	-1.2	V
$t_{rr}$	Diode Reverse Recovery Time	$I_F = 4.0\text{A}, dI_F/dt = 100\text{A}/\mu\text{s}$	-	11	-	ns
$Q_{rr}$	Diode Reverse Recovery Charge		-	3	-	nC


### Schottky Diode Characteristic

$V_R$	Reverse Voltage	$I_R = 1\text{mA}$	20	-	-	V
$I_R$	Reverse Leakage	$V_R = 5\text{V}$	$T_J = 25^\circ\text{C}$	-	-	100
			$T_J = 100^\circ\text{C}$			10
$V_F$	Forward Voltage	$I_F = 1\text{A}$	$T_J = 25^\circ\text{C}$	-	0.32	0.39


**Electrical Characteristics**  $T_A = 25^\circ\text{C}$  unless otherwise noted

**Notes:**

1.  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta CA}$  is guaranteed by design while  $R_{\theta CA}$  is determined by the user's board design.



a)  $70^\circ\text{C/W}$  when mounted on  
a  $1\text{in}^2$  pad of 2 oz copper




b)  $150^\circ\text{C/W}$  when mounted on  
a minimum pad of 2 oz  
copper


Scale 1: 1 on letter size paper

2. Pulse Test: Pulse Width < 300  $\mu\text{s}$ , Duty Cycle < 2.0%


## Typical Characteristics




**Figure 1. On-Region Characteristics**




**Figure 2. On-Resistance Variation with Drain Current and Gate Voltage**




**Figure 3. On-Resistance Variation with Temperature**



**Figure 4. On-Resistance Variation with Gate-to-Source Voltage**




**Figure 5. Transfer Characteristics**




**Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature**


### Typical Characteristics




**Figure 7. Gate Charge Characteristics**




**Figure 8. Capacitance Characteristics**



**Figure 9. Schottky Diode Forward Voltage**




**Figure 10. Schottky Diode Reverse Current**



**Figure 11. Transient Thermal Response Curve**

Thermal characterization performed using the conditions described in Note 1b.  
Transient thermal response will change depending on the circuit board design.



NOTES: UNLESS OTHERWISE SPECIFIED

- A) CONFORMS TO JEDEC REGISTRATION, MO-229, VARIATION WEEA
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.
- D) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009.
- E) DRAWING FILE NAME: MKT-MLP06HREV2

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor](#):

[FDFM2N111](#)



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литер Н,  
помещение 100-Н Офис 331