

# 74VHCT138A

## 3-to-8 Decoder/Demultiplexer

### Features

- High Speed:  $t_{PD} = 7.6ns$  (Typ.) at  $V_{CC} = 5V$
- Low power dissipation:  $I_{CC} = 4\mu A$  (Max.) at  $T_A = 25^\circ C$
- Power down protection is provided on all inputs and outputs
- Pin and function compatible with 74HCT138

### General Description

The VHCT138A is an advanced high speed CMOS 3-to-8 DECODER fabricated with silicon gate CMOS technology. It achieves the high speed operation similar to equivalent Bipolar Schottky TTL while maintaining the CMOS low power dissipation.


When the device is enabled, 3 Binary Select inputs ( $A_0$ ,  $A_1$  and  $A_2$ ) determine which one of the outputs ( $\overline{O_0}$ – $\overline{O_7}$ ) will go LOW. When enable input  $E_3$  is held LOW or either  $\overline{E_1}$  or  $\overline{E_2}$  is held HIGH, decoding function is inhibited and all outputs go HIGH.  $E_3$ ,  $\overline{E_1}$  and  $\overline{E_2}$  inputs are provided to ease cascade connection and for use as an address decoder for memory systems. Protection circuits ensure that 0V to 7V can be applied to the input pins without regard to the supply voltage and to the output pins with  $V_{CC} = 0V$ . These circuits prevent device destruction due to mismatched supply and input/output voltages. This device can be used to interface 3V to 5V systems and two supply systems such as battery backup.

### Ordering Information

| Order Number  | Package Number | Package Description                                                          |
|---------------|----------------|------------------------------------------------------------------------------|
| 74VHCT138AM   | M16A           | 16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow |
| 74VHCT138ASJ  | M16D           | 16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide                |
| 74VHCT138AMTC | MTC16          | 16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide  |

Surface mount packages are also available on Tape and Reel. Specify by appending the suffix letter "X" to the ordering number.



## Connection Diagram



## Pin Description

| Pin Names                 | Description    |
|---------------------------|----------------|
| $A_0$ – $A_2$             | Address Inputs |
| $\bar{E}_1$ – $\bar{E}_2$ | Enable Inputs  |
| $E_3$                     | Enable Input   |
| $\bar{O}_0$ – $\bar{O}_7$ | Outputs        |

## Logic Symbols



## Truth Table


| Inputs      |             |       |       |       |       | Outputs     |             |             |             |             |             |             |             |
|-------------|-------------|-------|-------|-------|-------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| $\bar{E}_1$ | $\bar{E}_2$ | $E_3$ | $A_0$ | $A_1$ | $A_2$ | $\bar{O}_0$ | $\bar{O}_1$ | $\bar{O}_2$ | $\bar{O}_3$ | $\bar{O}_4$ | $\bar{O}_5$ | $\bar{O}_6$ | $\bar{O}_7$ |
| H           | X           | X     | X     | X     | X     | H           | H           | H           | H           | H           | H           | H           | H           |
| X           | H           | X     | X     | X     | X     | H           | H           | H           | H           | H           | H           | H           | H           |
| X           | X           | L     | X     | X     | X     | H           | H           | H           | H           | H           | H           | H           | H           |
| L           | L           | H     | L     | L     | L     | L           | H           | H           | H           | H           | H           | H           | H           |
| L           | L           | H     | H     | L     | L     | H           | L           | H           | H           | H           | H           | H           | H           |
| L           | L           | H     | L     | H     | L     | H           | H           | L           | H           | H           | H           | H           | H           |
| L           | L           | H     | H     | H     | L     | H           | H           | H           | L           | H           | H           | H           | H           |
| L           | L           | H     | L     | L     | H     | H           | H           | H           | H           | L           | H           | H           | H           |
| L           | L           | H     | H     | L     | H     | H           | H           | H           | H           | H           | L           | H           | H           |
| L           | L           | H     | L     | H     | H     | H           | H           | H           | H           | H           | H           | L           | H           |
| L           | L           | H     | H     | H     | H     | H           | H           | H           | H           | H           | H           | H           | L           |

H = HIGH Voltage Level

L = LOW Voltage Level

X = Immaterial

## Logic Diagram



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol    | Parameter                                | Rating                                    |
|-----------|------------------------------------------|-------------------------------------------|
| $V_{CC}$  | Supply Voltage                           | –0.5V to +7.0V                            |
| $V_{IN}$  | DC Input Voltage                         | –0.5V to +7.0V                            |
| $V_{OUT}$ | DC Output Voltage<br>Note 1<br>Note 2    | –0.5V to 7.0V<br>–0.5V to $V_{CC} + 0.5V$ |
| $I_{IK}$  | Input Diode Current                      | –20mA                                     |
| $I_{OK}$  | Output Diode Current <sup>(3)</sup>      | ±20mA                                     |
| $I_{OUT}$ | DC Output Current                        | ±25mA                                     |
| $I_{CC}$  | DC $V_{CC}$ /GND Current                 | ±75mA                                     |
| $T_{STG}$ | Storage Temperature                      | –65°C to +150°C                           |
| $T_L$     | Lead Temperature (Soldering, 10 seconds) | 260°C                                     |

## Recommended Operating Conditions<sup>(4)</sup>

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to absolute maximum ratings.

| Symbol     | Parameter                                          | Rating                       |
|------------|----------------------------------------------------|------------------------------|
| $V_{CC}$   | Supply Voltage                                     | 4.5V to +5.5V                |
| $V_{IN}$   | Input Voltage                                      | 0V to +5.5V                  |
| $V_{OUT}$  | Output Voltage<br>Note 1<br>Note 2                 | 0V to 5.5V<br>0V to $V_{CC}$ |
| $T_{OPR}$  | Operating Temperature                              | –40°C to +85°C               |
| $t_r, t_f$ | Input Rise and Fall Time, $V_{CC} = 5.0V \pm 0.5V$ | 0 ~ 20ns/V                   |

### Notes:

1.  $V_{CC} = 0V$ .
2. HIGH or LOW state.  $I_{OUT}$  absolute maximum rating must be observed.
3.  $V_{OUT} < GND$ ,  $V_{OUT} > V_{CC}$  (Outputs Active).
4. Unused inputs must be held HIGH or LOW. They may not float.

## DC Electrical Characteristics

| Symbol           | Parameter                      | V <sub>CC</sub> (V) | Conditions                                                                      | T <sub>A</sub> = 25°C |      |      | T <sub>A</sub> = -40°C to +85°C |      | Units |
|------------------|--------------------------------|---------------------|---------------------------------------------------------------------------------|-----------------------|------|------|---------------------------------|------|-------|
|                  |                                |                     |                                                                                 | Min.                  | Typ. | Max. | Min.                            | Max. |       |
| V <sub>IH</sub>  | HIGH Level Input Voltage       | 4.5 – 5.5           |                                                                                 | 2.0                   |      |      | 2.0                             |      | V     |
| V <sub>IL</sub>  | LOW Level Input Voltage        | 4.5 – 5.5           |                                                                                 |                       |      | 0.8  |                                 | 0.8  | V     |
| V <sub>OH</sub>  | HIGH Level Output Voltage      | 4.5                 | V <sub>IN</sub> = V <sub>IH</sub><br>or V <sub>IL</sub> I <sub>OH</sub> = -50μA | 4.4                   | 4.5  |      | 4.4                             |      | V     |
|                  |                                |                     | I <sub>OH</sub> = -8mA                                                          | 3.94                  |      |      | 3.80                            |      |       |
| V <sub>OL</sub>  | LOW Level Output Voltage       | 4.5                 | V <sub>IN</sub> = V <sub>IH</sub><br>or V <sub>IL</sub> I <sub>OL</sub> = 50μA  |                       | 0.0  | 0.1  |                                 | 0.1  | V     |
|                  |                                |                     | I <sub>OL</sub> = 8mA                                                           |                       |      | 0.36 |                                 | 0.44 |       |
| I <sub>IN</sub>  | Input Leakage Current          | 0 – 5.5             | V <sub>IN</sub> = 5.5V or GND                                                   |                       |      | ±0.1 |                                 | ±1.0 | μA    |
| I <sub>CC</sub>  | Quiescent Supply Current       | 5.5                 | V <sub>IN</sub> = V <sub>CC</sub> or GND                                        |                       |      | 4.0  |                                 | 20.0 | μA    |
| I <sub>CCT</sub> | Maximum I <sub>CC</sub> /Input | 5.5                 | V <sub>IN</sub> = 3.4V, All other inputs = V <sub>CC</sub> or GND               |                       |      | 1.35 |                                 | 1.50 | mA    |
| I <sub>OFF</sub> | Output Leakage Current         | 0                   | V <sub>OUT</sub> = 5.5V                                                         |                       |      | 0.5  |                                 | 5.0  | μA    |

## AC Electrical Characteristics

| Symbol                              | Parameter                                                             | V <sub>CC</sub> (V) | Conditions             | T <sub>A</sub> = 25°C |      |      | T <sub>A</sub> = -40°C to +85°C |      | Units |
|-------------------------------------|-----------------------------------------------------------------------|---------------------|------------------------|-----------------------|------|------|---------------------------------|------|-------|
|                                     |                                                                       |                     |                        | Min.                  | Typ. | Max. | Min.                            | Max. |       |
| t <sub>PLH</sub> , t <sub>PHL</sub> | Propagation Delay, A <sub>n</sub> to O <sub>n</sub>                   | 5.0 ± 0.5           | C <sub>L</sub> = 15pF  |                       | 7.6  | 10.4 | 1.0                             | 12.0 | ns    |
|                                     |                                                                       |                     | C <sub>L</sub> = 50pF  |                       | 8.1  | 11.4 | 1.0                             | 13.0 |       |
| t <sub>PLH</sub> , t <sub>PHL</sub> | Propagation Delay, E <sub>3</sub> to O <sub>n</sub>                   | 5.0 ± 0.5           | C <sub>L</sub> = 15pF  |                       | 6.6  | 9.1  | 1.0                             | 10.5 | ns    |
|                                     |                                                                       |                     | C <sub>L</sub> = 50pF  |                       | 7.1  | 10.1 | 1.0                             | 11.5 |       |
| t <sub>PLH</sub> , t <sub>PHL</sub> | Propagation Delay, E <sub>1</sub> or E <sub>2</sub> to O <sub>n</sub> | 5.0 ± 0.5           | C <sub>L</sub> = 15pF  |                       | 7.0  | 9.6  | 1.0                             | 11.0 | ns    |
|                                     |                                                                       |                     | C <sub>L</sub> = 50pF  |                       | 7.5  | 10.6 | 1.0                             | 12.0 |       |
| C <sub>IN</sub>                     | Input Capacitance                                                     |                     | V <sub>CC</sub> = Open |                       | 4    | 10   |                                 | 10   | pF    |
| C <sub>PD</sub>                     | Power Dissipation Capacitance                                         |                     | <sup>(5)</sup>         |                       | 49   |      |                                 |      | pF    |




**Note:**

5. C<sub>PD</sub> is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation:

$$I_{CC} (\text{Opr.}) = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}$$

## Physical Dimensions

Dimensions are in millimeters unless otherwise noted.



DETAIL A  
SCALE: 2:1

NOTES: UNLESS OTHERWISE SPECIFIED



- A) THIS PACKAGE CONFORMS TO JEDEC MS-012, VARIATION AC, ISSUE C, DATED MAY 1990.
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS DO NOT INCLUDE MOLD FLASH OR BURRS.
- D) STANDARD LEAD FINISH:  
200 MICROINCHES / 5.08 MICRONS MIN.  
LEAD/TIN (SOLDER) ON COPPER.

M16AREVK

**Figure 1. 16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow Package Number M16A**

### Physical Dimensions (Continued)


Dimensions are in millimeters unless otherwise noted.



DIMENSIONS ARE IN MILLIMETERS

NOTES:

- A. CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.




M16DREVC

**Figure 2. 16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M16D**

**Physical Dimensions** (Continued)

Dimensions are in millimeters unless otherwise noted.



MTC16rev4

**Figure 3. 16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide Package Number MTC16**



## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                      |                         |                                                                                     |                        |
|--------------------------------------|-------------------------|-------------------------------------------------------------------------------------|------------------------|
| ACE <sup>®</sup>                     | HiSeC <sup>™</sup>      | Power-SPM <sup>™</sup>                                                              | TinyBuck <sup>™</sup>  |
| Across the board. Around the world.™ | <i>i-Lo</i> ™           | PowerTrench <sup>®</sup>                                                            | TinyLogic <sup>®</sup> |
| ActiveArray™                         | ImpliedDisconnect™      | Programmable Active Droop™                                                          | TINYOPTO™              |
| Bottomless™                          | IntelliMAX™             | QFET <sup>®</sup>                                                                   | TinyPower™             |
| Build it Now™                        | ISOPLANAR™              | QS™                                                                                 | TinyWire™              |
| CoolFET™                             | MICROCOUPLER™           | QT Optoelectronics™                                                                 | TruTranslation™        |
| CorePLUS™                            | MicroPak™               | Quiet Series™                                                                       | µSerDes™               |
| CROSSVOLT™                           | MICROWIRE™              | RapidConfigure™                                                                     | UHC <sup>®</sup>       |
| CTL™                                 | Motion-SPM™             | RapidConnect™                                                                       | UniFET™                |
| Current Transfer Logic™              | MSX™                    | ScalarPump™                                                                         | VCX™                   |
| DOMETM                               | MSXPro™                 | SMART START™                                                                        | Wire™                  |
| E <sup>2</sup> CMOS™                 | OCX™                    | SPM <sup>®</sup>                                                                    |                        |
| EcoSPARK <sup>®</sup>                | OCXPro™                 | STEALTH™                                                                            |                        |
| EnSigna™                             | OPTOLOGIC <sup>®</sup>  | SuperFET™                                                                           |                        |
| FACT Quiet Series™                   | OPTOPLANAR <sup>®</sup> | SuperSOT™-3                                                                         |                        |
| FACT <sup>®</sup>                    | PACMAN™                 | SuperSOT™-6                                                                         |                        |
| FAST <sup>®</sup>                    | PDP-SPM™                | SuperSOT™-8                                                                         |                        |
| FASTr™                               | POP™                    | SyncFET™                                                                            |                        |
| FPS™                                 | Power220 <sup>®</sup>   | TCM™                                                                                |                        |
| FRFET <sup>®</sup>                   | Power247 <sup>®</sup>   | The Power Franchise <sup>®</sup>                                                    |                        |
| GlobalOptoisolator™                  | PowerEdge™              |  ™ |                        |
| GTO™                                 | PowerSaver™             | TinyBoost™                                                                          |                        |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                               |
|--------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                       |
| Preliminary              | First Production       | This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.                                                   |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild Semiconductor. The datasheet is printed for reference information only.                                      |

Rev. I27



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331