

Part Number: APBA3010YSGC-GX

Yellow  
Super Bright Green

### Features




- 3.0mmx1.0mm right angle SMT LED, 2.0mm thickness.
- Low power consumption.
- Wide viewing angle.
- Ideal for backlight and indicator.
- Various colors and lens types available.
- Package : 2000pcs / reel.
- Moisture sensitivity level : level 3.
- Tinned pads for improved solderability.
- RoHS compliant.

### Description

The Yellow source color devices are made with Gallium Arsenide Phosphide on Gallium Phosphide Yellow Light Emitting Diode.

The Super Bright Green source color devices are made with Gallium Phosphide Green Light Emitting Diode.

### Package Dimensions



#### Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.15(0.006)$  unless otherwise noted.
3. The specifications, characteristics and technical data described in the datasheet are subject to change without prior notice.
4. The device has a single mounting surface. The device must be mounted according to the specifications.



## Selection Guide

| Part No.        | Dice                     | Lens Type   | Iv (mcd) [2]<br>@ 20mA |      | Viewing<br>Angle [1] |
|-----------------|--------------------------|-------------|------------------------|------|----------------------|
|                 |                          |             | Min.                   | Typ. |                      |
| APBA3010YSGC-GX | Yellow (GaAsP/GaP)       | Water Clear | 5                      | 8    | 140°                 |
|                 | Super Bright Green (GaP) |             | 5                      | 15   |                      |

### Notes:

1.  $\theta_{1/2}$  is the angle from optical centerline where the luminous intensity is 1/2 of the optical peak value.
2. Luminous intensity/ luminous Flux: +/-15%.
3. Luminous intensity value is traceable to the CIE127-2007 compliant national standards.

## Electrical / Optical Characteristics at TA=25°C

| Symbol                | Parameter                | Device                       | Typ.       | Max.       | Units | Test Conditions            |
|-----------------------|--------------------------|------------------------------|------------|------------|-------|----------------------------|
| $\lambda_{peak}$      | Peak Wavelength          | Yellow<br>Super Bright Green | 590<br>565 |            | nm    | I <sub>F</sub> =20mA       |
| $\lambda_D$ [1]       | Dominant Wavelength      | Yellow<br>Super Bright Green | 588<br>568 |            | nm    | I <sub>F</sub> =20mA       |
| $\Delta\lambda_{1/2}$ | Spectral Line Half-width | Yellow<br>Super Bright Green | 35<br>30   |            | nm    | I <sub>F</sub> =20mA       |
| C                     | Capacitance              | Yellow<br>Super Bright Green | 20<br>15   |            | pF    | V <sub>F</sub> =0V; f=1MHz |
| V <sub>F</sub> [2]    | Forward Voltage          | Yellow<br>Super Bright Green | 2.1<br>2.2 | 2.5<br>2.5 | V     | I <sub>F</sub> =20mA       |
| I <sub>R</sub>        | Reverse Current          | Yellow<br>Super Bright Green |            | 10<br>10   | uA    | V <sub>R</sub> = 5V        |

### Notes:


1. Wavelength: +/-1nm.
2. Forward Voltage: +/-0.1V.
3. Wavelength value is traceable to the CIE127-2007 compliant national standards.

## Absolute Maximum Ratings at TA=25°C






| Parameter                | Yellow         | Super Bright Green | Units |
|--------------------------|----------------|--------------------|-------|
| Power dissipation        | 75             | 62.5               | mW    |
| DC Forward Current       | 30             | 25                 | mA    |
| Peak Forward Current [1] | 140            | 140                | mA    |
| Reverse Voltage          | 5              |                    | V     |
| Operating Temperature    | -40°C To +85°C |                    |       |
| Storage Temperature      | -40°C To +85°C |                    |       |

### Note:






1. 1/10 Duty Cycle, 0.1ms Pulse Width.



## APBA3010YSGC-GX Yellow




## Super Bright Green



## APBA3010YSGC-GX

Reflow soldering is recommended and the soldering profile is shown below.  
Other soldering methods are not recommended as they might cause damage to the product.


Reflow Soldering Profile For Lead-free SMT Process.




### NOTES:

1. We recommend the reflow temperature 245°C(+/-5°C). The maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.


### Recommended Soldering Pattern (Units : mm; Tolerance: $\pm 0.1$ )



### Reel Dimension




### Tape Dimensions (Units : mm)



PACKING & LABEL SPECIFICATIONS

APBA3010YSGC-GX



|                                                                                                                      |                                               |
|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>Kingbright</b>                                                                                                    |                                               |
| P/NO: APBA3010XXX                                                                                                    |                                               |
| QTY: 2,000 pcs                                                                                                       | Q.C. <div>Q C<br/>XX XX XXXX<br/>PASSED</div> |
| S/N: XXXX                                                                                                            |                                               |
| CODE: XXX                                                                                                            |                                               |
| LOT NO:                                                                                                              |                                               |
| <br>XXXXXXXXXXXXXXXXXXXXXXXXXXXX |                                               |
| RoHS Compliant                                                                                                       |                                               |

All design applications should refer to Kingbright application notes available at <http://www.KingbrightUSA.com/ApplicationNotes>



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331